

--esimene SQL päring

```
SELECT *  
FROM sales;
```

--konkreetsse veeru valimine

```
SELECT customer_id, total_price, sale_date  
FROM sales;
```

--veergude ümbernimetamine

```
select  
customer_id AS klient,  
total_price AS summa,  
sale_date AS kuupäev  
FROM sales;
```

--tulemuste arvu piiramine

```
SELECT customer_id, total_price  
FROM sales  
LIMIT 10;
```

--tulemuste sorteerimine--

```
SELECT customer_id, total_price  
FROM sales  
ORDER BY total_price;  --hinna järgi sorteerimine kasvavalt--
```

--hinna järgi sorteerimine kahanevalt--

```
SELECT customer_id, total_price  
FROM sales  
ORDER BY total_price DESC;
```

--päring 1--

```
SELECT *  
FROM sales  
LIMIT 5; --kokku 5 veergu--
```

--päring 2--

```
SELECT sale_id, customer_id, total_price, sale_date  
FROM sales  
LIMIT 10;
```

--milline on suurim summa 10 rea sees?--

```
SELECT sale_id, customer_id, total_price, sale_date  
FROM sales  
ORDER BY total_price DESC --suurim on 2170,40--  
LIMIT 10;
```

--sorteeri ja piira--

```
SELECT sale_id, total_price AS summa  
FROM sales  
ORDER BY total_price desc --sorteeri kahanevalt--  
LIMIT 5;
```

--Harjutus 1B--

```
SELECT sale_id, total_price AS summa
```

```
FROM sales
```

```
ORDER BY total_price ASC --sorteeri kasvavalt--
```

```
LIMIT 5;
```

--kõige väiksem müük on -1405,32--

--Näen negatiivseid müüke--

--Harjutus 1C--

```
select
```

```
customer_id AS kliendi_id,
```

```
sale_date AS kuupäev,
```

```
total_price AS summa
```

```
FROM sales
```

```
ORDER BY sale_date desc
```

```
LIMIT 20;
```

--kliendi ID, kuupäeva ja summaga — sorteerituna kuupäeva järgi (uuemad enne)--

--Osa 2 WHERE--

--Where põhistruktuur UrbanStyle näide: müügid üle 100 euro--

```
SELECT sale_id, total_price
```

```
FROM sales
```

```
WHERE total_price > 100
```

```
ORDER BY total_price DESC;
```

--müügid vahemikus 100-500 eurot

SELECT sale_id, total_price

FROM sales

WHERE total_price BETWEEN 100 AND 500;

--Müügid Tallinna või Tartu kauplustes

SELECT sale_id, total_price, channel

FROM sales

Where channel IN ('Tallinn', 'Tartu');

--Kliendi, kelle nimi algab "K"-ga

SELECT customer_id, first_name, last_name

FROM customers

WHERE first_name LIKE 'K%';

-- Suured müügid Tallinnast

SELECT sale_id, total_price, channel

FROM sales

WHERE total_price > 500 AND channel = 'Tallinn';

-- Müügid, mis on kas väga suured VÕI väga väikesed

SELECT sale_id, total_price

FROM sales

WHERE total_price > 500 OR total_price < 10;

-- Selge järjekord sulgudega

```
SELECT sale_id, total_price, channel
FROM sales
WHERE (channel = 'Tallinn' OR channel = 'Tartu')
AND total_price > 100;
```

```
--Harjutus 2A- suured tellimused
SELECT sale_id, customer_id, total_price
FROM sales
WHERE total_price > 500
ORDER BY total_price DESC;
```

```
--kindla perioodi müügid
SELECT sale_id, sale_date, total_price
FROM sales
WHERE sale_date BETWEEN '2024-01-01' AND '2024-03-31'
ORDER BY sale_date;
```

```
--NULL väärtuse otsimine
SELECT sale_id, customer_id, total_price
FROM sales
WHERE customer_id IS NULL;
```

```
--Harjutus 2B summa on üle 200 euro, tellimus on tehtud 2024. aastal
SELECT sale_id, sale_date, total_price
FROM sales
WHERE sale_date BETWEEN '2024-01-01' AND '2024-12-31' AND total_price > 200;
```

--Ainult konkreetse asukoha tellimused- Tartu

SELECT sale_id, sale_date, total_price, channel

FROM sales

WHERE channel = 'Tartu' AND sale_date BETWEEN '2024-01-01' AND '2024-12-31' AND
total_price > 200;

--Harjutus 2C sinu päring "kahtlaste" ridade leidmiseks:

SELECT total_price, customer_id

FROM sales

WHERE total_price <= 0 OR customer_id IS NULL;

-- Kõik kanalid (korduvad)

SELECT channel

FROM sales;

-- Tulemus: tuhandeid ridu, paljud korduvad

-- Ainult unikaalsed kanalid

SELECT DISTINCT channel

FROM sales;

-- Tulemus: 3-5 rida (nt Tallinn, Tartu, Pärnu, E-pood)

-- Mitu rida on tabelis kokku?

SELECT COUNT(*) AS ridade_arv

FROM sales;

-- Mitu rida omab customer_id väärtust (mitte NULL)?

```
SELECT COUNT(customer_id) AS klientidega_tellimused  
FROM sales;
```

-- Mitu ERINEVAT klienti on tellimusi teinud?

```
SELECT COUNT(DISTINCT customer_id) AS unikaalseid_kliente  
FROM sales;
```

-- Mitu customer_id on NULL?

```
SELECT  
    COUNT(*) AS kokku,  
    COUNT(customer_id) AS klientidega,  
    COUNT(*) - COUNT(customer_id) AS puuduvaid  
FROM sales;
```

-- Samm A: Mitu rida kokku?

```
SELECT COUNT(*) FROM sales;
```

-- Samm B: Mitu unikaalset sale_id on?

```
SELECT COUNT(DISTINCT sale_id) FROM sales;
```

-- Kui A > B, siis on duplikaadid!

--kui palju on unikaalseid kliente

```
SELECT  
    COUNT(*) AS ridade_arv,
```

```
COUNT(customer_id) AS klientidega,  
COUNT(*) - COUNT(customer_id) AS puudub_klient,  
COUNT(DISTINCT customer_id) AS unikaalseid_kliente  
FROM sales;
```

```
--Unikaalsed kliendid  
  
SELECT DISTINCT channel  
  
FROM sales  
  
ORDER BY channel;
```

```
--Harjutus 3B Leia kõigi ridade arv  
  
SELECT COUNT(*) AS kokku FROM sales;
```

```
--Leia unikaalsete ridade arv  
  
SELECT COUNT (DISTINCT sale_id) AS unikaalseid FROM sales;
```

```
--duplikaatide arvu leidmine  
  
SELECT  
  
COUNT(*) AS kokku,  
  
COUNT (DISTINCT sale_id) AS unikaalseid,  
  
COUNT(*) - COUNT (DISTINCT sale_id) AS duplikaadid  
  
FROM sales;
```

```
--puuduvate hindade leidmine  
  
select  
  
COUNT (*) AS koguarv,
```



```
COUNT (DISTINCT category) AS kategooriad,  
COUNT(*) - COUNT (DISTINCT cost_price) AS puuduvad_hinnad  
FROM products;
```

-- Küsimus: mitu duplikaati on?

```
SELECT  
    COUNT(*) AS ridu_kokku,  
    COUNT(DISTINCT sale_id) AS unikaalseid,  
    COUNT(*) - COUNT(DISTINCT sale_id) AS duplikaate  
FROM sales;
```

--Mitmel real puudub customer_id

```
SELECT COUNT (*) customer_id  
FROM sales  
WHERE customer_id IS NULL;
```

--kümme suurimat tellimust

```
SELECT sale_id, customer_id, total_price  
FROM sales  
ORDER BY total_price desc  
LIMIT 10;
```

--10 väiksemat tellimust ja read, kus summa on 0 või väiksem

```
SELECT total_price, sale_id  
FROM sales  
WHERE total_price <= 0
```

ORDER BY total_price asc

LIMIT 10;