



main.c



Share

Run

Output

```
1 // Online C compiler to run C program online
2 #include <stdio.h>
3
4 int main() {
5     printf("Hello World!");
6     return 0;
7 }
```

Hello World!

=== Code Execution Successful ===



JS

TS

GO



main.c

```
1 #include <stdio.h>
2
3 int main() {
4     int a, b, sum;
5
6     printf("Enter value of a: ");
7     scanf("%d", &a);
8
9     printf("Enter value of b: ");
10    scanf("%d", &b);
11
12    sum = a + b;
13
14    printf("Sum = %d", sum);
15
16    return 0;
17 }
```



Share

Run

Output

Enter value of a: 4

Enter value of b: 6

Sum = 10

=== Code Execution Successful ===

JS

TS





main.c



Share

Run

Output

```
1 #include <stdio.h>
2
3 int main() {
4     int a, b, area;
5
6     printf("Enter length: ");
7     scanf("%d", &a);
8
9     printf("Enter breadth: ");
10    scanf("%d", &b);
11
12    area = a * b;
13
14    printf("Area of rectangle = %d", area);
15
16    return 0;
17 }
```

Enter length: 6
Enter breadth: 8
Area of rectangle = 48

=== Code Execution Successful ===



main.c



Share

Run

Output

```
1 #include <stdio.h>
2
3 int main() {
4     float celsius, fahrenheit;
5
6     printf("Enter temperature in Celsius: ");
7     scanf("%f", &celsius);
8
9     fahrenheit = (celsius * 9 / 5) + 32;
10
11    printf("Temperature in Fahrenheit = %.2f", fahrenheit);
12
13    return 0;
14 }
```

Enter temperature in Celsius: 100
Temperature in Fahrenheit = 212.00

=== Code Execution Successful ===



main.c



Share

Run

Output

```
1 #include <stdio.h>
2
3 int main() {
4     float p, r, t, si;
5
6     printf("Enter Principal Amount: ");
7     scanf("%f", &p);
8
9     printf("Enter Rate of Interest : ");
10    scanf("%f", &r);
11
12    printf("Enter Time in Years: ");
13    scanf("%f", &t);
14
15    si = (p * r * t) / 100;
16
17    printf("Simple Interest = %.2f", si);
18
19    return 0;
20 }
```

Enter Principal Amount: 1500

Enter Rate of Interest : 12

Enter Time in Years: 3

Simple Interest = 540.00

=== Code Execution Successful ===



main.c



Share

Run

Output

```
1 #include <stdio.h>
2
3 int main() {
4     int a, b, temp;
5
6     printf("Enter value of a: ");
7     scanf("%d", &a);
8
9     printf("Enter value of b: ");
10    scanf("%d", &b);
11
12    temp = a;
13    a = b;
14    b = temp;
15
16    printf("After swapping:\n");
17    printf("a = %d\n", a);
18    printf("b = %d", b);
19
20    return 0;
21 }
```

Enter value of a: 5

Enter value of b: 9

After swapping:

a = 9

b = 5

=== Code Execution Successful ===