

main.c



Share

Run

Output

```
1  #include <stdio.h>
2
3- int main() {
4      int num;
5
6      printf("Enter an integer: ");
7      scanf("%d", &num);
8
9-      if (num % 2 == 0) {
10         printf("%d is an Even number.\n", num);
11-     } else {
12         printf("%d is an Odd number.\n", num);
13     }
14
15     return 0;
16 }
```

Enter an integer: 26
26 is an Even number.

=== Code Execution Successful ===

main.c



Share

Run

Output

```
1 #include <stdio.h>
2
3 int main() {
4     int a, b, c;
5
6     printf("Enter three numbers: ");
7     scanf("%d %d %d", &a, &b, &c);
8
9     if (a >= b && a >= c) {
10         printf("%d is the largest number.\n", a);
11     } else if (b >= a && b >= c) {
12         printf("%d is the largest number.\n", b);
13     } else {
14         printf("%d is the largest number.\n", c);
15     }
16
17     return 0;
18 }
```

Enter three numbers: 4 6 8
8 is the largest number.

=== Code Execution Successful ===

JS

TS

GO



main.c



Share

Run

Output

Enter a year: 1900
1900 is not a leap year.

=== Code Execution Successful ===



```
1 #include <stdio.h>
2
3 int main() {
4     int year;
5
6     printf("Enter a year: ");
7     scanf("%d", &year);
8
9     if (year % 400 == 0 && year % 100 != 0)
10         printf("%d is a leap year.\n", year);
11     else
12         printf("%d is not a leap year.\n", year);
13
14     return 0;
15 }
```



JS

TS

GO



main.c



Share

Run

Output

Enter marks: 86
Grade B

=== Code Execution Successful ===

```
1 #include <stdio.h>
2
3 int main() {
4     int marks;
5
6     printf("Enter marks: ");
7     scanf("%d", &marks);
8
9     if (marks >= 90)
10         printf("Grade A\n");
11     else if (marks >= 80 && marks < 90)
12         printf("Grade B\n");
13     else if (marks >= 70 && marks < 80)
14         printf("Grade C\n");
15     else if (marks >= 60 && marks < 70)
16         printf("Grade D\n");
17     else
18         printf("Grade F\n");
19
20     return 0;
21 }
```



JS

TS



main.c



Share

Run

Output

```
1 #include <stdio.h>
2
3 int main() {
4     int a;
5
6     printf("Enter a number: ");
7     scanf("%d", &a);
8
9     if (a > 0)
10         printf("Positive number\n");
11     else if (a < 0)
12         printf("Negative number\n");
13     else
14         printf("Zero");
15
16     return 0;
17 }
```

Enter a number: -6
Negative number

=== Code Execution Successful ===

main.c



Share

Run

Output

```
1 #include <stdio.h>
2
3 int main() {
4     float a, b;
5     char op;
6
7     printf("Enter an operator (+, -, *, /): ");
8     scanf("%c", &op);
9
10    printf("Enter two numbers: ");
11    scanf("%f %f", &a, &b);
12
13    if (op == '+')
14        printf("Result = %.2f\n", a + b);
15    else if (op == '-')
16        printf("Result = %.2f\n", a - b);
17    else if (op == '*')
18        printf("Result = %.2f\n", a * b);
19    else if (op == '/')
20        printf("Result = %.2f\n", a / b);
21    else
22        printf("Invalid operator");
23
24    return 0;
25 }
```

Enter an operator (+, -, *, /): *
Enter two numbers: 5.7 2.5
Result = 14.25

=== Code Execution Successful ===