

Commands and Codes

Demo: User Defined Function | Queries

```
-- creating sample UDF which concatenates two column values
CREATE OR REPLACE FUNCTION f_concat_ws(s1 VARCHAR, s2 VARCHAR)
RETURNS VARCHAR
STABLE
AS $$
SELECT CONCAT($1, concat(' ', $2))
$$ LANGUAGE sql

-- using UDF
SELECT f_concat_ws(firstname, lastname) from tickit.users;
```

Demo: Stored Procedures | Queries

```
-- creating stored procedure
Create or replace procedure update_sales_price(v_sales_id INT, v_new_price DECIMAL(8,2))
Language plpgsql
AS $$
Begin
    update sales
    SET pricepaid = v_new_price
    where salesid = v_sales_id;
    if not found then
        raise notice 'no sales record found for sales id %', v_sales_id;
    end if;
End;
$$;

-- calling the stored procedure for non existing salesid
Call update_sales_price(1234567, 100.00);

-- calling the stored procedure for existing salesid
Call update_sales_price(123456, 3300.00);

-- query to get data for existing salesid
Select * from sales where salesid = 123456
```

Demo: Materialized Views | Queries

```
-- create schema
create schema mat_view_demo

-- set search path
SET search_path = mat_view_demo, public;

-- query to get the event(eventname) and the total sales associated with it
SELECT e.eventname eventname, sum(s.pricepaid) total_sales
```

```

FROM event e, sales s WHERE e.eventid = s.eventid GROUP BY e.eventnameorder by e.eventname

-- create materialized view
CREATE MATERIALIZED VIEW tickets_mv AS (SELECT e.eventname eventname, sum(s.pricepaid) total_sales FROM
event e, sales s WHERE e.eventid = s.eventid GROUP BY e.eventname)

-- check the view data
select * from mat_view_demo.tickets_mv order by eventname

-- update the results
update sales s set pricepaid= pricepaid*2 where eventid in (select eventid from event where eventname
= '.38 Special')

-- refresh the view data
refresh materialized view mat_view_demo.tickets_mv;

-- auto refresh
CREATE MATERIALIZED VIEW tickets_mv_2 AUTO REFRESH YES AS (SELECT e.eventname eventname,
sum(s.pricepaid) total_sales FROM event e, sales s WHERE e.eventid = s.eventid GROUP BY e.eventname)

```