❖ WISH-HTNG Web Service (External System ⇨ WISH Front Office)

Objective:

This HTNG Web service interface is to interact with WISH from any external system through web methods defined in web service.

Pull Service (ARIAndReservationPullService)

Under this service, External system can do the following operations into WISH.

- GetHotelAvailability (Availability Information)
- GetHotelRatePlan (Rate Plan Information)
- RetrieveReservations (Reservation Information)

WISHFrontOffice Service

- AcknowledgeAvailabilty (Acknowledgement of Availability Request)
- AcknowledgeRates (Acknowledgement of Rates Request)

To interact with WISH through this web service interface, external system has to add web reference from internet address, given by Prologic First, into their application and then call desired web method of the web service.

All the input parameters and result parameters are in structured format provided by HTNG.

➢ How to Setup Server and Mapping XML for HTNG:

In HTNGWebservice's Web.Config XML File set these key values …

```
<appSettings>
    <add key="Server" value="Server\WISH"/>
    <add key="PropertyId" value="PROP1"/>
    <add key="SourceId" value="WISH"/>
    <add key="Database" value="sprocdb"/>
    <add key="UserId" value="OPM1"/>
    <add key="ConfigFilePath" value="Config/"/>
    <add key="HTNGMappingXML" value="Config/XML/HTNGMapping.xml"/>
    <add key="SecurityXML" value="Config/XML/Security.xml"/>
    <add key="CultureInfo" value="en-US"/>
    <add key="DateFormat" value="yyyy-MM-dd"/>
    <add key="DateSeparator" value="-"/>
    <add key="AutoAssignRoomOnCheckin" value="N"/>
    <add key="SUPPRESS_ERROR_MSG" value="Y"/>
    <add key="TAXCalculationByPMS" value="Y"/>
    <add key="SpecialAccountId" value="0"/>
    <add key="AR_SpecialAccountId" value="0"/>
    <add key="SpecialAccountPaymentId" value="0"/>
    <add key="DummyDecimalPlaces" value="0"/>
    <add key="MaxCRSFilesAllowedAsPending" value="50"/>
    <add key="MaxAvailabilityFilesAllowedAsPending" value="50"/>
    <!-- 14->Reservation Id, 40->Confirmation Number -->
    <add key="IDTypeForPDSReservationUpdate" value="14"/>
    <!-- Used for CRS (Specify N if used for CRS else Y) -->
    <add key="DONTMAPLOCALCRSID" value="Y"/>
    <!--Here SynXis expecting CRS from Reservation Response with their ID and value
"PMS" with Guest ID-->
    <add key="ExternalAndPMSSourceValue" value="CRS|PMS"/>
    <!--
```


Copyright © Prologic First India Pvt. Ltd.

```
Here Specify QikInn PDF Retrieve URL (WISH.Net and I-Pad Integration for Malaysia)
                    -->
    <add key="QikInnPdfRetrieveUrl"
value="http://ubicompsystem.dyndns.org:8080/ca/qikpadTerminal/retrievePdf"/>
    <add key="ValidateUniqueConfirmationNo" value="N"/>
    <add key="KioskSingleCall" value="Y"/>

    <add key="UpdateOTRF_WithGuestId" value="N"/>

    <!--

    BulkPostingMaxTransactionAllowed
    validation where transaction count cannot be more than configured.
    -->
    <add key="BulkPostingMaxTransactionAllowed" value="500"/>
    <add key="UseDefaultEtaEtd" value="N"/>
    <add key="DefaultEtaTime" value="00:00"/>
    <add key="UseDefaultEtaEtd" value="00:00"/>
    <add key="ApplicationPath" value="~"/>
    <add key="AllowMultiStay" value="N"/>
    <add key="CurrentAddressLength" value="50"/>
    <add key="AllowRoomAssignForComponentRooms" value="N"/>

  </appSettings>
```

Change Server name in Server Key Field.

Mapping Portion

Open HTNGMapping.xml file from config\XML directory for mapping of Master Code of External System codes with that of WISH Master Codes and do the mapping.
Following Mapping Codes needs to be required for Rates/Reservations/Availability

1. Rate Code Mapping

For Rate Code, only default needs to be specified because it will pick rate code from its SOURCE.
Please refer to the following sample.

```
<DEFAULT-RATECODE>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</DEFAULT-RATECODE>
<RATECODE>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</RATECODE>
```


Copyright © Prologic First India Pvt. Ltd.

2. Room Type Mapping

For Room Type Mapping, Default should be blank.
Please refer to the following sample.

```
<DEFAULT-ROOMTYPE>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </DEFAULT-ROOMTYPE>

 <ROOMTYPE>
   <Code>CODE1</Code>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </ROOMTYPE>
```

3. Market Segment Mapping

For Rates:
It is required for Rates Creation in WISH.Net PMS from External System.

For Reservation:
If Market Code is coming from External System is not a blank then following mapping needs to be created.

```
<DEFAULT-MARKETSEGMENT>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </DEFAULT-MARKETSEGMENT>

 <MARKETSEGMENT>
   <Code>CODE1</Code>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </MARKETSEGMENT>
```

4. Business Source Mapping

Please refer to the following sample

```
<DEFAULT-BUSINESSSOURCE>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </DEFAULT-BUSINESSSOURCE>
```


Copyright © Prologic First India Pvt. Ltd.

5. FX Code Mapping

For FX Code Mapping, Please refer to the following sample

```
<DEFAULT-FXCODE>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </DEFAULT-FXCODE>

 <FXCODE>
   <Code>CODE1</Code>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </FXCODE>
```

6. Credit Card Code Mapping

For Credit Card Code Mapping, default will be CASH.

Please refer to the following sample

```
<DEFAULT-PAYMENTMETHOD>
   <WISHCode>CASH</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </DEFAULT-PAYMENTMETHOD>

 <PAYMENTMETHOD>
   <Code>CODE1</Code>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </PAYMENTMETHOD>
```

7. Special Service Code Mapping

Please refer to the following sample.

```
<DEFAULT-SPECIALSERVICE>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </DEFAULT-SPECIALSERVICE>

 <SPECIALSERVICE>
   <Code>CODE1</Code>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
```


Copyright © Prologic First India Pvt. Ltd.

```
    <Source>SOURCE</Source>
  </SPECIALSERVICE>
```

8. Title Code Mapping

Please refer to the following sample.

```
<DEFAULT-TITLE>
    <WISHCode>CODE</WISHCode>
    <PropertyId>PROP</PropertyId>
    <Source>SOURCE</Source>
  </DEFAULT-TITLE>

  <TITLE>
    <Code>CODE1</Code>
    <WISHCode>CODE</WISHCode>
    <PropertyId>PROP</PropertyId>
    <Source>SOURCE</Source>
  </TITLE>
```

9. Travel Agent Mapping

Please refer to the following sample.

```
 <DEFAULT-TRAVELAGENTID>
    <WISHCode>CODE</WISHCode>
    <PropertyId>PROP</PropertyId>
    <Source>SOURCE</Source>
  </DEFAULT-TRAVELAGENTID>
  <TRAVELAGENTID>
    <Code>CODE1</Code>
    <WISHCode>CODE</WISHCode>
    <PropertyId>PROP</PropertyId>
    <Source>SOURCE</Source>
  </TRAVELAGENTID>
```

10. Corporate Mapping

Please refer to the following sample

```
<DEFAULT-CORPACCTID>
    <WISHCode>CODE</WISHCode>
    <PropertyId>PROP</PropertyId>
    <Source>SOURCE</Source>
  </DEFAULT-CORPACCTID>
  <CORPACCTID>
    <Code>CODE1</Code>
    <WISHCode>CODE</WISHCode>
```


Copyright © Prologic First India Pvt. Ltd.

```
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</CORPACCTID>
```

11. Terms Mapping

Please refer to the following sample

```
<DEFAULT-MEALPLANID>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</DEFAULT- MEALPLANID>
<MEALPLANID>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</MEALPLANID>
```

For Default Mapping of Masters take reference of the following Section –

```
<DEFAULT-TITLE>
   <WISHCode>MR.</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
</DEFAULT-TITLE>
```

If this section is defined then, if any Title from external system is not defined in this xml Will be mapped to 'MR.' Charge code of WISH

Default Section for Each Master should be defined only once in the XML
Take Reference from Config\XML\HTNGMapping.xml file.

Settings need to be defined in Advance control in System Administrator:

Control Code	Description	Int Val	Character Value	Remarks
PDSINS	HTNG-PDS Interface Installed(1-Yes/0-No)	1	PEGS	In Int Val, Specify 1 – Means Installed. In Character Value, Specify the Source Code ie PEGS used for PEGASUS. Or It can be anything based on Client. If User is using Multiple Source then specify Character Value in the following way e.g. User is having PEGS and KSK (kiosk) then value will be PEGS|KSK
RTSRC	Source List for Rate Update	0	PEGS	In Character Value, Specify the Source Code ie PEGS used for PEGASUS. If User is using Multiple Source then specify Character Value in the following way e.g. User is having PEGS and KSK (kiosk)

Copyright © Prologic First India Pvt. Ltd.

				then value will be PEGS|KSK This will get used in Trigger applied for Rate Management means If there is any change in Rate Code. Then It will insert an entry in parmdb..if_rates And values of the following fields get inserted. 1. rate_code (Pick it from Rate Mgmt) 2. source_id (eg It will be same as PEGS or KSK as defined for AVLSRC) 3. htng_model(e.g. PDS because PDSINS is 1) 4. mode(eg NE(New) or (UP) Update) 5. deliver_flag 6. property_id
AVLSRC	Source List for Availability Update	0	PEGS	In Character Value, Specify the Source Code ie PEGS used for PEGASUS. If User is using Multiple Source then specify Character Value in the following way e.g. User is having PEGS and KSK (kiosk) then value will be PEGS|KSK This will get used in Trigger applied for Availability Management means If there is any change in PMS Availability. Then It will insert an entry in hotel..if_avail And values of the following fields get inserted. 1. room_type (Pick it from Availability Mgmt) 2. date (Availability Date) 3. available (Availability Figures) 4. closed_for_arr_dep (Old Status of Closed For Arrival/Departure) 5. property_id (Hotel Code) 6. source_id (eg It will be same as PEGS or KSK as defined for AVLSRC) 7. htng_model(e.g. PDS because PDSINS is 1) 8. closed_for_arr_dep_new (New Status of Closed For Arrival/Departure) 9. deliver_flag (Default = "N" On selection of records value will be "W", and AcknowledgeAvailability deletes those records with status "W"
GSTSRC	Source List for Guest Status Notification	0	Same as PDSINS	If Char value is specified then it will generate Guest IDs affected during Create/Modify/Cancel/Checkin/Checkout so that same information can be retrieved.
PDSCNT	PDS Records Count to be	10	N	Default Char Value : N

Copyright © Prologic First India Pvt. Ltd.

	pushed			If GSTSRC is defined and to reduce the load on Service while pulling records It is recommended to Use this control And Update Char Value = "Y" Int value will be used how many updated records User wants to receive at a time.
LOGPGE	Purge Days for Interface Log	30	Y	Recommended Char value = "Y" with purge days as 30.
IFCHTR	Fire Trigger for Channel (Y/N)	0	N	Default Char Value is "N", for channel allocation this will be "Y"
CHNAVL	Validate Channel Availability (Y)es,(N)o	0	Y	For Channel allocation case, this will be "Y" else "N".

- **GetHotelAvailability**

The Hotel Availability Get message pair provides the ability for a booking source to request availability status from a specified hotel property(s). The request message allows the booking source to resynchronize availability due to a system outage or if a hotel property is behind a restrictive firewall, the need to request availability is necessary.

The Hotel Availability Get request message allows a booking source to filter another system for detailed availability. The request message can be minimally limited to an individual property or a collection of properties for a specified date range or it can further specify a rate plan(s), room type(s), rate plan/room type combinations, restrictions and revenue management qualifiers.

Based on the criteria specified in the request message, the response message contains the set of availability controls.

Behavior

The process being facilitated is that of requesting availability and/or inventory and/or restrictions from System A to System B (where system A is generally, but not exclusively, a CRS and system B is generally, but not exclusively, a PMS).

Based on the type of information that needs to be exchanged, System A will select the appropriate usage profile and fill in the XML according to the guidelines provided in the specific profile.

System A will then send the XML to the appropriate webservice set up by System B. System B will respond using the correct response for the selected profile. System A will log the response received from System B.

Behavior expected prior to Transmission
The behavior expected from System A will be:
• Usage of the appropriate profile for the type of information to be sent
• Translation of availability information into codes understood by System B (if required)
• Provision of all fields classed as mandatory in the profile

Copyright © Prologic First India Pvt. Ltd.

• Validation of XML message format
• Transmission of the XML to appropriate URL set up by System B using the appropriate identification criteria (soap user and password provided by System B)

Behavior expected upon receipt of response message from Recipient
Once the XML has been processed by System B, System A will need to:
• Keep a log of the response message transmitted back by System B
• Be able to evaluate error responses coming from System B
• React to error responses as need: by modifying the XML and/or ensuring correct mapping tables are used

Behavior expected from Recipient System
Upon receipt of the XML message the behavior expected from System B will be:

• Process XML received by System A
• Return hotel availability data and/or inventory and/or restriction information contained in the XML requested by System A
• If it is not possible to process the message: create an error response as defined in the profile and transmit the response to System A
• Acknowledge successful/unsuccessful processing of the request using the appropriate response message

1. Get Availability Request

For Getting Availability for Room Type and Date Range HTNG suggests following xml formats. (Request)

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns="http://www.opentravel.org/OTA/2003/05"
xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurityutility-1.0.xsd">
  <soapenv:Header>
    <wsse:Security mustUnderstand="1">
      <wsse:UsernameToken wsu:Id="UsernameToken-72135529">
        <wsse:Username>SUP</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-
profile-1.0#PasswordText">SUP</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
    <wsa:To>http://localhost/htng/ARIAndReservationPullService.asmx</wsa:To>
    <wsa:Action>http://localhost/htng/ARIAndReservationPullService.asmx/GetHotelAvailability</wsa:Action>
  </soapenv:Header>
  <soapenv:Body>
    <OTA_HotelAvailGetRQ xsi:schemaLocation="http://www.opentravel.org/OTA/2003/05
OTA_HotelAvailGetRQ.xsd" EchoToken="String" TimeStamp="2011-06-13" Target="Production" Version="1.000"
xmlns="http://www.opentravel.org/OTA/2003/05" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance">
      <POS>
        <Source >
          <RequestorID ID="KSK"  />
        </Source>
      </POS>
      <HotelAvailRequests>
        <HotelAvailRequest>
          <HotelRef HotelCode="DEMO"/>
          <DateRange Start="2012-04-04" End="2012-04-10"/>
```


Copyright © Prologic First India Pvt. Ltd.

```
        <RoomTypeCandidates>
          <RoomTypeCandidate RoomTypeCode = "" />
        </RoomTypeCandidates>
        <TPA_Extensions>
          <UpdatedAvailability>N</UpdatedAvailability>
          <GetTimeSlotAvailability>Y</GetTimeSlotAvailability>
          <TimeSlotHours>10</TimeSlotHours>
        </TPA_Extensions>
      </HotelAvailRequest>
    </HotelAvailRequests>
  </OTA_HotelAvailGetRQ>
 </soapenv:Body>
</soapenv:Envelope>
```

Login Credentials have been shown in this format, Part of SOAP Header in SOAP Envelope. User Name and password highlighted in the following XML Tag.

```
<wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd">
        <wsse:UsernameToken xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
          <wsse:Username>SUP</wsse:Username>
          <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">SUP</wsse:Password>
        </wsse:UsernameToken>
      </wsse:Security>
```

URL of the Web Service has been showing in the following XML Format of the Request Message, part of SOAP Header in SOAP Envelope.

```
<wsa:To> http://localhost/htng/ARIAndReservationPullService.asmx</wsa:To>
```

Usage Profile Table (OTA_HotelAvailGetRQ)

The availability request is sent using the OTA_HotelAvailGetRQ message.

Element | @Attribute	Num	Description/Contents
OTA_HotelAvailGetRQ	1	Root element of the message.
@EchoToken	0..1	Optional.
@TimeStamp	1	Timestamp of the transaction.
@Version	1	Version is a mandatory attribute in OTA. Therefore it must remain in HTNG in order to be able to use the same message
OTA_HotelAvailGetRQ/POS/Source	1	Optional. This holds details regarding the requestor. It may be repeated to also accommodate the delivery systems.
OTA_HotelAvailGetRQ/POS/Source/RequestorID	1	The system sending the request message. An identifier of the entity making the request (e.g. ATA/IATA/ID number, Electronic Reservation Service Provider (ERSP), Association of British Travel Agents (ABTA)).
@Type	1	Type attribute uses the OTA code list UIT. For example, type 22 – ERSP (Electronic reservation service provider).
@Id	1	ID is used for the name or ID of the requestor. For example,

Copyright © Prologic First India Pvt. Ltd.

		Passkey.
OTA_HotelAvailGetRQ/HotelAvailRequests	1	Container for the individual HotelAvailRequests(s).
OTA_HotelAvailGetRQ/HotelAvailRequests /HotelAvailRequest	1	Provides the criteria to specify availability details to return. The criteria can include date ranges, room and products, rate plans, hurdle rate, etc. Optional. Although at least one should be sent for the message to be meaningful. Criteria and upper limit to be defined by trading partners.
@SendBookingLimit	0..1	Sending system requesting the booking limit to be returned.
@BookingLimitMessageType	0..1	Sending system requesting the booking limit of a particular type to be returned.
OTA_HotelAvailGetRQ/HotelAvailRequests /HotelAvailRequest/DateRange	1	A date or range of dates for the request criteria.
@Start, @End	1	The first and last dates for which the availability request is for.
OTA_HotelAvailGetRQ/HotelAvailRequests /HotelAvailRequest/ RoomTypeCandidates	0..n	Collection of room stay candidates.
OTA_HotelAvailGetRQ/HotelAvailRequests /HotelAvailRequest/ RoomTypeCandidates/RoomTypeCandidate	0..n	Element used to specify room products.
@RoomTypeCode	1..n	Conditionally mandatory if element is present. The room type code whose availability is being requested.
OTA_HotelAvailGetRQ/HotelAvailRequests /HotelAvailRequest/ HotelRef	1	Indicates the detail of hotel reference information.
@ HotelCode	1	This is the code of the property whose availability is being requested.
@ ChainCode	0..1	Optional. The chain code for which the availability request is for.
@ BrandCode	0..1	Optional. The brand code for which the availability request is for.
OTA_HotelAvailGetRQ/HotelAvailRequests /HotelAvailRequest/ TPA_Extensions	1	
OTA_HotelAvailGetRQ/HotelAvailRequests /HotelAvailRequest/ TPA_Extensions/ UpdatedAvailability	1	If “Y” then External System will get Updated Availability of WISH. If “N” then External System will get Complete Availability of WISH.
OTA_HotelAvailGetRQ/HotelAvailRequests /HotelAvailRequest/ TPA_Extensions/ GetTimeSlotAvailability	1	If “Y” then External System will get Time Based Availability of WISH. If “N” then External System will get Actual Availability of WISH.
OTA_HotelAvailGetRQ/HotelAvailRequests /HotelAvailRequest/ TPA_Extensions/ TimeSlotHours	1	Used to specify Time Slot Hours View for Time Based Availability. Use this if GetTimeSlotAvailability is set to “Y” e.g. Following means to Get 10 Hours Availability of the date range. <TimeSlotHours>10</TimeSlotHours>

2. Availability Response

Response XML Message from WISH will be in the following format as per HTNG Standards.

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:wsse="http://docs.oasis-
```


Copyright © Prologic First India Pvt. Ltd.

```
open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
  <soap:Header>
<wsa:Action>http://localhost/htng/ARIAndReservationPullService.asmx/GetHotelAvailabilityResponse</wsa:Action>
    <wsa:MessageID>urn:uuid:18ba6678-b33c-40e4-8fdf-93633c12524d</wsa:MessageID>
    <wsa:RelatesTo>urn:uuid:1d7cff2a-4789-4aa8-9b59-d2448dff47b7</wsa:RelatesTo>
    <wsa:To>http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:To>
    <wsse:Security>
      <wsu:Timestamp wsu:Id="Timestamp-f2e9606e-1642-4947-9de3-a6078ff02667">
        <wsu:Created>2010-12-09T08:07:05Z</wsu:Created>
        <wsu:Expires>2010-12-09T08:12:05Z</wsu:Expires>
      </wsu:Timestamp>
    </wsse:Security>
  </soap:Header>
    <soap:Body>
    <OTA_HotelAvailGetRS EchoToken="String" TimeStamp="2012-11-16T07:33:03.5841657Z" Version="1.000"
xmlns="http://www.opentravel.org/OTA/2003/05">
      <Success/>
      <AvailStatusMessages HotelCode="DEMO">
        <AvailStatusMessage BookingLimitMessageType="SetLimit" BookingLimit="24">
          <StatusApplicationControl Start="2013-04-10" End="2013-05-15" InvTypeCode="BV"/>
          <RestrictionStatus Restriction="Master" Status="Open"/>
        </AvailStatusMessage>
        <AvailStatusMessage BookingLimitMessageType="SetLimit" BookingLimit="18">
          <StatusApplicationControl Start="2013-05-16" End="2013-05-18" InvTypeCode="BV"/>
          <RestrictionStatus Restriction="Arrival" Status="Close"/>
        </AvailStatusMessage>
        <AvailStatusMessage BookingLimitMessageType="SetLimit" BookingLimit="15">
          <StatusApplicationControl Start="2013-05-16" End="2013-05-18" InvTypeCode="BV"/>
          <RestrictionStatus Restriction="Departure" Status="Close"/>
        </AvailStatusMessage>
        <AvailStatusMessage>
          <StatusApplicationControl Start="2013-05-19" End="2013-05-20" InvTypeCode="BV"/>
          <RestrictionStatus Status="Close"/>
        </AvailStatusMessage>
        <AvailStatusMessage BookingLimitMessageType="SetLimit" BookingLimit="30">
          <StatusApplicationControl Start="2013-04-10" End="2013-05-20" InvTypeCode="SWV"/>
          <RestrictionStatus Restriction="Master" Status="Open"/>
        </AvailStatusMessage>
        <AvailStatusMessage BookingLimitMessageType="SetLimit" BookingLimit="58">
          <StatusApplicationControl Start="2013-04-10" End="2013-05-20" InvTypeCode="WV"/>
          <RestrictionStatus Restriction="Master" Status="Open"/>
        </AvailStatusMessage>
      </AvailStatusMessages>
    </OTA_HotelAvailGetRS>
  </soap:Body>
</soap:Envelope>
```

Master Open (means Availability exists) Response Message

This Response will give the availability details in above format. In this format Availability status will be defined in <AvailStatusMessage> Sections. These Section can be multiple for Multiple room types. This response will give the maximum availability through out the date range specified in request.

```
<AvailStatusMessage BookingLimitMessageType="SetLimit" BookingLimit="24">
```


Copyright © Prologic First India Pvt. Ltd.

```
    <StatusApplicationControl Start="2013-04-10" End="2013-05-15" InvTypeCode="BV"/>
    <RestrictionStatus Restriction="Master" Status="Open"/>
</AvailStatusMessage>
```

Note: In above response message Room Type “BV” from “2013-04-10” to “2013-05-15” room availability is “24”.

Arrival Close Response Message

```
<AvailStatusMessage BookingLimitMessageType=”SetLimit” BookingLimit=”18”>
  <StatusApplicationControl Start=”2013-05-16” End=”2013-05-18” InvTypeCode=”BV”/>
  <RestrictionStatus Restriction=”Arrival” Status=”Close”/>
</AvailStatusMessage>
```

Note: In above response message Arrival is Closed for Room Type “BV” from “2013-05-16” to “2013-05-18” room availability is “18”.

Departure Close Response Message

```
<AvailStatusMessage BookingLimitMessageType=”SetLimit” BookingLimit=”15”>
  <StatusApplicationControl Start=”2013-05-16” End=”2013-05-18” InvTypeCode=”BV”/>
  <RestrictionStatus Restriction=”Departure” Status=”Close”/>
</AvailStatusMessage>
```

Note: In above response message Departure is Closed for Room Type “BV” from “2013-05-16” to “2013-05-18” room availability is “15”.

Rooms Closed Response Message (No Availability)

```
<AvailStatusMessage>
  <StatusApplicationControl Start="2013-05-19" End="2013-05-20" InvTypeCode="BV"/>
  <RestrictionStatus Status="Close"/>
</AvailStatusMessage>
```

Note: In above response message Rooms are not available for Room Type “BV” from “2013-05-19” to “2013-05-20” .

Usage Profile Table (OTA_HotelAvailGetRS)

Element |@Attribute	Num	Description/Contents
OTA_HotelAvailGetRS	1	Root element of the message.
@EchoToken	0..1	Optional.
@TimeStamp	1	Timestamp of the transaction.
@Version	1	Version is a mandatory attribute in OTA. Therefore it must remain in HTNG in order to be able to use the same message
OTA_HotelAvailGetRS/Success	1	This is the annotation that the availability request was received successfully. It could be combined with warning messages if some of the messages in the

Copyright © Prologic First India Pvt. Ltd.

		batch had issues.
OTA_HotelRatePlanRS / Errors	0..1	Optional.
OTA_HotelRatePlanRS / Errors / Error	1..99	Mandatory.
@Type	1	Mandatory in OTA. Refers to OTA EWT list (error warning type).
@Code	0..1	Optional. Refers to OTA list ERR. Should be used wherever possible.
OTA_HotelAvailGetRS/ AvailStatusMessages		
@ HotelCode	1	Hotel Code the request was for.
@ ChainCode	0..1	Optional.
@ BrandCode	0..1	Optional.
OTA_HotelAvailGetRS/ AvailStatusMessages/AvailStatusMessage	1	The AvailStatusMessage. It is here that one indicates whether the inventory is opened, closed, closed on request, etc.
@BookingLimitMessageType	0..1	If requested mandatory. Enumerated values are used to indicate whether the booking limit sent in the transmission is used to set, adjust or delete the booking limit. (SetLimit, AdjustLimit, RemoveLimit).
@BookingLimit	0..1	If requested mandatory. This is the maximum number of rooms for the **InvTypeCode** sent that can be booked. Although all restrictions are optional, at least one should be sent for the message to have any meaning.
OTA_HotelAvailGetRS/ AvailStatusMessages/AvailStatusMessage/ StatusApplicationControl	1	Information in what the AvailStatus Message applies to (I.e, the combination of inventory and rates codes) and the period of application.
@Start, @End	1	The first and last dates for which the availability update is being sent.
@InvTypeCode	1	The room type code whose availability is being requested.

➢ AcknowledgeAvailabilty

1. Acknowledge availability request

After getting the successful response of OTA_HotelAvailGetRS, User should call web-method "AcknowlegeAvailability" using the following request, this will delete previously retrieved records.

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:typ="http://www.prologicfirst.com/Htng/MasterDataService/Types">
  <soapenv:Header/>
  <soapenv:Body>
    <typ:HotelAvailabilityRequest>
      <typ:SourceID>KSK</typ:SourceID>
      <typ:PropertyID>DEMO</typ:PropertyID>
    </typ:HotelAvailabilityRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

Usage Profile Table (Acknowledgement - HotelAvailabilityRequest)

The availability request is sent using the HotelAvailabilityRequest message.

Copyright © Prologic First India Pvt. Ltd.

Element | @Attribute	Num	Description/Contents
HotelAvailabilityRequest	1	Root element of the message.
HotelAvailabilityRequest / SourceID	1	Mandatory Field, Used for External System Id. Eg. PEGS, SITM, KSK etc.
HotelAvailabilityRequest / PropertyId	1	Mandatory Field, Used for Hotel Code.

2. Acknowledge availability Success Response

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <HotelAvailabilityResponse xmlns="http://www.prologicfirst.com/Htng/MasterDataService/Types">
      <Result resultStatusFlag="SUCCESS" code="">
        <Text xmlns="http://www.prologicfirst.com/Htng/Common/Types">
          <TextElement>Return Value: 0 - Availability successfully acknowledged.</TextElement>
        </Text>
      </Result>
    </HotelAvailabilityResponse>
  </soap:Body>
</soap:Envelope>
```

3. Acknowledge availability Warning Response

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <HotelAvailabilityResponse xmlns="http://www.prologicfirst.com/Htng/MasterDataService/Types">
      <Result resultStatusFlag="WARNING" code="-50">
        <Text xmlns="http://www.prologicfirst.com/Htng/Common/Types">
          <TextElement>No data qualified for Availability Acknowledgment.</TextElement>
        </Text>
      </Result>
    </HotelAvailabilityResponse>
  </soap:Body>
</soap:Envelope>
```

Usage Profile Table (Acknowledgement - HotelAvailabilityResponse)

The Acknowledge Availability response is processed using the HotelAvailabilityResponse message.

Element | @Attribute	Num	Description/Contents
HotelAvailabilityResponse	1	Root element of the message.
HotelAvailabilityResponse / Result	1	Result for Success/Fail
HotelAvailabilityResponse / Result / @ resultStatusFlag	1	SUCCESS / FAIL / WARNING
@ code	1	Any value it can hold.
HotelAvailabilityResponse / Result / Text / TextElement	1	Response / Failure message for User.

Copyright © Prologic First India Pvt. Ltd.

- **GetHotelRatePlan**

The HotelRatePlan message provides the ability to search for active rate plans and offers. The message will be used primarily to ensure that two systems are in sync. It can be used in place of the HotelRatePlanNotif message when a pull model is desired.

The HotelRatePlan Request message allows one system to query another for detailed rate plan information including availability, pricing, and viewership. By supplying different criteria (e.g., specific rate code, dates), the request message can limit the number of rate plans and/or offers returned by the response.

1. Get Hotel Rate Plan Request (OTA_HotelRatePlanRQ)

For Getting Availability for Rates HTNG suggests following xml formats. (Request)

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:ns="http://www.opentravel.org/OTA/2003/05"
xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurityutility-1.0.xsd">
 <soapenv:Header>
  <wsse:Security mustUnderstand="1">
   <wsse:UsernameToken wsu:Id="UsernameToken-72135529">
    <wsse:Username>SUP</wsse:Username>
    <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-
1.0#PasswordText">SUP</wsse:Password>
   </wsse:UsernameToken>
  </wsse:Security>
  <wsa:To>http://localhost/htng/ARIAndReservationPullService.asmx</wsa:To>
  <wsa:Action>http://localhost/htng/ARIAndReservationPullService.asmx/GetHotelRatePlan</wsa:Action>
 </soapenv:Header>
 <soapenv:Body>
  <ns:OTA_HotelRatePlanRQ EchoToken="" TimeStamp="" Target="" Version="">
   <ns:POS>
    <ns:Source>
     <ns:RequestorID  ID="KSK">
     </ns:RequestorID>
    </ns:Source>
   </ns:POS>
   <ns:RatePlans>
    <ns:RatePlan>
     <!--Optional:-->
     <ns:DateRange Start="" End=""/>
     <!--Optional:-->
     <ns:RatePlanCandidates>
      <!--1 or more repetitions:-->
      <ns:RatePlanCandidate RatePlanCode="PERA" />
     </ns:RatePlanCandidates>
     <ns:HotelRef HotelCode="DEMO" />
     <!--Optional:-->
     <ns:TPA_Extensions>
      <!--You may enter any elements at this point-->
      <UpdatedRate>Y</UpdatedRate>
     </ns:TPA_Extensions>
    </ns:RatePlan>
   </ns:RatePlans>
```


Copyright © Prologic First India Pvt. Ltd.

```
    </ns:OTA_HotelRatePlanRQ>
  </soapenv:Body>
</soapenv:Envelope>
```

Login Credentials have been shown in this format, Part of SOAP Header in SOAP Envelope. User Name and password highlighted in the following XML Tag.

```
<wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd">
        <wsse:UsernameToken xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
          <wsse:Username>SUP</wsse:Username>
          <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">SUP</wsse:Password>
        </wsse:UsernameToken>
</wsse:Security>
```

URL of the Web Service has been showing in the following XML Format of the Request Message, part of SOAP Header in SOAP Envelope.

```
<wsa:To> http://localhost/htng/ARIAndReservationPullService.asmx</wsa:To>
```

Usage Profile Table (OTA_HotelRatePlanRQ)

This rate request is sent using the OTA_HotelRatePlanRQ message.

Element | @Attribute	Num	Description/Contents
OTA_HotelRatePlanRQ	1	Root element of the message.
@EchoToken	0..1	Optional.
@TimeStamp	1	Timestamp of the transaction.
@Version	1	Version is a mandatory attribute in OTA. Therefore it must remain in HTNG in order to be able to use the same message
OTA_HotelRatePlanRQ / POS / Source	1	Optional. This holds details regarding the requestor. It may be repeated to also accommodate the delivery systems.
OTA_HotelRatePlanRQ / POS / Source / RequestorID	1	The system sending the request message. An identifier of the entity making the request (e.g. ATA/IATA/ID number, Electronic Reservation Service Provider (ERSP), Association of British Travel Agents (ABTA)).
@Type	1	Type attribute uses the OTA code list UIT. For example, type 22 – ERSP (Electronic reservation service provider).
@Id	1	ID is used for the name or ID of the requestor. For example, Passkey.
OTA_HotelRatePlantRQ / RatePlans	1	Element grouping the rate plans to be transferred.
OTA_HotelRatePlanRQ / RatePlans / RatePlan	1..n	Element defining rate plan being sent. Upper limit to be agreed by trading partners
OTA_HotelRatePlanRQ / RatePlans / RatePlan / DateRange	0..1	Element defining date range criteria requested
@Start, @End	1	This is to request rate data limited to a particular date range
OTA_HotelRatePlanRQ / RatePlans /	1	

Copyright © Prologic First India Pvt. Ltd.

RatePlan / RatePlanCandidates / RatePlanCandidate		
@RatePlanCode	0..1	This is the rate plan which is being uploaded/downloaded
OTA_HotelRatePlanRQ / RatePlans / RatePlan / RatePlanCandidates / RatePlanCandidate/ HotelRef	1	This is the code of the property
OTA_HotelRatePlanRQ / RatePlans / RatePlan / TPA_Extensions	1	
OTA_HotelRatePlanRQ / RatePlans / RatePlan / TPA_Extensions/ UpdatedRate		If "Y" then External System will get Updated Rates of WISH. If "N" then External System will get Complete Rates of WISH.

2. Get Hotel Rate Plan Response (OTA_HotelRatePlanRS)

Response XML Message from WISH will be in the following format as per HTNG Standards.

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
            xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
            xmlns:xsd="http://www.w3.org/2001/XMLSchema"
            xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
            xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
            xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
  <soap:Header>
<wsa:Action>http://localhost/htng/ARIAndReservationPullService.asmx/GetHotelRatePlanResponse</wsa:Action
>
    <wsa:MessageID>urn:uuid:f25a22d7-ed9e-4fb2-b6e3-749a85f3c5bf</wsa:MessageID>
    <wsa:RelatesTo>urn:uuid:c7c4ab53-2942-4245-b16a-036c8452e49b</wsa:RelatesTo>
    <wsa:To>http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:To>
    <wsse:Security>
      <wsu:Timestamp wsu:Id="Timestamp-b3042470-e580-4606-b957-780ef1ed28f5">
        <wsu:Created>2012-11-16T08:12:22Z</wsu:Created>
        <wsu:Expires>2012-11-16T08:17:22Z</wsu:Expires>
      </wsu:Timestamp>
    </wsse:Security>
  </soap:Header>
  <soap:Body>
    <OTA_HotelRatePlanRS TimeStamp="2012-11-16T06:39:08.7797082Z" Version="1"
xmlns="http://www.opentravel.org/OTA/2003/05">
      <Success/>
      <RatePlans HotelCode="DEMO">
        <RatePlan Start="2012-04-04" End="2014-04-03" DecimalPlaces="2" RatePlanCode="PERA"
RatePlanCategory="O" RatePlanNotifType="New" MarketCode="ISDR">
          <BookingRules>
            <BookingRule>
              <LengthsOfStay>
                <LengthOfStay Time="2" TimeUnit="Day" MinMaxMessageType="SetMinLOS"/>
              </LengthsOfStay>
              <LengthsOfStay>
                <LengthOfStay Time="4" TimeUnit="Day" MinMaxMessageType="SetMaxLOS"/>
              </LengthsOfStay>
              <LengthsOfStay>
                <LengthOfStay Time="3" TimeUnit="Hour" MinMaxMessageType="SetMinLOS"/>
              </LengthsOfStay>
```


Copyright © Prologic First India Pvt. Ltd.

```
          </BookingRule>
        </BookingRules>
        <Rates>
          <Rate Start="2012-04-03" End="2014-04-03" Mon="true" Tue="true" Weds="true" Thur="true" Fri="true"
Sat="true" Sun="true" CurrencyCode="EURO" DecimalPlaces="2" InvTypeCode="BV">
            <BaseByGuestAmts>
              <BaseByGuestAmt AmountBeforeTax="100.0000" RateOverrideIndicator="true" NumberOfGuests="1"
AgeQualifyingCode="10"/>
              <BaseByGuestAmt AmountBeforeTax="200.0000" RateOverrideIndicator="true" NumberOfGuests="2"
AgeQualifyingCode="10"/>
              <BaseByGuestAmt AmountBeforeTax="300.0000" RateOverrideIndicator="true" NumberOfGuests="3"
AgeQualifyingCode="10"/>
            </BaseByGuestAmts>
            <AdditionalGuestAmounts>
              <AdditionalGuestAmount AgeQualifyingCode="12" Amount="150.0000"/>
              <AdditionalGuestAmount AgeQualifyingCode="9" Amount="250.0000"/>
              <AdditionalGuestAmount AgeQualifyingCode="8" Amount="50.0000"/>
            </AdditionalGuestAmounts>
          </Rate>
          <Rate Start="2012-04-03" End="2014-04-03" Mon="true" Tue="true" Weds="true" Thur="true" Fri="true"
Sat="true" Sun="true" CurrencyCode="EURO" DecimalPlaces="2" InvTypeCode="SWV">
            <BaseByGuestAmts>
              <BaseByGuestAmt AmountBeforeTax="100.0000" RateOverrideIndicator="true" NumberOfGuests="1"
AgeQualifyingCode="10"/>
              <BaseByGuestAmt AmountBeforeTax="200.0000" RateOverrideIndicator="true" NumberOfGuests="2"
AgeQualifyingCode="10"/>
              <BaseByGuestAmt AmountBeforeTax="300.0000" RateOverrideIndicator="true" NumberOfGuests="3"
AgeQualifyingCode="10"/>
            </BaseByGuestAmts>
            <AdditionalGuestAmounts>
              <AdditionalGuestAmount AgeQualifyingCode="12" Amount="150.0000"/>
              <AdditionalGuestAmount AgeQualifyingCode="9" Amount="250.0000"/>
              <AdditionalGuestAmount AgeQualifyingCode="8" Amount="50.0000"/>
            </AdditionalGuestAmounts>
          </Rate>
          <Rate Start="2012-04-03" End="2014-04-03" Mon="true" Tue="true" Weds="true" Thur="true" Fri="true"
Sat="true" Sun="true" CurrencyCode="EURO" DecimalPlaces="2" InvTypeCode="WV">
            <BaseByGuestAmts>
              <BaseByGuestAmt AmountBeforeTax="100.0000" RateOverrideIndicator="true" NumberOfGuests="1"
AgeQualifyingCode="10"/>
              <BaseByGuestAmt AmountBeforeTax="200.0000" RateOverrideIndicator="true" NumberOfGuests="2"
AgeQualifyingCode="10"/>
              <BaseByGuestAmt AmountBeforeTax="300.0000" RateOverrideIndicator="true" NumberOfGuests="3"
AgeQualifyingCode="10"/>
            </BaseByGuestAmts>
            <AdditionalGuestAmounts>
              <AdditionalGuestAmount AgeQualifyingCode="12" Amount="150.0000"/>
              <AdditionalGuestAmount AgeQualifyingCode="9" Amount="250.0000"/>
              <AdditionalGuestAmount AgeQualifyingCode="8" Amount="50.0000"/>
            </AdditionalGuestAmounts>
          </Rate>
        </Rates>
        <Description Name="Short Description">
          <Text>SHORT DESC PERA</Text>
        </Description>
        <Description Name="Long Description">
```


Copyright © Prologic First India Pvt. Ltd.

```
        <Text>LONG DESCRIPTION PERA</Text>
       </Description>
      </RatePlan>
     </RatePlans>
    </OTA_HotelRatePlanRS>
  </soap:Body>
</soap:Envelope>
```

Usage Profile Table (OTA_HotelRatePlanRS)

The rate plan response is sent using the OTA_HotelRatePlanRS message.

Element | @Attribute	Num	Description/Contents
OTA_HotelRatePlanRS	1	Root element of the message.
@Timestamp	1	Time of the transaction.
@Version	1	Version is a mandatory attribute in OTA; therefore, it must remain Mandatory in HTNG in order to be able to use the same message.
OTA_HotelRatePlanRS / Success	1	This is the annotation that the availability status message batch was received successfully. It could be combined with warning messages if some of the messages in the batch had issues.
OTA_HotelRatePlanRS / Errors	0..1	Optional.
OTA_HotelRatePlanRS / Errors / Error	1..99	Mandatory.
@Type	1	Mandatory in OTA. Refers to OTA EWT list (error warning type).
@Code	0..1	Optional. Refers to OTA list ERR. Should be used wherever possible.
OTA_HotelRatePlanRS / RatePlans	1	Element grouping the rate plans to be transferred.
@HotelCode	1	This is the code of the property whose availability is being updated.
OTA_HotelRatePlanRS / RatePlans / RatePlan	1..n	Element defining rate plan being sent. Upper limit to be agreed by trading partners.
@RatePlanCode	1	This is the rate plan which is being uploaded/downloaded.
@RatePlanCategory	0..1	This is the segment/category to which the rate being uploaded/downloaded belongs. Only one RatePlanCategory is acceptable for RatePlan code; therefore, the RatePlanCategory must be the same for all seasons passed.
@MarketCode	0..1	String attribute to indicate the market code for the rate. Only one MarketCode is acceptable for RatePlan code; therefore, the MarketCode must be the same for all seasons passed.
OTA_HotelRatePlanRS / RatePlans / RatePlan / Description	2	This element should be repeated twice: one instance for the short description and the other for the long description of the rate that is being uploaded/downloaded.
@Name	1	This element should be repeated twice: one instance for the short description and the other for the long description of the rate that is being uploaded/downloaded.

Copyright © Prologic First India Pvt. Ltd.

		Its value must be 'Short decription' in one instance and 'Long Description' in the other.
OTA_HotelRatePlanRS / RatePlans / RatePlan / Description / Text	1	This element inside the Description element described above has the actual text corresponding to the long and short description of the rate being uploaded/downloaded.
OTA_HotelRatePlanRS / RatePlans / RatePlan/ BookingRules/ BookingRule	1..n	
OTA_HotelRatePlanRS / RatePlans / RatePlan/ BookingRules/ BookingRule/ LengthsOfStay/ LengthOfStay	0..1	Length of Stay can have min LOS, Max LOS and Min LOS for hour
OTA_HotelRatePlanRS / RatePlans / RatePlan / Rates	0..1	Includes all rates loaded for the rate plan.
OTA_HotelRatePlanRS / RatePlans / RatePlan / Rates / Rate	1..n	Upper limit may be agreed upon partners.
@Start, @End	0..1	This set of Start and End attribute represent the start and end of each season which is being transferred with the rate. HOWEVER, if the Start and End attribute at rate plan level are used to indicate each season, the Start and End attribute at rate level WOULD ONLY BE USED in case of DOW variations – if no DOW variation is needed the Start and end attributes at Rate level could be omitted.
@CurrencyCode	1	This is the currency associated to the rate that is being uploaded/downloaded – it could be different to the currency loaded for the property.
@Mon,@Tue,@Weds,@Thur, @Fri,@Sat,@Sun	0..1 per day	These DOW indicators are used to specify to which days the rate passed is applicable. If one is sent, they must all be sent and rates must be sent for each exception. If there is an exception to the pricing DOW indicators must be passed and the Rate element is then repeated for the exception days. Exceptions to the pricing are only allowed if no stay or arrival restrictions have been applied.
@InvTypeCode	1	This is the room type for which the rates are transferred. For each room type a new instance of the Rate element must be passed.
OTA_HotelRatePlanRS / RatePlans / RatePlan / Rates / Rate / BaseByGuestAmnts / BaseByGuestAmt	1..n	At least one instance for NumberOfGuest=1 is mandatory for the RatePlanNotifType New or Overlay. For the RatePlanNotifType of Delta or Remove it is optional.
@NumberOfGuests	1	The NumberOfGuest Attribute indicates what type of rate is being passed – if NumberOfGuests is = 1 then we are transmitting a single rate, if higher than 1 then it is a double or full occupancy rate.
@AmountBeforeTax or @AmountAfterTax	1	Either @AmountBeforeTax or AmountAfterTax is Mandatory for each @NumberOfGuests. Partners must select whether to send either the @AmountBeforeTax or @AmountAfterTax (or both) attributes.
OTA_HotelRatePlanRS / RatePlans /	0..n	Used to transfer extra adult and extra child

Copyright © Prologic First India Pvt. Ltd.

RatePlan / Rates / Rate / AdditionalGuestAmounts / AdditionalGuestAmount		information.
@AgeQualifyingCode	0..1	@AgeQualifyingCode - 8 = child, 9 = Teenager, 10 = adult, 12 = Additional occupant with adult

➢ AcknowledgeRates

1. Acknowledge Rate request

After getting the successful response of OTA_HotelRatePlanRS, User should call web-method "AcknowlegeRates" using the following request, this will delete previously retrieved records.

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:typ="http://www.prologicfirst.com/Htng/MasterDataService/Types">
  <soapenv:Header/>
  <soapenv:Body>
    <typ:HotelRateRequest>
      <typ:SourceID>WISH</typ:SourceID>
      <typ:PropertyID>DEMO</typ:PropertyID>
    </typ:HotelRateRequest>
  </soapenv:Body>
</soapenv:Envelope>
```

Usage Profile Table (Acknowledgement - HotelRateRequest)

The availability request is sent using the HotelRateRequest message.

Element | @Attribute	Num	Description/Contents
HotelRateRequest	1	Root element of the message.
HotelRateRequest / SourceID	1	Mandatory Field, Used for External System Id. Eg. PEGS, SITM, KSK etc.
HotelRateRequest / PropertyId	1	Mandatory Field, Used for Hotel Code.

2. Acknowledge Rates Success Response

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <HotelRateResponse xmlns="http://www.prologicfirst.com/Htng/MasterDataService/Types">
      <Result resultStatusFlag="SUCCESS" code="">
        <Text xmlns="http://www.prologicfirst.com/Htng/Common/Types">
          <TextElement>Return Value: 0 - Rates successfully acknowledged.</TextElement>
        </Text>
      </Result>
    </HotelRateResponse>
  </soap:Body>
</soap:Envelope>
```

Usage Profile Table (Acknowledgement - HotelRateResponse)

The Acknowledge Availability response is processed using the HotelRateResponse message.

Copyright © Prologic First India Pvt. Ltd.

Element | @Attribute	Num	Description/Contents
HotelRateResponse	1	Root element of the message.
HotelRateResponse / Result	1	Result for Success/Fail
HotelRateResponse / Result / @ resultStatusFlag	1	SUCCESS / FAIL / WARNING
@ code	1	Any value it can hold.
HotelRateResponse / Result / Text / TextElement	1	Response / Failure message for User.

➢ RetrieveReservations

The basic reservation retrieval usage profile covers the basic use case in which one system queries another system for a particular reservation by passing the confirmation number and verification information.

1. Retrieve Reservations Request (OTA_ReadRQ)

The reservation retrieval request will make use of the OTA_ReadRQ message
For Getting Reservations, HTNG suggests following xml formats. (Request)

```
<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing">
  <soap:Header>
    <wsa:Action>http://htng.org/2010B/HTNG_ARIAndReservationPullService#RetrieveReservations</wsa:Action>
    <wsa:MessageID>urn:uuid:9b38c723-464c-4ef9-a628-76b027df9ac9</wsa:MessageID>
    <wsa:ReplyTo>
      <wsa:Address>http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:Address>
    </wsa:ReplyTo>
    <wsa:To>http://localhost/htng/ARIAndReservationPullService.asmx</wsa:To>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-
1.0.xsd">
      <wsse:UsernameToken xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-
utility-1.0.xsd">
        <wsse:Username>SUP</wsse:Username>
        <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-
1.0#PasswordText">SUP</wsse:Password>
      </wsse:UsernameToken>
    </wsse:Security>
  </soap:Header>
```


Copyright © Prologic First India Pvt. Ltd.

```
<soap:Body>
 <OTA_ReadRQ EchoToken="" Version="1" xmlns="http://www.opentravel.org/OTA/2003/05">
  <POS>
   <Source TerminalID="">
    <RequestorID Type="18" ID="WISH"/>
   </Source>
  </POS>
  <ReadRequests>
   <ReadRequest>
    <UniqueID ID="100001"/>
    <Verification>
     <PersonName>
      <GivenName/>
      <Surname/>
     </PersonName>
     <Email/>
     <TelephoneInfo RPH=""/>
     <PaymentCard CardNumber="" ExpireDate=""/>
     <CustLoyalty MembershipID=""/>
     <ReservationTimeSpan/>
     <TPA_Extensions>
      <LastUpdatedDateTime xmlns="" xmlns:ns3="http://www.opentravel.org/OTA/2003/05"/>
      <GetModifiedRecords xmlns=""
xmlns:ns3="http://www.opentravel.org/OTA/2003/05"></GetModifiedRecords>
      <ConfirmationNumber xmlns=""
xmlns:ns3="http://www.opentravel.org/OTA/2003/05"></ConfirmationNumber>
     </TPA_Extensions>
    </Verification>
   </ReadRequest>
  </ReadRequests>
 </OTA_ReadRQ>
</soap:Body>
</soap:Envelope>
```

Login Credentials have been shown in this format, Part of SOAP Header in SOAP Envelope. User Name and password highlighted in the following XML Tag.

```
<wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-
1.0.xsd">
        <wsse:UsernameToken xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-
wssecurity-utility-1.0.xsd">
         <wsse:Username>SUP</wsse:Username>
         <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-
profile-1.0#PasswordText">SUP</wsse:Password>
        </wsse:UsernameToken>
</wsse:Security>
```

URL of the Web Service has been showing in the following XML Format of the Request Message, part of SOAP Header in SOAP Envelope.

```
<wsa:To> http://localhost/htng/ARIAndReservationPullService.asmx</wsa:To>
```

Usage Profile Table (OTA_ReadRQ)

Copyright © Prologic First India Pvt. Ltd.

Element | @Attribute	Num	Description/Contents
OTA_ReadRQ	1	Root element of the message.
@EchoToken	0..1	As per OTA Specifications.
@Version	1	Version is a mandatory attribute in OTA – therefore it must remain mandatory in HTNG in order to be able to use the same message
@TimeStamp	1	time of the transaction
OTA_ReadRQ / POS / Source / RequestorID	1	This identifies the system which is sending the reservation.
@Type	1	Type attribute uses the OTA code list UIT and ID is used for the name or ID of the requestor. For example, type 22 – ERSP (Electronic reservation service provider) and ID: SynXis
@ID	1	The Id used will be agreed to by the trading partners and remain the same throughout the messages
OTA_ReadRQ / ReadRequests / HotelReadRequest	1	Must be sent for the message to have a meaning. For a pull reservation, the HotelReadRequest element will be used since the confirmation number is not known.
@HotelCode	1	This is the property for which the reservations are being transferred.
@ChainCode	0..1	ChainCode indicates the chain to which the property belongs.
@BrandCode	0..1	BrandCode indicates the Brand within the Chain to which the property belongs.
OTA_ReadRQ / ReadRequests / HotelReadRequest/ Verification / PersonName	0..1	Detailed name information
OTA_ReadRQ / ReadRequests / HotelReadRequest / Verification / PersonName / GivenName		First Name
OTA_ReadRQ / ReadRequests / HotelReadRequest / Verification / PersonName / SurName	0..1	Family name, last name.
OTA_ReadRQ / ReadRequests / HotelReadRequest / Verification/Email	0..1	Information on an email address.
OTA_ReadRQ / ReadRequests / HotelReadRequest / Verification/TelephoneInfo	0..1	Information on a telephone number.
@PhoneNumber	0..1	Telephone number assigned to a single location.
OTA_ReadRQ / ReadRequests / HotelReadRequest / Verification/PaymentCard	0..1	Payment Card information.
@CardNumber	0..1	Credit card number embossed on the card.
OTA_ReadRQ / ReadRequests / HotelReadRequest / Verification/ CustLoyalty	0..1	Program rewarding frequent use by accumulating credits for services provided by vendors.
@MembershipID	0..1	Unique identifier of the member in the program (membership number, account number, etc.).
OTA_ReadRQ / ReadRequests / HotelReadRequest / Verification/ ReservationTimeSpan	0..1	The start and end date of the reservation.
@End	0..1	The ending value of the time span.
@Start	0..1	The starting value of the time span.

Copyright © Prologic First India Pvt. Ltd.

OTA_ReadRQ / ReadRequests / HotelReadRequest / Verification/ TPA_Extensions		
@ LastUpdatedDateTime	1	Search based Bookings created/modified after this mentioned date.
@ GetModifiedRecords	1	If value is “Y” then it will return reservations created/modified in PMS. Note : Advance Control “GSTSRC” should be “”Y to take care of this case. If this value is “Y” then @LastUpdatedDateTime is of no use.
ConfirmationNumber	1	Search based on PMS Confirmation No

2. Retrieve Reservations Response (OTA_ReadRQ)

Response XML Message from WISH will be in the following format as per HTNG Standards.

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:wsse="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
  <soap:Header>
<wsa:Action>http://localhost/htng/ARIAndReservationPullService.asmx/RetrieveReservationsResponse</wsa:Ac
tion>
    <wsa:MessageID>urn:uuid:3fae6b13-94eb-46cf-9d2e-f91b7713cb77</wsa:MessageID>
    <wsa:RelatesTo>urn:uuid:19b3ba3b-1292-45b3-beb2-6bcb78fc1d18</wsa:RelatesTo>
    <wsa:To>http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:To>
    <wsse:Security>
      <wsu:Timestamp wsu:Id="Timestamp-13015d1e-87cb-4335-bc9f-42834ffb553b">
        <wsu:Created>2010-12-09T08:19:26Z</wsu:Created>
        <wsu:Expires>2010-12-09T08:24:26Z</wsu:Expires>
      </wsu:Timestamp>
    </wsse:Security>
  </soap:Header>
  <soap:Body>
<OTA_ResRetrieveRS TimeStamp="2011-08-24T06:41:24.2177955Z" Version="0" TransactionStatusCode="Start"
xmlns="http://www.opentravel.org/OTA/2003/05">
    <ReservationsList>
      <HotelReservation CreateDateTime="2010-06-02T15:22:00" CreatorID="CRS#" LastModifyDateTime="2010-06-
06T00:00:00" LastModifierID="CRS#" ResStatus="Commit">
        <UniqueID Type="14" ID="199147"/>
        <RoomStays>
          <RoomStay RoomStayStatus="Reserved">
            <RoomTypes>
              <RoomType RoomTypeCode="JR" RoomID="82">
                <RoomDescription Language="en-US">
                  <Text Language="en-US">JUNIOR SUITE</Text>
                </RoomDescription>
              </RoomType>
            </RoomTypes>
            <RatePlans>
              <RatePlan RatePlanCode="ERM0" RatePlanName="EURO NET"/>
            </RatePlans>
```


Copyright © Prologic First India Pvt. Ltd.

```
          <RoomRates>
            <RoomRate>
              <Rates>
                <Rate EffectiveDate="2010-06-07" ExpireDate="2010-06-12" RateTimeUnit="Day"
RateTypeCode="ERM0">
                  <Base AmountBeforeTax="276.0000" CurrencyCode="EURO"/>
                </Rate>
                <Rate EffectiveDate="2010-06-12" ExpireDate="2010-06-15" RateTimeUnit="Day"
RateTypeCode="COSO">
                  <Base AmountBeforeTax="0.0000" CurrencyCode="EURO"/>
                </Rate>
              </Rates>
            </RoomRate>
          </RoomRates>
          <GuestCounts>
            <GuestCount AgeQualifyingCode="10" Count="2"/>
            <GuestCount AgeQualifyingCode="8" Count="1"/>
            <GuestCount AgeQualifyingCode="9" Count="1"/>
          </GuestCounts>
          <TimeSpan Start="2010-06-07" End="2010-06-15"/>
          <Guarantee>
            <GuaranteesAccepted>
              <GuaranteeAccepted GuaranteeTypeCode="CSH">
                <PaymentCard CardCode="" CardNumber="" ExpireDate=""/>
              </GuaranteeAccepted>
            </GuaranteesAccepted>
          </Guarantee>
          <BasicPropertyInfo HotelCode="LPM" HotelCityCode="MAURITIUS" HotelName="LE PRINCE, MAURICE"/>
          <TPA_Extensions>
            <KeepRate xmlns="">Y</KeepRate>
            <DayUse xmlns="">Y</DayUse>
            <SpecialGuest xmlns="">N</SpecialGuest>
            <ChannelId xmlns="">SFCR</ChannelId>
            <SubChannelId xmlns="">HSD</SubChannelId>
            <AllowSameConfirmationNo xmlns="">N</AllowSameConfirmationNo>
            <ConfirmationNo xmlns="">10046296</ConfirmationNo>
            <CreateIndividualBooking xmlns="">N</CreateIndividualBooking>
            <ContactEmail xmlns=""></ContactEmail>
            <Guaranteed xmlns="">Y</Guaranteed>
            <GuestClass xmlns="">REG</GuestClass>
            <GSTINNumber xmlns=""></GSTINNumber>
            <SVCardNumber xmlns=""></SVCardNumber>
             <GuestNotes xmlns="">BASE AMOUNT : RS.22291</GuestNotes>
            <VATFiscalNo xmlns=""></VATFiscalNo>
            <CashOnly xmlns="">N</CashOnly>
             <SharePersonalInfo xmlns="">Y</SharePersonalInfo>
            <StorePersonalInfo xmlns="">Y</StorePersonalInfo>
          </TPA_Extensions>
          <Comments>
            <Comment GuestViewable="true">
              <Text>RM INCL ABF TO TA</Text>
            </Comment>
```


Copyright © Prologic First India Pvt. Ltd.

```
          </Comments>
          <Memberships>
            <Membership ProgramCode="" AccountID=""/>
          </Memberships>
        </RoomStay>
      </RoomStays>
      <Services>
        <Service ServiceInventoryCode="NB"/>
      </Services>
      <ResGuests>
        <ResGuest>
          <Profiles>
            <ProfileInfo>
              <UniqueID Type="1" ID="0"/>
              <Profile ProfileType="1">
                <Customer>
                  <PersonName>
                    <NamePrefix>MR</NamePrefix>
                    <GivenName>MARTIAL</GivenName>
                    <Surname>DELIAT</Surname>
                  </PersonName>
                  <Telephone PhoneNumber="0682252366" FormattedInd="false"/>
                  <Email/>
                  <Address Type="1">
                    <AddressLine>14 RUE DES RECOLLETS</AddressLine>
                    <AddressLine/>
                    <AddressLine/>
                    <CityName>BRIVE</CityName>
                    <PostalCode>19100</PostalCode>
                    <StateProv StateCode=""/>
                    <CountryName Code="">FRANCE</CountryName>
                  </Address>
                  <CustLoyalty ProgramID="" MembershipID=""/>
                </Customer>
              </Profile>
            </ProfileInfo>
            <ProfileInfo>
              <UniqueID Type="5" ID="TOURINTR"/>
              <Profile ProfileType="4">
                <CompanyInfo>
                  <CompanyName>TOURINTER FRANCE</CompanyName>
                  <AddressInfo Type="2">
                    <AddressLine>42 RUE DE L`UNIVERSITE</AddressLine>
                    <CityName>LYON</CityName>
                    <PostalCode>69007</PostalCode>
                    <CountryName>FRANCE</CountryName>
                  </AddressInfo>
                  <TelephoneInfo PhoneNumber="02033472771616" PhoneTechType="1" PhoneLocationType="7"
FormattedInd="false"/>
                  <TelephoneInfo PhoneNumber="02033478378092" PhoneTechType="3" FormattedInd="false"/>
                </CompanyInfo>
              </Profile>
            </ProfileInfo>
          </Profiles>
        </ResGuest>
        <ArrivalTransport>
```


Copyright © Prologic First India Pvt. Ltd.

```
            <TransportInfo ID="BA145" Time="2009-12-19T15:00:00" Type="Air"/>
          </ArrivalTransport>
          <DepartureTransport>
            <TransportInfo ID="BA146" Time="2009-12-22T19:00:00" Type="Air"/>
          </DepartureTransport>
        </ResGuests>
        <ResGlobalInfo>
          <HotelReservationIDs>
            <HotelReservationID ResID_Type="14" ResID_Value="199147"/>
            <HotelReservationID ResID_Type="40" ResID_Value="10068061"/>
          </HotelReservationIDs>
        </ResGlobalInfo>
      </HotelReservation>
    </ReservationsList>
    <Success/>
  </OTA_ResRetrieveRS>
 </soap:Body>
</soap:Envelope>
```

The OTA_ResRetrieveRS message is used to return reservations requested by the OTA_ReadRQ message.

Usage Profile Table

Element | @Attribute	Num	Description/Contents
OTA_ResRetrieveRS	1	Root element of the message.
@EchoToken	0..1	As per OTA Specifications.
@Version	1	Version is a mandatory attribute in OTA; therefore, it must remain Mandatory in HTNG in order to be able to use the same message
@TimeStamp	1	Time of the transaction.
OTA_ResRetrieveRS / ReservationsList /	1	Must be sent for the message to have a meaning.
OTA_ResRetrieveRS / ReservationsList / HotelReservation	0...n	Contains the reservations which match the requested criteria. The HotelReservation node should be identical to the HotelReservation node used in the OTA_HotelResNotifRQ messages for book, modify, and cancel. If a HotelReservation node does not exist, no reservations are available which meet the search criteria.
@CreatorID	1	The CreatorID is the identifier of the user or, in its absence, the office that originated the reservation.
@ CreateDateTime	1	This is the date when the reservation was first made.
@ResStatus	1	Commit or Modify
OTA_ResRetrieveRS / ReservationsList /HotelReservation / UniqueID	1	The unique ID depends on the system generating the booking, i.e. if the booking is generated by the PMS this field would contain the PMS confirmation number , if the system is a CRS, the CRS confirmation number. The Unique ID generated by the system originating the booking must be carried through to the final receiver of the booking (generally the PMS) to ensure that the client can use the same confirmation number whether he / she deals with the web site originating the booking or the central reservation office of the hotel or the property itself
@Type	1	Type is assigned codes from the UIT (Unique Id Type) code list.

Copyright © Prologic First India Pvt. Ltd.

		If the originator is a CRS the recommended value for this message is 14 – Reservation. If the originator is a PMS the recommended value for this message would be 10 – Hotel
@ID	1	ID is the actual confirmation number
OTA_ResRetrieveRS / ReservationsList /HotelReservation / RoomStays / RoomStay	1..n	One instance of RoomStay per Room type booked.
@RoomStayStatus	1	Indicates the status of the reservation. Values are: Reserved Inhouse Checkedout Cancelled Noshow Waitlisted Requestdenied (TurnAway in WISH)
OTA_ResRetrieveRS / ReservationList / HotelReservation / RoomStays / RoomStay / RoomTypes	1	A collection of Room Types associated with a particular Room Stay.
OTA_ResRetrieveRS / ReservationList / HotelReservation / RoomStays / RoomStay / RoomTypes / RoomType	1	Provides details regarding rooms, usually guest rooms.
@RoomTypeCode	1	Specific system room type code, i.e., A1K, A1Q, etc.
@RoomID	0..1	A string value representing the unique identification of a room if the request is looking for a specific room.
OTA_ResRetrieveRS / ReservationList / HotelReservation / RoomStays / RoomStay / RoomTypes / RoomType / RoomDescription / Text	0..1	Textual information regarding the room .
@Language	0..1	Language identification.
OTA_ResRetrieveRS / ReservationList / HotelReservation / RoomStays / RoomStay / RatePlans / RatePlan	1	Defines the details of the rate plan as used in the booking process.
@RatePlanCode	1	A string value may be used to request a particular code or an ID if the guest qualifies for a specific rate, such as AARP, AAA, a corporate rate, etc., or to specify a negotiated code as a result of a negotiated rate.
@RatePlanName	1	Provides the name of the rate plan or group. Typically used with RatePlanType to further describe the rate plan.
OTA_ResRetrieveRS / ReservationList / HotelReservation / RoomStays / RoomStay /RoomRates / RoomRate / Rates / Rate	1..n	At least one instance of Rate per Rate plan. Multiple instances of the Rate element must be sent if rate changes apply to the booking.
@RateTimeUnit	1	The RateTimeUnit is an enumeration which HTNG should default to “Day”.
@EffectiveDate	1	The Effective date attribute indicates the starting date of when a specific rate value is applied. This is needed when during the stay there are some rate changes and therefore one instance of the Base element applies to part of the stay and another instance of the Base element applies to another part of the stay. The effective date here refers to

Copyright © Prologic First India Pvt. Ltd.

		the Base that is passed in this instance of Rate element.
@ExpireDate	1	The Expire date indicates the day when the specific value of the rate is changed to another value.
OTA_ResRetrieveRS / ReservationList / HotelReservation / RoomStays / RoomStay /RoomRates / RoomRate / Rates / Rate / Base	1	Mandatory in both OTA and HTNG if an instance of RoomRate is passed.
@CurrencyCode	1	CurrencyCode used ISO 4217 codes to indicate the currency of the rate that is being booked.
@AmountBeforeTax OR @AmountAfterTax	1	Either @AmountBeforeTax or AmountAfterTax is Mandatory for each @NumberOfGuests. Partners must select whether to send either the @AmountBeforeTax or @AmountAfterTax (or both) attributes.
OTA_ResRetrieveRS / ReservationList /HotelReservation / RoomStays / RoomStay / GuestCounts	1	Contains the guest counts of the booking.
OTA_ResRetrieveRS / ReservationList /HotelReservation / RoomStays / RoomStay / GuestCounts / GuestCount	1..n	Contains the type and number of guests included in the reservation.
@AgeQualifyingCode	1	The two codes used from the OTA AQC code list are: 8-Child, 10-Adult.
@Count	1	Count will include the number and will be repeated for each Type of guest.
OTA_ResRetrieveRS / ReservationList / HotelReservation / RoomStays / RoomStay / TimeSpan	1	The Time Span which covers the Room Stay.
@End	1	The ending value of the time span.
@Start	1	The starting value of the time span.
OTA_ResRetrieveRS / ReservationList / HotelReservation / RoomStays / RoomStay / Guarantee	1	An enumerated type defining the guarantee to be applied to this reservation.
@GuaranteeCode	1	Guarantee Code.
OTA_ResRetrieveRS / ReservationList / HotelReservation / RoomStays / RoomStay / Guarantee / GuaranteesAccepted / PaymentCard	0..1	Identification about a specific credit card.
@CardNumber	1	Mandatory if credit card guarantee info is passed. This is the actual number of the credit card used as guarantee.
@CardCode	0..1	The Card code is the 2-letter code indicative of the card (VS, MC, AX, etc.).
@ExpireDate	0..1	Mandatory if credit card guarantee info is passed. This is the expiry date of the credit card used as guarantee.
OTA_ResRetrieveRS / ReservationList / HotelReservation / RoomStays / RoomStay / BasicPropertyInfo	1	
@HotelCode	1	This is the property for which the reservations are being transferred.
@ChainCode	0..1	ChainCode indicates the chain to which the property belongs.
@BrandCode	0..1	BrandCode indicates the Brand within the Chain to which the property belongs.
OTA_ResRetrieveRS / ReservationList	0..n	The element Membership is Optional but both attributes

Copyright © Prologic First India Pvt. Ltd.

/ HotelReservation / RoomStays / RoomStay / Memberships / Membership		would need to be Mandatory.
@ProgramCode	1	The loyalty program to which the account ID belongs to.
@AccountID	1	The account that needs to be credited with points for the stay booked.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest /	1..n	
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / UniqueID	0..9	Used to allow additional ids for matching purposes
@ Type	1	The Type attribute refers to OTA code type UIT and the choices recommended by HTNG should be: 1 – Customer 4 – Company 5 –Travel Agency
@ID	1	The actual ID.
OTA_ResRetrieveRS / ReservationList / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / UniqueID / CompanyName	0..1	Further identifier
@Code	1	
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile	1..n	
@ProfileType	1	This is used to pass the profile info for the guest, the Company, and the Travel agency. For the individual guest the code used in ProfileType is the OTA PRT code 1- [Customer], For a company it is PRT Code – 3 [Corporation]. For a travel agency it is PRT code 4 – [Travel agent].
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer	1	Guest Information
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / PersonName / NamePrefix	0..1	Optional but should be highly recommended by HTNG that partners use it if possible. This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's name Prefix.
OTA_ResRetrieveRS / ReservationList / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / PersonName / GivenName	0..1	Optional. This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's name First name.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / PersonName / Surname	1	Mandatory if a guest profile is passed. This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's name Surname.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo /	1..n	Mandatory if a guest profile is passed. This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be

Copyright © Prologic First India Pvt. Ltd.

Profile / Customer / Telephone		used to pass the guest's phone numbers and fax number.
@PhoneLocationType	0..1	The PhoneLocationType attribute refers to the OTA PLT code list and indicates where the phone number is based - the values to be used by HTNG are: 6 - Home, 7 - Office, 8 - Other (e.g., cell phone).
@PhoneTechType	0..1	The PhoneTechType attribute refers to the OTA PTT code list and indicates which type of number is transmitted (phone *versus* fax). The codes to be used by HTNG are: code 1 -Voice, code 3 -Fax code 5 - Mobile.
@PhoneNumber	1	PhoneNumber contains the actual number as a string of max 32 characters and it is Mandatory.
@FormattedInd	1	FormattedInd is Mandatory. If the partner can use Country and Area codes then it should be set to NO. If country code and area code are passed then they should not appear again in the PhoneNumber field. If the partner cannot use country and area code then entire number is passed in the PhoneNumber field and FormattedInd. It should be set to YES if the number needs to be parsed as there is a separation of the different parts or set to NO to indicate that the PhoneNumber field contains the entire phone number without a specific format.
OTA_ResRetrieveRS / ReservationList / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Email	0..5	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's email address.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Address	0..5	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's mail address.
@Type	1	The Type attribute uses the OTA code list CLT and indicates the type of address provided (Home - code 1 *versus* business - code 2 or Other - code 3, in the case of the Guest details) and must be passed if an address is passed.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Address / AddressLine	0..5	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's address. More than one line can be sent.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Address / CityName	0..1	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's city.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Address / StateProv	0..1	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's State.
@StateCode	0..1	State expressed in the Standard 2-8 characters code.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests /	0..1	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This

Copyright © Prologic First India Pvt. Ltd.

ResGuest / Profiles / ProfileInfo / Profile / Customer / Address / PostalCode		field would be used to pass the guest's Postal / ZIP code.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Address / CountryName	0..1	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's Country.
@Code	0..1	Country expressed in the Standard ISO 3166 code.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / AddressInfo / AddressLine	0..5	Mandatory if a company or travel agency profile is passed. Address line is repeatable up to 5 times. This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's address. Type attribute is not needed here as it is clearly a business address.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / AddressInfo / CityName	0..1	This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's City.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / AddressInfo / StateProv	0..1	This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's State.
@StateCode	0..1	State expressed in the Standard 2-8 characters code.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / AddressInfo / PostalCode	0..1	This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's postal or ZIP code.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / AddressInfo / CountryName	0..1	Optional. This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's Country.
@Code	0..1	Country expressed in the Standard ISO 3166 codes.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / TelephoneInfo	1..n	This element is used for the Company or Travel Agency's phone and numbers. PhoneLocationType is not needed here as this is an office telephone.
@PhoneTechType	0..1	The PhoneTechType attribute refers to the OTA PTT code list and indicates which type of number is transmitted (phone *versus* fax). The codes to be used by HTNG are: Code 1 –Voice Code 3 –Fax Code 5- Mobile
@PhoneNumber	1	PhoneNumber contains the actual number as a string of max 32 characters and it is Mandatory.
@FormattedInd	1	FormattedInd is Mandatory. If the partner can use Country

Copyright © Prologic First India Pvt. Ltd.

		and Area codes then it should be set to NO. If country code and area code are passed then they should not appear again in the PhoneNumber field. If the partner cannot use country and area code then the entire number is passed in the PhoneNumber field and FormattedInd. It should be set to YES if the number needs to be parsed as there is a separation of the different parts or set to NO to indicate that the PhoneNumber field contains the entire phone number without a specific format.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / Email	0..1	This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's email. EmailType attribute is not needed here as it is clearly a business address.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / ArrivalTransport / TransportInfo	0..1	The 3 attributes below are used to indicate the arrival details for the guests to which the booking pertains.
@Type	0..1	Type is used to indicate the method of conveyance of this guest. Values: Air, Rail, Bus, Boat, Private Auto, Other.
@ID	0..1	ID is the actual identifier of this transportation method (e.g., flight number).
@Time	0..1	Time is the estimated arrival time.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGuests / ResGuest / DepartureTransport / TransportInfo		The 3 attributes are used to indicate the departure details for the guests to which the booking pertains.
@Type	0..1	Type is used to indicate the method of conveyance of this guest. Values: Air, Rail, Bus, Boat, Private Auto, Other.
@ID	0..1	ID is the actual identifier of this transportation method (e.g., flight number).
@Time	0..1	Time is the estimated departure time.
OTA_ResRetrieveRS / ReservationList /HotelReservation / ResGlobalInfo / HotelReservationIDs / HotelReservationID	0..n	The HotelReservationID element can be repeated multiple types to transfer: 1. The PNR number for the reservation assigned by the GDS 2. The reservation number for reservations that are linked to this reservation as associated reservation either for guests travelling together, sharing a room, or as part of an Itinerary
@ResID_Type	1	ResID_Type is assigned values from the UIT code list. 10 – Reservation Server 13 – Internet Broker 14 – Reservation Broker 24 – Travel Agent PNR 25- Associated reservation (travelling with) 26- Associated itinerary reservation 27- Associated shared reservation 34 – Master Itinerary For any other type of system the implementing partners should agree on the appropriate code from the OTA UIT code list.
@ResID_Value	1	If HotelReservationID is passed to transfer the PNR, ResID_Value is the PNR passed by the GDS. If HotelReservationID is passed to transfer the associated

Copyright © Prologic First India Pvt. Ltd.

		reservations, ResID_Value would be the confirmation number of the reservation which is associated to the one that is being transferred.

Copyright © Prologic First India Pvt. Ltd.