❖ **HTNG Web Interface (External System ⇨ WISH Front Office)**

Objective:

This HTNG Web service interface is to interact with WISH from any external system through web methods defined in web service.

1. Push Service (ARIAndReservationPushService)
   Under this service, External system can do the following operations into WISH
   .
   - OTA_HotelResNotifRQ (Reservation Create/Modify/Cancel)
   - OTA_HotelRatePlanNotifRQ (Rates Create/Modify)

To interact with WISH through this web service interface, external system has to add web reference from internet address, given by Prologic First, into their application and then call desired web method of the web service.

All the input parameters and result parameters are in structured format provided by HTNG.

➢ **How to Setup Server and Mapping XML for HTNG:**

In HTNGWebservice's Web.Config XML File set these key values …

```
<appSettings>
   <add key="Server" value="Server\WISH"/>
   <add key="PropertyId" value="PROP1"/>
   <add key="SourceId" value="WISH"/>
   <add key="Database" value="sprocdb"/>
   <add key="UserId" value="OPM1"/>
   <add key="ConfigFilePath" value="Config/"/>
   <add key="HTNGMappingXML" value="Config/XML/HTNGMapping.xml"/>
   <add key="SecurityXML" value="Config/XML/Security.xml"/>
   <add key="CultureInfo" value="en-US"/>
   <add key="DateFormat" value="yyyy-MM-dd"/>
   <add key="DateSeparator" value="-"/>
   <add key="AutoAssignRoomOnCheckin" value="N"/>
   <add key="SUPPRESS_ERROR_MSG" value="Y"/>
   <add key="TAXCalculationByPMS" value="Y"/>
   <add key="SpecialAccountId" value="0"/>
   <add key="AR_SpecialAccountId" value="0"/>
   <add key="SpecialAccountPaymentId" value="0"/>
   <add key="DummyDecimalPlaces" value="0"/>
   <add key="MaxCRSFilesAllowedAsPending" value="10"/>
   <add key="MaxAvailabilityFilesAllowedAsPending" value="1"/>
   <!-- 14->Reservation Id, 40->Confirmation Number -->
   <add key="IDTypeForPDSReservationUpdate" value="14"/>
   <!-- Used for CRS (Specify N if used for CRS else Y) -->
   <add key="DONTMAPLOCALCRSID" value="Y"/>
   <!--Here SynXis expecting CRS from Reservation Response with their ID and
value "PMS" with Guest ID-->
   <add key="ExternalAndPMSSourceValue" value="CRS|PMS"/>
   <!--
Here Specify QikInn PDF Retrieve URL (WISH.Net and I-Pad Integration for
Malaysia)
                    -->
   <add key="QikInnPdfRetrieveUrl"
value="http://ubicompsystem.dyndns.org:8080/ca/qikpadTerminal/retrievePdf"/>
   <add key="ValidateUniqueConfirmationNo" value="N"/>
   <add key="KioskSingleCall" value="Y"/>
```


Copyright © Prologic First India Pvt. Ltd.

```
    <add key="UpdateOTRF_WithGuestId" value="N"/>

    <!--

    BulkPostingMaxTransactionAllowed
    validation where transaction count cannot be more than configured.
    -->
    <add key="BulkPostingMaxTransactionAllowed" value="500"/>

    <!--If UseDefaultEtaEtd = "Y" and 3rd Party not sending this
info then Set as per configuration-->
    <add key="UseDefaultEtaEtd" value="N"/>
    <add key="DefaultEtaTime" value="00:00"/>
    <add key="UseDefaultEtaEtd" value="00:00"/>
    <add key="ApplicationPath" value="~"/>
    <add key="AllowMultiStay" value="N"/>
    <add key="CurrentAddressLength" value="50"/>
    <add key="AllowRoomAssignForComponentRooms" value="N"/>

  </appSettings>
```

Note.

- To handle multi-stay reservations, AllowMultiStay should be “Y” then in that case all modifications/cancellations will be based on external party reference no, currently modify/cancel is based on Guest Id.

Change Server name in Server Key Field.

Mapping Portion

Open HTNGMapping.xml file from config\XML directory for mapping of Master Code of External System codes with that of WISH Master Codes and do the mapping.

Following Mapping Codes needs to be required for Rates/Reservations/Availability

1. **Rate Code Mapping**

For Rate Code, If required then specify default.
Please refer to the following sample.

```
<DEFAULT-RATECODE>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</DEFAULT-RATECODE>

<RATECODE>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</RATECODE>
```


Copyright © Prologic First India Pvt. Ltd.

2. Room Type Mapping

For Room Type Mapping, Default should be blank.
Please refer to the following sample.

```
<DEFAULT-ROOMTYPE>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</DEFAULT-ROOMTYPE>

<ROOMTYPE>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</ROOMTYPE>
```

3. Market Segment Mapping

For Rates:
It is required for Rates Creation in WISH.Net PMS from External System.

For Reservation:
If Market Code is coming from External System is not a blank then following mapping needs to be created.

```
<DEFAULT-MARKETSEGMENT>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </DEFAULT-MARKETSEGMENT>

 <MARKETSEGMENT>
   <Code>CODE1</Code>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </MARKETSEGMENT>
```

4. Business Source Mapping

Please refer to the following sample

```
<DEFAULT-BUSINESSSOURCE>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</DEFAULT-BUSINESSSOURCE >
```


Copyright © Prologic First India Pvt. Ltd.

5. FX Code Mapping

For FX Code Mapping, Please refer to the following sample

```
<DEFAULT-FXCODE>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
 </DEFAULT-FXCODE>

 <FXCODE>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
 </FXCODE>
```

6. Credit Card Code Mapping

For Credit Card Code Mapping, default will be CASH.

Please refer to the following sample

```
 <DEFAULT-PAYMENTMETHOD>
  <WISHCode>CASH</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
 </DEFAULT-PAYMENTMETHOD>

 <PAYMENTMETHOD>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
 </PAYMENTMETHOD>
```

7. Special Service Code Mapping

Please refer to the following sample.

```
 <DEFAULT-SPECIALSERVICE>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
 </DEFAULT-SPECIALSERVICE>

 <SPECIALSERVICE>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
```


Copyright © Prologic First India Pvt. Ltd.

```
</SPECIALSERVICE>
```

8. Title Code Mapping

Please refer to the following sample.

```
<DEFAULT-TITLE>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</DEFAULT-TITLE>

<TITLE>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</TITLE>
```

9. Reason Code Mapping

Reason Code is used for the reason defined in Cancel Reservation
In WISH, there is no code is associated to it, so in PMS default will be get used which is ****

Please refer to the following sample.

```
<DEFAULT-REASONCODE>
  <WISHCode>****</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>PEGS</Source>
</DEFAULT-REASONCODE>

<REASONCODE>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</REASONCODE>
```

10. Travel Agent Mapping

Please refer to the following sample.

```
<DEFAULT-TRAVELAGENTID>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
 </DEFAULT-TRAVELAGENTID>
 <TRAVELAGENTID>
   <Code>CODE1</Code>
   <WISHCode>CODE</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>SOURCE</Source>
```


Copyright © Prologic First India Pvt. Ltd.

```
</TRAVELAGENTID>
```

11. Corporate Mapping

Please refer to the following sample

```
<DEFAULT-CORPACCTID>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</DEFAULT-CORPACCTID>
<CORPACCTID>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</CORPACCTID>
```

12. Terms Mapping

Please refer to the following sample

```
<DEFAULT-MEALPLANID>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</DEFAULT- MEALPLANID>
<MEALPLANID>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</MEALPLANID>
```

13. Guest Class Mapping

Please refer to the following sample.

```
<DEFAULT-GUESTCLASS>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</DEFAULT- GUESTCLASS >

<GUESTCLASS>
  <Code>CODE1</Code>
  <WISHCode>CODE</WISHCode>
  <PropertyId>PROP</PropertyId>
  <Source>SOURCE</Source>
</GUESTCLASS>
```

For Default Mapping of Masters take reference of the following Section –

Copyright © Prologic First India Pvt. Ltd.

```
<DEFAULT-TITLE>
   <WISHCode>MR.</WISHCode>
   <PropertyId>PROP</PropertyId>
   <Source>PEGS</Source>
</DEFAULT-TITLE>
```

If this section is defined then, if any Title from external system is not defined in this xml Will be mapped to 'MR.' Charge code of WISH

Default Section for Each Master should be defined only once in the XML

Take Reference from Config\XML\HTNGMapping.xml file.

Settings need to be defined in Advance control in System Administrator:

Control Code	Description	Int Val	Character Value	Remarks
CHNAVL	Validate Channel Availability (Y)es,(N)o	0	N	Default Char Value : N If User wants to Bookings to use Channel Allocation then Char Value should be "Y" In case User wants to stamp Channel Id for Bookings coming from Channels e.g. Rate Tiger, Salesforce etc but don't want to define channel allocation (or don't want to maintain channel availability) then this will be "N".

Configuration of the Travel Agent & Corporate Accounts

1. For Corporate, please use following id (COMP100) for mapping purpose.

```
<ResGuests xmlns="http://www.opentravel.org/OTA/2003/05">
  <ResGuest ResGuestRPH="1" PrimaryIndicator="true">
   <Profiles>
    <ProfileInfo>
     <UniqueID Type="4" ID_Context="ProfileID" ID="COMP100" />
     <Profile ProfileType="3">
      <CompanyInfo>
       <AddressInfo Type="3">
        <AddressLine>123 main street</AddressLine>
        <CityName>Phoenix</CityName>
        <PostalCode>85010</PostalCode>
        <StateProv StateCode="AZ" />
        <CountryName Code="US" />
       </AddressInfo>
       <TelephoneInfo PhoneNumber="1234567890" PhoneTechType="1" FormattedInd="false" />
       <Email>company1@test.com</Email>
      </CompanyInfo>
     </Profile>
    </ProfileInfo>
   </Profiles>
  </ResGuest>
```


Copyright © Prologic First India Pvt. Ltd.

```
  </ResGuests>
```

2. For Travel Agent, please use following id (TRAVEL100) for mapping purpose.

```
<ResGuests xmlns="http://www.opentravel.org/OTA/2003/05">
  <ResGuest ResGuestRPH="1" PrimaryIndicator="true">
   <Profiles>
     <ProfileInfo>
      <UniqueID Type="5" ID="TRAVEL100">
       <CompanyName>Travel Agent Test</CompanyName>
      </UniqueID>
      <Profile ProfileType="4">
       <CompanyInfo>
        <AddressInfo>
         <AddressLine>547 West Madison</AddressLine>
         <CityName>New York City</CityName>
         <PostalCode>21207</PostalCode>
         <StateProv StateCode="NY" />
         <CountryName Code="US" />
        </AddressInfo>
        <TelephoneInfo PhoneNumber="212-427-6648" PhoneTechType="1" FormattedInd="false" />
        <Email>travel100@test.com</Email>
       </CompanyInfo>
      </Profile>
     </ProfileInfo>
   </Profiles>
  </ResGuest>
 </ResGuests>
```

- OTA_HotelResNotifRQ

The basic reservation notification usage profile covers the basic use-case in which a system with the ability to book, modify, and/or cancel reservations is notifying other systems of its activity. The intent of the messages exchanged is to keep all the participating systems up-to-date on all reservations at the property.

This usage profile includes simple reservations.

```
<soapenv:Envelope xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurityutility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
 <soapenv:Header>
  <wsse:Security mustUnderstand="1">
   <wsse:UsernameToken wsu:Id="UsernameToken-72135529">
    <wsse:Username>SUP</wsse:Username>
    <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">SUP</wsse:Password>
   </wsse:UsernameToken>
  </wsse:Security>
  <!--<wsa:MessageID>http://localhost/msg?id=72135530</wsa:MessageID> -->
  <wsa:To>http://localhost/htng/ARIAndReservationPushService.asmx</wsa:To>
<wsa:Action>http://localhost/htng/ARIAndReservationPushService.asmx/OTA_HotelResNotifRQ</wsa:Action>
 </soapenv:Header>
```


Copyright © Prologic First India Pvt. Ltd.

```
  <soapenv:Body>
    <OTA_HotelResNotifRQ xmlns="http://www.opentravel.org/OTA/2003/05"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation=http://www.opentravel.org/OTA/2003/05 OTA_HotelResNotifRQ.xsd EchoToken="6079"
PrimaryLangID="en-us" Target="Test" TimeStamp="2009-09-16T15:04:56" Version="2.001" ResStatus="Commit">
       <POS>
         <Source ISOCountry="DE" PseudoCityCode="RESOFFFRA">
          <RequestorID ID="TrustCRS" Type="22"/>
          <BookingChannel Primary="true" Type="5">
           <CcompanyName Code="VC"/>
          </BookingChannel>
         </Source>
       </POS>
     <HotelReservations>
      <HotelReservation CreateDateTime="2009-09-16T15:00:24" CreatorID="HEOWFRAN" LastModifierID="HEOWFRAN"
LastModifyDateTime="2009-09-16T15:00:24" >
        <UniqueID ID="6079" Type="14"/>
        <RoomStays>
         <RoomStay MarketCode="ANDY" SourceOfBusiness="WEBS">
          <RoomTypes/>
          <RatePlans PriceViewableInd="true">
           <RatePlan />
          </RatePlans>
          <RoomRates>
           <RoomRate NumberOfUnits="1" RatePlanCategory="C" RatePlanCode="CB1" RoomTypeCode="A1Q">
            <Rates>
             <Rate EffectiveDate="2009-12-19" ExpireDate="2009-12-20" RateTimeUnit="Day" UnitMultiplier="1">
              <Base AmountBeforeTax="900.00" CurrencyCode="EGP"/>
             </Rate>
             <Rate EffectiveDate="2009-12-20" ExpireDate="2009-12-22" RateTimeUnit="Day" UnitMultiplier="2">
              <Base AmountBeforeTax="550.00" CurrencyCode="EGP"/>
             </Rate>
            </Rates>
           </RoomRate>
          </RoomRates>
          <GuestCounts>
           <GuestCount AgeQualifyingCode="10" Count="1"/>
           <GuestCount AgeQualifyingCode="8" Count="1"/>
          </GuestCounts>
          <TimeSpan End="2009-12-22" Start="2009-12-19"/>
          <Guarantee GuaranteeCode="Credit Card" GuaranteeType="CC/DC/Voucher">
           <GuaranteesAccepted>
            <GuaranteeAccepted>
             <PaymentCard CardCode="VI" CardNumber="4444333322221111" CardType="1" ExpireDate="1009">
              <CardHolderName>Pasetti Francesca/Ms</CardHolderName>
             </PaymentCard>
            </GuaranteeAccepted>
           </GuaranteesAccepted>
          </Guarantee>
          <DepositPayments/>
          <Total AmountAfterTax="1450.00" AmountBeforeTax="1450.00" CurrencyCode="EGP">
           <Taxes/>
          </Total>
          <BasicPropertyInfo HotelCode="DEMO" />
          <TPA_Extensions>
           <KeepRate>Y</KeepRate>
```


Copyright © Prologic First India Pvt. Ltd.

```
            <DayUse>N</DayUse>
            <SpecialGuest>N</SpecialGuest>
            <ChannelId></ChannelId>
            <SubChannelId></ SubChannelId >
            <AllowSameConfirmationNo></ AllowSameConfirmationNo >
            <ConfirmationNo></ConfirmationNo >
            <CreateIndividualBooking></CreateIndividualBooking>
            <ContactEmail></ContactEmail>
            <Guaranteed></Guaranteed>
            <GuestClass></GuestClass>
            <GuestNotes></GuestNotes>
            <VATFiscalNo></VATFiscalNo>
            <GSTINNumber></GSTINNumber>
            <SVCardNumber></SVCardNumber>
            <SHAREPERSONALINFO></SHAREPERSONALINFO>
            <STOREPERSONALINFO></STOREPERSONALINFO>
           </TPA_Extensions>
           <Memberships>
            <Membership AccountID="12345689" ProgramCode="Card1"/>
            <Membership AccountID="12345688" ProgramCode="Card2"/>
           </Memberships>
           <Comments>
            <Comment GuestViewable="true">
             <Text>Test reservation pull format</Text>
            </Comment>
            <Comment GuestViewable="false">
             <Text>Includes rate value changes |RC: 19 DEC 09 -550.00 /</Text>
            </Comment>
           </Comments>
           <SpecialRequests>
            <SpecialRequest RequestCode="VP">
             <Text>VIP GUEST/TREATMENT</Text>
            </SpecialRequest>
            <SpecialRequest RequestCode="TR">
             <Text>AIRPORT TRANSFER/ROUND TRIP</Text>
            </SpecialRequest>
           </SpecialRequests>
          </RoomStay>
         </RoomStays>
         <Services>
          <Service ServiceInventoryCode="NB"/>
         </Services>
         <ResGuests>
          <ResGuest ResGuestRPH="0">
           <Profiles>
            <ProfileInfo>
             <Profile ProfileType="1">
              <Customer>
               <PersonName>
                <NamePrefix>Ms</NamePrefix>
                <GivenName>Francesca</GivenName>
                <Surname>Pasetti</Surname>
               </PersonName>
               <Telephone FormattedInd="false" PhoneLocationType="6" PhoneNumber="49696640110"
PhoneTechType="1"/>
               <Telephone FormattedInd="false" PhoneLocationType="6" PhoneNumber="49696640115"
```


Copyright © Prologic First India Pvt. Ltd.

```
PhoneTechType="3"/>
                <Email DefaultInd="true" EmailType="1">abcd@cd.com</Email>
                <Address Type="1">
                  <AddressLine>Trust Palace</AddressLine>
                  <AddressLine>15 Trust street</AddressLine>
                  <CityName>York</CityName>
                  <PostalCode>YO23 1DU</PostalCode>
                  <StateProv StateCode="NY"/>
                  <CountryName Code="GB"/>
                </Address>
                <Document DocID="P2587979" DocType="2" BirthDate="1970-12-08" EffectiveDate="2008-03-07"
ExpireDate="2018-03-06" DocHolderNationality="DEU" Gender="Female" />
                <CustLoyalty MembershipID="LH7585465445" ProgramID="FrequentGuest"/>
              </Customer>
            </Profile>
          </ProfileInfo>
          <ProfileInfo>
            <UniqueID Type="4" ID_Context="ProfileID" ID="COMP100" />
            <Profile ProfileType="3">
              <CompanyInfo>
                <CompanyName Code="NHC789789" CodeContext="ID2">Hotel Reservation</CompanyName>
                <AddressInfo Type="2">
                  <AddressLine>Trust Palace</AddressLine>
                  <AddressLine>Swinestrasse 18</AddressLine>
                  <CityName>Frankfurt</CityName>
                  <PostalCode>60121</PostalCode>
                  <StateProv StateCode="BV"/>
                  <CountryName Code="DE"/>
                </AddressInfo>
                <TelephoneInfo FormattedInd="false" PhoneLocationType="7" PhoneNumber="49669664456456"
PhoneTechType="1"/>
                <TelephoneInfo FormattedInd="false" PhoneLocationType="7" PhoneNumber="49669664123123"
PhoneTechType="3"/>
                <Email DefaultInd="true" EmailType="2">abcd@cd.com</Email>
              </CompanyInfo>
            </Profile>
          </ProfileInfo>
          <ProfileInfo>
            <UniqueID Type="5" ID="TRAVEL100">
            <Profile ProfileType="4">
              <CompanyInfo>
                <CompanyName Code="NHT123123" CodeContext="ID2">Agency</CompanyName>
                <AddressInfo Type="2">
                  <AddressLine>Travel place</AddressLine>
                  <AddressLine>Surriergate</AddressLine>
                  <CityName>Frankfurt</CityName>
                  <PostalCode>60121</PostalCode>
                  <StateProv StateCode="BV"/>
                  <CountryName Code="DE"/>
                </AddressInfo>
                <TelephoneInfo FormattedInd="false" PhoneLocationType="7" PhoneNumber="49669528528"
PhoneTechType="1"/>
                <TelephoneInfo FormattedInd="false" PhoneLocationType="7" PhoneNumber="59669528529"
PhoneTechType="3"/>
                <Email DefaultInd="true" EmailType="2">abcd@cd.com</Email>
              </CompanyInfo>
```


Copyright © Prologic First India Pvt. Ltd.

```
            </Profile>
          </ProfileInfo>
        </Profiles>
        <ArrivalTransport>
          <TransportInfo ID="BA145" Time="2009-12-19T15:00:00" Type="Air"/>
        </ArrivalTransport>
        <DepartureTransport>
          <TransportInfo ID="BA146" Time="2009-12-22T19:00:00" Type="Air"/>
        </DepartureTransport>
      </ResGuest>
    </ResGuests>
    <ResGlobalInfo>
      <HotelReservationIDs>
        <HotelReservationID ResID_Source="TrustCRS" ResID_Type="14" ResID_Value="6079"/>
        <HotelReservationID ResID_Source="TrustCRS" ResID_Type="26" ResID_Value="6074"/>
      </HotelReservationIDs>
    </ResGlobalInfo>
  </HotelReservation>
 </HotelReservations>
</OTA_HotelResNotifRQ>
</soapenv:Body>
</soapenv:Envelope>
```

Login Credentials have been shown in this format, Part of SOAP Header in SOAP Envelope. User Name and password highlighted in the following XML Tag.

```
<wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd">
        <wsse:UsernameToken xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
          <wsse:Username>SUP</wsse:Username>
          <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#PasswordText">SUP</wsse:Password>
        </wsse:UsernameToken>
      </wsse:Security>
```

URL of the Web Service has been showing in the following XML Format of the Request Message, part of SOAP Header in SOAP Envelope.

```
<wsa:To> http://localhost/htng/ARIAndReservationPushService.asmx</wsa:To>
```

TPA Extentions

HTNG Field DocumentType Attributes	Remarks
TPA_Extensions -> KeepRate	If Y then Keep rate flag will be Y else No.
TPA_Extensions -> DayUse	For Day Use Guest, this should be Y else N
TPA_Extensions -> SpecialGuest	Send Y if Guest is special guest else N
TPA_Extensions -> Channel Id	Optional, If Guest is from channel then send Channel Id Eg. Salesforce
TPA_Extensions -> SubChannelId	Optional, if Guest is from Channel -> Subchannel e.g.

Copyright © Prologic First India Pvt. Ltd.

	Salesforce received booking from Booking.com Then Subchannel will be Booking.com
TPA_Extensions -> AllowSameConfirmationNo	Optional, Default will be N This is used to link multiple reservation under same confirmationno For First Booking, this will be N For Next Booking, this will be Y and TPA_Extensions -> ConfirmationNo will have PMS ConfirmationNo.
TPA_Extensions -> ConfirmationNo	If TPA_Extensions -> AllowSameConfirmationNo = "Y" Then send PMS Confirmation No in this field.
TPA_Extensions -> CreateIndividualBooking	Used for optimization and reduce load on server If Number of Units > 1 and if this value is Y. In this case, it will create same no. of bookings with same details. If Number of Units > 1 and if this value is N. Then it will distribute adult and rate amount accordingly in each booking. It will divide rate with No of Units And distribute adult count based on No Of Rooms received in each booking. So e.g. If No. Of Units = 3 and adult count = 5 Then for 1st Booking it will Update adult count = 3 And remaining 2 bookings as 1.
TPA_Extensions -> ContactEmail	Send Email of Guest.
TPA_Extensions -> Guaranteed	Send Y or N, If Guest is Guaranteed Guest.
TPA_Extensions -> GuestClass	Update Guest Class of Guest. e.g. VIP, NORM etc.
TPA_Extensions -> GuestNotes	Reservation Notes
TPA_Extensions -> VATFiscalNo	Guest's Vat/Fiscal No
TPA_Extensions -> GSTINNumber	Guest's GSTIN Number, Will be stored in Guest Options "GSTN"
TPA_Extensions -> SVCardNumber	Guest's SV Card Number, Will be stored in Guest Options "SVCD"
TPA_Extensions -> SHAREPERSONALINFO	Guest's Preference to share Personal Information or not, will be stored in Guest Options "SHRP". Used for GDPR Compliance
TPA_Extensions -> STOREPERSONALINFO	Guest's Preference to store Personal Information or not, will be stored in Guest Options "PINF". Used for GDPR Compliance

Passport/Identification/Others and Visa Details

1. Passport/Identification/Others

HTNG Field DocumentType Attributes	**Remarks**
@ DocType	**For Passport** Value can be "2", "P","PASSPORT" **For Identification** Value can be "5", "I","IDENTIFICATION" **For Others**

Copyright © Prologic First India Pvt. Ltd.

	Value can be “17”, “XX”
@ DocID	PASSPORT/IDENTIFICATION/OTHER NUMBER
@ DocIssueCountry	ISSUE PLACE
@ DocHolderNationality	NATIONALITY
@ ExpireDate	DATE EXPIRE
@ EffectiveDate	ISSUE DATE
@ BirthDate	GUEST DOB
@ Gender	Male, Female, Unknown

2. Visa

HTNG Field DocumentType Attributes	**Remarks**
DocumentType @ DocType	For Visa Value can be “1”, “V”,”VISA”
@ DocID	VISA NUMBER
@ Remark	VISA TYPE
@ ExpireDate	VISA DATE EXPIRE
@ EffectiveDate	VISA DATE ISSUE

The book reservation request, as well as the Modification and Cancellation request, is made using the OTA_HotelResNotifRQ message.

Usage Profile Table

Element | @Attribute	**Num**	**Description/Contents**
OTA_HotelResNotifRQ	1	Root element of the message.
@EchoToken	0..1	As per OTA Specifications.
@Version	1	Version is a mandatory attribute in OTA; therefore, it must remain Mandatory in HTNG in order to be able to use the same message
@TimeStamp	1	Time of the transaction.
@ResStatus	1	Of all the enumerations listed by OTA, the one recommended by HTNG for this message should be:“Commit”
OTA_HotelResNotifRQ / POS / Source / RequestorID	1	This identifies the system which is sending the reservation.
@Type	1	Type attribute uses the OTA code list UIT and ID is used for the name or ID of the requestor. For example, type 22 – ERSP (Electronic reservation service provider) and ID: TrustCRS.
@ID	1	The ID used will be agreed by the trading partners and remain the same throughout the messages.
OTA_HotelResNotifRQ / POS / Source / BookingChannel	1..2	This element is used to pass the booking source for the reservation. To send secondary booking channel information an additional Source element needs to be sent.
@Type	1	Type is mandatory in OTA and indicates the type of booking channel. Refers to OTA code list BCT (Booking Channel Type): 1 GDS

Copyright © Prologic First India Pvt. Ltd.

		2 PMS etc.
@Primary	1	Primary attribute would be set to “true” if only one booking channel is transferred. Only one source should be marked “true” if multiple sources are sent.
OTA_HotelResNotifRQ / POS / Source / BookingChannel / CompanyName	0	The name of the booking source.
@Code	0..1	Code is Optional and can be used to transfer the code of the Booking channel if such code is a recognized industry standard – the name, however, should always be sent as well as the code.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation	1	Must be sent for the message to have a meaning.
@CreatorID	1	The CreatorID is the identifier of the user or, in its absence, the office that originated the reservation.
@ CreateDateTime	1	This is the date when the reservation was first made.
@ResStatus	0..1	Indicates the current status of the reservation. Valid values are dependant on the roles: Reservation Broker ▫ Reservation Server • Reserved • Waitlisted Reservation Server ▫ Reservation Broker • Reserved • Waitlisted • In-house
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / UniqueID	1	The unique ID is the product of the system which sent the messages. For example, if the message is generated by the PMS, this field would contain the PMS confirmation number; if the system is a CRS, the CRS confirmation number.
@Type	1	Type is assigned codes from the UIT (Unique ID Type) code list. If the originator is a CRS, the recommended value for this message is 14 – Reservation. If the originator is a PMS, the recommended value for this message would be 10 – Hotel.
@ID	1	ID is the actual confirmation number.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay	1..n	One instance of RoomStay per Room type booked.
@MarketCode	0..1	This is the code that relates to the market being sold and may be needed by the PMS for tracking purposes.
@ SourceOfBusiness	0..1	Used to specify where the business came from; e.g., radio, newspaper ad, or it could be a referring property.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / RatePlans /	0..1	The RatePlans element is not required but can be sent to give further details on the rates booked in this reservation.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / RatePlans / RatePlan /	1..n	A collection of rate plans to be booked.
@RatePlanCode	1	This is the code of the rate booked
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / RoomRates / RoomRate /	1..n	One instance of RoomRate per room/rate booked. If multiple room types can be booked, then the element “RoomRate” must be repeated for each room type booked in the reservation. If more than one Rate plan can be booked in one reservation

Copyright © Prologic First India Pvt. Ltd.

		the entire RoomRate element must be repeated for each Room/rate combination.
@RatePlanCategory	0..1	This is the category or segment which the rate being booked belongs to.
@RoomTypeCode	1	This is the room type code booked in the reservation.
@InvBlockCode	0..1	If the room booked is part of a block the block code or suitable default string agreed by the implementing partners should be transferred in this field.
@NumberOfUnits	1	This is the number of rooms booked for the room type code listed in the RoomTypeCode attribute. In the case of shared reservations, this value will always be "1".
@RatePlanCode	1	This is the rate booked for the room type code listed in the RoomTypeCode attribute.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomRates / RoomRate / Rates / Rate	1..n	At least one instance of Rate per Rate plan. Multiple instances of the Rate element must be sent if rate changes apply to the booking.
@RateTimeUnit	1	The RateTimeUnit is an enumeration which HTNG should default to “Day”.
@EffectiveDate	1	The Effective date attribute indicates the starting date of when a specific rate value is applied. This is needed when during the stay there are some rate changes and therefore one instance of the Base element applies to part of the stay and another instance of the Base element applies to another part of the stay. The effective date here refers to the Base that is passed in this instance of Rate element.
@ExpireDate	1	The Expire date indicates the day when the specific value of the rate is changed to another value.
@UnitMultiplier	1	UnitMultiplier indicates how many days the rate is applicable for.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomRates / RoomRate / Rates / Rate / Base	1	Mandatory in both OTA and HTNG if an instance of RoomRate is passed.
@CurrencyCode	1	CurrencyCode used ISO 4217 codes to indicate the currency of the rate that is being booked.
@AmountBeforeTax	0	AmountBeforeTax if available can be sent for each @NumberOfGuests.
@AmountAfterTax	1	AmountAfterTax is Mandatory for each @NumberOfGuests.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / GuestCounts	1	Contains the guest counts of the booking.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / GuestCounts / GuestCount	1..n	Contains the type and number of guests included in the reservation.
@AgeQualifyingCode	1	The two codes used from the OTA AQC code list are: 8-Child, 10-Adult.
@Count	1	Count will include the number and will be repeated for each Type of guest.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / TimeSpan	1	These are the in and out date of the booking.
@Start	1	Check in date.

Copyright © Prologic First India Pvt. Ltd.

@End	1	Check out date.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / Guarantee	0..5	Guarantee provided with the reservation.
@GuaranteeType	1	This is the attribute that indicates what guarantee is provided with the reservation. The enumerated values can be: "GuaranteeRequired" "None" "CC / DC / Voucher" "Profile" "Deposit" "PrePay"
@GuaranteeCode	0..1	This is the guarantee code used in the CRS.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / Guarantee / GuaranteesAccepted / GuaranteeAccepted / PaymentCard	1	
@CardType	0..1	Optional field. However, if it is used, all of the sub-elements and attributes listed below will also need to be sent. This is the code of the card used as guarantee for the booking. CardType uses an OTA list. The only item of the CDT list to be used is nr 1 – Credit to indicate we are passing a credit card.
@CardCode	0..1	The Card code is the 2-letter code indicative of the card (VS, MC, AX, etc.).
@CardNumber	0..1	Mandatory if credit card guarantee info is passed. This is the actual number of the credit card used as guarantee.
@ExpireDate	0..1	Mandatory if credit card guarantee info is passed. This is the expiry date of the credit card used as guarantee.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / Guarantee / GuaranteesAccepted / GuaranteeAccepted / PaymentCard / CardHolderName	0..1	Mandatory if credit card guarantee info is passed. This is the name of the card holder. If the system transmitting the info does not hold the cc holder name, it should not be passed rather than passing incorrect details.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / Total	0..1	This is the total amount for the stay.
@CurrencyCode	1	CurrencyCode used ISO 4217 codes to indicate the currency of the total rate.
@AmountBeforeTax OR @AmountAfterTax	1	Either @AmountBeforeTax or AmountAfterTax is Mandatory for each @NumberOfGuests. Partners must select whether to send either the @AmountBeforeTax or @AmountAfterTax (or both) attributes.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / Total / Taxes	0..1	Optional. Can be used for Total Pricing.
@ Amount	0..1	Total Amount of Taxes applied to the booking.
@CurrencyCode	0..1	Currency of the total Amount of Taxes.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / Total / Taxes / Tax	0..99	Optional. Can be used for Total Pricing.
@Type	0..1	The Type attribute is an enumeration to indicate whether the tax is “inclusive”, “exclusive”, or “cumulative”.
@Code	0..1	The Code attribute refers to OTA list FTT (fee tax type) and is used to indicate the specific tax or fee that is being transferred.

Copyright © Prologic First India Pvt. Ltd.

@Amount	0..1	Amount of the specific tax/fee transferred.
@CurrencyCode	0..1	Currency for the Amount of the specific tax/fee transferred
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / BasicPropertyInfo	1	
@HotelCode	1	This is the property for which the reservations are being transferred.
@ChainCode	0..1	ChainCode indicates the chain to which the property belongs.
@BrandCode	0..1	BrandCode indicates the Brand within the Chain to which the property belongs.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / Comments / Comment	1	
@Name	0..1	Allows types of Comments to be differentiated. Valid values would be determined by Trader-Partners
@GuestViewable	0	This indicates that the comment can actually be seen by the guest and is necessary when two different types of comments are passed: one which is guest viewable and one that isn't. The Attribute is of Boolean nature. If this is true then it will set the value in billing instructions If this is false then value will be shown in remarks.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / Comments / Comment / Text	1	Comments
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / SpecialRequests / SpecialRequest /	0..n	
@RequestCode	1	Indicates the special requests associated to the reservation. If a special request is passed it must be passed with the RequestCode attribute, which is therefore conditionally Mandatory. If no code is available the partners should agree on a code to be transferred in conjunction with the TEXT element below.
@CodeContext	0..1	If the system sending the information differentiates the request codes in various groups (for instance, room features *versus* special requests, etc.), the context of the code should be sent to indicate whether the request sent is indeed a room feature or a special request or belongs to any other grouping – must be agreed upon implementing partners based on the functionality of the systems involved.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / RoomStays / RoomStay / SpecialRequests / SpecialRequest / Text	0..1	Provides more information about the request code or provides description for requests that are yet uncoded.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest /	1..n	

Copyright © Prologic First India Pvt. Ltd.

@ResGuestRPH	1	For simple reservations: If profiles for guest, travel agency, and company are available, they would all be linked to a sigle ResGuestRPH. A comment has been entered with OTA for phase 2 to accomodate more complex scenarios.
@PrimaryIndicator	0..1	New attribute in OTA 2007A. This indicates the primary guest on a reservation. In the case of multiple guests on a reservation, the guest responsible for payment, etc. will be marked true. Currently Optional in OTA schema but needs to be Mandatory to support passing of multiple guests on a reservation (Additional Profile).
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / UniqueID	0..9	Used to allow additional ids for matching purposes
@ Type	1	The Type attribute refers to OTA code type UIT and the choices recommended by HTNG should be: 1 – Customer 4 – Company 5 –Travel Agency
@ID	1	The actual ID.
@ID_Context	0..1	ID_Context is Optional and would be used to identify the source of the ID (for instance, for a Travel agency ID we could have IATA or ABTA, etc.).
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / UniqueID / CompanyName	0..1	Further identifier
@CodeContext		
@Code		
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile	1..n	
@ProfileType	1	This is used to pass the profile info for the guest, the Company, and the Travel agency. For the individual guest the code used in ProfileType is the OTA PRT code 1-[Customer], For a company it is PRT Code – 3 [Corporation]. For a travel agency it is PRT code 4 – [Travel agent].
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer	1	Customer
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / PersonName / NamePrefix	0..1	Optional but should be highly recommended by HTNG that partners use it if possible. This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's name Prefix.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / PersonName / GivenName	0..1	Optional. This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's name First name.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer /	0..1	Optional. This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's name Middle name.

Copyright © Prologic First India Pvt. Ltd.

PersonName / MiddleName		
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / PersonName / Surname	1	Mandatory if a guest profile is passed. This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's name Surname.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Telephone	1..n	Mandatory if a guest profile is passed. This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's phone numbers and fax number.
@PhoneLocationType	0..1	The PhoneLocationType attribute refers to the OTA PLT code list and indicates where the phone number is based – the values to be used by HTNG are: 6 – Home, 7 – Office, 8 – Other (e.g., cell phone).
@PhoneTechType	0..1	The PhoneTechType attribute refers to the OTA PTT code list and indicates which type of number is transmitted (phone *versus* fax). The codes to be used by HTNG are: code 1 –Voice, code 3 –Fax code 5 – Mobile.
@Phone Number	1	PhoneNumber contains the actual number as a string of max 32 characters and it is Mandatory.
@FormattedInd	1	FormattedInd is Mandatory. If the partner can use Country and Area codes then it should be set to NO. If country code and area code are passed then they should not appear again in the PhoneNumber field. If the partner cannot use country and area code then entire number is passed in the PhoneNumber field and FormattedInd. It should be set to YES if the number needs to be parsed as there is a separation of the different parts or set to NO to indicate that the PhoneNumber field contains the entire phone number without a specific format.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Email	0..5	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's email address.
@EmailType,	0..1	The Email Type attribute uses the OTA code list EAT and indicates the type of email address provided (personal – code 1 *versus* business – code 2, in the case of the Guest details) and must be passed if more than one email address is passed. If only one email address is passed it can be Optional.
@DefaultInd	0..1	DefaultInd is Optional and would indicate whether the email is the primary email for the profile.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Address	0..5	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's mail address.
@Type	1	The Type attribute uses the OTA code list CLT and indicates the type of address provided (Home – code 1 *versus* business – code 2 or Other – code 3, in the case of the Guest details) and must be passed if an address is passed.

Copyright © Prologic First India Pvt. Ltd.

HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Address / AddressLine	0..5	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's address. More than one line can be sent.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Address / CityName	0..1	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's city.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Address / StateProv	0..1	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's State.
@StateCode	0..1	State expressed in the Standard 2-8 characters code.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Address / PostalCode	0..1	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's Postal / ZIP code.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / Address / CountryName	0..1	This path is used to transmit the Customer details. Details of the company or Travel agency use a different path. This field would be used to pass the guest's Country.
@Code	0..1	Country expressed in the Standard ISO 3166 code.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / Customer / CustLoyalty	0..5	Optional. This path enables the user to pass specific IDs linked to the guest profile.
@ProgramID	0..1	The ProgramID attribute can be used to indicate the program that is being passed. For instance, we could use it to pass: Frequent Guest, Frequent Traveller, and Company ID.
@MembershipID	0..1	The membershipID attribute will indicate the actual number.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / AddressInfo / AddressLine	0..5	Mandatory if a company or travel agency profile is passed. Address line is repeatable up to 5 times. This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's address. Type attribute is not needed here as it is clearly a business address.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / AddressInfo / CityName	0..1	This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's City.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / AddressInfo / StateProv	0..1	This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's State.
@StateCode	0..1	State expressed in the Standard 2-8 characters code.

Copyright © Prologic First India Pvt. Ltd.

OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / AddressInfo / PostalCode	0..1	This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's postal or ZIP code.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / AddressInfo / CountryName	0..1	Optional. This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's Country.
@Code	0..1	Country expressed in the Standard ISO 3166 codes.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / TelephoneInfo	1..n	Mandatory if a company or travel agency profile is passed. This element is used to pass the Company or Travel Agency's phone and numbers. PhoneLocationType is not needed here as this is an office telephone.
@PhoneTechType	0..1	The PhoneTechType attribute refers to the OTA PTT code list and indicates which type of number is transmitted (phone *versus* fax). The codes to be used by HTNG are: Code 1 –Voice Code 3 –Fax Code 5- Mobile
@Phone Number	1	PhoneNumber contains the actual number as a string of max 32 characters and it is Mandatory.
@FormattedInd	1	FormattedInd is Mandatory. If the partner can use Country and Area codes then it should be set to NO. If country code and area code are passed then they should not appear again in the PhoneNumber field. If the partner cannot use country and area code then the entire number is passed in the PhoneNumber field and FormattedInd. It should be set to YES if the number needs to be parsed as there is a separation of the different parts or set to NO to indicate that the PhoneNumber field contains the entire phone number without a specific format
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / Profiles / ProfileInfo / Profile / CompanyInfo / Email	0..1	This path is used to transmit the details for a Company or Travel agency profile. This element is used to pass the Company or Travel Agency's email. EmailType attribute is not needed here as it is clearly a business address.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / ArrivalTransport / TransportInfo	0..1	The 3 attributes below are used to indicate the arrival details for the guests to which the booking pertains.
@Type	0..1	Type is used to indicate the method of conveyance of this guest. Values: Air, Rail, Bus, Boat, Private Auto, Other.
@ID	0..1	ID is the actual identifier of this transportation method (e.g., flight number).
@Time	0..1	Time is the estimated arrival time.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGuests / ResGuest / DepartureTransport / TransportInfo	0..1	The 3 attributes are used to indicate the departure details for the guests to which the booking pertains.
@Type	0..1	Type is used to indicate the method of departure of this guest. Values: Air, Rail, Bus, Boat, Private Auto, Other.
@ID	0..1	ID is the actual identifier of this transportation method (e.g.,

Copyright © Prologic First India Pvt. Ltd.

		flight number).
@Time	0..1	Time is the expected departure time.
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGlobalInfo / HotelReservationIDs / HotelReservationID	0..n	The HotelReservationID element can be repeated multiple types to transfer: 1. The PNR number for the reservation assigned by the GDS 2. The reservation number for reservations that are linked to this reservation as associated reservation either for guests travelling together, sharing a room, or as part of an Itinerary
@ResID_Type	1	ResID_Type is assigned values from the UIT code list. 10 – Reservation Server 13 – Internet Broker 14 – Reservation Broker 24 – Travel Agent PNR 25- Associated reservation (travelling with) 26- Associated itinerary reservation 27- Associated shared reservation 34 – Master Itinerary For any other type of system the implementing partners should agree on the appropriate code from the OTA UIT code list.
@ResID_Value	1	If HotelReservationID is passed to transfer the PNR, ResID_Value is the PNR passed by the GDS. If HotelReservationID is passed to transfer the associated reservations, ResID_Value would be the confirmation number of the reservation which is associated to the one that is being transferred.
@ResID_Source	0..1	A unique identifier to indicate the source system which generated the ResID_Value

Reservation Response

The reservation response is made using the OTA_HotelResNotifRS message.

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:wsse="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
  <soap:Header>
    <wsa:Action>http://localhost/htng/ARIAndReservationPushService.asmx/OTA_HotelResNotifRS </wsa:Action>
    <wsa:MessageID>urn:uuid:3fae6b13-94eb-46cf-9d2e-f91b7713cb77</wsa:MessageID>
    <wsa:RelatesTo>urn:uuid:19b3ba3b-1292-45b3-beb2-6bcb78fc1d18</wsa:RelatesTo>
    <wsa:To>http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:To>
    <wsse:Security>
      <wsu:Timestamp wsu:Id="Timestamp-13015d1e-87cb-4335-bc9f-42834ffb553b">
        <wsu:Created>2010-12-09T08:19:26Z</wsu:Created>
        <wsu:Expires>2010-12-09T08:24:26Z</wsu:Expires>
      </wsu:Timestamp>
    </wsse:Security>
  </soap:Header>
  <soap:Body>
    <OTA_HotelResNotifRS xmlns="http://www.opentravel.org/OTA/2003/05"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://www.opentravel.org/OTA/2003/05 OTA_HotelResNotifRS.xsd" Version="1.003"
EchoToken="879791878" TimeStamp=" 2005-10-09T18:52:15" ResResponseType="Committed">
```


Copyright © Prologic First India Pvt. Ltd.

```
    <Success/>
    <HotelReservations>
     <HotelReservation>
      <UniqueID Type="14" ID="3741"/>
      <ResGlobalInfo>
       <HotelReservationIDs>
        <HotelReservationID ResID_Type="10" ResID_Value="100001"/>
         <HotelReservationID ResID_Type="40" ResID_Value="10018888"/>
        <!-- Res ID Type 10 = Hotel from OTA code table UIT -->
       </HotelReservationIDs>
      </ResGlobalInfo>
     </HotelReservation>
    </HotelReservations>
   </OTA_HotelResNotifRS>
  </soap:Body>
</soap:Envelope>
```

Usage profile

Element | @Attribute	Num	Description/Contents
OTA_HotelResNotifRS	1	Root element of the message.
@EchoToken	0..1	As per OTA Specifications.
@Version	1	Version is a mandatory attribute in OTA; therefore, it must remain Mandatory in HTNG in order to be able to use the same message.
@TimeStamp	1	Time of the transaction.
@ResResponseType	1	Given that the OTA_HotelResNotifRQ message is used for additions, modifications, and cancellations, this attribute is used to replicate whether the original message was an addition, a modification, or a cancellation and does not refer to the status of the transaction itself but rather to the nature of the original message. The only three enumerations allowed will therefore be: Committed, Modified, and Cancelled. In this case Committed would be used.
OTA_HotelResNotifRS / Errors / Error	1..99	Mandatory ONLY if Success element is not sent. Only needed if RQ message was unsuccessful.
@Type	1	Mandatory in OTA. Refers to OTA EWT list (error warning type).
@Code	0..1	Refers to OTA list ERR. Should be used wherever possible.
@RecordID	0..1	If the receiving system is able to identify within a batch of reservations which reservation failed, the uniqueID of the rejected reservation should be reported here.
OTA_HotelResNotifRS / Success	1	Mandatory if no Errors were sent. This is the annotation that the reservation batch was received successfully. It could be combined with warning messages if some of the reservations in the batch had issues.
OTA_HotelResNotifRS / Warnings / Warning	0..99	Can be used in conjunction with Success message.
@Type	1	Refers to OTA EWT list (error warning type).
@Code	0..1	Refers to OTA list ERR. Should be used wherever possible.
@RecordID	0..1	If the receiving system is able to identify within a batch of reservations which reservation has a warning, the uniqueID of that reservation should be reported here.
OTA_HotelResNotifRS / HotelReservations / HotelReservation		

Copyright © Prologic First India Pvt. Ltd.

@ResStatus		Indicates the current status of the reservation. Valid values are dependant on the roles: Reservation Broker ▫ Reservation Server • Reserved • Waitlisted Reservation Server ▫ Reservation Broker • Reserved • Waitlisted
OTA_HotelResNotifRS / HotelReservations / HotelReservation / UniqueID	1	This is the confirmation number for the reservation assigned by the immediate originator of the booking (i.e., the system which sent the OTA_HotelResNotifRQ message for which the OTA_HotelresNotifRS message is sent).
@Type	1	Type is assigned values from the UIT code list. If the original system was a CRS: Type = 14 – Reservation ID is the actual confirmation number If it was a PMS: Type = 10 - Hotel
@ID	1	ID is the CRS confirmation number (or PMS number if the reservation was originated in the PMS).
OTA_HotelResNotifRQ / HotelReservations / HotelReservation / ResGlobalInfo / HotelReservationIDs / HotelReservationID	1..n	This is the confirmation number associated by the system which received the booking.
@ResID_Type	1	ResID_Type is assigned values from the UIT code list. 10 – Reservation Server 13 – Internet Broker 14 – Reservation Broker 24 – Travel Agent PNR 25- Associated reservation (travelling with) 26- Associated itinerary reservation 27- Associated shared reservation 34 – Master Itinerary For any other type of system the implementing partners should agree on the appropriate code from the OTA UIT code list.
@ResID_Value	1	ResID_Value is the actual confirmation number.
@ResID_Source	0..1	A unique identifier to indicate the source system which generated the ResID_Value

- OTA_HotelRatePlanNotifRQ

Update Rates

The update rates usage profile covers the pushing of rate plan definitions from one system to another. This usage profile includes standard rates

Update Rate Request

The update rate request is sent using the OTA_HotelRatePlanNotifRQ message.

The request XML message will be like as following.

```
<soapenv:Envelope xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:wsu="http://docs.oasis-
```


Copyright © Prologic First India Pvt. Ltd.

```
open.org/wss/2004/01/oasis-200401-wss-wssecurityutility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
 <soapenv:Header>
  <wsse:Security mustUnderstand="1">
   <wsse:UsernameToken wsu:Id="UsernameToken-72135529">
    <wsse:Username>SUP</wsse:Username>
    <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-
1.0#PasswordText">SUP</wsse:Password>
   </wsse:UsernameToken>
  </wsse:Security>
  <!--<wsa:MessageID>http://localhost/msg?id=72135530</wsa:MessageID> -->
  <wsa:To>http://localhost/htng/ARIAndReservationPushService.asmx</wsa:To>
<wsa:Action>http://localhost/htng/ARIAndReservationPushService.asmx/OTA_HotelRatePlanNotifRQ</wsa:Action>
 </soapenv:Header>
 <soapenv:Body>
  <OTA_HotelRatePlanNotifRQ Version="1.001" EchoToken="000" TimeStamp="2005-08-03T09:30:47-05:00">
   <RatePlans HotelCode="CMRM">
    <RatePlan RatePlanCode="PERA" RatePlanCategory="O" RatePlanNotifType="New" MarketCode="ISDR">
     <BookingRules>
      <BookingRule>
       <LengthsOfStay>
        <LengthOfStay Time="2" TimeUnit="Day" MinMaxMessageType="SetMinLOS"/>
       </LengthsOfStay>
      </BookingRule>
     </BookingRules>
     <Rates>
      <Rate Start="2012-04-03" End="2014-04-03" Mon="true" Tue="true" Weds="true" Thur="true" Fri="true"
Sat="true" Sun="true" CurrencyCode="EURO" DecimalPlaces="2" InvCode="BV">
       <BaseByGuestAmts>
        <!--Single Rate-->
        <BaseByGuestAmt AmountBeforeTax="100.0000" RateOverrideIndicator="true" NumberOfGuests="1"
AgeQualifyingCode="10"/>
        <!--Double Rate-->
        <BaseByGuestAmt AmountBeforeTax="200.0000" RateOverrideIndicator="true" NumberOfGuests="2"
AgeQualifyingCode="10"/>
        <!--Triple Rate-->
        <BaseByGuestAmt AmountBeforeTax="300.0000" RateOverrideIndicator="true" NumberOfGuests="3"
AgeQualifyingCode="10"/>
       </BaseByGuestAmts>
       <AdditionalGuestAmounts>
        <!--Extra Rate-->
        <AdditionalGuestAmount AgeQualifyingCode="12" Amount="150.0000"/>
        <!--Youth Rate-->
        <AdditionalGuestAmount AgeQualifyingCode="9" Amount="250.0000"/>
        <!--Child Rate-->
        <AdditionalGuestAmount AgeQualifyingCode="8" Amount="50.0000"/>
       </AdditionalGuestAmounts>
      </Rate>
      <Rate Start="2012-04-03" End="2014-04-03" Mon="true" Tue="true" Weds="true" Thur="true" Fri="true"
Sat="true" Sun="true" CurrencyCode="EURO" DecimalPlaces="2" InvCode="SWV">
       <BaseByGuestAmts>
        <BaseByGuestAmt AmountBeforeTax="100.0000" RateOverrideIndicator="true" NumberOfGuests="1"
AgeQualifyingCode="10"/>
        <BaseByGuestAmt AmountBeforeTax="200.0000" RateOverrideIndicator="true" NumberOfGuests="2"
```


Copyright © Prologic First India Pvt. Ltd.

```
AgeQualifyingCode="10"/>
            <BaseByGuestAmt AmountBeforeTax="300.0000" RateOverrideIndicator="true" NumberOfGuests="3"
AgeQualifyingCode="10"/>
          </BaseByGuestAmts>
          <AdditionalGuestAmounts>
            <AdditionalGuestAmount AgeQualifyingCode="12" Amount="150.0000"/>
            <AdditionalGuestAmount AgeQualifyingCode="9" Amount="250.0000"/>
            <AdditionalGuestAmount AgeQualifyingCode="8" Amount="50.0000"/>
          </AdditionalGuestAmounts>
        </Rate>
        <Rate Start="2012-04-03" End="2014-04-03" Mon="true" Tue="true" Weds="true" Thur="true" Fri="true"
Sat="true" Sun="true" CurrencyCode="EURO" DecimalPlaces="2" InvCode="WV">
          <BaseByGuestAmts>
            <BaseByGuestAmt AmountBeforeTax="100.0000" RateOverrideIndicator="true" NumberOfGuests="1"
AgeQualifyingCode="10"/>
            <BaseByGuestAmt AmountBeforeTax="200.0000" RateOverrideIndicator="true" NumberOfGuests="2"
AgeQualifyingCode="10"/>
            <BaseByGuestAmt AmountBeforeTax="300.0000" RateOverrideIndicator="true" NumberOfGuests="3"
AgeQualifyingCode="10"/>
          </BaseByGuestAmts>
          <AdditionalGuestAmounts>
            <AdditionalGuestAmount AgeQualifyingCode="12" Amount="150.0000"/>
            <AdditionalGuestAmount AgeQualifyingCode="9" Amount="250.0000"/>
            <AdditionalGuestAmount AgeQualifyingCode="8" Amount="50.0000"/>
          </AdditionalGuestAmounts>
        </Rate>
      </Rates>
      <Description Name="Short Description">
        <Text>SHORT DESC PERA</Text>
      </Description>
      <Description Name="Long Description">
        <Text>LONG DESCRIPTION PERA</Text>
      </Description>
    </RatePlan>
  </RatePlans>
 </OTA_HotelRatePlanNotifRQ>
</soapenv:Body>
</soapenv:Envelope>
```

Login Credentials have been shown in this format, Part of SOAP Header in SOAP Envelope. User Name and password highlighted in the following XML Tag.

```
<wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd">
        <wsse:UsernameToken xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-
utility-1.0.xsd">
          <wsse:Username>SUP</wsse:Username>
          <wsse:Password Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-
1.0#PasswordText">SUP</wsse:Password>
        </wsse:UsernameToken>
      </wsse:Security>
```

URL of the Web Service has been showing in the following XML Format of the Request Message, part of SOAP Header in SOAP Envelope.

Copyright © Prologic First India Pvt. Ltd.

```
<wsa:To> http://localhost/htng/ARIAndReservationPushService.asmx</wsa:To>
```

Update Rate Request

The update rate request is sent using the OTA_HotelRatePlanNotifRQ message.

Usage Profile Table

Element | @Attribute	Num	Description/Contents
OTA_HotelRatePlanNotifRQ	1	Root element of the message.
@EchoToken	0..1	Optional.
@Timestamp	1	Time of the transaction.
@Version	1	Version is a mandatory attribute in OTA; therefore, it must remain Mandatory in HTNG in order to be able to use the same message.
@MessageContentCode	1	The attribute refers to the MCC OTA code list which includes Rate, Package, Group.
OTA_HotelRatePlanNotifRQ / RatePlans	1	Element grouping the rate plans to be transferred.
@HotelCode	1	This is the code of the property whose availability is being updated.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan	1..n	Element defining rate plan being sent. Upper limit to be agreed by trading partners.
@RatePlanCode	1	This is the rate plan which is being uploaded/downloaded.
@RatePlanCategory	0..1	This is the segment/category to which the rate being uploaded/downloaded belongs. Only one RatePlanCategory is acceptable for RatePlan code; therefore, the RatePlanCategory must be the same for all seasons passed.
@ RatePlanStatusType	0..1	The status of the rate plan – Initial, Active, Deactivated.
@BaseRatePlanCode	0..1	The rate plan this rate plan is derived from.Used for Character Strings, length 1 to 64.
@AdjustedAmount	0..1	The amount which should be added to the base rate plan to determine the price of this derived rate plan.Specifies an amount, max 3 decimals.
@AdjustedPercentage	0..1	The percentage off the base rate plan amount used to determine the price of this derived rate plan.Used for percentage values.
@AdjustUpIndicator	0..1	When true, the adjusted amount or adjusted percentage is added to the amount specified for the base rate plan to determine the derived rate amount. When false, the adjusted amount or adjusted percentage is subtracted from the amount specified for the base rate plan to determine the derived rate amount.
@ExtraNightRatePlancode	0..1	Used to indicate what rate plan is used for shoulder night(s) booked in addition to the base nights.Used for Character Strings, length 1 to 64.
@YieldDeltaAmount	0..1	Numeric attribute indicating the amount to be added or subtracted to the rate to determine the real “yieldable” value of the rate.
@MarketCode	0..1	String attribute to indicate the market code for the

Copyright © Prologic First India Pvt. Ltd.

		rate. Only one MarketCode is acceptable for RatePlan code; therefore, the MarketCode must be the same for all seasons passed.
@RestrictedDisplayIndicator	0..1	This attribute is a boolean to indicate if the rate is to be considered “Confidential”. Only one Confidential attribute is acceptable for each RatePlan code; therefore, the attribute must be the same for all seasons passed.
@RatePlanNotifType	1	This enumeration indicates whether the upload/download is meant to overwrite existing data or add to it. Possible enumerations are: New, Delta, Overlay, Remove.
@Start, @End	1	In general, the Start and End attributes used at the RatePlan level should be used as follows: the Start attribute should be equal to the earliest Start attribute at the Rate level, and the End attribute should be equal to the latest End attribute at the Rate level. In other words, the Start and End attributes at the RatePlan level should specify the entire span of dates representing the Rate elements found in the Rates collection. HOWEVER, the same Start and End attribute or Rate Plan level could be used to indicate the actual seasons of the rate if the two systems integrating using this message intend to transfer some of the elements at rate plan level as season-based elements. For instance, if the two systems are both capable of treating the “Commissionable” indicator as a seasonal item rather than an item that applies to the entire rate. If the Start and End attribute at rate plan level are used to indicate each season, the Start and End attribute at rate level WOULD ONLY BE USED in case of DOW variations – if no DOW variation is needed the Start and end attributes at Rate level could be omitted.
RatePlans / RatePlan / Description	2	This element should be repeated twice: one instance for the short description and the other for the long description of the rate that is being uploaded/downloaded.
@Name	1	This element should be repeated twice: one instance for the short description and the other for the long description of the rate that is being uploaded/downloaded. Its value must be ‘Short decription’ in one instance and ‘Long Description’ in the other.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / Description / Text	1	This element inside the Description element described above has the actual text corresponding to the long and short description of the rate being uploaded/downloaded.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / UniqueID	1	
@Type	1	Refers to OTA code list UIT – nr 16 = Reference. This is used to identify each single rate plan message for error reporting purposes.

Copyright © Prologic First India Pvt. Ltd.

@ID	1	ID is a unique incremental number for each rate plan message that identifies that specific message.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / Commission	0..1	
@Percent	0..1	This is the amount of commission paid to an agency for booking the rate that is being uploaded/downloaded.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / Rates	0..1	Includes all rates loaded for the rate plan.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / Rates / Rate	1..n	Upper limit may be agreed upon partners.
@Start, @End	0..1	This set of Start and End attribute represent the start and end of each season which is being transferred with the rate. HOWEVER, if the Start and End attribute at rate plan level are used to indicate each season, the Start and End attribute at rate level WOULD ONLY BE USED in case of DOW variations – if no DOW variation is needed the Start and end attributes at Rate level could be omitted.
@CurrencyCode	1	This is the currency associated to the rate that is being uploaded/downloaded – it could be different to the currency loaded for the property.
@Mon,@Tue,@Weds,@Thur, @Fri,@Sat,@Sun	0..1 per day	These DOW indicators are used to specify to which days the rate passed is applicable. If one is sent, they must all be sent and rates must be sent for each exception. If there is an exception to the pricing DOW indicators must be passed and the Rate element is then repeated for the exception days. Exceptions to the pricing are only allowed if no stay or arrival restrictions have been applied.
@InvCode	1	This is the room type for which the rates are transferred. For each room type a new instance of the Rate element must be passed. If the room type is transmitted with rate values attached it will be considered opened at the price indicated. If the room type is passed with a 0 value it will be considered closed for that rate plan (i.e., not applicable for the rate plan). If in a modification message a room type that was previously loaded is Not sent, then it remains unchanged.
@Status	0..1	This is used to indicate for each room code passed for the rate whether it is opened or closed. Default value to be agreed by partners.
@RateTimeUnit, @UnitMultiplier	0..1	If NOT sent the default assumed is always 1 day (i.e., the rate is based on a nightly rate). Rate Time unit is an Enumeration of time units upon which the RateAmount is based (e.g., daily, weekly, single rate for full stay). UnitMultiplier is the number of RateTimeUnits that the rate Amount is based upon (e.g., rate for one day in case of nightly rates).
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / Rates / Rate / BaseByGuestAmnts /	1..n	AT LEAST 1 INSTANCE FOR NUMBEROFGUESTS=1 is Mandatory. At least one instance for NumberOfGuest=1 is

Copyright © Prologic First India Pvt. Ltd.

BaseByGuestAmt		mandatory for the RatePlanNotifType = New or Overlay. For the RatePlanNotifType of Delta or Remove it is optional
@NumberOfGuests	1	The NumberOfGuest Attribute indicates what type of rate is being passed – if NumberOfGuests is = 1 then we are transmitting a single rate, if higher than 1 then it is a double or full occupancy rate.
@AmountBeforeTax or @AmountAfterTax	1	Either @AmountBeforeTax or AmountAfterTax is Mandatory for each @NumberOfGuests. Partners must select whether to send either the @AmountBeforeTax or @AmountAfterTax (or both) attributes.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / Rates / Rate / AdditionalGuestAmounts / AdditionalGuestAmount	0..n	Used to transfer extra adult and extra child information.
@AgeQualifyingCode	0..1	@AgeQualifyingCode - 8 = child, 10 = adult.
@Percent OR @Amount	0..1	This is the percentage of the single rate that represents the child rate. Could also be expressed as fixed amount.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules	0..1	Optional. Used to transfer booking rules.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule	1	Mandatory if BookingRules is transferred.
@MinAdvancedBookingOffset	0..1	This is the minimum amount of days prior to arrival that the rate can be booked.
@MaxAdvancedBookingOffset	0..1	This is the maximum amount of days prior to arrival that the rate can be booked.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / LengthsOfStay	1	SetMinLOS & SetMaxLOS Mandatory.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / LengthsOfStay / LengthOfStay	2	SetMinLOS & SetMaxLOS Mandatory
@MinMaxMessageType =SetMinLOS, @Time @TimeUnit	1	This is the minimum length of stay requirement associated to the rate that is being uploaded/downloaded. See note at the beginning of the document with regards to alternative solution on how to transmit the LOS restrictions.
@MinMaxMessageType =SetMaxLOS, @Time @TimeUnit	1	This is the maximum length of stay requirement associated to the rate that is being uploaded/downloaded. See note at the beginning of the document with regards to alternative solution on how to transmit the LOS restrictions.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / DOW_Restrictions / AvailableDaysOfWeek	0..1	Element ot transfer DOW when stay is possible.
@Mon,@Tue,@Weds,@Thur, @Fri,@Sat,@Sun	0..1 per day	The day of the week indicators selected are those in which the rate plan is available and therefore could

Copyright © Prologic First India Pvt. Ltd.

		be used to reflect when STAY is possible. Days marked as 0 (boolean) would mean on those days the rate is not available and therefore stay would not be possible. If one DOW indicator is used they must all be used.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / DOW_Restrictions / ArrivalDaysOfWeek	0..1	Element ot transfer DOW when arrival is possible.
@Mon,@Tue,@Weds,@Thur,@Fri,@Sat,@Sun	0..1 per day	The day of the week indicators set to 1 are those in which Arrival is allowed. Those set to 0 are the days in which arrival is not allowed.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / Viewerships	0..n	
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / Viewerships / Viewership /	1	Path to BookingChannelCodes
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / Viewerships / Viewership / BookingChannelsCodes /	0..1	
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / Viewerships / Viewership / BookingChannelsCodes / BookingChannelCode	0..n	This would be used to indicate which Channels are allowed to view and book the rate. Could be substituted with SystemCode.
@Sort	0..1	The attribute “sort” can be associated to each code. Must be a string where we can pass C for closed as well as a selling order.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / RatePlanLevelFee	0..1	Linked to Total Pricing – used to pass all Tax and fees info.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / RatePlanLevelFee / Fee	1..n	Repeatable once per fee.
@Type	0..1 per Fee	An enumeration to indicate whether the fee is inclusive, exclusive, or cumulative.
@Code	0..1 per Fee	The Code attribute refers to the OTA FeeTaxType code list and is used to indicate what fee is being transferred. Code used will be: 17– Total Tax 16 – Surcharge 14 – Service charge 27 – Miscellaneous 19 – VAT/GST Tax 8 – Lodging tax 15 – State tax 3 – City tax 10 – Occupancy tax 34 – Local Fee A request has been made to OTA for the MPT list to be accessible from the same attribute so that meal plan info can also be passed in the same field.
@Amount OR @Percent	1 per Fee	Either @Amount or @Percent is Mandatory.

Copyright © Prologic First India Pvt. Ltd.

@Charge Unit	0..1	Charge Unit is used to indicate the unit of measure of the fee/tax passed: Based on the OTACharge Type code list, some examples are: 18 - Per room per stay 19 - Per room per night 20 - Per person per stay 21 - Per person per night
@CurrencyCode	0..1	
@MandatoryIndicator	0..1	MandatoryIndicator is a boolean Attribute. This will indicate if the fee or meal plan passed is Mandatory or not and will help in the determination of the calculation for total pricing.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / RatePlanLevelFee / Fee / Description	0..1	Linked to Total Pricing – used to pass all tax and fees info. For fees and tax that are not OTA coded, Description/Text will be used to indicate the fee that is being passed. Only one description allowed for each fee element.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / RatePlanLevelFee / Fee / Description / Text	1	Description of the fee.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / CancelPenalties /	0..1	Used to transfer the Cancellation penalty for the rate plan transferred.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / CancelPenalties / CancelPenalty	0..1	
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / CancelPenalties / CancelPenalty / Deadline	0..1	
@AbsoluteDeadline	0..1	This is used to indicate the “exact date” or “exact date and time” by which a reservation made for the rate passed needs to be cancelled in order to avoid penalties.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / CancelPenalties / CancelPenalty / Deadline		This is used to indicate the “number of days or hours”, “before arrival”, or “after booking” by which a reservation made for the rate passed needs to be cancelled in order to avoid penalties.
		The following three attributes are used to indicate the “number of days or hours”, “before arrival”, or “after booking” by which a reservation made for the rate passed needs to be cancelled in order to avoid penalties.
@OffsetDropTime	0..1	An enumeration to indicate BeforeArrival or AfterBooking.
@OffsetUnitMultiplier	0..1	a numeric to indicate the number of hours or days by which to cancel.

Copyright © Prologic First India Pvt. Ltd.

@OffsetTimeUnit	0..1	An enumeration to indicate whether we are talking about hours or days. Possible enumerations for Ota are various BUT RECOMMENDED ENUMERATIONS to be used by HTNG should only be: Hour and Day.
OTA_HotelRatePlanNotifRQ / RatePlans / RatePlan / BookingRules / BookingRule / CancelPenalties / CancelPenalty / AmountPercent	1	Conditionally Mandatory. If a Deadline is passed, then an AmountPercent must also be indicated using the appropriate attribute.
@NmbrOfNights OR @Amount OR @Percent	1	Conditionally Mandatory.

Update Rate Response

The update rate response is sent using the OTA_HotelRatePlanNotifRS message.

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing" xmlns:wsse="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
  <soap:Header>
    <wsa:Action>http://localhost/htng/ARIAndReservationPushService.asmx/OTA_HotelRatePlanNotifRS</wsa:Action>
    <wsa:MessageID>urn:uuid:3fae6b13-94eb-46cf-9d2e-f91b7713cb77</wsa:MessageID>
    <wsa:RelatesTo>urn:uuid:19b3ba3b-1292-45b3-beb2-6bcb78fc1d18</wsa:RelatesTo>
    <wsa:To>http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:To>
    <wsse:Security>
      <wsu:Timestamp wsu:Id="Timestamp-13015d1e-87cb-4335-bc9f-42834ffb553b">
        <wsu:Created>2010-12-09T08:19:26Z</wsu:Created>
        <wsu:Expires>2010-12-09T08:24:26Z</wsu:Expires>
      </wsu:Timestamp>
    </wsse:Security>
  </soap:Header>
  <soap:Body>
    <OTA_HotelRatePlanNotifRS xmlns="http://www.opentravel.org/OTA/2003/05"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://www.opentravel.org/OTA/2003/05 OTA_HotelRatePlanNotifRS.xsd" Version="1.001"
EchoToken="000" TimeStamp="2005-08-03T09:30:47-05:00">
      <Success/>
    </OTA_HotelRatePlanNotifRS>
  </soap:Body>
</soap:Envelope>
```

The update rate response is sent using the OTA_HotelRatePlanNotifRS message.

Usage Profile Table

Element | @Attribute	Num	Description/Contents
OTA_HotelRatePlanNotifRS	1	Root element of the message.
@EchoToken	0..1	Optional.
@Version	1	Version is a mandatory attribute in OTA; therefore, it must remain Mandatory in HTNG in order to be able to use the same message.
@Timestamp	1	Time of the transaction.
OTA_HotelRatePlanNotifRS / Errors	1	The attribute refers to the MCC OTA code list which includes Rate, Package, Group.

Copyright © Prologic First India Pvt. Ltd.

OTA_HotelRatePlanNotifRS / Errors / Error	1..99	Mandatory.
@Type	1	Mandatory in OTA. Refers to OTA EWT list (error warning type).
@Code	0..1	Refers to OTA list ERR. Should be used wherever possible.
@RecordID	0..1	If the receiving system is able to identify within a batch of availability status messages which specific message failed, the UniqueID of the message should be reported here.
OTA_HotelRatePlanNotifRS / Success	1	This is the annotation that the rate plan message batch was received successfully. It could be combined with warning messages if some of the messages in the batch had issues.
OTA_HotelRatePlanNotifRS / Warnings	1	The attribute refers to the MCC OTA code list which includes Rate, Package, Group.
OTA_HotelRatePlanNotifRS / Warnings / Warning	1..99	Mandatory.
@Type	1	Mandatory in OTA. Refers to OTA EWT list (error warning type).
@Code	0..1	Refers to OTA list ERR. Should be used wherever possible.
@RecordID	0..1	If the receiving system is able to identify within a batch of availability status messages which specific message failed, the UniqueID of the message should be reported here.

Copyright © Prologic First India Pvt. Ltd.