



Touché RESTful APIs For 3rd Party Integration

Jun 30, 2017

Technical Specification



Document Control

Version	Date	Amended By	Remarks
2.0.0.0	08 Jun 2015	Bharat	Specification for API GetOutletDetails
2.0.0.1	26 Jul 2015	Partha	Specification for API - SaveOrder - MoveTableItems - CancelItems
2.0.0.2	08 Feb 2016	Partha	Specification for API GetAllOpenChecks
2.0.0.3	18 Feb 2016	Partha	Specification for API GetClosedOrders
2.0.0.3	04 May 2016	Partha	Specification for API SettleOrder
2.0.0.4	30 Jun 2016	Partha	Specification for API ItemAvailabilityStatus



TABLE OF CONTENTS

1. OVERVIEW.....	4
2. COMMUNICATION	4
3. MESSAGES.....	4
3.1 GetOutletDetails	4
3.2 SaveOrder	8
3.3 MoveTableItems	12
3.4 CancelItems	15
3.5 GetAllOpenChecks	19
3.6 GetClosedOrders	20
3.7 SettleOrder	23
3.8 ItemAvailabilityStatus	24



1. OVERVIEW

Touché APIs provides set of web services based on REST API.

2. Communication

Touché Service supports the exchange of messages via Hyper Text Transport Protocol (HTTP). The request and response are based on JSON string. It should be noted that the request must adhere to a valid JSON string and must have the Parameter name same as defined for each of the API.

3. Messages

Following section describes the valid request and response from the API. It also describes the response in case of failures.

The API's base URL for any request will be <http://<ServerURL>/ToucheAPI/> followed by the method name.

3.1 GetOutletDetails

This method returns the following details of the requested outlet

- Menus
 - Menu Head
 - Sub menu
 - Items of the Menu
 - Modifier/Condiment of the Menu Items

Method Name	<i>GetOutletDetails</i>
URL	<a href="http://<ServerURL>/ToucheLite/GetOutletDetails">http://<ServerURL>/ToucheLite/GetOutletDetails
Sample Request	RequestString={"appKey":"test","deviceId":"f7ce5f599ed109d8","propertyId":"BOGGN","timestamp":1444284643970,"outletCode":"GNBL","userId":"999"}
Sample URL	<a appkey\":\"test\",\"deviceid\":\"f7ce5f599ed109d8\",\"propertyid\":\"boggn\",\"timestamp\":1444284643970,\"outletcode\":\"gnbl\",\"userid\":\"999\"}"="" href="http://<ServerURL>/ToucheLite/GetOutletDetails?RequestString={\">http://<ServerURL>/ToucheLite/GetOutletDetails? RequestString={"appKey":"test","deviceId":"f7ce5f599ed109d8","propertyId":"BOGGN","timestamp":1444284643970,"outletCode":"GNBL","userId":"999"}

Request Parameter Details:-

Parameter	Type	Description
OutletCode	String	Outlet code
PropertyId	String	Property Id
AppKey	String	App key
Timestamp	String	Time Stamp
DeviceId	String	Device Id
UserId	String	User Id

Success

```
{
  "ResponseStatus": {
    "ResponseCode": 0,
    "ResponseFlag": "SUCCESS",
    "ResponseMessage": ""
  },
  "OutletMenus": [
    {
      "MenuCode": "MBAR",
      "MenuName": "MINI BAR",
      "SubMenus": [
        {
          "SubMenuCode": "MBAR",
          "SubMenuName": "MINI BAR",
          "MenuItems": [
            {
              "ItemCode": "MB08",
              "SubMenuCode": "MBAR",
              "ItemName": "MINI BAR CHOCOLATE",
              "ItemDescription": null,
              "ItemImageUrl": "",
              "ItemPrice": 125,
              "ItemHappyHourPrice": 125,
              "ItemType": "MI",
              "ItemAccount": "FD",
              "ItemAccountName": "FOOD",
              "ItemPriceWithTax": 140.625,
              "ItemHappyHourPriceWithTax": 140.625,
              "AddOnCategories": null,
              "PackageConstituents": null
            },
            {
              "ItemCode": "PK01",
              "SubMenuCode": "MBAR",
              "ItemName": "5 Beers",
              "ItemDescription": null,
              "ItemImageUrl": "",
              "ItemPrice": 500,
              "ItemHappyHourPrice": 500,
              "ItemType": "FP",
              "ItemAccount": "HB",
              "ItemAccountName": "HARD BEVERAGE",
              "ItemPriceWithTax": 600,
              "ItemHappyHourPriceWithTax": 600,
              "AddOnCategories": null,
              "PackageConstituents": [
                {
                  "ItemQuantity": 5,
                  "ItemCode": "MB15",
```

	<pre> "ItemName": "BEER KINGFISHER PINT", "ItemPrice": 100, "ItemType": "PC", "ItemAccount": "HB", "ItemAccountName": "HARD BEVERAGE" }], { "ItemCode": "MB12", "SubMenuCode": "MBAR", "ItemName": "WHISKY TEACHERS 50", "ItemDescription": null, "ItemImageUrl": "", "ItemPrice": 350, "ItemHappyHourPrice": 350, "ItemType": "MI", "ItemAccount": "HB", "ItemAccountName": "HARD BEVERAGE", "ItemPriceWithTax": 420, "ItemHappyHourPriceWithTax": 420, "AddOnCategories": null, "PackageConstituents": null }, { "ItemCode": "262", "SubMenuCode": "MBAR", "ItemName": "Party Box for 5", "ItemDescription": null, "ItemImageUrl": "", "ItemPrice": 110, "ItemHappyHourPrice": 110, "ItemType": "MI", "ItemAccount": "OT", "ItemAccountName": "OTHERS", "ItemPriceWithTax": 0, "ItemHappyHourPriceWithTax": 0, "AddOnCategories": null, "PackageConstituents": null }] } </pre>
Fail	<pre> { ResponseStatus: { ResponseCode: 100, ResponseFlag: "Fail", ResponseMessage: "No Menu Available" } } </pre>



	<pre>}, OutletMenus: null }</pre>
--	-----------------------------------

Response Details:-

Parameter	Type	Description
OutletMenus	String	Outlet Menu
MenuCode	String	Menu Code
MenuName	String	Menu Name
SubMenus	ArrayList	Sub-menus of a Menu can be created
SubMenuCode	String	Sub Menu code
SubMenuName	String	Sub Menu description
MenuItems	ArrayList	Each sub menu can contain more than 1 item
ItemCode	String	Item code
SubMenuCode	String	Sub menu code
ItemName	String	Item Name
ItemDescription	String	Description
ItemPrice	Float	Normal price of an item
ItemHappyHourPrice	Float	Happy hour price of an item
ItemType	String	Valid Values : MI (Menu Items) OI (Open Item) FP (Fixed Package) MO (Modifier) CO (Condiment)
ItemImageUrl	String	Image of an item (url)
ItemAccount	String	Item Account or category (Food or beverage...etc.)
ItemAccountName	String	Item Account Name
ItemPriceWithTax	Float	Item Price inclusive of taxes
ItemHappyHourPriceWithTax	Float	Item Happy hour price with tax
PackageConstituents	ArrayList	It has the data pertaining to the Constituents of the Packaged Items
ItemQuantity	Float	Package Item Quantity
ItemCode	String	Item Code
ItemName	String	Item Name
ItemPrice	Float	Item Price
ItemType	String	Valid Values PC (Package Constituent)
ItemAccount	String	Item Account or category (Food or beverage...etc.)
ItemAccountName	String	Item Account or category Name (Food or beverage...etc.)
AddOnCategories	ArrayList	Item AddOn Category
CategoryCode	String	Addon category code
CategoryName	String	Addon category name



AddOnAllowedQuantity	Integer	Addon allowed quantity
AddOnType	String	Addon type
AddOnItems	ArrayList	An item may have more than 1 Modifier or Condiment
AddOnCode	String	Modifier or Condiment defined for the item
AddOnName	String	Description
AddOnPrice	Float	Normal price of an add-on item
AddOnHappyHourPrice	Float	Happy hour price of an add-on item
AddOnAccount	String	Add-on account code
AddOnAccountName	String	Add-on account name
AddOnNCPrice	Float	Add-on item non-chargeable price

Response Status:-

Response Value	Description
0	Success
100 or NULL	Fail

3.2 SaveOrder

This method is used for saving orders. Orders can be new order or existing order.

Method Name	SaveOrder
URL	<a href="http://<ServerURL>/ToucheLite/SaveOrder">http://<ServerURL>/ToucheLite/SaveOrder
Sample Request	{ "PropertyId": " BOGGN", "UserId": "999", "OutletCode": "GNBL", "DeviceId": "999", "GuestName": null, "TipAmount": 0, "CreateOnAuditDate": null, "Check": { "TableNumber": null, "Covers": 0, "IsResident": null, "IsNonChargeable": null, "Comments": null, "CheckNumber": "", "GuestProfile": [{ "GuestProfileCode": 1047, "GuestImageUrl": null, "GuestName": "ShaluKumarSharma", "GuestPhoneNumber": null, "GuestMembershipId": "AF-JDFH", "GuestCityName": null, "IsClubMemberProfile": null, "GuestDepartment": null, "ContactAddressType": "RESI" }] }

	<pre> }}, "OrderLineItems": [{ "ItemCode": "2446", "ItemName": "RED THAI SHRIMP CURRY", "SubMenuCode": "G145", "ItemType": "MI", "ItemPrice": 499, "IsHappyHour": null, "ItemStatus": null, "CourseNumber": 0, "CoverNumber": 0, "OrderedQuantity": 4, "KotComment": null, "ItemAccount": "FD", "ParentItemCode": null, "ItemAccountName": null, "ParentItemSequenceNumber": 0, "PackageConstituentLineItems": null, "AddOnLineItems": null }], "ExternalReference": { "ExternalReferenceNumber": "T0007419", "ExternalReferenceType": "P" } }, "DiscountSlab": { "DiscountName": null, "IsAdhoc": null, "AskGuestDetails": null, "DiscountCode": null, "DiscountDetails": null } }</pre>
--	---

Request Parameter Details:-

Parameter	Type	Description
OutletCode	String	Outlet code
PropertyId	String	Property Id
AppKey	String	App key
Timestamp	String	Time Stamp
DeviceId	String	Device Id
UserId	String	User Id
GuestName	String	Name of the Guest
TipAmount	Float	Amount of TIPS
Check	Object	Object of Check
TableNumber	String	Table number of the Order
Covers	Integer/Number	Total PAX for the Order
IsResident	String	If the Order is for In House



Touché RESTful APIs

		Guest of the Hotel then the value should be "Y" else "N"
IsNonChargeable	String	"Y" for NC KOT ; "N" for Normal order
Comments	String	Comments for the order. Max length 100 characters
CheckNumber	String	Order Number.
OrderLineItems	Arraylist	Contains the items in the order
ItemCode	String	Item Code
ItemName	String	Item Name
SubMenuCode	String	Menu Code in which the item belongs
ItemType	String	Probable Value MI: Menu Item/Regular Item
ItemPrice	Float	Price of the item
IsHappyHour	String	If the item ordered during Happy Hour. Y: Ordered during Happy Hour N: Normal hour
ItemStatus	String	Status of the item in the order PO: Saved VT: Voided XI : Moved the item to another order XO: Moved in from another order
CourseNumber	Integer/number	Course number of the item ordered
CoverNumber	Integer/number	Cover which ordered the item
OrderedQuantity	Float	Quantity of the item ordered
KotComment	String	Comment on the item for KOT
ItemAccount	String	Item revenue head
ParentItemCode	String	Parent item code
ItemAccountName	String	Revenue head name
ParentItemSequenceNumber	Integer/Number	Item sequence of the parent item code
PackageConstituentLineItems	ArrayList [Optional] value can be null	Item Package details Optional Can be NULL
ItemQuantity	Integer	Item quantity
ItemCode	String	Item code
ItemName	String	Item name
ItemPrice	Float	Item price
ItemAccount	String	Item Account Code
ItemType	String	Item type
AddOnLineItems	ArrayList [Optional]	Modifier/Condiment List



	value can be null	
AddOnCode	String	Modifier or Condiment defined for the item
AddOnName	String	Description
AddOnType	String	Defines the type of an add-on item (whether it is an open item or menu item or condiment or modifier).
GuestProfile	ArrayList [Optional] value can be null	Guest Details associated with the check/Order
GuestCityName	String	Guest city name
GuestEmailId	String	Guest email id
GuestMembershipId	String	Membership id
GuestName	String	Guest Name
GuestPhoneNumber	String	Guest phone number
GuestProfileCode	Integer	Guest profile code
ExternalReference	Object	Define the Order details of Food Panda
ExternalReferenceNumber	String	Food Panda order number
ExternalReferenceType	String	Value should be "P"

Response Details:-

Parameter	Type	Description
CheckNumber	String	Check Number
Balance	Double	Total Balance
CheckStatus	String	Check Status
ResponseStatus	Object	Response from the API
ResponseCode	String	Code of the response. Correlate with below table
ResponseFlag	String	Success : For success API FAIL: Failure of API. Correlate with below table
ResponseMessage	String	Message of the string

Response Status:-

Response Value	Description
0	Success
1	OutletCode is null or blank
2	Temp table Failure
3	Item Code/Menu Code/Item Type is null or blank
11	Invalid Outlet
12	Invalid Menu
13	Invalid Menu and Item Link
14	Invalid UserId
15	Invalid Item Type
16	Invalid Table Number
4 or NULL	Fail

3.3 MoveTableItems

This method is used for moving items from one table to another. If items from one table is moved to a new check then 'NewCheckDetails' object must have details of the new check.

Method Name	<i>MoveTableItems</i>
URL	<a href="http://<ServerURL>/ToucheLite/MoveTableItems">http://<ServerURL>/ToucheLite/MoveTableItems

Request Parameter Details:-

Parameter	Type	Description
OutletCode	String	Outlet code
PropertyId	String	Property Id
AppKey	String	App key
Timestamp	String	Time Stamp
DeviceId	String	Device Id
UserId	String	User Id
MoveToCheckNumber	String	Target Open Check/Order Number
Check	Object	Object of Check
TableNumber	String	Table number of the Order
Covers	Integer/Number	Total PAX for the Order
IsResident	String	If the Order is for In House Guest of the Hotel then the value should be "Y" else "N"
IsNonChargeable	String	"Y" for NC KOT ; "N" for Normal order
Comments	String	Comments for the order. Max length 100 characters
CheckNumber	String	Order Number.
OrderLineItems	Arraylist	Contains the items in the order
ItemCode	String	Item Code
ItemName	String	Item Name
SubMenuCode	String	Menu Code in which the item belongs
ItemType	String	Probable Value MI: Menu Item/Regular Item
ItemPrice	Float	Price of the item
IsHappyHour	String	If the item ordered during Happy Hour. Y: Ordered during Happy Hour N: Normal hour
ItemStatus	String	Status of the item in the order



		PO: Saved VT: Voided XI : Moved the item to another order XO: Moved in from another order
CourseNumber	Integer/number	Course number of the item ordered
CoverNumber	Integer/number	Cover which ordered the item
OrderedQuantity	Float	Quantity of the item ordered
KotComment	String	Comment on the item for KOT
ItemAccount	String	Item revenue head
ParentItemCode	String	Parent item code
ItemAccountName	String	Revenue head name
ParentItemSequenceNumber	Integer/Number	Item sequence of the parent item code
PackageConstituentLineItems	ArrayList	Item Package details Optional Can be NULL
ItemQuantity	Integer	Item quantity
ItemCode	String	Item code
ItemName	String	Item name
ItemPrice	Float	Item price
ItemAccount	String	Item Account Code
ItemType	String	Item type
AddOnLineItems	ArrayList	Modifier/Condiment List
AddOnCode	String	Modifier or Condiment defined for the item
AddOnName	String	Description
AddOnType	String	Defines the type of an add-on item (whether it is an open item or menu item or condiment or modifier).
GuestProfile	Object	Guest Details associated with the check/Order
GuestCityName	String	Guest city name
GuestEmailId	String	Guest email id
GuestMembershipId	String	Membership id
GuestName	String	Guest Name
GuestPhoneNumber	String	Guest phone number
GuestProfileCode	Integer	Guest profile code
NewCheckDetails	Object	New order/Check details information
Comments	String	Check Comments
TableNumber	String	Table Number
IsNonChargeable	String	Is Nc Check (Y/N)
IsResident	String	Is resident (Y/N)
Covers	Integer	Number of covers

Response Details:-

Parameter	Type	Description
Check		
CheckNumber	String	CheckNumber
CheckStatus	String	Check Status (PO/VT/ST)
NewCheckDetails		
TableNumber	String	Table Number
Covers	Integer	Number of covers on a table
IsResident	String	
IsNonChargeable	String	Is it a NC Check (Y/N)
GuestProfile		
GuestName	String	Guest name
GuestPhoneNumber	String	Phone number
GuestMembershipId	String	Membership Id
GuestCityName	String	City name
GuestProfileCode	String	Profile Code
GuestEmailId	String	Email Id
Comments	String	Check Comments
Order		
SubTotal	Float	Sub-Total
Discount	Float	Total Discount
Taxes	Float	Total Taxes
Balance	Float	Total balance (Inclusive of discount and taxes)
DiscountSlab		
DiscountCode		
DiscountDetails	ArrayList	Discount details
ItemAccount	String	Item account code
Discount	Double	Discount type (fixed or percentage)
DiscountIndicator	String	Discount Indicator (P or F)
FiredCourseNumbers	ArrayList	All Courses which are fired
OrderLineItems	ArrayList	List of items ordered
ItemCode	String	Item code
ItemName	String	Item name
SubMenuCode	String	Menu Code
ItemType	String	Type of item (menu item, open item, etc...)
ItemPrice	Float	Item Price
IsHappyHour	String	Is it a happy hour check (Yes/No)
ItemStatus	String	Item Status (PO/VT/XO/XI)
CourseNumber	Integer	Course Number
CoverNumber	Integer	Cover Number
OrderedQuantity	Integer	Ordered quantity
KotComment	String	Kot comment for the item
ItemAccount	String	Item Account code (FD/BV/TB/AL/OT)
AddOnLineItems	ArrayList	Add-On Items
AddOnCode	String	Modifier or Condiment defined for the item
AddOnName	String	Description
AddOnType	String	Defines the type of an add-on item (whether it is an open item or menu item or condiment or modifier).
AddOnPrice	Float	Normal price of an add-on item

AddOnQuantity	Float	Add On Quantity ordered
AddOnAccount	String	Addon account code
AddOnStatus	String	Addon status
IsHappyHour	String	Is happy hour running (Yes/No)
PackageConstituents	ArrayList	Package Items
ItemQuantity	Integer	Item quantity
ItemCode	String	Item code
ItemName	String	Item name
ItemType	String	Item Type (MI, OI, etc...)
ItemPrice	Float	Item price
ItemAccount	String	Item Account Code
GuestDetails		
GuestComments	ArrayList	Guest Comments
GuestPreferences	ArrayList	Guest Preferences
OutletName	String	Outlet Name
MenuItemName	String	Item Name
NumberOfTimesOrdered	Integer	Number of times the item is ordered

Response Status:-

Response Value	Description
0	Success
1	OutletCode is null or blank
2	Temp table Failure
3	Item Code/Menu Code/Item Type is null or blank
11	Invalid Outlet
12	Invalid Menu
13	Invalid Menu and Item Link
14	Invalid UserId
15	Invalid Item Type
100 or NULL	Fail

3.4 CancelItems

This method is used for cancelling or voiding previously saved items in the check.

Method Name	CancelItems
URL	<a href="http://<ServerURL>/ToucheLite/CancelItems">http://<ServerURL>/ToucheLite/CancelItems
Sample Request	<pre>{ "PropertyId": "BOGGN", "UserId": "999", "OutletCode": "GNBL", "DeviceId": "999", "GuestName": null, "TipAmount": 0, "CreateOnAuditDate": null, "Check": { "TableNumber": null, "Covers": 0, "IsResident": null, "IsNonChargeable": null, </pre>

	<pre> "Comments": null, "CheckNumber": "B0089963", "GuestProfile": null, "OrderLineItems": [{ "ItemCode": "2446", "ItemName": "RED THAI SHRIMP CURRY", "SubMenuCode": "G145", "ItemType": "MI", "ItemPrice": 499, "IsHappyHour": null, "ItemStatus": null, "CourseNumber": 0, "CoverNumber": 0, "OrderedQuantity": 1, "KotComment": null, "ItemAccount": "FD", "ParentItemCode": null, "ItemAccountName": null, "ParentItemSequenceNumber": 0, "PackageConstituentLineItems": null, "AddOnLineItems": null }], "ExternalReference": { "ExternalReferenceNumber": "T0007419", "ExternalReferenceType": "P" } }, "VoidReason": { "Code": "GCOR", "Reason": "GUEST CANCELLED THE ORDER", "UserInputAllowed": "N" } } </pre>
--	--

Request Parameter Details:-

Parameter	Type	Required	Description
OutletCode	String	Yes	Outlet code
PropertyId	String	Yes	Property Id
AppKey	String	Yes	App key
Timestamp	String	Yes	Time Stamp
DeviceId	String	Yes	Device Id
UserId	String	Yes	User Id
MoveToCheckNumber	String	Yes	Target Open Check/Order Number
Check	Object		Object of Check
TableNumber	String		Table number of the



Touché RESTful APIs

			Order
Covers	Integer/Number		Total PAX for the Order
IsResident	String		If the Order is for In House Guest of the Hotel then the value should be "Y" else "N"
IsNonChargeable	String		"Y" for NC KOT ; "N" for Normal order
Comments	String		Comments for the order. Max length 100 characters
CheckNumber	String		Order Number.
OrderLineItems	Arraylist		Contains the items in the order
ItemCode	String		Item Code
ItemName	String		Item Name
SubMenuCode	String		Menu Code in which the item belongs
ItemType	String		Probable Value MI: Menu Item/Regular Item
ItemPrice	Float		Price of the item
IsHappyHour	String		If the item ordered during Happy Hour. Y: Ordered during Happy Hour N: Normal hour
ItemStatus	String		Status of the item in the order PO: Saved VT: Voided XI : Moved the item to another order XO: Moved in from another order
CourseNumber	Integer/number		Course number of the item ordered
CoverNumber	Integer/number		Cover which ordered the item
OrderedQuantity	Float		Quantity of the item ordered
KotComment	String		Comment on the item for KOT
ItemAccount	String		Item revenue head
ParentItemCode	String		Parent item code
ItemAccountName	String		Revenue head name



ParentItemSequenceNumber	Integer/Number		Item sequence of the parent item code
PackageConstituentLineItems	ArrayList		Item Package details Optional Can be NULL
ItemQuantity	Integer		Item quantity
ItemCode	String		Item code
ItemName	String		Item name
ItemPrice	Float		Item price
ItemAccount	String		Item Account Code
ItemType	String		Item type
AddOnLineItems	ArrayList		Modifier/Condiment List
AddOnCode	String		Modifier or Condiment defined for the item
AddOnName	String		Description
AddOnType	String		Defines the type of an add-on item (whether it is an open item or menu item or condiment or modifier).
VoidReason	Object		Void reason
Code	String		Code of the Reason
Reason	String		Reason description
UserInputAllowed	String		If the user can define the reason description. Valid values Y: Yes (allowed to give/Change the description) N: NO (not allowed to give/Change the description)

Response Details:-

Parameter	Type	Description
CheckNumber	String	Check Number
Balance	Double	Total Balance
CheckStatus	String	Check Status
ResponseStatus	Object	Response from the API
ResponseCode	String	Code of the response. Correlate with below table
ResponseFlag	String	Success : For success API FAIL: Failure of API. Correlate with below table
ResponseMessage	String	Message of the string

Response Status:-

Response Value	Description
0	Success

1	OutletCode is null or blank
2	Temp table Failure
3	Item Code/Menu Code/Item Type is null or blank
11	Invalid Outlet
12	Invalid Menu
13	Invalid Menu and Item Link
14	Invalid UserId
15	Invalid Item Type
16	Invalid Table Number
4 or NULL	Fail

3.5 GetAllOpenChecks

This method returns all the Open Checks of an outlet for the current business Date as well as the tables which are vacant.

Method Name	<i>GetAllOpenChecks</i>
URL	<a href="http://<ServerURL>/ToucheLite/GetAllOpenChecks">http://<ServerURL>/ToucheLite/GetAllOpenChecks
Sample Request	{"PropertyId":"BOGGN","deviceId":"bbc77b1efc8ee78d","AppKey":"DEMI","Timestamp":"12032013","OutletCode":"GNBL"}
Sample URL	<a href="http://<ServerURL>/ToucheAPI/ToucheLite/GetAllOpenChecks?RequestString={\" propertyid\":\"boggn\",\"deviceid\":\"bbc77b1efc8ee78d\",\"appkey\":\"demi\",\"timestamp\":\"12032013\",\"outletcode\":\"gnbl\"}"="">http://<ServerURL>/ToucheAPI/ToucheLite/GetAllOpenChecks? RequestString={"PropertyId":"BOGGN","deviceId":"bbc77b1efc8ee78d","AppKey":"DEMI","Timestamp":"12032013","OutletCode":"GNBL"}

Request Parameter Details:-

Parameter	Type	Required	Description
PropertyId	String	Yes	Property Id
AppKey	String	Yes	App Key
Timestamp	String	Yes	Time Stamp
DeviceId	String	Yes	Device Id
OutletCode	String	Yes	Outlet Code

Success	{ "Checks": [{ "IsNonChargeable": "N", "CheckNumber": "M00024", "TableNumber": "21", "CoverNumber": 1, "CourseNumber": 1, "CheckOpenTime": "12:05", "ServerName": "John Martin", "ServerCode": "999", "TotalOrderPrice": 276, "GuestName": "", "Comment": "", "CheckStatus": "PO", "IsCheckLinked": "N" }] }
---------	--

	<pre> }, { "CheckNumber": "M00026", "TableNumber": "25", "CoverNumber": 1, "CourseNumber": 1, "CheckOpenTime": "12:58", "ServerName": "John Martin", "ServerCode": "999", "TotalOrderPrice": 1306, "GuestName": "", "Comment": "medium spicy", "CheckStatus": "PO", "IsNonChargeable": "N", "IsCheckLinked": "N" }], "ResponseStatus": { "ResponseCode": "0", "ResponseFlag": "SUCCESS", "ResponseMessage": null } } </pre>

Response Details:-

Parameter	Type	Description
Checks	ArrayList	List of all the open checks
IsNonChargeable	String	Is it a NC Check(Y/N)
CheckNumber	String	Check Number
TableNumber	String	Table Number
CoverNumber	String	Total Covers
CourseNumber	String	Course Number
CheckOpenTime	String	Check Open Date
ServerName	String	Server Name
ServerCode	String	Server Code
TotalOrderPrice	String	Total Price
GuestName		Guest Name
Comment	String	Comment on the check
CheckStatus	String	Check Status - PO (OPEN) - ST (SETTLED) - VT (VOIDED)

3.6 GetClosedOrders

This method returns all the Closed Checks of an outlet for the Date range.

Method Name	<i>GetClosedOrders</i>
URL	<a href="http://<ServerURL>/ToucheLite/GetClosedOrders">http://<ServerURL>/ToucheLite/GetClosedOrders
Sample Request	{

	<pre> "appKey": "demo", "deviceId": "cf83185b6df5740b", "propertyId": "HINC", "timestamp": 1454066573367, "outletCode": "TBC", "userId": "888", "DateStart": "20jul2015", "DateEnd": "20jul2015" } </pre>

Request Parameter Details:-

Parameter	Type	Required	Description
PropertyId	String	Yes	Property Id
AppKey	String	Yes	App Key
Timestamp	String	Yes	Time Stamp
DeviceId	String	Yes	Device Id
OutletCode	String	Optional	Outlet Code
DateStart	String	Yes	Begin date
DateEnd	String	Optional	End Date

Success	<pre> { "ResponseStatus": { "ResponseCode": "0", "ResponseFlag": "SUCCESS", "ResponseMessage": null } "OutletOrders": [{ "OutletCode": "TBC", "OutletDescription": "THE DEMO OUTLET", "Orders": [{ "OrderDate": "20/07/2015 12:00:00 AM", "OrderDetails": [{ "CheckNumber": "00014498", "OpenTime": "12:04", "CloseTime": "12:15", "DebitTotal": 0, "CreditTotal": 0, "OrderItems": [{ "ItemCode": "1977", "ItemDescription": "DOUBLE ESPRESSO", "Quantity": 1, "Value": 180, "OrderTime": "12:04" }, { "ItemCode": "1977", "ItemDescription": "DOUBLE ESPRESSO", "Quantity": -1, "Value": -180, "OrderTime": "12:15" }, { "ItemCode": "1992", "ItemDescription": "CAPPUCCINO", "Quantity": 3, </pre>
---------	---



	<pre> "Value": 360, "OrderTime": "12:04" }, { "ItemCode": "1992", "ItemDescription": "CAPPUCCINO", "Quantity": -3, "Value": -360, "OrderTime": "12:15" }}, "OrderPayments": [] }} } </pre>

Response Details:-

Parameter	Type	Description
OutletOrders	ArrayList	List of all the Closed checks for outlet wise
OutletCode	String	Outlet code defined in Touché
OutletDescription	String	Outlet Name as defined in Touché
Orders	ArrayList	Contains all the orders Date wise
OrderDetails	ArrayList	Array list containing each of the order for a date
OrderDate	String	Details of the order for the date
OrderDetails	Array List	Array list containing each order
CheckNumber	String	Check number or Order number maintained in Touché
OpenTime	String	Open time of the order creation
CloseTime	String	Close time of order (time when the order was completely settled)
DebitTotal	Double	Total order value
CreditTotal	Double	Total payment or settlement value
OrderItems	ArrayList	Items in order is contained in the arraylist
ItemCode	String	Unique code of the item defined in Touché
ItemDescription	String	Name of item defined in Touché
Quantity	Float	Quantity ordered in the order. This can have –ve values in case of items when voided and also decimal values when items are split into multiple checks/orders
Value	double	Total value of the item. Value can have –ve values depending on voiding of items.
OrderTime	String	Time when item was saved with order
OrderPayments	ArrayList	Contains all the payments or settlements against the order.
PaymentCode	String	Payment code defined in Touché
PaymentDescription	String	Payment description defined in Touché
Amount	Double	Payment amount
PaymentTime	String	Time of payment transaction.

3.7 SettleOrder

This method will return all the discounts defined in Touché for the outlet specified in the request.

Method Name	<i>SettleOrder</i>
URL	<a href="http://<ServerURL>/ToucheAPI/ToucheLite/SettleOrder">http://<ServerURL>/ToucheAPI/ToucheLite/SettleOrder
Sample Request	<pre>{ "appKey": "test", "deviceId": "d1b4dae3723293cf", "propertyId": "BOGGN", "timestamp": 1419920490603, "cardDetails": { "cardExpiryDate": null, "cardNumber": null, "cardStrip": null }, "userId": "999", "settlementType": "CA", "checkNumber": "M0015803", "isCompletelySettled": "Y", "outletCode": "MB", "settlementOptionCode": "CASH", "settleGuestDetails": { "accountId": null, "guestName": null, "roomNumber": null, "membershipId": null, "pointsRedeemed": 0, "guestProfileCode": 0 }, "receivedAmount": 14130.67, "checkBalance": 14122.5, "shiftNumber": 1, "checkAmount": 14122.5 }</pre>

Request Parameter Details:-

Parameter	Type	Description
AppKey	String	App key
Timestamp	String	Time Stamp
DeviceId	String	Device Id
PropertyId	String	Property Id
OutletCode	String	Outlet for which the settlements is required
UserId	String	Will get only applicable settlement options
cardDetails	Object	Credit Card Details
cardExpiryDate	String	Credit Expiry date
cardNumber	String	Credit card number
cardStrip	String	Magnetic strip value



settlementType	String	Settlement type : value from Settlement Options
isCompletlySettled	String	Y/N. Y if the settlement is complete
settlementOptionCode	String	Correlate with settlement option
settleGuestDetails	Object	
accountId	String	Special account id
guestName	String	Name of the guest
roomNumber	String	Room number for room settlement
membershipId	String	Club Member id for club settlement
pointsRedeemed	Int	Settlement against points earned. CI type of settlement
guestProfileCode	Int	Guest profile id
receivedAmount	Float	Amount to settle
checkBalance	Float	Balance of check
checkAmount	Float	Total value of check
shiftNumber	Int	Current shift number

Success	{ "ResponseStatus": { "ResponseCode": "0", "ResponseFlag": "Success", "ResponseMessage": "" } }
Fail	{ "ResponseStatus": { "ResponseCode": "101", "ResponseFlag": "Fail", "ResponseMessage": "" } }

Response Status:-

Response Value	Description
0	Success
100	Fail

3.8 ItemAvailabilityStatus

This end point will return the availability status of item(s) for all or with in a menu.

Method Name	SettleOrder
URL	<a href="http://<ServerURL>/ToucheAPI/ToucheLite/ItemAvailabilityStatus">http://<ServerURL>/ToucheAPI/ToucheLite/ItemAvailabilityStatus
Sample Request	{ "appKey": "test", "deviceId": "d1b4dae3723293cf", "propertyId": "BOGGN", "timestamp": 1419920490603, }



	<pre>"UserId": "999", "MenuCode": "", "ItemCode": "" }</pre>
--	--

Request Parameter Details:-

Parameter	Type	Description
AppKey	String	App key
Timestamp	String	Time Stamp
DeviceId	String	Device Id
PropertyId	String	Property Id
OutletCode	String	Outlet for which the settlements is required
UserId	String	Will get only applicable settlement options
MenuCode	String	Menu code as defined in Touché POS
ItemCode	String	Item Code as defined in Touché POS

Success	<pre>{ "ResponseStatus": { "ResponseCode": 0, "ResponseFlag": "SUCCESS", "ResponseMessage": "" }, "ItemAvailabilityList": [{ "ItemName": "BLUO SPECIAL NACHOS", "ItemCode": "1001", "IsAvailable": "Y" }, { "ItemName": "BLUO SPECIAL NACHOS", "ItemCode": "1001", "IsAvailable": "Y" }, { "ItemName": "MURG BIRYANI", "ItemCode": "1102", "IsAvailable": "N" }, { "ItemName": "CHICKEN FRIED RICE", "ItemCode": "1103", "IsAvailable": "N" }] }</pre>
Fail	<pre>{ "ResponseStatus": { "ResponseCode": "101", "ResponseFlag": "Fail", "ResponseMessage": "" } }</pre>



	} }
--	--------

Response Status:-

Response Value	Description
0	Success
100	Fail

Response Details:-

Parameter	Type	Description
ResponseStatus	Object	Response Object
ResponseCode	Int	0 : success ; > 0 : Fail
ResponseFlag	String	Success or FAIL
ResponseMessage	String	Error Response
ItemAvailabilityList	ArrayList	Array list containing each of the Item status
ItemName	String	Description of Item
ItemCode	String	Item Code
IsAvailable	String	Y : Available; N : Not Available