

VoxPro API — Access & Recording Guide

Audience: Engineers and AI assistants working in this repository.

Purpose: Document how to retrieve call logs from the PeopleLogic **VoxPro** telephony system and how to download the associated **WAV** call recordings. This is the source of truth for any Pluto integration that analyzes recruiter–candidate phone conversations.

Status: API behavior and recording URLs confirmed on live data. **Pluto integration implemented** in `pluto/voxpro/` with HTTP routes under `/api/voxpro/calls/`. This file remains the external API contract; pipeline details below.

1. System context

Item	Detail
Product	VoxPro — internal PBX/VoIP used by recruiters at PeopleLogic
Host	<code>office.peoplelogic.in</code>
Use in Pluto	Fetch all calls for a candidate phone number → download recordings → transcribe → merge → AI call analysis (see product discussions; implementation lives under <code>pluto/voxpro/</code> when added)
Network	Pluto (or any client) must run on a network that can reach <code>http://office.peoplelogic.in</code> (VPN/LAN). No HTTPS in current deployment.

Troubleshooting: HTTP 404 with “Access Denied”

If `log_pull` returns **404** and the body is HTML `<b>Access Denied</b>` (Apache), the URL is correct but your **client IP is blocked**. This is not a Pluto bug.

Check	Action
VPN / office LAN	Connect to PeopleLogic VPN or run Pluto on a server inside the office network
Smoke test	<code>python scripts/test_voxpro_flow.py 9599015158 --days 30</code> — expect HTTP 200 and a JSON array
Wrong symptom	True “not found” would differ; live failures observed are Access Denied on all path variants

Pluto maps this to a clear API error (503) for the Call Analysis UI.

2. Call log API — `log_pull`

Endpoint

Property	Value
URL	<code>http://office.peoplelogic.in/Voxpro/api/log_pull</code>
Method	<code>GET</code>
Header	<code>Content-Type: application/json</code>
Body	JSON (sent with the GET request — non-standard; clients must not strip the body)

Postman uses `disableBodyPruning: true` for this reason. In code, use an HTTP library that allows a JSON body on GET (e.g. Python `requests.request("GET", url, json=payload)`).

Request body

```
{ "from": "2025-11-22 15:19:09", "to": "2026-01-20 15:19:10", "phone": "9599015158",  
  "status": "CONNECTED" }
```

Field	Type	Required	Description
<code>from</code>	string	Yes	Range start. Format: YYYY-MM-DD HH:MM:SS
<code>to</code>	string	Yes	Range end. Same format as <code>from</code>
<code>phone</code>	string	No	10-digit mobile number (no country code in samples). Filters calls where the number appears in src or dst
<code>status</code>	string	No	"CONNECTED" or "NOT CONNECTED". Omit to return all statuses

Phone filter behavior (important)

When phone is set, VoxPro returns the candidate's **full history** for that number:

- **OUTGOING** — agent extension in `src` (e.g. "362"), customer number in `dst`
- **INCOMING** — customer number in `src`, agent extension in `dst`

So one `phone` query returns both directions and all agents who called that number within the date range. Pluto should **not** pull the entire company log and filter locally — always pass `phone` for candidate-centric workflows.

Example request (curl)

curl does not reliably send a body with GET. Prefer Python or Postman. Example with Python:

```
import requests url = "http://office.peoplelogic.in/Voxpro/api/log_pull" payload = {
  "from": "2025-11-01 00:00:00", "to": "2026-05-20 23:59:59", "phone": "9599015158", } resp =
requests.request("GET", url, json=payload, timeout=60) resp.raise_for_status() calls =
resp.json() # list of dicts
```

Response

- **HTTP status:** 200 OK
- **Body:** JSON array of call objects (may be empty [])

Sample record

```
{ "sln": "2741533", "datetime": "2026-01-08 15:46:46", "email_id":
"suriya.e@peoplelogic.in", "src": "362", "dst": "9599015158", "dest_type": "", "did": "",
"dur": "161", "callmethod": "OUTGOING", "rec_fname": "2026-01-08_15:46:46_362_9599015158",
"rec_location": "MUSIC/2026/01/08", "status": "CONNECTED", "dtmf": "", "MRD_NUM": "" }
```

Field reference

Field	Description
<code>sln</code>	Unique call ID — use for deduplication in Pluto DB
<code>datetime</code>	Call timestamp YYYY-MM-DD HH:MM:SS
<code>email_id</code>	Agent email (maps to Pluto <code>users.email</code>)
<code>src</code>	Source: extension (outgoing) or customer number (incoming)
<code>dst</code>	Destination: customer number (outgoing) or extension (incoming)
<code>dest_type</code>	e.g. "Extension", "Time_condition", or ""
<code>did</code>	DID for incoming routing; often empty on outgoing
<code>dur</code>	Duration in seconds as string (e.g. "161", "0"). "" (empty) = no connected talk time → treat as no recording for Pluto (see §2.1)
<code>callmethod</code>	"OUTGOING" or "INCOMING"

rec_fname	Recording base name without .wav extension
rec_location	Folder path under the office host (e.g. MUSIC/2026/01/08)
status	"CONNECTED" or "NOT CONNECTED"
dtmf	DTMF digits if any; usually empty
MRD_NUM	Internal reference; usually empty

rec_fname naming pattern

```
{datetime}_{extension}_{phone} # typical OUTGOING (includes agent extension)
{datetime}_{phone} # some INCOMING (customer number only, no extension in name)
```

Examples:

- Outgoing: 2026-01-08_15:46:46_362_9599015158
- Incoming: 2026-01-08_15:46:33_9599015158

URL construction is the same in all cases (see §3).

2.1 dur — fetch vs analyze

VoxPro API: `log_pull` returns **all** call rows for the phone in the date range. There is **no server-side filter** on `dur`. Pluto filters locally after the response.

Pluto rule (default VOXPRO_MIN_DUR_SECONDS=5):

dur	Pluto behaviour
"" (empty)	Skip — no connected talk time
"0" ... "5"	Stored in DB for audit; not downloaded, transcribed, or shown in Call Analysis UI
">5" (e.g. "8", "161")	Download WAV, merge/STT, LLM analysis, show in UI

```
# pluto/voxpro/client.py – duration strictly greater than 5 seconds dur_meets_minimum(dur)
# alias: dur_has_recording(dur)
```

Caveats (still verify with HTTP):

1. **Retention** — Old rows can have `dur` set but the .wav file returns **404** (file deleted, log kept). Always handle failed downloads.
2. **Rare edge case** — Some `NOT CONNECTED` rows have `dur=""` but a WAV file still exists on disk. Pluto skips those for candidate analysis.
3. **Tune threshold** — Set `VOXPRO_MIN_DUR_SECONDS` in `.env` if product wants a different cutoff.

Call Analysis UI copy: “Showing calls with duration > 5 seconds only.”

3. Call recordings — download URL

Recordings are **not** returned in the `log_pull` JSON. They are separate **WAV** files on the same host.

URL format (confirmed)

```
http://office.peoplelogic.in/{rec_location}/{rec_fname}.wav
```

Part	Source
Base	<code>http://office.peoplelogic.in</code>
Path	<code>rec_location</code> from log row (no leading slash)
File	<code>rec_fname + .wav</code>

Construction (pseudo-code)

```
base = "http://office.peoplelogic.in" url = base + "/" + rec_location.strip("/") + "/" +  
rec_fname + ".wav"
```

Worked example

From the sample record above:

```
rec_location = MUSIC/2026/01/08 rec_fname = 2026-01-08_15:46:46_362_9599015158 →  
http://office.peoplelogic.in/MUSIC/2026/01/08/2026-01-08_15:46:46_362_9599015158.wav
```

Confirmed: `GET` that URL returns **200 OK** with WAV audio binary.

Example download (Python)

```
import requests def voxpro_recording_url(rec_location: str, rec_fname: str) -> str: base =  
"http://office.peoplelogic.in" loc = rec_location.strip("/") return  
f"{base}/{loc}/{rec_fname}.wav" url = voxpro_recording_url("MUSIC/2026/01/08",  
"2026-01-08_15:46:46_362_9599015158") r = requests.get(url, timeout=120)  
r.raise_for_status() with open("call_2741533.wav", "wb") as f: f.write(r.content)
```

When a recording may be missing or useless

Condition	Guidance
<code>dur</code> is ""	Skip — no recording to analyze (primary gate)
<code>dur</code> is numeric but HTTP 404	Log row only; file purged — skip

<code>rec_fname</code> or <code>rec_location</code> empty	Do not build URL
HTTP non-200 on <code>.wav</code>	Log and skip that call; do not fail entire batch
Very large date ranges	<code>log_pull</code> may return many rows — chunk by month or cap lookback (e.g. 90 days)

4. Pluto pipeline (implemented)

For a single candidate phone number, `pluto.voxpro.pipeline.run_call_analysis()`:

1. **Normalize phone** — 10-digit form for `log_pull`.
2. **log_pull** + upsert `voxpro_calls` (dedupe on `sln`).
3. **Download WAVs** where `dur > VOXPRO_MIN_DUR_SECONDS` (default 5) → `uploads/calls/{sln}.wav`.
4. **Merge audio** (primary) — `pydub` + **ffmpeg** → `merged_{phone}_{batch}.wav`; skip if over size/duration caps.
5. **Speech-to-text** — Groq Whisper primary; Gemini fallback; per-call STT if merge/STT fails.
6. **LLM analysis** — `generate_content_unified()` → JSON + markdown in `candidate_call_analyses`.

HTTP routes (login required)

Method	Path	Purpose
POST	<code>/api/voxpro/calls/fetch</code>	Ingest logs; optional download only
POST	<code>/api/voxpro/calls/analyze</code>	Full pipeline (rate limit 3/min)
GET	<code>/api/voxpro/calls?phone=</code>	Cached calls + latest analysis

System dependencies

- Python: `pydub` (see `requirements.txt`)
- OS: **ffmpeg** on PATH (`sudo apt install ffmpeg` on Linux)

Smoke test

```
python scripts/test_voxpro_flow.py 9599015158 --download 2
```

5. Live data observations

- `dur` is an **empty string** (not `"0"`) when `status` is `"NOT CONNECTED"`.
- INCOMING not connected may have `dest_type`: `"Time_condition"` (routing rule before agent).

- INCOMING connected calls may show `dur: "0"` or a positive value; may include `did`.
- The same phone can appear with **multiple** `email_id` values across calls.
- Authentication is **not** documented on these endpoints — access is effectively **internal network trust**. Do not expose VoxPro URLs on the public internet without a gateway.

6. Environment variables (Pluto)

See `.env.example` and [../guides/ENV AND MODELS.md](#).

7. Related repository files

Path	Role
<code>docs/integrations/VOXPRO_API.md</code>	This document
<code>pluto/voxpro/</code>	Client, ingest, merge, transcribe, analyze, pipeline
<code>pluto/routes/voxpro_views.py</code>	Flask handlers
<code>pluto/blueprints/pluto_api.py</code>	Route registration
<code>templates/call_analysis.html</code>	Dedicated beta page (<code>/call-analysis</code>)
<code>static/js/call-analysis-page.js</code>	Call Analysis page UI
<code>static/js/voxpro-calls.js</code>	Legacy inline UI (unused; kept for reference)
<code>scripts/test_voxpro_flow.py</code>	Log pull + download smoke test

If this document and the code disagree, **verify against VoxPro live behavior** and update this file.

8. Quick reference card

```
LOGS: GET http://office.peoplelogic.in/Voxpro/api/log_pull Body: { "from": "...", "to": "...", "phone": "10digits", "status": optional } RECORDING: http://office.peoplelogic.in/{rec_location}/{rec_fname}.wav DEDUPE KEY: slno MERGE KEY: phone (10-digit) + optional job/candidate link in Pluto
```

Last updated from confirmed integration findings (log_pull + WAV URL 200 OK).