Supplementary Material for CFFM-Net: Reliability-Gated Mamba Fusion of Visible and Thermal Images for Detection, Tracking and Multi-Camera Analytics

Ritesh Roshan

This document holds the material moved out of the main paper to meet the page limit. Every number comes from the same result files as the main paper and no claim differs. Tables are numbered S1 onward.

S1. Per-seed results

Table S1 lists every run behind the headline comparison, with the mean and sample standard deviation over seeds. Table S2 gives the per-seed mAP margin of v2 over the concat baseline, which is the quantity averaged in Table I of the main paper.

S2. Fine size bands on M3FD

Table S3 gives the finer size bands behind the small-object analysis of the main paper.

S3. Degradation probe of the round-one models

Table S4 gives the LLVIP degradation probe that preceded the fault benchmark. It uses the round-one models at 30 epochs and one seed.

S4. Ablation detail

Table S5 lists every variant of the ablation of the main paper and Table S6 the margin over the control in each round.

S5. Multi-camera results

Table S7 reports detection, tracking and counting. Zero-shot, the detector has high precision (92.1 %) and low recall (46.5 %), giving a MODA of 42.5 %. These are the numbers of a detector that has never seen the viewpoint: it finds 443 people and misses 509. Fine-tuning on the training frames lifts MODA to 77.4 %, with recall 87.3 % and precision 89.8 %, and cuts the misses to 121 at the price of more false positives (94 against 38). Localisation quality, MODP, is similar for the two, 77.6 % and 76.5 %.

On the ground-plane tracks the system reaches MOTA 79.4 % and IDF1 84.9 %, with 18 identity switches, and tracks 25 of 41 people for most of their presence. Counting is accurate enough to be useful: the mean absolute error of the total count is 1.43 people on a mean of 23.8 people per frame, a relative error of 6.0 %, and the error per zone ranges from 0.43 to 1.18 people. Crossings of the reference line number 11 in one direction and 0 in the other. The busiest zone is the second, with 46 tracks and a mean dwell of 12.4 s, against 5.7 s in the first and 4.0 s in the third.

These results describe the multi-camera layer on RGB input; they say nothing about visible-thermal fusion.

S6. Stream monitor timing

Table S8 gives the detection and recovery delay of the stream monitor and its false alarms for each scripted link fault of the live runtime experiment, with the monitor feeding the model (on) and only observing (off).

S7. Live runtime measurements

Table S9 gives the soak test and the link-fault run of the live runtime experiment on replayed KAIST sequences.

TABLE S1
PER-SEED ACCURACY IN PERCENT, 80 EPOCHS. THE LAST THREE COLUMNS ARE COCO SIZE BANDS.

Dataset	Model	Seed	mAP	mAP_{50}	Precision	Recall	Small	Medium	Large
LLVIP	Concat, modality dropout	0	64.8	97.2	96.8	91.7	8.0	64.7	66.1
		1	66.3	96.6	97.0	91.7	9.6	65.8	69.3
		2	65.2	96.6	96.7	90.6	11.0	64.6	68.3
	mean ± std		65.5 ± 0.8	96.8 ± 0.4	96.9 ± 0.2	91.3 ± 0.6	9.6 ± 1.5	65.0 ± 0.6	67.9 ± 1.6
	CFFM-Net v2	0	65.6	97.0	96.4	92.4	8.2	65.5	66.8
		1	66.0	96.6	97.1	91.2	9.0	65.5	68.7
		2	67.1	97.2	96.4	92.4	10.2	66.5	70.5
	mean ± std		66.2 ± 0.8	96.9 ± 0.3	96.6 ± 0.5	92.0 ± 0.7	9.1 ± 1.0	65.8 ± 0.6	68.7 ± 1.9
M3FD	Concat, modality dropout	0	53.5	82.2	85.5	76.4	34.9	67.5	87.0
		1	53.5	81.7	86.4	74.2	34.6	66.9	88.4
		2	52.9	81.8	87.6	74.3	34.8	65.9	86.2
	mean ± std		53.3 ± 0.3	81.9 ± 0.3	86.5 ± 1.1	74.9 ± 1.2	34.8 ± 0.2	66.8 ± 0.8	87.2 ± 1.1
	CFFM-Net v2	0	53.7	82.7	88.8	74.4	34.9	66.8	87.4
		1	54.0	83.4	88.7	75.0	35.1	66.5	87.8
		2	53.9	82.2	85.7	75.0	35.5	66.9	88.0
	mean ± std		53.9 ± 0.1	82.7 ± 0.6	87.7 ± 1.8	74.8 ± 0.4	35.2 ± 0.3	66.7 ± 0.2	87.7 ± 0.3

TABLE S2
PER-SEED MAP MARGIN OF CFFM-NET V2 OVER THE CONCAT BASELINE, IN PERCENTAGE POINTS.

Dataset	Seed 0	Seed 1	Seed 2
LLVIP	+0.7	−0.4	+1.9
M3FD	+0.3	+0.5	+1.0

TABLE S3
M3FD AVERAGE PRECISION IN THE FINER SIZE BANDS, PERCENT, PER SEED AND AS MEAN AND SAMPLE STANDARD DEVIATION.

Model	Seed	Very tiny	Tiny	Small
Concat, modality dropout	0	7.5	24.7	48.6
	1	7.8	25.5	47.3
	2	7.6	21.6	49.2
	mean ± std	7.6 ± 0.2	23.9 ± 2.1	48.4 ± 1.0
CFFM-Net v2	0	7.6	24.7	47.9
	1	7.7	24.9	48.4
	2	8.9	25.3	48.6
	mean ± std	8.0 ± 0.8	24.9 ± 0.3	48.3 ± 0.4

TABLE S4
DEGRADATION PROBE ON LLVIP, MAP IN PERCENT, ROUND-ONE MODELS (30 EPOCHS, SEED 0).

Condition	v1	v1, no gate	Concat
Clean	62.9	62.6	65.0
Visible dark	59.9	54.2	61.0
Visible drop	56.7	57.0	61.8
Visible drop, flagged	59.5	57.0	61.8
Thermal drop	2.2	0.7	0.3
Thermal drop, flagged	17.4	0.7	0.3
Thermal shift 4 px	53.3	51.8	51.6
Thermal shift 8 px	32.6	31.1	29.7
Thermal shift 16 px	2.8	2.9	1.7

TABLE S5
ABLATION OF MAP IN PERCENT. A DASH MARKS A RUN THAT WAS NOT MADE.

Variant	LLVIP	M3FD
Round one, 30 epochs, seed 0		
Two-stream concat	64.9	50.5
CFFM-Net v1	62.9	47.9
v1, no gate	62.6	–
v1, gated conv	62.8	–
Concat + P2 head	63.2	–
v1, no P2 head	63.5	–
Rounds three and four, 80 epochs, seed 0		
Concat, modality dropout	64.8	53.5
CFFM-Net v2	65.6	53.7
Concat, fault training	66.4	52.9
CFFM-Net v3	64.0	51.9
v3, no reliability branch	67.2	53.3

TABLE S6
ROUND HISTORY: MAP MARGIN OF CFFM-NET OVER ITS CONTROL IN PERCENTAGE POINTS.

Comparison	LLVIP	M3FD
Round one, v1 against concat (30 epochs)	−2.1	−2.6
Head control, v1 without P2 against concat with P2	+0.3	–
Round three, v2 against concat (seed 0)	+0.7	+0.3
Round three, v2 against concat (three-seed mean)	+0.8	+0.6
Round four, v3 against fault-trained concat	−2.4	−0.9
Round four, v3 against v3 without reliability branch	−3.2	−1.4
Round four, v3 against v2	−1.5	−1.8

TABLE S7
MULTI-CAMERA ANALYTICS. DETECTION USES ZERO-SHOT AND FINE-TUNED YOLO26-M WITH GROUND-PLANE FUSION; TRACKING AND COUNTING ARE REPORTED ONCE.

Measure	Zero-shot	Fine-tuned
Detection		
MODA (%)	42.5	77.4
MODP (%)	77.6	76.5
Precision (%)	92.1	89.8
Recall (%)	46.5	87.3
True positives	443	831
False positives	38	94
False negatives	509	121
Tracking		
MOTA (%)	79.4	
IDF1 (%)	84.9	
ID switches	18	
Mostly tracked of 41	25	
Counting		
Count MAE (people)	1.43	
Relative error (%)	6.0	
Zone one MAE	0.93	
Zone two MAE	1.18	
Zone three MAE	0.43	

TABLE S8
STREAM MONITOR TIMING FOR EACH SCRIPTED FAULT, WITH THE MONITOR FEEDING THE MODEL (ON) AND ONLY OBSERVING (OFF). DELAYS ARE SECONDS FROM ONSET OR END OF THE FAULT TO THE FIRST CHANGE OF STATE.

	Detect (s)		Recover (s)		False alarms (%)	
Fault	On	Off	On	Off	On	Off
Thermal unplugged, 6 s	0.29	0.28	0.19	0.18	4.3	5.0
Visible frozen, 6 s	0.69	0.52	0.10	0.13	0.0	0.0
Thermal stalled, 3 s	0.31	0.26	0.12	0.16	6.1	8.0

TABLE S9
LIVE RUNTIME ON REPLAYED KAIST SEQUENCES. SOAK: PAIRED CAMERAS AT THE STATED RATE. LINK FAULTS: 20 FPS WITH A SCRIPTED CABLE PULL, FREEZE AND STALL. DRIFT IS THE LATE MINUS THE EARLY MEDIAN END-TO-END DELAY. ONE RUN PER ROW.

	Soak		Link faults	
Measure	30 fps	20 fps	Monitor on	Monitor off
Run time (s)	594	117	107	107
Throughput (frames/s)	12.4	12.7	11.8	12.0
Capture drop (%)	58.8	36.3	–	–
End-to-end median (ms)	94.4	100.0	101.5	100.7
End-to-end p95 (ms)	117.9	129.9	139.4	139.4
Inference median (ms)	70.9	68.3	72.6	70.5
Inference p95 (ms)	88.7	89.3	98.6	99.9
Drift (ms)	+0.3	+8.2	+10.7	−2.8
GPU memory growth (MB)	−1	0	+1	−1
Miss rate, all frames (%)	–	–	27.9	27.1
Camera reconnects	–	–	10	10