

AWS bucket setup and mounting in it ubuntu server , setting up permission

Creating user in AWS and create Access key and Secret key

- Navigate to IAM service.
- Click on Users in the left sidebar.
- Create User and provide name with Set permission
- Point to create access key at right top
- Select the dropbox which is required (Other) and click next
- You will get the Access and Secret key (Download .csv file)

Creating AWS bucket

- Login to AWS account
- Point to S3 and create bucket
- Bucket type — General purpose
- Bucket name — Provide name
- Object Ownership — ACLs disabled
- Bucket Versioning — Disable
- Rest leave everything default and create bucket

Create user in AWS

- Go to IAM user
- Under Access management go to user
- Click on create user and provide a username
- Permissions can be set later, click create user

Create Group in AWS

- Go to IAM user
- Under Access management go to User groups
- Create group and provide a name

Create IAM user policy

- Go to IAM user
- Under Access management go to Policies
- Click on create policy and point to JSON
- In Policy editor , specify the policy below mentioned (according to your bucket)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AllowS3Access",
      "Effect": "Allow",
      "Action": [
        "s3:PutObject",
        "s3:GetObject"
      ],
      "Resource": "arn:aws:s3:::tnd-bucket-styra/*"
    },
    {
      "Sid": "AllowListBucket",
      "Effect": "Allow",
      "Action": "s3:ListBucket",
      "Resource": "arn:aws:s3:::tnd-bucket-styra"
    },
    {
      "Sid": "AllowSTS",
      "Effect": "Allow",
      "Action": [
        "sts:AssumeRole",
        "sts:GetCallerIdentity"
      ],
      "Resource": "*"
    }
  ]
}
```

- Provide the name for your policy and create policy

Create Permission policy for YOUR USER

- Go to Access management — User — Permissions —Add permissions — Create inline policy — JSON
- In Policy editor, add the below specified policy (update accordingly to your bucket)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "VisualEditor0",
      "Effect": "Allow",
      "Action": [
        "s3:PutObject",
        "s3:GetObject",
        "s3:ListBucket"
      ],
      "Resource": "arn:aws:s3:::tnd-bucket-styra/"
    },
    {
      "Sid": "VisualEditor1",
      "Effect": "Allow",
      "Action": [
        "sts:AssumeRole",
        "sts:GetCallerIdentity"
      ],
      "Resource": "*"
    }
  ]
}
```

- Click next and provide a name for your policy
- Add another policy for S3 by clicking on Add permission option
- Add another policy for Administrator Access by clicking on Add permission option

Permissions policies (3)

Permissions are defined by policies attached to the user directly or through groups.

Search

Filter by Type

All types

☐	Policy name	Type	Attached via
☐	 AdministratorAccess	AWS managed - job function	Directly
☐	 s3access	Customer managed	Group s3user
☐	 Styra-TnD-S3-User-Policy	Customer inline	Inline

Add USER to GROUP

- Go to user
- Under user go to group
- See for the option add user to group
- Add the the created group to that user

Create ROLE and attach permission to ROLES

- Go to IAM policy
- Under Access management go to role and create role
- Select the Trusted Entity Type as AWS service
- Select the Use case as S3
- Add permission for Administrator Access
- Provide a role name
- For trusted entity policy provide the below specified conditions (AWS ARN replace)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Principal": {
        "Service": "s3.amazonaws.com",
        "AWS": "arn:aws:iam::247789200269:user/karthik"
      },
      "Action": "sts:AssumeRole"
    }
  ]
}
```

Attach policy to ROLE

- Point to Role in Access managemnet
- Go to Add permissions – Add Policy
- Select the policy which is created for earlier in POLICY
- Attach the policy to ROLE

Instaling and configuring AWS CLI

- Run the below command in the ubuntu server where you want to install AWS CLI
- `sudo apt install -y curl unzip`
- `curl "https://awscli.amazonaws.com/awscli-exe-linux-x86_64.zip" -o "awscliv2.zip"`
- `unzip awscliv2.zip`
- `sudo ./aws/install`
- `aws --version`
- `aws configure`
 - Access key
 - Secret Key
 - Region
 - json

```
root@mescom-dtlms-prod:/# aws configure
AWS Access Key ID [None]: AKIATTMLDE0GZZT0LHG3
AWS Secret Access Key [None]: RUSWybMPGnMn/MihwZCm+NEn2XPdHwoqjf1Zm/K2
Default region name [None]: ap-south-1
Default output format [None]: json
root@mescom-dtlms-prod:/#
```