

Started on	Friday, 24 April 2026, 9:50 PM
State	Finished
Completed on	Friday, 24 April 2026, 10:35 PM
Time taken	45 mins 8 secs
Grade	9.00 out of 10.00 (90%)

Question 1

Correct Mark 1.00 out of 1.00

Given an array `nums` containing `n` distinct numbers in the range `[0, n]`, return *the only number in the range that is missing from the array*.

Example 1:

Input: `nums = [3,0,1]`

Output: `2`

Explanation: `n = 3` since there are 3 numbers, so all numbers are in the range `[0,3]`. 2 is the missing number in the range since it does not appear in `nums`.

Example 2:

Input: `nums = [0,1]`

Output: `2`

Explanation: `n = 2` since there are 2 numbers, so all numbers are in the range `[0,2]`. 2 is the missing number in the range since it does not appear in `nums`.

Example 3:

Input: `nums = [9,6,4,2,3,5,7,0,1]`

Output: `8`

Explanation: `n = 9` since there are 9 numbers, so all numbers are in the range `[0,9]`. 8 is the missing number in the range since it does not appear in `nums`.

For example:

Test	Result
<code>print(missingNumber([3,0,1]))</code>	<code>2</code>
<code>print(missingNumber([0,1]))</code>	<code>2</code>

Answer: (penalty regime: 0 %)

Reset answer

```
1 def missingNumber(nums):
2     n = len(nums)
3     expected_sum = n*(n+1)//2
4     actual_sum = sum(nums)
5     return expected_sum - actual_sum
6
```

	Test	Expected	Got	
✓	<code>print(missingNumber([3,0,1]))</code>	<code>2</code>	<code>2</code>	✓

	Test	Expected	Got	
✓	print(missingNumber([0,1]))	2	2	✓
✓	print(missingNumber([9,6,4,2,3,5,7,0,1]))	8	8	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 2 | Incorrect Mark 0.00 out of 1.00

String should contain only the words are not palindrome.

Sample Input 1

Malayalam is my mother tongue

Sample Output 1

is my mother tongue

Answer: (penalty regime: 0 %)

```

1 def is_palindrome_linear(word):
2     word = word.lower()
3     n = len(word)
4     for i in range(n//2):
5         if word[i] != word[n - i - 1]:
6             return False
7     return True
8
9 def binary_search(arr, key):
10    low = 0
11    high = len(arr) - 1
12
13    while low <= high:
14        mid = (low + high) // 2
15        if arr[mid] == key:
16            return True
17        elif arr[mid] < key:
18            low = mid + 1
19        else:
20            high = mid - 1
21    return False
22
23 s = input().split()
24
25 pal_list = []
26 for word in s:
27     if is_palindrome_linear(word):
28         pal_list.append(word.lower())
29
30 pal_list.sort()
31
32 result = []
33 for word in s:
34     if not binary_search(pal_list, word.lower()):
35         result.append(word)
36
37 print(" ".join(result))

```

	Input	Expected	Got	
✓	Malayalam is my mother tongue	is my mother tongue	is my mother tongue	✓

Your code failed one or more hidden tests.

Your code must pass all tests to earn any marks. Try again.

Incorrect

Marks for this submission: 0.00/1.00.

Question 3 | Correct Mark 1.00 out of 1.00

You are given an $m \times n$ integer matrix `matrix` with the following two properties:

- Each row is sorted in non-decreasing order.
- The first integer of each row is greater than the last integer of the previous row.

Given an integer `target`, return `True` if `target` is in `matrix` or `False` otherwise.

You must write a solution in $O(\log(m * n))$ time complexity.

Example 1:

1	3	5	7
10	11	16	20
23	30	34	60

Input: `matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]]`, `target = 3`

Output: `True`

Example 2:

1	3	5	7
10	11	16	20
23	30	34	60

Input: `matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]]`, `target = 13`

Output: `False`

For example:

Test	Result
<code>print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 13))</code>	False
<code>print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 3))</code>	True

Answer: (penalty regime: 0 %)

Reset answer

```

1 def searchMatrix(matrix: list[list[int]], target: int) -> bool:
2     m, n = len(matrix), len(matrix[0])
3     l, r = 0, m*n-1
4     while l <= r:
5         mid = (l + r)//2
6         val = matrix[mid//n][mid % n]
7         if val == target:
8             return True
9         elif val < target:
10            l = mid + 1
11        else:
12            r = mid - 1
13    return False

```

	Test	Expected	Got	
✓	print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 13))	False	False	✓
✓	print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 3))	True	True	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4 | Correct Mark 1.00 out of 1.00

Given two Strings s1 and s2, remove all the characters from s1 which is present in s2.

Constraints

1<= string length <= 200

Sample Input 1

experience
enc

Sample Output 1

xpri

Answer: (penalty regime: 0 %)

```
1 s1 = input().strip()
2 s2 = set(input().strip())
3 print("".join(ch for ch in s1 if ch not in s2))
```

	Input	Expected	Got	
✓	experience enc	xpri	xpri	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5 | Correct Mark 1.00 out of 1.00

Balanced strings are those that have an equal quantity of 'L' and 'R' characters.

Given a balanced string s, split it in the maximum amount of balanced strings.

Return the maximum amount of split balanced strings.

Example 1:

Input:

RLRRLRLRL

Output:

4

Explanation: s can be split into "RL", "RRL", "RL", "RL", each substring contains same number of 'L' and 'R'.

Example 2:

Input:

RLLLLRRRLR

Output:

3

Explanation: s can be split into "RL", "LLLR", "LR", each substring contains same number of 'L' and 'R'.

Example 3:

Input:

LLLLRRRR

Output:

1

Explanation: s can be split into "LLLLRRRR".

Constraints:

1 <= s.length <= 1000

s[i] is either 'L' or 'R'.

s is a balanced string.

For example:

Test	Result
print(BalancedStrings('RLRRLRLRL'))	4
print(BalancedStrings('RLLLLRRRLR'))	3

Answer: (penalty regime: 0 %)

Reset answer

```
1 def BalancedStrings(s):
2     count = 0
3     balance = 0
4     for ch in s:
5         if ch == 'L':
6             balance += 1
7         else:
8             balance -= 1
9         if balance == 0:
10             count += 1
11     return count
```


	Test	Expected	Got	
✓	print(BalancedStrings('RLRRLRLRL'))	4	4	✓
✓	print(BalancedStrings('RLLLLRRRLR'))	3	3	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 6 | Correct Mark 1.00 out of 1.00

Given an array of integers `nums` which is sorted in ascending order, and an integer `target`, write a function to search `target` in `nums`.

If `target` exists, then return its index. Otherwise, return `-1`.

You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: `nums = [-1,0,3,5,9,12]`, `target = 9`

Output: `4`

Explanation: 9 exists in `nums` and its index is 4

Example 2:

Input: `nums = [-1,0,3,5,9,12]`, `target = 2`

Output: `-1`

Explanation: 2 does not exist in `nums` so return -1

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-10^4 < \text{nums}[i], \text{target} < 10^4$
- All the integers in `nums` are **unique**.
- `nums` is sorted in ascending order.

For example:

Test	Result
<code>print(search([-1,0,3,5,9,12],9))</code>	4

Answer: (penalty regime: 0 %)

Reset answer

```

1 def search(nums, target):
2     l,r = 0, len(nums)-1
3     while l <= r:
4         mid = (l+r)//2
5         if nums[mid] == target:
6             return mid
7         elif nums[mid] < target:
8             l = mid + 1
9         else:
10            r = mid - 1
11     return -1
12

```

	Test	Expected	Got	
✓	<code>print(search([-1,0,3,5,9,12],9))</code>	4	4	✓

	Test	Expected	Got	
✓	print(search([-1,0,3,5,9,12],2))	-1	-1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 7 | Correct Mark 1.00 out of 1.00

Two string values S1, S2 are passed as the input. The program must print first N characters present in S1 which are also present in S2.

Input Format:

The first line contains S1.

The second line contains S2.

The third line contains N.

Output Format:

The first line contains the N characters present in S1 which are also present in S2.

Boundary Conditions:

$2 \leq N \leq 10$

$2 \leq \text{Length of } S1, S2 \leq 1000$

Example Input/Output 1:

Input:

```
abcbde
cdefghbb
3
```

Output:

```
bcd
```

Note:

b occurs twice in common but must be printed only once.

Answer: (penalty regime: 0 %)

```
1 s1 = input().strip()
2 s2 = input().strip()
3 n = int(input())
4 res = []
5 seen = set()
6 for ch in s1:
7     if ch in s2 and ch not in seen:
8         res.append(ch)
9         seen.add(ch)
10 if len(res) == n:
11     break
12 print("".join(res))
```

	Input	Expected	Got	
✓	abcbde cdefghbb 3	bcd	bcd	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 8 | Correct Mark 1.00 out of 1.00

Given an list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element $a[i]$ is a peak element if

$A[i-1] \leq A[i] \geq a[i+1]$ for middle elements. $[0 < i < n-1]$

$A[i-1] \leq A[i]$ for last element $[i=n-1]$

$A[i] \geq A[i+1]$ for first element $[i=0]$

Input Format

The first line contains a single integer n , the length of A .

The second line contains n space-separated integers, $A[i]$.

Output Format

Print peak numbers separated by space.

Sample Input

5

8 9 10 2 6

Sample Output

10 6

For example:

Input	Result
4 12 3 6 8	12 8

Answer: (penalty regime: 0 %)

```

1 n = int(input())
2 arr = list(map(int, input().split()))
3 print(*[arr[i] for i in range(n) if (i == 0 and arr[i] >= arr[i + 1]) or (i==n-1 and arr[i] >= arr[i-1]) or (0<i<n

```

	Input	Expected	Got	
✓	7 15 7 10 8 9 4 6	15 10 9 6	15 10 9 6	✓

	Input	Expected	Got	
✓	4 12 3 6 8	12 8	12 8	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 9 | Correct Mark 1.00 out of 1.00

An list contains N numbers and you want to determine whether two of the numbers sum to a given number K. For example, if the input is 8, 4, 1, 6 and K is 10, the answer is yes (4 and 6). A number may be used twice.

Input Format

The first line contains a single integer n , the length of list

The second line contains n space-separated integers, list[i].

The third line contains integer k.

Output Format

Print Yes or No.

Sample Input

```
7
0 1 2 4 6 5 3
1
```

Sample Output

Yes

For example:

Input	Result
5 8 9 12 15 3 11	Yes
6 2 9 21 32 43 43 1 4	No

Answer: (penalty regime: 0 %)

```
1 def findpair(nums, k):
2     seen = set()
3     for num in nums:
4         if (k - num) in seen:
5             return "Yes"
6         seen.add(num)
7     return "No"
8
9 n = int(input())
10 nums = list(map(int, input().split()))
11 k = int(input())
12 print(findpair(nums, k))
```


	Input	Expected	Got	
✓	5 8 9 12 15 3 11	Yes	Yes	✓
✓	6 2 9 21 32 43 43 1 4	No	No	✓
✓	6 13 42 31 4 8 9 17	Yes	Yes	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 10 | Correct Mark 1.00 out of 1.00

Write a Python program for binary search.

For example:

Input	Result
1,2,3,5,8 6	False
3,5,9,45,42 42	True

Answer: (penalty regime: 0 %)

```
1 arr = list(map(int, input().split(',')))
2 target = int(input())
3 arr.sort()
4 l,r = 0, len(arr)-1
5 found = False
6 while l <= r:
7     mid = (l + r)// 2
8     if arr[mid] == target:
9         found = True
10        break
11    elif arr[mid] < target:
12        l = mid + 1
13    else:
14        r = mid - 1
15 print(found)
```

	Input	Expected	Got	
✓	1,2,3,5,8 6	False	False	✓
✓	3,5,9,45,42 42	True	True	✓
✓	52,45,89,43,11 11	True	True	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.