

ASSIGNMENT 7

AIM: Insert the keys into a hash table of length m using open addressing using double hashing with $h(k)=(1+k\text{mod}(m-1))$.

OBJECTIVE: To study and learn the concepts of double hashing.

THEORY: **Double hashing** is a collision resolving technique in **Open Addressed** Hash tables. Double hashing uses the idea of applying a second hash function to key when a collision occurs.

Double hashing can be done using:

$(\text{hash1}(\text{key}) + i * \text{hash2}(\text{key})) \% \text{TABLE_SIZE}$

Here $\text{hash1}()$ and $\text{hash2}()$ are hash functions and TABLE_SIZE is size of hash table.

(We repeat by increasing i when collision occurs)

First hash function is typically $\text{hash1}(\text{key}) = \text{key} \% \text{TABLE_SIZE}$

A popular second hash function is:

$\text{hash2}(\text{key}) = \text{PRIME} - (\text{key} \% \text{PRIME})$ where PRIME is a prime smaller than the TABLE_SIZE .

A good second Hash function is:


- It must never evaluate to zero
- Must make sure that all cells can be probed

ALGORITHM:

Skill Development Lab-II 2018-19

Lets say, $\text{Hash1}(\text{key}) = \text{key} \% 13$

$\text{Hash2}(\text{key}) = 7 - (\text{key} \% 7)$



PROGRAM:

```
#include <iostream>
using namespace std;
class dr
{
    int n=10;
    int arr[100][3];
    int c;
public:
    dr()
    {
        cout<<"Table of size "<<n<<" created\n";
        for(int i=0;i<n;i++)
        {
            arr[i][0]=0;
            arr[i][1]=-1;
            arr[i][2]=-1;
        }
        c=0;
    }
    void add(int,int);
    int find_key(int);
    void display();
    void update_val(int,int);
};
void dr::add(int key,int value)
{
    int new_hash_addr1,new_hash_addr2,main_hash_addr=-1,j=0;
```

Skill Development Lab-II 2018-19


```
if(this->find_key(key)!=-1)
{
    cout<<"Key already exists\n";
    return;
}
if(c==(n-1))
{
    cout<<"Table full, request denied\n";
}
new_hash_addr1=(key)%n;
new_hash_addr1=1+(key%(n-1));
if(arr[new_hash_addr1][1]==-1)
{
    arr[new_hash_addr1][0]=key;
    arr[new_hash_addr1][1]=value;
}
else if(arr[new_hash_addr2][1]==-1)
{
    arr[new_hash_addr2][0]=key;
    arr[new_hash_addr2][1]=value;
}
else
{
    while(arr[new_hash_addr2][2]!=-1)
    {
        main_hash_addr=new_hash_addr2;
        new_hash_addr2=arr[main_hash_addr][2];
    }
    main_hash_addr=new_hash_addr2;
    for(int i=0;i<n;i++)
    {
        new_hash_addr2=(main_hash_addr+i)%n;
        if(arr[new_hash_addr2][1]==-1)
        {
            arr[new_hash_addr2][0]=key;
            arr[new_hash_addr2][1]=value;
            arr[main_hash_addr][2]=new_hash_addr2;
            c++;
            break;
        }
    }
}
}
void dr::display()
{
    cout<<"Key\t\tValue\t\tChain\n";
    for(int i=0;i<n;i++)
    {
        cout<<arr[i][0]<<"\t\t"<<arr[i][1]<<"\t\t"<<arr[i][2]<<endl;
    }
}
int dr::find_key(int key)
{
    int search_addr=key%n,f=0;
```

Skill Development Lab-II 2018-19

```
while(arr[search_addr][0]!=key && arr[search_addr][2]!=-1)
{
    search_addr=arr[search_addr][2];
}
if(arr[search_addr][0]==key)
{
    return arr[search_addr][1];
}
else if(arr[search_addr][2]==-1)
{
    return -1;
}
}
int main()
{
    char r;
    do
    {
        char op;
        dr table;
        int c;
        do
        {
            cout<<"-----Menu-----\n";
            cout<<"1] Insert value\n2] Display\n";
            cout<<"_____ \n";
            cout<<"Enter your choice: ";
            cin>>c;
            switch(c)
            {
                case 1: {
                    int key,val;
                    cout<<"Enter key: ";
                    cin>>key;
                    cout<<"Enter value: ";
                    cin>>val;
                    table.add(key,val);
                }
                break;
                case 2: table.display();
                break;
                default:cout<<"Invalid\n";
            }
            cout<<"\nDo you wish to go again? ";
            cin>>op;
        }while(op=='y' || op=='Y');
        cout << "Test pass?(y/n): " << endl;
        cin>>r;
    }while(r=='n' || r=='N');
    cout<<"*****\n";
    cout<<"*   Thank You!   *\n";
    cout<<"*****\n";
    return 0;
}
```

Skill Development Lab-II 2018-19

OUTPUT:



```
himanshu@himanshu-Inspiron-3558: ~/new/sd
File Edit View Search Terminal Help
-----Menu-----
1] Insert value
2] Display

Enter your choice: 1
Enter key: 5
Enter value: 45

Do you wish to go again? y
-----Menu-----
1] Insert value
2] Display


Enter your choice: 1
Enter key: 4
Enter value: 56

Do you wish to go again? y
-----Menu-----
1] Insert value
2] Display

Enter your choice: 1
Enter key: 1
Enter value: 49

Do you wish to go again? y
-----Menu-----
1] Insert value
2] Display

Enter your choice: 1
```



```
himanshu@himanshu-Inspiron-3558: ~/new/sd
File Edit View Search Terminal Help
-----Menu-----
1] Insert value
2] Display

Enter your choice: 1
Enter key: 1
Enter value: 49

Do you wish to go again? y
-----Menu-----
1] Insert value
2] Display

Enter your choice: 1
Enter key: 6
Enter value: 89


Do you wish to go again? y
-----Menu-----
1] Insert value
2] Display

Enter your choice: 1
Enter key: 7
Enter value: 46

Do you wish to go again? y
-----Menu-----
1] Insert value
2] Display

Enter your choice: 1
Enter key: 6
Enter value: 44
```

Skill Development Lab-II 2018-19



```
himanshu@himanshu-Inspiron-3558: ~/new/sd
File Edit View Search Terminal Help
Enter your choice: 1
Enter key: 6
Enter value: 89

Do you wish to go again? y
-----Menu-----
1] Insert value
2] Display

Enter your choice: 1
Enter key: 7
Enter value: 46

Do you wish to go again? y
-----Menu-----
1] Insert value
2] Display

Enter your choice: 2
Key      Value      Chain
0        -1        -1
0        -1        -1
1        49        -1
0        -1        -1
0        -1        -1
4        56        -1
5        45        -1
6        89        -1
7        46        -1
0        -1        -1

Do you wish to go again? ☐
```

48 of 51
Comp-S.Y.-B-Tech.pdf
100%
48
CURRICULUM BOOK
48
Department of Computer Engineering

CONCLUSION: We successfully implemented open addressing using double hashing.