

dlnd_tv_script_generation

April 22, 2020

1 TV Script Generation

In this project, you'll generate your own [Seinfeld](#) TV scripts using RNNs. You'll be using part of the [Seinfeld dataset](#) of scripts from 9 seasons. The Neural Network you'll build will generate a new, "fake" TV script, based on patterns it recognizes in this training data.

1.1 Get the Data

The data is already provided for you in `./data/Seinfeld_Scripts.txt` and you're encouraged to open that file and look at the text. >* As a first step, we'll load in this data and look at some samples. * Then, you'll be tasked with defining and training an RNN to generate a new script!

```
In [16]: """
         DON'T MODIFY ANYTHING IN THIS CELL
         """
         # load in data
         import helper
         data_dir = './data/Seinfeld_Scripts.txt'
         text = helper.load_data(data_dir)
```

1.2 Explore the Data

Play around with `view_line_range` to view different parts of the data. This will give you a sense of the data you'll be working with. You can see, for example, that it is all lowercase text, and each new line of dialogue is separated by a newline character `\n`.

```
In [17]: view_line_range = (0, 10)

         """
         DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
         """
         import numpy as np

         print('Dataset Stats')
         print('Roughly the number of unique words: {}'.format(len({word: None for word in text.

         lines = text.split('\n')
```

```

print('Number of lines: {}'.format(len(lines)))
word_count_line = [len(line.split()) for line in lines]
print('Average number of words in each line: {}'.format(np.average(word_count_line)))

print()
print('The lines {} to {}'.format(*view_line_range))
print('\n'.join(text.split('\n')[view_line_range[0]:view_line_range[1]]))

```

Dataset Stats

Roughly the number of unique words: 46367

Number of lines: 109233

Average number of words in each line: 5.544240293684143

The lines 0 to 10:

jerry: do you know what this is all about? do you know, why were here? to be out, this is out...

jerry: (pointing at georges shirt) see, to me, that button is in the worst possible spot. the se

george: are you through?

jerry: you do of course try on, when you buy?

george: yes, it was purple, i liked it, i dont actually recall considering the buttons.

1.3 Implement Pre-processing Functions

The first thing to do to any dataset is pre-processing. Implement the following pre-processing functions below: - Lookup Table - Tokenize Punctuation

1.3.1 Lookup Table

To create a word embedding, you first need to transform the words to ids. In this function, create two dictionaries: - Dictionary to go from the words to an id, we'll call `vocab_to_int` - Dictionary to go from the id to word, we'll call `int_to_vocab`

Return these dictionaries in the following **tuple** (`vocab_to_int`, `int_to_vocab`)

```

In [18]: import problem_unittests as tests
         from collections import Counter

         def create_lookup_tables(text):
             """
             Create lookup tables for vocabulary
             :param text: The text of tv scripts split into words
             :return: A tuple of dicts (vocab_to_int, int_to_vocab)
             """

```