

Assignment25

Multiple User Login Scenario

Scenario:

Test login functionality using multiple usernames and passwords.

Task:

Use @DataProvider.

Test Data:

admin / admin123

user / user123

test / test123

Solution-----

```
package Testing_practice;
```

```
import org.testng.annotations.Test;
```

```
import org.testng.annotations.DataProvider;
```

```
import org.openqa.selenium.By;
```

```
import org.openqa.selenium.WebDriver;
```

```
import org.openqa.selenium.WebElement;
```

```
import org.openqa.selenium.chrome.ChromeDriver;
```

```
import org.testng.annotations.AfterClass;
```

```
public class LoginValidation {
```

```
    WebDriver driver;
```

```

        @DataProvider(name="data")

public Object[][] dp() {

    return new Object[][] {

        { "username", "password" },//valid username and password

        { "admin", "admin123"}, //invalid username and valid password

        { "invalid", "admin123"}, //invalid username and valid password

        { "invalid", "invalid"} //invalid username and password

    };

}

@Test(dataProvider = "data")

public void f(String username1, String password1) {

    driver=new ChromeDriver();

    driver.manage().window().maximize();


    driver.get("http://zero.webappsecurity.com/login.html");


    WebElement user=driver.findElement(By.id("user_login"));

    user.sendKeys(username1);


    WebElement pass=driver.findElement(By.id("user_password"));

    user.sendKeys(password1);

```

```
driver.findElement(By.name("submit")).click();
```

```
}
```

```
//assignment1
```

```
// checking for validate search
```

```
// use assert for search button clickable
```

```
// asdjhga 578695,!@#$%^& ,shadjhsa766543,(product,name,brand name,rating based ,
```

```
// price based,discount)
```

```
// assignment 2
```

```
// register 5 user
```

```
@AfterClass
```

```
public void afterClass() {
```

```
//      driver.close();
```

```
}
```

```
}
```

Smoke and Regression Scenario

Scenario: Company wants to execute smoke tests separately.

Task: Create:

- 2 smoke test methods
- 2 regression test methods

Use groups.

```
package Testing_practice;
```

```
import org.testng.annotations.Test;
```

```
import org.testng.asserts.SoftAssert;
```

```
import org.testng.annotations.BeforeTest;
```

```
import org.testng.Assert;
```

```
import java.time.Duration;
```

```
import org.openqa.selenium.WebDriver;
```

```
import org.openqa.selenium.chrome.ChromeDriver;
```

```
import org.openqa.selenium.edge.EdgeDriver;
```

```
import org.openqa.selenium.firefox.FirefoxDriver;
```

```
import org.openqa.selenium.support.ui.WebDriverWait;

import org.testng.annotations.AfterTest;


public class Assert_Test {


    WebDriver driver;

    WebDriverWait wait;


    @Test(groups="smoke")

    public void chrome()

    {

        driver=new ChromeDriver();

        driver.get("https://www.selenium.dev/");

    }

    @Test(groups="regression")

    public void firefox()

    {

        driver=new FirefoxDriver();

        driver.get("https://www.selenium.dev/");

    }

    @Test (groups="regression")

    public void edge()

    {
```

```
        driver=new EdgeDriver();

        driver.get("https://www.selenium.dev/");

    }

@Test(groups="smoke")
public void titlevalidation()
{
    SoftAssert soft=new SoftAssert();

    String expectedtitle="Selenium dev";

    String actualtitle=driver.getTitle();

    soft.assertEquals(actualtitle, expectedtitle,"Title Validation is fail");

    String expectedurl="https://www.selenium.dev";

    String actualurl=driver.getCurrentUrl();

    soft.assertEquals(actualurl, expectedurl,"Url Validation is fail");

    Assert.assertTrue(true,"Pause");

}

@AfterTest

public void afterTest() {
```

```
        driver.close();  
    }  
}
```

For smoke testing

```
=====
Suite
Total tests run: 2, Passes: 2, Failures: 0, Skips: 0
=====
```

```
For regression testing =====
Suite
Total tests run: 2, Passes: 2, Failures: 0, Skips: 0
=====
```