Networking Commands with Examples

Command	Example	Use
1. ping	`ping google.com`	Checks connectivity between your computer and a host.
2. tracert	`tracert google.com`	Shows the route taken by packets to reach a destination (Windows).
3. nslookup	`nslookup google.com`	Finds the IP address associated with a domain name.
4. netstat	`netstat -an`	Displays active network connections and listening ports.
5. ARP	`arp -a`	Displays the ARP table containing IP and MAC address mappings.
6. RARP	No standard modern command	Reverse Address Resolution Protocol finds an IP address using a MAC address; it is obsolete and replaced by BOOTP/DHCP.
7. ip	`ip addr show`	Displays IP addresses and network interfaces (Linux).
8. ifconfig	`ifconfig`	Displays or configures network interfaces (Linux/Unix).

9. dig	`dig google.com`	Queries DNS servers to retrieve domain information.
10. route	`route print`	Displays the routing table on Windows.

Additional useful examples

- Ping a specific IP: `ping 8.8.8.8`
- Trace route on Linux: `traceroute google.com`
- Find DNS mail records: `nslookup -type=MX google.com`
- Display all connections: `netstat -a`
- Display ARP entries on Linux: `ip neigh`
- Display the Linux routing table: `ip route`
- Query DNS A records: `dig google.com A`
- Display IP configuration on Windows: `ipconfig`
- Display network interfaces on Linux: `ifconfig eth0`

Note: `tracert`, `ipconfig`, and `route print` are Windows commands, while `ip`, `ifconfig`, and `dig` are commonly used on Linux/Unix. Some Linux commands may require installation or administrator privileges.