

[Dashboard](#) / [My courses](#) / [CS23331-DAA-2023-CSE](#) / [Dynamic Programming](#) / [1-DP-Playing with Numbers](#)

Started on	Monday, 18 November 2024, 9:04 PM
State	Finished
Completed on	Monday, 18 November 2024, 9:20 PM
Time taken	16 mins 34 secs
Grade	10.00 out of 10.00 (100%)

Question **1**

Correct

Mark 10.00 out of 10.00

Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer 'n' two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3. Write any efficient algorithm to find the possible ways.

Example 1:**Input:** 6**Output:** 6**Explanation:** There are 6 ways to 6 represent number with 1 and 3

1+1+1+1+1+1

3+3

1+1+1+3

1+1+3+1

1+3+1+1

3+1+1+1

Input Format

First Line contains the number n

Output Format**Print: The number of possible ways 'n' can be represented using 1 and 3**

Sample Input

6

Sample Output

6

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  long long countWays(int n) {
4      long long dp[n + 1];
5      dp[0] = 1;
6
7      for (int i = 1; i <= n; i++) {
8          dp[i] = dp[i - 1];
9          if (i >= 3) dp[i] += dp[i - 3];
10     }
11
12     return dp[n];
13 }
14
15 int main() {
16     int n;
17     scanf("%d", &n);
18     printf("%lld\n", countWays(n));
19     return 0;
20 }
21

```

	Input	Expected	Got	
✓	6	6	6	✓
✓	25	8641	8641	✓
✓	100	24382819596721629	24382819596721629	✓

Passed all tests! ✓

Correct

Marks for this submission: 10.00/10.00.

◀ 5-Implementation of Quick Sort

Jump to...

[2-DP-Playing with chessboard](#)

[Dashboard](#) / [My courses](#) / [CS23331-DAA-2023-CSE](#) / [Dynamic Programming](#) / [2-DP-Playing with chessboard](#)

Started on	Monday, 18 November 2024, 9:03 PM
State	Finished
Completed on	Monday, 18 November 2024, 9:20 PM
Time taken	17 mins 32 secs
Grade	10.00 out of 10.00 (100%)

Question 1

Correct

Mark 10.00 out of 10.00

Playing with Chessboard:

Ram is given with an $n \times n$ chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position ($n-1$, $n-1$) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:**Input**

```
3
1 2 4
2 3 4
8 7 1
```

Output:

```
19
```

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value: $1+2+8+7+1=19$

Input Format

First Line contains the integer n

The next n lines contain the $n \times n$ chessboard values

Output Format

Print Maximum monetary value of the path

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2
3 int findMaxPath(int n, int board[][n]) {
4     int dp[n][n];
5     dp[0][0] = board[0][0];
6
7     for (int i = 1; i < n; i++) dp[i][0] = dp[i - 1][0] + board[i][0];
8     for (int j = 1; j < n; j++) dp[0][j] = dp[0][j - 1] + board[0][j];
9
10    for (int i = 1; i < n; i++) {
11        for (int j = 1; j < n; j++) {
12            dp[i][j] = (dp[i - 1][j] > dp[i][j - 1] ? dp[i - 1][j] : dp[i][j - 1]) + board[i][j];
13        }
14    }
15
16    return dp[n - 1][n - 1];
17 }
18
19 int main() {
20     int n;
21     scanf("%d", &n);
22     int board[n][n];
23     for (int i = 0; i < n; i++) {
24         for (int j = 0; j < n; j++) {
25             scanf("%d", &board[i][j]);
26         }
27     }
28     printf("%d\n", findMaxPath(n, board));
29     return 0;
30 }
```

31 |

	Input	Expected	Got	
✓	3 1 2 4 2 3 4 8 7 1	19	19	✓
✓	3 1 3 1 1 5 1 4 2 1	12	12	✓
✓	4 1 1 3 4 1 5 7 8 2 3 4 6 1 6 9 0	28	28	✓

Passed all tests! ✓

Correct

Marks for this submission: 10.00/10.00.

[◀ 1-DP-Playing with Numbers](#)

Jump to...

[3-DP-Longest Common Subsequer](#)

[Dashboard](#) / [My courses](#) / [CS23331-DAA-2023-CSE](#) / [Dynamic Programming](#) / [3-DP-Longest Common Subsequence](#)

Started on	Monday, 18 November 2024, 8:57 PM
State	Finished
Completed on	Monday, 18 November 2024, 9:17 PM
Time taken	20 mins 26 secs
Marks	1.00/1.00
Grade	10.00 out of 10.00 (100%)

Question **1**

Correct

Mark 1.00 out of 1.00

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1	a	g	g	t	a	b	
s2	g	x	t	x	a	y	b

The length is 4

Solving it using Dynamic Programming

For example:

Input	Result
aab azb	2

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <string.h>
3
4  int longestCommonSubsequence(char *s1, char *s2) {
5      int m = strlen(s1);
6      int n = strlen(s2);
7
8      int dp[m + 1][n + 1];
9
10     for (int i = 0; i <= m; i++) {
11         for (int j = 0; j <= n; j++) {
12             if (i == 0 || j == 0) {
13                 dp[i][j] = 0;
14             } else if (s1[i - 1] == s2[j - 1]) {
15                 dp[i][j] = dp[i - 1][j - 1] + 1;
16             } else {
17                 dp[i][j] = (dp[i - 1][j] > dp[i][j - 1]) ? dp[i - 1][j] : dp[i][j - 1];
18             }
19         }
20     }
21
22     return dp[m][n];
23 }
24
25 int main() {
26     char s1[100];
27     char s2[100];
28
29     scanf("%s", s1);
30     scanf("%s", s2);
31
32     int lcsLength = longestCommonSubsequence(s1, s2);
33     printf("%d", lcsLength);
34
35     return 0;

```



```
36 | }
37 |
```

	Input	Expected	Got	
✓	aab azb	2	2	✓
✓	ABCD ABCD	4	4	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

◀ 2-DP-Playing with chessboard

Jump to...

4-DP-Longest non-decreasing Subsequer

[Dashboard](#) / [My courses](#) / [CS23331-DAA-2023-CSE](#) / [Dynamic Programming](#) / [4-DP-Longest non-decreasing Subsequence](#)

Started on	Monday, 18 November 2024, 9:01 PM
State	Finished
Completed on	Monday, 18 November 2024, 9:16 PM
Time taken	15 mins 6 secs
Marks	1.00/1.00
Grade	10.00 out of 10.00 (100%)

Question 1

Correct

Mark 1.00 out of 1.00

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int longestNonDecreasingSubsequence(int arr[], int n) {
4      int dp[n];
5      for (int i = 0; i < n; i++) dp[i] = 1;
6
7      for (int i = 1; i < n; i++) {
8          for (int j = 0; j < i; j++) {
9              if (arr[i] >= arr[j] && dp[i] < dp[j] + 1) {
10                 dp[i] = dp[j] + 1;
11             }
12         }
13     }
14
15     int maxLength = 0;
16     for (int i = 0; i < n; i++) {
17         if (dp[i] > maxLength) {
18             maxLength = dp[i];
19         }
20     }
21
22     return maxLength;
23 }
24
25 int main() {
26     int n;
27     scanf("%d", &n);
28     int arr[n];
29     for (int i = 0; i < n; i++) {
30         scanf("%d", &arr[i]);
31     }
32     printf("%d", longestNonDecreasingSubsequence(arr, n));
33     return 0;
34 }
35

```

	Input	Expected	Got	
✓	9 -1 3 4 5 2 2 2 2 3	6	6	✓
✓	7 1 2 2 4 5 7 6	6	6	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[◀ 3-DP-Longest Common Subsequence](#)

Jump to...

[1-Finding Duplicates- \$O\(n^2\)\$ Time Complexity, \$O\(1\)\$ Space Complex](#)