

[Dashboard](#) / [My courses](#) / [CS23331-DAA-2023-CSE](#) / [Greedy Algorithms](#) / [1-G-Coin Problem](#)

<b>Started on</b>	Monday, 19 August 2024, 10:17 AM
<b>State</b>	Finished
<b>Completed on</b>	Monday, 19 August 2024, 11:49 AM
<b>Time taken</b>	1 hour 31 mins
<b>Marks</b>	1.00/1.00
<b>Grade</b>	<b>10.00</b> out of 10.00 ( <b>100%</b> )

## Question 1

Correct

Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int main ()
4  {
5      int n,cnt=0;
6      scanf("%d", &n);
7
8      if (n>=1000) {
9          cnt+=n/1000;
10         n=n%1000;
11     }
12     if (500<=n && n<1000) {
13         cnt+=n/500;
14         n=n%500;
15     }
16     if (100<=n && n<500) {
17         cnt+=n/100;
18         n=n%100;
19     }
20     if (50<=n && n<100) {
21         cnt+=n/50;
22         n=n%50;
23     }
24     if (20<=n && n<50) {
25         cnt+=n/20;
26         n=n%20;
27     }
28     if (10<=n && n<20) {
29         cnt+=n/10;
30         n=n%10;
31     }
32     if (5<=n && n<10) {
33         cnt+=n/5;
34         n=n%5;
35     }
36     if (2<=n && n<5) {
37         cnt+=n/2;
38         n=n%2;
39     }
40     if (1<=n && n<2) {

```

```
41         cnt+=n/1;  
42         n=n%1;  
43     }  
44     printf("%d",cnt);  
45  
46 }
```

	Input	Expected	Got	
✓	49	5	5	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[◀ Problem 5: Finding Complexity using counter method](#)

Jump to...

[2-G-Cookies Probl](#)

[Dashboard](#) / [My courses](#) / [CS23331-DAA-2023-CSE](#) / [Greedy Algorithms](#) / [2-G-Cookies Problem](#)

<b>Started on</b>	Wednesday, 28 August 2024, 10:08 PM
<b>State</b>	Finished
<b>Completed on</b>	Thursday, 29 August 2024, 11:07 AM
<b>Time taken</b>	12 hours 58 mins
<b>Marks</b>	1.00/1.00
<b>Grade</b>	<b>10.00</b> out of 10.00 ( <b>100%</b> )

Question **1**

Correct

Mark 1.00 out of 1.00

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child  $i$  has a greed factor  $g[i]$ , which is the minimum size of a cookie that the child will be content with; and each cookie  $j$  has size  $s[j]$ . If  $s[j] \geq g[i]$ , we can assign the cookie  $j$  to the child  $i$ , and the child  $i$  will be content. Your goal is to maximize the number of your content children and output the maximum number.

**Example 1:****Input:**

```
3
1 2 3
2
1 1
```

**Output:**

```
1
```

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

**Constraints:**

```
1 <= g.length <= 3 * 10^4
0 <= s.length <= 3 * 10^4
1 <= g[i], s[j] <= 2^31 - 1
```

**Answer:** (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
#include <stdio.h>

int main () {

    int child;
    scanf("%d", &child);
    int g[child];
    for (int i=0; i<child; i++) {
        scanf("%d", &g[i]);
    }

    int cookie;
    scanf("%d", &cookie);
    int s[cookie];
    for (int i=0; i<cookie; i++) {
        scanf("%d", &s[i]);
    }
}
```

	Input	Expected	Got	
✓	2	2	2	✓
	1 2			
	3			
	1 2 3			

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

◀ 1-G-Coin Problem

Jump to...

3-G-Burger Problem

[Dashboard](#) / [My courses](#) / [CS23331-DAA-2023-CSE](#) / [Greedy Algorithms](#) / [3-G-Burger Problem](#)

<b>Started on</b>	Wednesday, 28 August 2024, 9:42 PM
<b>State</b>	Finished
<b>Completed on</b>	Wednesday, 28 August 2024, 10:42 PM
<b>Time taken</b>	1 hour
<b>Marks</b>	1.00/1.00
<b>Grade</b>	<b>10.00</b> out of 10.00 ( <b>100%</b> )

Question **1**

Correct

Mark 1.00 out of 1.00

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.

If he has eaten  $i$  burgers with  $c$  calories each, then he has to run at least  $3^i * c$  kilometers to burn out the calories. For example, if he ate 3 burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are  $(3^0 * 1) + (3^1 * 3) + (3^2 * 2) = 1 + 9 + 18 = 28$ .

But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance

he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm. Apply greedy approach to solve the problem.

**Input Format**

First Line contains the number of burgers

Second line contains calories of each burger which is  $n$  space-separated integers

**Output Format**

Print: Minimum number of kilometers needed to run to burn out the calories

**Sample Input**

```
3
5 10 7
```

**Sample Output**

```
76
```

**For example:**

Test	Input	Result
Test Case 1	3 1 3 2	18

**Answer:** (penalty regime: 0 %)

```

1  #include<stdio.h>
2  #include<math.h>
3  int main()
4  {
5      int x;
6      scanf("%d", &x);
7      int a[x];
8      for(int i=0; i<=x; i++)
9      {
10         scanf("%d", &a[i]);
11     }
12     int t;
13     for(int j=0; j<=x; j++)
14     {
15         for(int k=j+1; k<=x-1; k++)
16         {
17             if(a[j]<a[k])
18             {
19                 t=a[j];
20                 a[j]=a[k];
21                 a[k]=t;
22             }
23         }
24     }
25     int s=0;
26     for(int i=0; i<x; i++)
27     {
```



```
28 |         s+=(pow(x, i)*a[i]);
29 |     }
30 |     printf("%d", s);
31 | }
32 |
```

	Test	Input	Expected	Got	
✓	Test Case 1	3 1 3 2	18	18	✓
✓	Test Case 2	4 7 4 9 6	389	389	✓
✓	Test Case 3	3 5 10 7	76	76	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

◀ 2-G-Cookies Problem

Jump to...

[4-G-Array Sum max probl](#)

[Dashboard](#) / [My courses](#) / [CS23331-DAA-2023-CSE](#) / [Greedy Algorithms](#) / [4-G-Array Sum max problem](#)

<b>Started on</b>	Wednesday, 28 August 2024, 9:24 PM
<b>State</b>	Finished
<b>Completed on</b>	Thursday, 5 September 2024, 10:20 AM
<b>Time taken</b>	7 days 12 hours
<b>Marks</b>	1.00/1.00
<b>Grade</b>	<b>10.00</b> out of 10.00 ( <b>100%</b> )

## Question 1

Correct

Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of  $\text{arr}[i] * i$ , where  $i$  is the index of the element ( $i = 0, 1, 2, \dots, N$ ). Write an algorithm based on Greedy technique with a Complexity  $O(n \log n)$ .

Input Format:

First line specifies the number of elements- $n$

The next  $n$  lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5  
2 5 3 4 0

Sample output:

40

**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  void mergesort(int arr[], int l, int r, int m)
4  {
5      int n1=m-l+1;
6      int n2=r-m;
7      int a[n1],b[n2];
8
9      for(int i=0; i<n1; i++)
10     {
11         a[i]=arr[l+i];
12     }
13
14     for(int i=0 ; i<n2 ; i++)
15     {
16         b[i]=arr[m+1+i];
17     }
18
19     int aptr=0, bptr=0, cptr=l;
20     while(aptr<n1 && bptr<n2)
21     {
22         if(a[aptr]<b[bptr])
23         {
24             arr[cptr]=a[aptr];
25             aptr++;
26         }
27         else
28         {
29             arr[cptr]=b[bptr];
30             bptr++;
31         }
32         cptr++;
33     }
34
35     while(aptr<n1)
36     {
37         arr[cptr]=a[aptr];
38         cptr++;
39         aptr++;
40     }
41     while(bptr<n2)
42     {
43         arr[cptr]=b[bptr];
44         cptr++;
45         bptr++;
46     }
47 }
```

```
44         cptr++;
45         bptr++;
46     }
47 }
48
49 void merge(int arr[], int l, int r)
50 {
51     if(l<r)
52     {
```

	Input	Expected	Got	
✓	5 2 5 3 4 0	40	40	✓
✓	10 2 2 2 4 4 3 3 5 5 5	191	191	✓
✓	2 45 3	45	45	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

◀ 3-G-Burger Problem

Jump to...

5-G-Product of Array elements-Minimi

[Dashboard](#) / [My courses](#) / [CS23331-DAA-2023-CSE](#) / [Greedy Algorithms](#) / [5-G-Product of Array elements-Minimum](#)

<b>Started on</b>	Wednesday, 28 August 2024, 9:06 PM
<b>State</b>	Finished
<b>Completed on</b>	Thursday, 29 August 2024, 11:04 AM
<b>Time taken</b>	13 hours 58 mins
<b>Marks</b>	1.00/1.00
<b>Grade</b>	<b>10.00</b> out of 10.00 ( <b>100%</b> )

## Question 1

Correct

Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the products (1 element from each) is minimum. That is  $\text{SUM} (A[i] * B[i])$  for all `i` is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int main() {
4      int n;
5      scanf("%d", &n);
6
7      int arrayOne[n], arrayTwo[n];
8      for (int i=0; i<n; i++) {
9          scanf("%d", &arrayOne[i]);
10     }
11     for (int i=0; i<n; i++) {
12         scanf("%d", &arrayTwo[i]);
13     }
14
15     for (int i=0; i<n-1; i++) {
16         for (int j=i+1; j<n; j++) {
17             if (arrayOne[j]>arrayOne[i]) {
18                 int temp=arrayOne[j];
19                 arrayOne[j]=arrayOne[i];
20                 arrayOne[i]=temp;
21             }
22             if (arrayTwo[j]<arrayTwo[i]) {
23                 int temp=arrayTwo[j];
24                 arrayTwo[j]=arrayTwo[i];
25                 arrayTwo[i]=temp;
26             }
27         }
28     }
29
30     int minSum=0;
31     for (int i=0; i<n; i++) {
32         minSum+=(arrayOne[i]*arrayTwo[i]);
33     }
34     printf("%d", minSum);
35     return 0;
36 }
```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

◀ 4-G-Array Sum max problem

Jump to...

1-Number of Zeros in a Given Ari