

Task 7. [C03]: Process Synchronization needs to be implemented to prevent data inconsistency among processes, process deadlocks.

Aim

To write a c program for process synchronization to implemented to prevent data inconsistency among processes, process deadlocks

program

```
#include <pthread.h>
#include <semaphore.h>
#include <stdio.h>
#define N 5
#define THINKING 2
#define HUNGRY 1
#define EATING 0
#define LEFT (phnum + 4) % N
#define RIGHT (phnum + 1) % N

int state[N];
int phil[N] = { 0, 1, 2, 3, 4 };
sem_t mutex;
sem_t S[N];
void test(int phnum)
{
    if (state[phnum] == HUNGRY
        && state[LEFT] != EATING
        && state[RIGHT] != EATING) {
        // state that eating
        state[phnum] = EATING;
        sleep(2);
        printf("Philosopher %d takes fork %d and %d\n",
               phnum + 1, LEFT + 1, phnum + 1);
        printf("Philosopher %d is Eating\n", phnum + 1);
        // sem_post(&S[phnum]) has no effect
        // during takefork
        // used to wake up hungry philosophers
        // during putfork
        sem_post(&S[phnum]);
    }
}
// take up chopsticks
void take_fork(int phnum)
{
    sem_wait(&mutex);

    // state that hungry
    state[phnum] = HUNGRY;
    printf("Philosopher %d is Hungry\n", phnum + 1);
    // eat if neighbours are not eating
    test(phnum);
    sem_post(&mutex);
    // if unable to eat wait to be signalled
```

```

        sem_wait(&S[phnum]);
        sleep(1);
    }
    // put down chopsticks
    void put_fork(int phnum)
    {
        sem_wait(&mutex);
        // state that thinking
        state[phnum] = THINKING;
        printf("Philosopher %d putting fork %d and %d down\n",
            phnum + 1, LEFT + 1, phnum + 1);
        printf("Philosopher %d is thinking\n", phnum + 1);
        test(LEFT);
        test(RIGHT);
        sem_post(&mutex);
    }
    void* philospher(void* num)
    {
        while (1) {
            int* i = num;
            sleep(1);
            take_fork(*i);
            sleep(0);
            put_fork(*i);
        }
    }
    int main()
    {
        int i;
        pthread_t thread_id[N];
        // initialize the semaphores
        sem_init(&mutex, 0, 1);
        for (i = 0; i < N; i++)
            sem_init(&S[i], 0, 0);
        for (i = 0; i < N; i++) {
            // create philosopher processes
            pthread_create(&thread_id[i], NULL,
                philospher, &phil[i]);
            printf("Philosopher %d is thinking\n", i + 1);
        }
        for (i = 0; i < N; i++)
            pthread_join(thread_id[i], NULL);
    }

```