



Local Search

Local search methods work on complete state formulations. They keep only a small number of nodes in memory.

Local search is useful for solving optimization problems:

- o Often it is easy to find a solution**

- o But hard to find the best solution**

Algorithm goal: find optimal configuration (e.g., TSP),



- Hill climbing
- Gradient descent
- Simulated annealing


- For some problems the state description contains all of the information relevant for a solution. Path to the solution is unimportant.

- Examples:

- o map coloring
- o 8-queens
- o cryptarithmic

Block Worlds Domain









Rule: Heuristic Function



$h_1(n)$ = add 1 if the block is on the correct location
subtract 1 if the block is on the incorrect location






Total Cost: +1


Start




Total Cost: +1




Total Cost: +1



Total Cost: ?





Total Cost: ?




Goal

Total Cost: +5






Total Cost: +1




Start




Goal


Total Cost: +1




Total Cost: +1




Total Cost: +1



Total Cost: +1



Total Cost: +1





Total Cost: +1



Rule



$h_2(n)$ = add 1 for every block in the correct structure that the block is sitting on
subtract 1 for every block in the incorrect structure






Total Cost: -1


Start




Total Cost: -1




Total Cost: ?



Total Cost: ?




Total Cost: ?





Total Cost: +11


Goal



Start





Goal




Total Cost: -1


Start




Total Cost: -1




Total Cost: +1




Total Cost: -3




Total Cost: 0







Total Cost: +1




Total Cost: ?




Total Cost: ?




Total Cost: ?




Total Cost: ?




Total Cost: ?




Total Cost: ?




Total Cost: +1




Total Cost: -4




Total Cost: -3




Total Cost: -2



Total Cost: +2




Total Cost: +1




Total Cost: +6

Final Solution



Local Maxima





Hill Climbing (Cont...)

Local maxima

Once the top of a hill is reached the algorithm will halt since every possible step leads down.

Plateaux


If the landscape is flat, meaning many states have the same goodness, algorithm degenerates to a random walk.

Ridges

If the landscape contains ridges, local improvements may follow a zigzag path up the ridge, slowing down the search.

Surface

Surface
h1: Local Maxima



Surface
h2: Global Maxima

