

```
client.c
1#include <stdio.h>
2#include <unistd.h>
3#include <fcntl.h>
4#include <string.h>
5
6int main()
7{
8    char message[100];
9
10   int fd = open("myfifo", O_WRONLY);
11
12   printf("Enter message: ");
13   fgets(message, sizeof(message), stdin);
14
15   write(fd, message, strlen(message) + 1);
16
17   close(fd);
18
19   return 0;
20}
```

Loading file "/mnt/c/Users/DELL/OneDrive/Desktop/OS/Practical/2520030283_Practical/Practical-06/client.c"...

C Tab Width: 4 Ln 1, Col 1 INS

```
server.c
1#include <stdio.h>
2#include <unistd.h>
3#include <fcntl.h>
4#include <sys/stat.h>
5
6int main()
7{
8    char buffer[100];
9
10   mkfifo("myfifo", 0666);
11
12   int fd = open("myfifo", O_RDONLY);
13
14   while (1)
15   {
16       read(fd, buffer, sizeof(buffer));
17
18       printf("Server received: %s\n", buffer);
19   }
20
21   close(fd);
22
23   return 0;
24}
```

Loading file "/mnt/c/Users/DELL/OneDrive/Desktop/OS/Practical/2520030283_Practical/Practical-06/server.c"...

C Tab Width: 4 Ln 1, Col 1 INS

```
GNU nano 8.7.1 signals.c
#include <stdio.h>
#include <signal.h>
#include <unistd.h>

void handler(int sig)
{
    if (sig == SIGINT)
        printf("\nSIGINT received\n");

    if (sig == SIGTERM)
        printf("SIGTERM received\n");

    if (sig == SIGUSR1)
        printf("SIGUSR1 received\n");
}

int main()
{
    signal(SIGINT, handler);
    signal(SIGTERM, handler);
    signal(SIGUSR1, handler);

    printf("Process ID: %d\n", getpid());
    printf("Waiting for signals...\n");

    while (1)
    {
        sleep(1);
    }

    return 0;
}
```

Help Exit Write Out Read File Where Is Replace Cut Paste Execute Justify Location Go To Line Undo Redo Set Mark Copy To Bracket Where Was

30°C Mostly cloudy 16:36 13-09-2026

```
dell@DESKTOP-EFR7Q53: /mnt/c/Users/DELL/OneDrive/Desktop/OS/Practical/2520030283_Practical/Practical-06$ ./client
Enter message: Hello Server
dell@DESKTOP-EFR7Q53: /mnt/c/Users/DELL/OneDrive/Desktop/OS/Practical/2520030283_Practical/Practical-06$ |
```