

FBLA App Technical Layer
Generated: 2026-03-10T13:02:34.368Z
Scope: FBLA/ excluding node_modules, .git, .expo

1. Technical Overview

- Runtime: Expo + React Native + TypeScript; expo-router file-based routing under FBLA/app/.
- State: local state + hook-based viewmodels; no external global store.
- Persistence: AsyncStorage (users DB, current session, reminders, messaging DB).
- UI: ThemeContext + themed hooks/components; vector icons + custom symbol wrapper.

2. Runtime & Boot Sequence

Process start -> expo-router/entry (FBLA/package.json)
-> FBLA/app/_layout.tsx (RootLayout): providers + Stack
-> FBLA/app/(tabs)/_layout.tsx (TabLayout): auth gating + Tabs
-> Route screen component: renders UI and calls viewmodels/services as needed

3. Routes & Navigation Map

- / -> FBLA/app/_layout.tsx | Root Expo Router layout: wraps providers + Stack navigator, and hovers into '(tabs)' group. Uses Expo Router APIs; file path is part of runtime route graph.
- / -> FBLA/app/(tabs)/_layout.tsx | Tabs layout: defines bottom tab navigation and typically performs auth gating/redirect logic. Uses Expo Router APIs; file path is part of runtime route graph. Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Polling/timers via setInterval: 1000ms. Router ops: replace^ 3.
- / -> FBLA/app/(tabs)/index.tsx | Uses Expo Router APIs; file path is part of runtime route graph. Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty. Polling/timers via setInterval: 1000ms. Router ops: push^ 1.
- / -> FBLA/app/index.tsx
- /auth-choice -> FBLA/app/(tabs)/auth-choice.tsx | Uses Expo Router APIs; file path is part of runtime route graph. Router ops: replace^ 2.
- /competition-code -> FBLA/app/(tabs)/competition-code.tsx
- /competition-event -> FBLA/app/(tabs)/competition-event.tsx
- /dashboard -> FBLA/app/(tabs)/dashboard.tsx | Uses Expo Router APIs; file path is part of runtime route graph. Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty. Polling/timers via setInterval: 1000ms. Router ops: replace^ 1.
- /event-map -> FBLA/app/(tabs)/event-map.tsx
- /home -> FBLA/app/(tabs)/home.tsx | Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty. Polling/timers via setInterval: 1000ms.
- /landing -> FBLA/app/(tabs)/landing.tsx | Uses Expo Router APIs; file path is part of runtime route graph. Router ops: replace^ 1.
- /login -> FBLA/app/(tabs)/login.tsx | Uses Expo Router APIs; file path is part of runtime route graph. Router ops: replace^ 2.
- /messages/[username] -> FBLA/app/(tabs)/messages/[username].tsx | Uses Expo Router APIs; file path is part of runtime route graph. Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty. Polling/timers via setInterval: 1000ms. Router ops: replace^ 1, back^ 1.
- /messaging -> FBLA/app/(tabs)/messaging.tsx | Uses Expo Router APIs; file path is part of runtime route graph. Uses memoization; values may intentionally not update if deps are empty. Router ops: push^ 2.
- /modal -> FBLA/app/modal.tsx | Uses Expo Router APIs; file path is part of runtime route graph.
- /news/[id] -> FBLA/app/(tabs)/news/[id].tsx | Uses Expo Router APIs; file path is part of runtime route graph.
- /other -> FBLA/app/(tabs)/other.tsx | Uses Expo Router APIs; file path is part of runtime route graph. Router ops: push^ 2.
- /practice-quiz-events -> FBLA/app/(tabs)/practice-quiz-events.tsx
- /practice-quiz-viewer -> FBLA/app/(tabs)/practice-quiz-viewer.tsx
- /profile-setup -> FBLA/app/(tabs)/profile-setup.tsx | Uses Expo Router APIs; file path is part of runtime route graph. Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty.

y. Uses calendar UI; date format and timezone handling are key. Router ops: replace³.
- /reminders/ -> FBLA/app/(tabs)/reminders/index.tsx | Uses calendar UI; date format and time zone handling are key.
- /signup -> FBLA/app/(tabs)/signup.tsx | Uses Expo Router APIs; file path is part of runtime route graph. Uses memoization; values may intentionally not update if deps are empty. Uses calendar UI; date format and timezone handling are key. Router ops: replace².

4. Subsystem Architecture

4.1 Auth + Session Gating

- Data: FBLA/lib/authStorage.ts (AsyncStorage-backed user DB + current session key).
- Gating: FBLA/app/(tabs)/_layout.tsx loads getCurrentUser() and redirects by AuthFlowState.
- Redirect allowlist when unauthenticated: /landing, /auth-choice, /login, /signup.
- Profile completeness gate: forces /profile-setup until profileComplete is true.

4.2 Reminders

- Route: FBLA/app/(tabs)/reminders/index.tsx
- ViewModel: FBLA/features/reminders/useRemindersViewModel.ts
- Domain helpers: FBLA/features/reminders/model.ts
- Persistence: UserRecord.reminders via setCurrentUserReminders().

4.3 Messaging

- Routes: FBLA/app/(tabs)/messaging.tsx, FBLA/app/(tabs)/messages/[username].tsx
- Storage: MESSAGES_DB_KEY; conversationId = sort([a,b]).join("__").
- APIs: getAllMembersDirectory(), getCurrentUserConversations(), getConversationWithUser(), sendMessageToUser().

4.4 Competition Tools

- Model: FBLA/models/competitionModel.ts (code -> schedule).
- ViewModel: FBLA/viewmodels/useCompetitionViewModel.ts (normalize + next upcoming).

4.5 Practice Quiz

- Model: FBLA/models/practiceQuizModel.ts
- ViewModel: FBLA/viewmodels/usePracticeQuizViewModel.ts
- PDF rendering: FBLA/screens/PracticeQuizViewerScreen.tsx uses react-native-pdf.

4.6 News

- Data: FBLA/lib/newsData.ts exports NEWS_ITEMS; route param id selects item.
- Route: FBLA/app/(tabs)/news/[id].tsx renders fallback when id not found.

5. Local Storage Schema

- USERS_DB_KEY = "@fbla_users_v1"
- CURRENT_USER_KEY = "@fbla_current_user_v1"
- MESSAGES_DB_KEY = "@fbla_messages_v1"
- Types: UserRecord, AllReminders, ConversationSummary/Detail, ChatMessage, MemberDirectoryItem.

6. Module Graph Summary

- Total files: 68
- Internal import edges: 59
- Most imported modules:
 - 16x FBLA/lib/authStorage.ts
 - 4x FBLA/hooks/use-color-scheme.ts
 - 4x FBLA/models/competitionModel.ts
 - 3x FBLA/components/themed-view.tsx
 - 3x FBLA/hooks/use-theme-color.ts
 - 2x FBLA/assets/images/logo.png
 - 2x FBLA/components/themed-text.tsx
 - 2x FBLA/constants/theme.ts
 - 2x FBLA/contexts/ThemeContext.tsx
 - 2x FBLA/features/social-media/socialMediaModel.ts

7. Per-File Technical Reference

Asset (4)

File: FBLA/assets/images/logo.png

- Size: 46035 bytes | Lines: 0 | SHA1: f5fc5bfd54de
- Used by: FBLA/app/(tabs)/index.tsx, FBLA/app/(tabs)/news/[id].tsx

File: FBLA/assets/maps/fbla_conference_map.png

- Size: 46035 bytes | Lines: 0 | SHA1: f5fc5bfd54de
- Used by: FBLA/screens/EventMapScreen.tsx

File: FBLA/assets/tests/Accounting Sample Questions.pdf

- Size: 169673 bytes | Lines: 0 | SHA1: 53647f1dd08c
- Used by: FBLA/screens/PracticeQuizViewerScreen.tsx

File: FBLA/assets/tests/Business Ethics Sample Questions.pdf

- Size: 190849 bytes | Lines: 0 | SHA1: 36494cffd97f
- Used by: FBLA/screens/PracticeQuizViewerScreen.tsx

Component (10)

File: FBLA/components/external-link.tsx

- Size: 794 bytes | Lines: 26 | SHA1: 45f9f4dff295
- Exports: ExternalLink
- Imports: expo-router, expo-web-browser, react
- Notes: Uses Expo Router APIs; file path is part of runtime route graph.
- Public API (exports):
 - function ExternalLink ({ href, ...rest }: Props)

File: FBLA/components/haptic-tab.tsx

- Size: 564 bytes | Lines: 19 | SHA1: 2e9b9836d394
- Exports: HapticTab
- Imports: @react-navigation/bottom-tabs, @react-navigation/elements, expo-haptics
- Public API (exports):
 - function HapticTab (props: BottomTabBarButtonProps)

File: FBLA/components/hello-wave.tsx

- Size: 405 bytes | Lines: 20 | SHA1: feb54e9004cf
- Exports: HelloWave
- Imports: react-native-reanimated
- Public API (exports):
 - function HelloWave ()

File: FBLA/components/messaging/ConversationCard.tsx

- Size: 1977 bytes | Lines: 63 | SHA1: 149d469f568c
- Exports: ConversationCard
- Imports: react, react-native, @/lib/authStorage
- Used by: FBLA/app/(tabs)/messaging.tsx
- Public API (exports):
 - function ConversationCard ({ item, onPress }: ConversationCardProps)

File: FBLA/components/parallax-scroll-view.tsx

- Size: 1996 bytes | Lines: 80 | SHA1: f546b79f53a0
- Exports: default(ParallaxScrollView)
- Imports: react, react-native, react-native-reanimated, @/components/themed-view, @/hooks/use-color-scheme, @/hooks/use-theme-color
- Public API (exports):
 - default function ParallaxScrollView ({
children,
headerImage,
headerBackgroundColor,

```
}: Props)
```

File: FBLA/components/themed-text.tsx

- Size: 1285 bytes | Lines: 61 | SHA1: 034b9d5cfaea
- Exports: ThemedTextProps, ThemedText
- Imports: react-native, @/hooks/use-theme-color
- Used by: FBLA/app/modal.tsx, FBLA/components/ui/collapsible.tsx
- Public API (exports):
 - type ThemedTextProps
 - function ThemedText ({
 style,
 lightColor,
 darkColor,
 type = 'default',
 ...rest
}): ThemedTextProps)

File: FBLA/components/themed-view.tsx

- Size: 470 bytes | Lines: 15 | SHA1: a18969dfaef9
- Exports: ThemedViewProps, ThemedView
- Imports: react-native, @/hooks/use-theme-color
- Used by: FBLA/app/modal.tsx, FBLA/components/parallax-scroll-view.tsx, FBLA/components/ui/collapsible.tsx
- Public API (exports):
 - type ThemedViewProps
 - function ThemedView ({ style, lightColor, darkColor, ...otherProps }: ThemedViewProps)

File: FBLA/components/ui/collapsible.tsx

- Size: 1362 bytes | Lines: 46 | SHA1: 71df826fbefb
- Exports: Collapsible
- Imports: react, react-native, @/components/themed-text, @/components/themed-view, @/components/ui/icon-symbol, @/constants/theme, @/hooks/use-color-scheme
- Public API (exports):
 - function Collapsible ({ children, title }: PropsWithChildren & { title: string })

File: FBLA/components/ui/icon-symbol.ios.tsx

- Size: 598 bytes | Lines: 33 | SHA1: f74d4f4b8b78
- Exports: IconSymbol
- Imports: expo-symbols, react-native
- Public API (exports):
 - function IconSymbol ({
 name,
 size = 24,
 color,
 style,
 weight = 'regular',

```
}: {  
  name: SymbolViewProps['name'];  
  size?: number;  
  color: string;  
  style?: StyleProp<ViewStyle>;  
  weight?: SymbolWeight;  
})
```

File: FBLA/components/ui/icon-symbol.tsx

- Size: 1479 bytes | Lines: 44 | SHA1: d86ab15f62c5
- Exports: IconSymbol
- Imports: @expo/vector-icons/MaterialIcons, expo-symbols, react, react-native
- Used by: FBLA/components/ui/collapsible.tsx
- Public API (exports):
 - function IconSymbol ({
 name,

```

    size = 24,
    color,
    style,
  }: {
    name: IconSymbolName;
    size?: number;
    color: string | OpaqueColorValue;
    style?: StyleProp<TextStyle>;
    weight?: SymbolWeight;
  })

```

Config/Code (6)

File: FBLA/app.json

- Size: 1155 bytes | Lines: 50 | SHA1: 5d767aed12d0

File: FBLA/eslint.config.js

- Size: 237 bytes | Lines: 11 | SHA1: c6f2f99b8765

- Imports: eslint/config, eslint-config-expo/flat

File: FBLA/package-lock.json

- Size: 483650 bytes | Lines: 13013 | SHA1: 71d7fb7cf5bd

File: FBLA/package.json

- Size: 1590 bytes | Lines: 53 | SHA1: 795b66a0a7fe

File: FBLA/scripts/reset-project.js

- Size: 3608 bytes | Lines: 113 | SHA1: c1dcd32cc86b

- Exports: default(Index)

- Imports: fs, path, readline

- Notes: Uses Expo Router APIs; file path is part of runtime route graph.

- Public API (exports):

- default function Index ()

File: FBLA/tsconfig.json

- Size: 242 bytes | Lines: 18 | SHA1: 49617b82a993

Constant (1)

File: FBLA/constants/theme.ts

- Size: 1630 bytes | Lines: 54 | SHA1: 33b07beb7689

- Exports: Colors, Fonts

- Imports: react-native

- Used by: FBLA/components/ui/collapsible.tsx, FBLA/hooks/use-theme-color.ts

- Public API (exports):

- const Colors

- const Fonts

Context (1)

File: FBLA/contexts/ThemeContext.tsx

- Size: 2160 bytes | Lines: 89 | SHA1: b09a5dc74afe

- Exports: ThemeProvider, useTheme

- Imports: react, @react-native-async-storage/async-storage

- Used by: FBLA/app/_layout.tsx, FBLA/app/index.tsx

- Notes: Uses AsyncStorage: JSON serialization, schema/versioning matters. Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. AsyncStorage ops: getItem¹, setItem¹.

- Public API (exports):

- const ThemeProvider
- const useTheme ()

Documentation (6)

File: FBLA/FBLA_SYSTEMS.txt

- Size: 6544 bytes | Lines: 100 | SHA1: 757c302b329f

File: FBLA/PRESENTATION_GUIDE.html

- Size: 8953 bytes | Lines: 218 | SHA1: fc9639f925de

File: FBLA/PRESENTATION_GUIDE.md

- Size: 6591 bytes | Lines: 171 | SHA1: c2fded036bc4

File: FBLA/PRESENTATION_GUIDE.pdf

- Size: 154543 bytes | Lines: 0 | SHA1: cb0fc65aac6c

File: FBLA/README.md

- Size: 1741 bytes | Lines: 51 | SHA1: 7c428cafa7b6

File: FBLA/SYSTEM_STORAGE_DETAILED.txt

- Size: 13160 bytes | Lines: 418 | SHA1: e46c7574e7a6

Feature (4)

File: FBLA/features/reminders/model.ts

- Size: 2452 bytes | Lines: 86 | SHA1: 4af54ad5511f

- Exports: ReminderFormData, loadCurrentUserReminders, persistCurrentUserReminders, getRemindersForTypeAndDate, buildMarkedDates, buildUpdatedRemindersAfterSave, buildUpdatedRemindersAfterDelete

- Imports: @/lib/authStorage

- Used by: FBLA/features/reminders/useRemindersViewModel.ts

- Public API (exports):

- type ReminderFormData
- const loadCurrentUserReminders
- const persistCurrentUserReminders async(reminders: AllReminders)
- const getRemindersForTypeAndDate
- const buildMarkedDates (allReminders: AllReminders, selectedType: CalendarType, selectedDate: string)
- const buildUpdatedRemindersAfterSave
- const buildUpdatedRemindersAfterDelete

File: FBLA/features/reminders/useRemindersViewModel.ts

- Size: 2876 bytes | Lines: 105 | SHA1: 27691ac5e986

- Exports: useRemindersViewModel

- Imports: react-native, react, @/lib/authStorage, ./model

- Used by: FBLA/app/(tabs)/reminders/index.tsx

- Notes: Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty. Polling/timers via setInterval: 2000ms.

- Public API (exports):

- function useRemindersViewModel ()

File: FBLA/features/social-media/socialMediaModel.ts

- Size: 5861 bytes | Lines: 189 | SHA1: d847b913b49c

- Exports: SocialMediaLinks, loadStoredSocialLinks, persistSocialLinks, searchChapterSocialLinks

- Imports: @react-native-async-storage/async-storage, @/lib/authStorage

- Used by: FBLA/app/(tabs)/dashboard.tsx, FBLA/features/social-media/useSocialMediaViewModel.ts

- Notes: Uses AsyncStorage: JSON serialization, schema/versioning matters. AsyncStorage ops: getItem[^] 1, setItem[^] 1.
- Public API (exports):
 - type SocialMediaLinks
 - const loadStoredSocialLinks
 - const persistSocialLinks async(links: SocialMediaLinks)
 - const searchChapterSocialLinks

File: FBLA/features/social-media/useSocialMediaViewModel.ts

- Size: 2114 bytes | Lines: 80 | SHA1: 9e67451ecb18
- Exports: useSocialMediaViewModel
- Imports: react-native, react, @/lib/authStorage, ./socialMediaModel
- Notes: Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty.
- Public API (exports):
 - function useSocialMediaViewModel ()

Hook (3)

File: FBLA/hooks/use-color-scheme.ts

- Size: 47 bytes | Lines: 2 | SHA1: d932151d9578
- Exports: useColorScheme
- Used by: FBLA/app/_layout.tsx, FBLA/components/parallax-scroll-view.tsx, FBLA/components/ui/collapsible.tsx, FBLA/hooks/use-theme-color.ts

File: FBLA/hooks/use-color-scheme.web.ts

- Size: 480 bytes | Lines: 22 | SHA1: 350188df443c
- Exports: useColorScheme
- Imports: react, react-native
- Notes: Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior.
- Public API (exports):
 - function useColorScheme ()

File: FBLA/hooks/use-theme-color.ts

- Size: 537 bytes | Lines: 22 | SHA1: 3fff5f3cb493
- Exports: useThemeColor
- Imports: @/constants/theme, @/hooks/use-color-scheme
- Used by: FBLA/components/parallax-scroll-view.tsx, FBLA/components/themed-text.tsx, FBLA/components/themed-view.tsx
- Public API (exports):
 - function useThemeColor (props: { light?: string; dark?: string }, colorName: keyof typeof Colors.light & keyof typeof Colors.dark)

Library (2)

File: FBLA/lib/authStorage.ts

- Size: 9862 bytes | Lines: 336 | SHA1: f6050ad214eb
- Exports: Reminder, ReminderMap, CalendarType, AllReminders, ChatMessage, ConversationSummary, ConversationDetail, MemberDirectoryItem, UserRecord, emptyReminders, signUpUser, loginUser, logoutUser, getCurrentUser, setCurrentUserReminders, setCurrentUserProfile, setCurrentUserDisplayName, getAllMembersDirectory, getCurrentUserConversations, getConversationWithUser, sendMessageToUser
- Imports: @react-native-async-storage/async-storage
- Used by: FBLA/app/(tabs)/_layout.tsx, FBLA/app/(tabs)/dashboard.tsx, FBLA/app/(tabs)/home.tsx, FBLA/app/(tabs)/index.tsx, FBLA/app/(tabs)/login.tsx, FBLA/app/(tabs)/messages/[username].tsx, FBLA/app/(tabs)/messaging.tsx, FBLA/app/(tabs)/profile-setup.tsx, FBLA/app/(tabs)/reminders/index.tsx, FBLA/app/(tabs)/signup.tsx, FBLA/components/messaging/ConversationCard.tsx, FBLA/features/reminders/model.ts, FBLA/features/reminders/useRemindersViewModel.ts, FBLA/features/social-media/socialMediaModel.ts, FBLA/features/social-media/useSocialMediaViewModel.ts,

FBLA/models/practiceQuizModel.ts

- Notes: Uses AsyncStorage: JSON serialization, schema/versioning matters. AsyncStorage ops: getItem[^] 10, setItem[^] 4, removeItem[^] 1.

- Public API (exports):
 - type Reminder
 - type ReminderMap
 - type CalendarType
 - type AllReminders
 - type ChatMessage
 - type ConversationSummary
 - type ConversationDetail
 - type MemberDirectoryItem
 - type UserRecord
 - const emptyReminders
 - const signUpUser async(username: string, password: string, displayName: string)
 - const loginUser async(username: string, password: string)
 - const logoutUser async()
 - const getCurrentUser
 - const setCurrentUserReminders async(reminders: AllReminders)
 - const setCurrentUserProfile async(profilePatch: Partial<UserRecord['profile']>)
 - const setCurrentUserDisplayName async(displayName: string)
 - const getAllMembersDirectory
 - const getCurrentUserConversations
 - const getConversationWithUser
 - const sendMessageToUser async(otherUsername: string, text: string)

File: FBLA/lib/newsData.ts

- Size: 3717 bytes | Lines: 71 | SHA1: 5ccb40e6f3e4
- Exports: NewsItem, NEWS_ITEMS
- Used by: FBLA/app/(tabs)/index.tsx, FBLA/app/(tabs)/news/[id].tsx
- Public API (exports):
 - type NewsItem
 - const NEWS_ITEMS

Model (2)

File: FBLA/models/competitionModel.ts

- Size: 5447 bytes | Lines: 118 | SHA1: 0c4220187d43
- Exports: PresentationSlot, CompetitionEvent, COMPETITION_EVENTS_BY_CODE, normalizeCompetitionCode, getCompetitionEventByCode
- Used by: FBLA/screens/CompetitionCodeScreen.tsx, FBLA/screens/CompetitionEventScreen.tsx, FBLA/screens/EventMapScreen.tsx, FBLA/viewmodels/useCompetitionViewModel.ts
- Public API (exports):
 - type PresentationSlot
 - type CompetitionEvent
 - const COMPETITION_EVENTS_BY_CODE
 - const normalizeCompetitionCode (code: string)
 - const getCompetitionEventByCode

File: FBLA/models/practiceQuizModel.ts

- Size: 2595 bytes | Lines: 93 | SHA1: 76d0243b0896
- Exports: PracticeQuizEvent, PRACTICE_QUIZ_EVENTS, PracticeQuizPrefs, loadPracticeQuizEvents, getPracticeQuizEventByName, loadPracticeQuizPrefs, persistPracticeQuizPrefs
- Imports: @react-native-async-storage/async-storage, @/lib/authStorage
- Used by: FBLA/viewmodels/usePracticeQuizViewModel.ts
- Notes: Uses AsyncStorage: JSON serialization, schema/versioning matters. AsyncStorage ops: getItem[^] 1, setItem[^] 1.
- Public API (exports):
 - type PracticeQuizEvent
 - const PRACTICE_QUIZ_EVENTS
 - type PracticeQuizPrefs

- const loadPracticeQuizEvents async()
- const getPracticeQuizEventByName async(eventName: string)
- const loadPracticeQuizPrefs
- const persistPracticeQuizPrefs async(prefs: PracticeQuizPrefs)

Route (22)

File: FBLA/app/_layout.tsx

- Size: 899 bytes | Lines: 28 | SHA1: 4fc5d755adcf
- Route: /
- Exports: unstable_settings, default(RootLayout)
- Imports: @react-navigation/native, expo-router, expo-status-bar, @/hooks/use-color-scheme, @/contexts/ThemeContext
- Notes: Root Expo Router layout: wraps providers + Stack navigator, anchors into '(tabs)' group. Uses Expo Router APIs; file path is part of runtime route graph.
- Public API (exports):
 - const unstable_settings
 - default function RootLayout ()

File: FBLA/app/(tabs)/_layout.tsx

- Size: 6912 bytes | Lines: 236 | SHA1: 55d291a1c39c
- Route: /
- Exports: default(TabLayout)
- Imports: expo-router, react, @expo/vector-icons/MaterialIcons, react-native, @/lib/authStorage
- Notes: Tabs layout: defines bottom tab navigation and typically performs auth gating/redirection logic. Uses Expo Router APIs; file path is part of runtime route graph. Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Polling/timers via setInterval: 1000ms. Router ops: replace^ 3.
- Public API (exports):
 - default function TabLayout ()

File: FBLA/app/(tabs)/auth-choice.tsx

- Size: 1803 bytes | Lines: 58 | SHA1: b39531a45566
- Route: /auth-choice
- Exports: default(AuthChoiceScreen)
- Imports: react, react-native, expo-router
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Router ops: replace^ 2.
- Public API (exports):
 - default function AuthChoiceScreen ()

File: FBLA/app/(tabs)/competition-code.tsx

- Size: 108 bytes | Lines: 4 | SHA1: 1e3ef0d6625c
- Route: /competition-code
- Exports: default
- Imports: @/screens/CompetitionCodeScreen
- Public API (exports):
 - default default

File: FBLA/app/(tabs)/competition-event.tsx

- Size: 111 bytes | Lines: 4 | SHA1: b1c296a2658d
- Route: /competition-event
- Exports: default
- Imports: @/screens/CompetitionEventScreen
- Public API (exports):
 - default default

File: FBLA/app/(tabs)/dashboard.tsx

- Size: 14111 bytes | Lines: 432 | SHA1: 20fded6c0e20
- Route: /dashboard

- Exports: default(DashboardScreen)
- Imports: react, react-native, @expo/vector-icons/MaterialIcons, @expo/vector-icons/Ionicons, expo-router, @/lib/authStorage, @/features/social-media/socialMediaModel
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty. Polling/timers via setInterval: 1000ms. Router ops: replace^ 1.
- Public API (exports):
 - default function DashboardScreen ()

File: FBLA/app/(tabs)/event-map.tsx

- Size: 87 bytes | Lines: 4 | SHA1: ad50c39c1a11
- Route: /event-map
- Exports: default
- Imports: @/screens/EventMapScreen
- Public API (exports):
 - default default

File: FBLA/app/(tabs)/home.tsx

- Size: 3731 bytes | Lines: 102 | SHA1: 7a4931e67fbd
- Route: /home
- Exports: default(HomeScreen)
- Imports: react, react-native, @/lib/authStorage
- Notes: Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty. Polling/timers via setInterval: 1000ms.
- Public API (exports):
 - default function HomeScreen ()

File: FBLA/app/(tabs)/index.tsx

- Size: 9681 bytes | Lines: 276 | SHA1: 32c577fcf875
- Route: /
- Exports: default(HomeScreen)
- Imports: react, react-native, expo-router, @expo/vector-icons/MaterialIcons, @/lib/authStorage, @/lib/newsData, @/assets/images/logo.png
- Used by: FBLA/app/index.tsx
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty. Polling/timers via setInterval: 1000ms. Router ops: push^ 1.
- Public API (exports):
 - default function HomeScreen ()

File: FBLA/app/(tabs)/landing.tsx

- Size: 1522 bytes | Lines: 47 | SHA1: 4234ec1f1ef6
- Route: /landing
- Exports: default(LandingScreen)
- Imports: react, react-native, expo-router
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Router ops: replace^ 1.
- Public API (exports):
 - default function LandingScreen ()

File: FBLA/app/(tabs)/login.tsx

- Size: 3239 bytes | Lines: 115 | SHA1: b85f90ced4ba
- Route: /login
- Exports: default(LoginScreen)
- Imports: react, react-native, expo-router, @/lib/authStorage
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Router ops: replace^ 2.
- Public API (exports):
 - default function LoginScreen ()

File: FBLA/app/(tabs)/messages/[username].tsx

- Size: 6020 bytes | Lines: 188 | SHA1: d1292d280ae2
- Route: /messages/[username]
- Exports: default(ConversationScreen)
- Imports: react, react-native, @expo/vector-icons/MaterialIcons, expo-router, @/lib/authStorage
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty. Polling/timers via setInterval: 1000ms. Router ops: replace^ 1, back^ 1.
- Public API (exports):
 - default function ConversationScreen ()

File: FBLA/app/(tabs)/messaging.tsx

- Size: 6640 bytes | Lines: 211 | SHA1: 100f905cfce1
- Route: /messaging
- Exports: default(MessagingScreen)
- Imports: react, react-native, @expo/vector-icons/MaterialIcons, expo-router, @react-navigation/native, @react-navigation/bottom-tabs, @/lib/authStorage, @/components/messaging/ConversationCard
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Uses memoization; values may intentionally not update if deps are empty. Router ops: push^ 2.
- Public API (exports):
 - default function MessagingScreen ()

File: FBLA/app/(tabs)/news/[id].tsx

- Size: 3014 bytes | Lines: 89 | SHA1: 6b72bd0cef88
- Route: /news/[id]
- Exports: default(NewsArticleScreen)
- Imports: react, react-native, expo-router, @/lib/newsData, @/assets/images/logo.png
- Notes: Uses Expo Router APIs; file path is part of runtime route graph.
- Public API (exports):
 - default function NewsArticleScreen ()

File: FBLA/app/(tabs)/other.tsx

- Size: 4651 bytes | Lines: 139 | SHA1: 707392986cd5
- Route: /other
- Exports: default(OtherScreen)
- Imports: react, react-native, @expo/vector-icons/MaterialIcons, expo-router
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Router ops: push^ 2.
- Public API (exports):
 - default function OtherScreen ()

File: FBLA/app/(tabs)/practice-quiz-events.tsx

- Size: 117 bytes | Lines: 4 | SHA1: 8d3033c5df14
- Route: /practice-quiz-events
- Exports: default
- Imports: @/screens/PracticeQuizEventsScreen
- Public API (exports):
 - default default

File: FBLA/app/(tabs)/practice-quiz-viewer.tsx

- Size: 117 bytes | Lines: 4 | SHA1: 32f602a239d0
- Route: /practice-quiz-viewer
- Exports: default
- Imports: @/screens/PracticeQuizViewerScreen
- Public API (exports):
 - default default

File: FBLA/app/(tabs)/profile-setup.tsx

- Size: 7790 bytes | Lines: 239 | SHA1: 178388f5c99d

- Route: /profile-setup
- Exports: default(ProfileSetupScreen)
- Imports: react, react-native, @react-native-picker/picker, react-native-calendars, @/lib/authStorage, expo-router
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty. Uses calendar UI; date format and timezone handling are key. Router ops: replace^ 3.
- Public API (exports):
 - default function ProfileSetupScreen ()

File: FBLA/app/(tabs)/reminders/index.tsx

- Size: 10325 bytes | Lines: 308 | SHA1: fde9ec78effd
- Route: /reminders/
- Exports: default(RemindersScreen)
- Imports: react, react-native, react-native-calendars, @expo/vector-icons/MaterialIcons, @/lib/authStorage, @/features/reminders/useRemindersViewModel
- Notes: Uses calendar UI; date format and timezone handling are key.
- Public API (exports):
 - default function RemindersScreen ()

File: FBLA/app/(tabs)/signup.tsx

- Size: 10367 bytes | Lines: 302 | SHA1: 57121274eabf
- Route: /signup
- Exports: default(SignupScreen)
- Imports: react, react-native, @expo/vector-icons/MaterialIcons, react-native-calendars, expo-router, @/lib/authStorage
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Uses memoization; values may intentionally not update if deps are empty. Uses calendar UI; date format and timezone handling are key. Router ops: replace^ 2.
- Public API (exports):
 - default function SignupScreen ()

File: FBLA/app/index.tsx

- Size: 222 bytes | Lines: 11 | SHA1: 6b96cdcaf481
- Route: /
- Exports: default(App)
- Imports: @/contexts/ThemeContext, ./(tabs)/index
- Public API (exports):
 - default function App ()

File: FBLA/app/modal.tsx

- Size: 703 bytes | Lines: 30 | SHA1: 1e156f254962
- Route: /modal
- Exports: default(ModalScreen)
- Imports: expo-router, react-native, @/components/themed-text, @/components/themed-view
- Notes: Uses Expo Router APIs; file path is part of runtime route graph.
- Public API (exports):
 - default function ModalScreen ()

Screen (5)

File: FBLA/screens/CompetitionCodeScreen.tsx

- Size: 3422 bytes | Lines: 117 | SHA1: fc1cc342e65c
- Exports: default(CompetitionCodeScreen)
- Imports: react, react-native, react-native-safe-area-context, expo-router, @/models/competitionModel
- Used by: FBLA/app/(tabs)/competition-code.tsx
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Router ops: push^ 1.
- Public API (exports):
 - default function CompetitionCodeScreen ()

File: FBLA/screens/CompetitionEventScreen.tsx

- Size: 6096 bytes | Lines: 179 | SHA1: e6d397e4dc43
- Exports: default(CompetitionEventScreen)
- Imports: react, react-native, react-native-safe-area-context, @expo/vector-icons/MaterialIcons, expo-router, @/viewmodels/useCompetitionViewModel, @/models/competitionModel
- Used by: FBLA/app/(tabs)/competition-event.tsx
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Uses memoization; values may intentionally not update if deps are empty. Router ops: push^ 1.
- Public API (exports):
 - default function CompetitionEventScreen ()

File: FBLA/screens/EventMapScreen.tsx

- Size: 1617 bytes | Lines: 52 | SHA1: a327d8000827
- Exports: default(EventMapScreen)
- Imports: react, react-native, react-native-safe-area-context, expo-router, @/models/competitionModel, ../assets/maps/fbla_conference_map.png
- Used by: FBLA/app/(tabs)/event-map.tsx
- Notes: Uses Expo Router APIs; file path is part of runtime route graph.
- Public API (exports):
 - default function EventMapScreen ()

File: FBLA/screens/PracticeQuizEventsScreen.tsx

- Size: 4719 bytes | Lines: 149 | SHA1: f5ec69428cab
- Exports: default(PracticeQuizEventsScreen)
- Imports: react, react-native, @expo/vector-icons/MaterialIcons, expo-router, @/viewmodels/usePracticeQuizViewModel
- Used by: FBLA/app/(tabs)/practice-quiz-events.tsx
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Router ops: push^ 1.
- Public API (exports):
 - default function PracticeQuizEventsScreen ()

File: FBLA/screens/PracticeQuizViewerScreen.tsx

- Size: 5442 bytes | Lines: 157 | SHA1: f6d4891ad3fc
- Exports: default(PracticeQuizViewerScreen)
- Imports: react, react-native, @expo/vector-icons/MaterialIcons, expo-constants, expo-router, @/viewmodels/usePracticeQuizViewModel, ../assets/tests/Accounting Sample Questions.pdf, ../assets/tests/Business Ethics Sample Questions.pdf, react-native-pdf
- Used by: FBLA/app/(tabs)/practice-quiz-viewer.tsx
- Notes: Uses Expo Router APIs; file path is part of runtime route graph. Uses memoization; values may intentionally not update if deps are empty. Renders PDFs; ensure native linking/permissions for device platforms. Router ops: back^ 1.
- Public API (exports):
 - default function PracticeQuizViewerScreen ()

ViewModel (2)

File: FBLA/viewmodels/useCompetitionViewModel.ts

- Size: 1301 bytes | Lines: 41 | SHA1: 56eb0474aeb9
- Exports: useCompetitionViewModel
- Imports: react, @/models/competitionModel
- Used by: FBLA/screens/CompetitionEventScreen.tsx
- Notes: Uses memoization; values may intentionally not update if deps are empty.
- Public API (exports):
 - function useCompetitionViewModel (rawCode: string)

File: FBLA/viewmodels/usePracticeQuizViewModel.ts

- Size: 2707 bytes | Lines: 100 | SHA1: f4f024dcb085
- Exports: usePracticeQuizViewModel, usePracticeQuizViewerViewModel
- Imports: react, @/models/practiceQuizModel
- Used by: FBLA/screens/PracticeQuizEventsScreen.tsx, FBLA/screens/PracticeQuizViewerScreen.t

SX

- Notes: Has React side effects via 'useEffect'; check dependency arrays for lifecycle behavior. Uses memoization; values may intentionally not update if deps are empty.
- Public API (exports):
 - function usePracticeQuizViewModel ()
 - function usePracticeQuizViewerViewModel (eventName: string)