



सैल सैल

STEEL AUTHORITY OF INDIA LIMITED
BOKARO STEEL PLANT
BOKARO STEEL CITY - 827001, JHARKHAND, INDIA
Test Certificate
HOT ROLLED MEDIUM AND HIGH
TENSILE STRUCTURAL STEEL

IS:2062



MATERIAL DESCRIPTION : HR PLATE IS 2062 E250BR SIALK
TEST CERTIFICATE NO. : 1074724
SHIPPING ADVICE NO. : 81360266
WAGON NO. : ECR11371

MILL : HRCF

DATE : 15.08.2025

DATE : 14.08.2025

TO

BM BSO KANPUR

WHM PANKI

PANKI , PO GANGAGANJ 208020

KANPUR

We certify that the material described below fully confirms to 2062:2011. Chemical composition and Mechanical / Physical properties of the product as tested in accordance with the scheme of testing and inspection contained in BIS Certification Marks License No: CM/L-0484856 are as indicated against each Coil / Cast No or Order No. The Material supplied conforms to the standard rolling / dimensional and weight tolerances.

(Please refer to 2062:2011 for details of specification requirements)

Chemical Analysis, Mechanical Properties, Specifications & Other Information																		
ITEM NO.	CAST NO.	BATCH NO.	SALES ORDER & SIZE (MM)	TON	C% (0.22 MAX)	Mn% (1.50 MAX)	P% (0.045 MAX)	S % (0.045 MAX)	Si% (0.03-0.40)	Al% (0.01-0.10)	CE% (0.41 MAX)	YS MPa (250 MIN)	UTS MPa (410 MIN)	El % (23 MIN)	BEND (2T)	ImpAv J (27MIN @RT)	EDGE ()	GRADE
1	2557407	1240030A	1201015275 8.000X1,800X8,000	12.750	0.15	0.75	0.013	0.010	0.148	0.034	0.278	347.0	470.0	30.0	OK	130	UnTrim	IS 2062 E250BR SIALK
2	2557412	1240508B	1201015275 8.000X1,800X8,000	11.820	0.13	0.72	0.019	0.009	0.169	0.030	0.253	324.0	461.0	30.0	OK	124	UnTrim	IS 2062 E250BR SIALK
3	2557412	1240510A	1201015275 8.000X1,800X8,000	15.420	0.13	0.72	0.019	0.009	0.169	0.030	0.253	324.0	461.0	30.0	OK	124	UnTrim	IS 2062 E250BR SIALK
4	2557416	1240654B	1201015275 8.000X1,800X8,000	13.620	0.15	0.73	0.020	0.009	0.152	0.042	0.277	336.0	477.0	30.0	OK	126	UnTrim	IS 2062 E250BR SIALK
5	2557400	1239898B	1201015275 8.000X1,800X8,000	10.650	0.15	0.83	0.022	0.017	0.113	0.032	0.294	328.0	446.0	30.0	OK	126	UnTrim	IS 2062 E250BR SIALK
TOTAL TONNAGE :				64.26														

Remarks: MTC is issued according to EN 10204 TYPE 3.1. Second set of mechanical properties pertains to the same heat

This is to certify that the above mentioned product do not contain any radioactive element higher than the natural level. The product or packing material does not contain any hazardous substance as per RoHS norms.

LEGEND (where applicable):				Hard = Hardness		No. 40-23-26		THIRD PARTY / BDOA		AUTHORISED SIGNATORY	
One Mpa=1 Nsq.mm=0.102 kg/sq.mm		MAE = Micro Alloying Elements		GC = Galvanised Corrugated		IMP = Impact Value (full size)		Issued Against Bill			
EL = Elongation		GPD = Galvanised Plain Deep Drawing		ST-RL=Stretched & Roller Levelled							
YS = Yield Stress		TXWX L = ThicknessXWidthXLength		COR-OD=Corrugated Ordinary							
UTS = Ultimate Tensile Strength		D.DRW = Deep Drawing		Process Route : BOF-LF-CCS-HSM							
CE = Carbon Equivalent		CUP = Cupping Value		FOR SENIOR MANAGER (MTL)							
				Process Route : BOF-LF-CCS-HSM				RESEARCH & CONTROL LABORATORY			