



सत सल

STEEL AUTHORITY OF INDIA LIMITED

BOKARO STEEL PLANT

CITY - 827001, JHARKHAND, INDIA

Test Certificate
HOT ROLLED MEDIUM AND HIGH
TENSILE STRUCTURAL STEEL

MILL : HRCF

MATERIAL DESCRIPTION : HR PLATE IS 2062 E250BR SIAIK
TEST CERTIFICATE NO. : 1074724
SHIPPING ADVISE NO. : 81360266
WAGON NO. : ECOR11371

DATE : 15.08.2025
DATE : 14.08.2025

TO
BM BSO KANPUR
WHM PANKI
PANKI , PO GANGAGANJ 208020
KANPUR

We certify that the material described below fully confirms to 2062:2011. Chemical composition and Mechanical / Physical properties of the product as tested in accordance with the scheme of testing and inspection contained in BIS Certification Marks License No: CM/L-0484856 are as indicated against each Coil / Cast No or Order No. The Material supplied conforms to the standard rolling / dimensional and weight tolerances.

(Please refer to 2062:2011 for details of specification requirements)

				Chemical Analysis, Mechanical Properties, Specifications & Other Information															
ITEM NO.	CAST NO.	BATCH NO.	SALES ORDER & SIZE (MM) T X W X L	TON	C % (0.22 MAX)	Mn % (1.50 MAX)	P % (0.045 MAX)	S % (0.045 MAX)	Si % (0.03-0.40)	Al % (0.01-0.10)	CE % (0.41 MAX)	YS MPa (250 MIN)	UTS MPa (410 MIN)	El % (23 MIN)	BEND (2T)	Impav J (27MIN @RT)	EDGE ()	GRADE	
1	2557407	1240030A	1201015275 8.000X1,800X8,000	12.750	0.15	0.75	0.013	0.010	0.148	0.034	0.278	347.0 330.0	470.0 457.0	30.0 33.0	OK	130	Untrim	IS 2062 E250BR SLAIR	
2	2557412	1240508B	1201015275 8.000X1,800X8,000	11.820	0.13	0.72	0.019	0.009	0.169	0.030	0.253	324.0 321.0	461.0 458.0	30.0 30.0	OK	124	Untrim	IS 2062 E250BR SLAIR	
3	2557412	1240510A	1201015275 8.000X1,800X8,000	15.420	0.13	0.72	0.019	0.009	0.169	0.030	0.253	324.0 321.0	461.0 458.0	30.0 30.0	OK	124	Untrim	IS 2062 E250BR SLAIR	
4	2557416	1240654B	1201015275 8.000X1,800X8,000	13.620	0.15	0.73	0.020	0.009	0.152	0.042	0.277	336.0 332.0	477.0 474.0	30.0 30.0	OK	126	Untrim	IS 2062 E250BR SLAIR	
5	2557400	1239898B	1201015275 8.000X1,800X8,000	10.650	0.15	0.83	0.022	0.017	0.113	0.032	0.294	328.0 330.0	446.0 450.0	30.0 30.0	OK	126	Untrim	IS 2062 E250BR SLAIR	
TOTAL TONNAGE :				64.26															

Remarks: MTC is issued according to EN 10204 TYPE 3.1. Second set of mechanical properties pertains to the same heat This is to certify that the above mentioned product do not contain any radioactive element higher than the natural level. The product or packing material does not contain any hazardous substance as per RoHS norms.

LEGEND (where applicable):

One Mpa=1 Nsq.mm=0.102 kg/sq.mm
EL = Elongation
YS = Yield Stress
UTS = Ultimate Tensile Strength
CE = Carbon Equivalent

MAE = Micro Alloying Elements
GC = Galvanised Corrugated
GPD = Galvanised Plain Deep Drawing
TXWX L = ThicknessXWidthXLength
D.DRW = Deep Drawing
CUP = Cupping Value

Hard = Hardness
IMP = Impact Value (Full Size)
COR-OD=Corrugated Ordinary

Process Route : BOF-LF-CCS-HSM

Issued Against Bill No. 247100043
2023.08

AUTHORISED SIGNATORY

FOR SENIOR MANAGER (MTL)
RESEARCH & CONTROL LABORATORY