



रॉल सॉल

STEEL AUTHORITY OF INDIA LIMITED
BOKARO STEEL PLANT
BOKARO STEEL CITY - 827001, JHARKHAND, INDIA

Test Certificate
HOT ROLLED MEDIUM AND HIGH
TENSILE STRUCTURAL STEEL

MILL : HRCF

MATERIAL DESCRIPTION : HR PLATE IS 2062 E250BR SLAK
TEST CERTIFICATE NO. : 10852294
SHIPPING ADVISE NO. : 81375296
WAGON NO. : SECR64205

DATE : 29.09.2025
DATE : 27.09.2025

TO
BM BSO KANPUR
WHM PANKI
PANKI , PO GANGAGANJ 208020
KANPUR

We certify that the material described below fully confirms to 2062:2011. Chemical composition and Mechanical / Physical properties of the product as tested in accordance with the scheme of testing and inspection contained in BIS Certification Marks License No: CM/L-0484856 are as indicated against each Coil / Cast No or Order No. The Material supplied conforms to the standard rolling / dimensional and weight tolerances.

(Please refer to 2062:2011 for details of specification requirements)

				Chemical Analysis, Mechanical Properties, Specifications & Other Information														
ITEM NO.	CAST NO.	BATCH NO.	SALES ORDER & SIZE (MM) T X W X L	TON	C% (0.22 MAX)	Mn% (1.50 MAX)	P% (0.045 MAX)	S % (0.045 MAX)	Si% (0.03- 0.40)	Al% (0.01- 0.10)	CE% (0.41 MAX)	YS MPA (250 MIN)	UTS MPA (410 MIN)	EL % (23 MIN)	BEND (2T)	Impav J (27MIN @RT)	EDGE ()	GRADE
1	2558519	1263325A	1201015275 8.000X1,800X8,000	15.510	0.15	0.73	0.018	0.014	0.104	0.035	0.276	362.0 335.0	490.0 440.0	30.0 30.0	OK	115	UnTrim	IS 2062 E250BR SLAK
2	2558519	1263325B	1201015275 8.000X1,800X8,000	14.570	0.15	0.73	0.018	0.014	0.104	0.035	0.276	362.0 335.0	490.0 440.0	30.0 30.0	OK	115	UnTrim	IS 2062 E250BR SLAK
3	2558519	1263324A	1201015275 8.000X1,800X8,000	15.510	0.15	0.73	0.018	0.014	0.104	0.035	0.276	362.0 335.0	490.0 440.0	30.0 30.0	OK	115	UnTrim	IS 2062 E250BR SLAK
4	2558519	1263324B	1201015275 8.000X1,800X8,000	14.560	0.15	0.73	0.018	0.014	0.104	0.035	0.276	362.0 335.0	490.0 440.0	30.0 30.0	OK	115	UnTrim	IS 2062 E250BR SLAK
TOTAL TONNAGE :				60.15														

Remarks: MTC is issued according to EN 10204 TYPE 3.1. Second set of mechanical properties pertains to the same heat

This is to certify that the above mentioned product do not contain any radioactive element higher than the natural level. The product or packing material does not contain any hazardous substance as per RoHS norms.

LEGEND (where applicable):

One Mpa=1 Nsq.mm=0.102 kg/sq.mm	MAE = Micro Alloying Elements	Hard = Hardness	AUTHORISED SIGNATORY
EL = Elongation	GC = Galvanised Corrugated	IMP = Impact Value (full size)	
YS = Yield Stress	GPD = Galvanised Plain Deep Drawing ST-RL=Stretched & Roller Levelled		
UTS = Ultimate Tensile Strength	TXWX.L = ThicknessXWidthXLength	COR-OD=Corrugated Ordinary	
CE = Carbon Equivalent	CUP = Cupping Value	Process Route : BOF-LF-CCS-HSM	

Issued Against Billing
No. 15510
Date 28.09.2025

AUTHORISED SIGNATORY

FOR SENIOR MANAGER (MTI)

RESEARCH & CONTROL LABORATORY