



STEEL AUTHORITY OF INDIA LIMITED
BOKARO STEEL PLANT
CITY - 827001, JHARKHAND, INDIA
Test Certificate
HOT ROLLED MEDIUM AND HIGH
TENSILE STRUCTURAL STEEL



MATERIAL DESCRIPTION : HR PLATE IS 2062 E250BR SLAK
TEST CERTIFICATE NO. : 1085294
SHIPPING ADVISE NO. : 81375296
WAGON NO. : SECR64205

MILL : HRCE
DATE : 29.09.2025
DATE : 27.09.2025

TO
BM BSO KANPUR
WHM PANKI
PANKI , PO GANGAGANJ 208020
KANPUR

We certify that the material described below fully confirms to 2062:2011. Chemical composition and Mechanical / Physical properties of the product as tested in accordance with the scheme of testing and inspection contained in BIS Certification Marks License No: CM/L-0484856 are as indicated against each Coil / Cast No or Order No. The Material supplied conforms to the standard rolling / dimensional and weight tolerances.

(Please refer to 2062:2011 for details of specification requirements)

		Chemical Analysis, Mechanical Properties, Specifications & Other Information																					
ITEM NO.	CAST NO.	BATCH NO.	SALES ORDER & SIZE (MM) T X W X L	TON	C% (0.22 MAX)	Mn% (1.50 MAX)	P% (0.045 MAX)	S % (0.045 MAX)	Si% (0.03-0.40)	Al% (0.01-0.10)	CE% (0.41 MAX)	YS MPa (250 MIN)	UTS MPa (410 MIN)	El % (23 MIN)	BEND (2r)	Impav J (27MIN @RT)	EDGE ()	GRADE					
1	2558519	1263325A	1201015275 8.000X1,800X8,000.	15.510	0.15	0.73	0.018	0.014	0.104	0.035	0.276	362.0 335.0	490.0 440.0	30.0 30.0	OK	115	UnTrim	IS 2062 E250BR SLAIR					
2	2558519	1263325B	1201015275 8.000X1,800X8,000	14.570	0.15	0.73	0.018	0.014	0.104	0.035	0.276	362.0 335.0	490.0 440.0	30.0 30.0	OK	115	UnTrim	IS 2062 E250BR SLAIR					
3	2558519	1263324A	1201015275 8.000X1,800X8,000	15.510	0.15	0.73	0.018	0.014	0.104	0.035	0.276	362.0 335.0	490.0 440.0	30.0 30.0	OK	115	UnTrim	IS 2062 E250BR SLAIR					
4	2558519	1263324B	1201015275 8.000X1,800X8,000	14.560	0.15	0.73	0.018	0.014	0.104	0.035	0.276	362.0 335.0	490.0 440.0	30.0 30.0	OK	115	UnTrim	IS 2062 E250BR SLAIR					
TOTAL TONNAGE :				60.15																			

Issued Against Bill No. 4004720076
14.5.20 DL 30.03.26
MT

Remarks: MTC is issued according to EN 10204 TYPE 3.1. Second set of mechanical properties pertains to the same heat
This is to certify that the above mentioned product do not contain any radioactive element higher than the natural level. The product or packing material does not contain any hazardous substance as per RoHS norms.

Auth Signatory

LEGEND (where applicable):		THIRD PARTY / DDQA		AUTHORISED SIGNATORY	
One Mpa=1 Nsq.mm=0.102 kg/sq.mm		MAE = Micro Alloying Elements		Hard = Hardness	
EL = Elongation		GC = Galvanised Corrugated		IMP = Impact Value (full size)	
YS = Yield Stress		GPD = Galvanised Plain Deep Drawing ST-RL=Stretched & Roller Levelled		TXWX L = ThicknessXWidthXLength	
UTS = Ultimate Tensile Strength		D.DRW = Deep Drawing		CCR-OD=Corrugated Ordinary	
CE = Carbon Equivalent		CUP = Cupping Value		Process Route : BOF-LF-CCS-HSM	

FOR SENIOR MANAGER (MTL)
RESEARCH & CONTROL LABORATORY