



STEEL AUTHORITY OF INDIA LIMITED
BOKARO STEEL PLANT
BOKARO STEEL CITY - 827001, JHARKHAND, INDIA
Test Certificate
STRUCTURAL STEEL PART 1
HOT ROLLED MEDIUM AND HIGH TENSILE STEEL



संलग्न SAIL

MATERIAL DESCRIPTION : HR COIL IS 2062 E250BR SIALK
TEST CERTIFICATE NO. : 1124795
SHIPPING ADVICE NO. : 81437380
WAGON NO. : SWR54565

MILL : HSM
DATE : 12.03.2026
DATE : 11.03.2026
TO
BM BSO JAIPUR
RAJASTHAN ISPAT UDYOG (DISTRIBUTOR)
E-341, ROAD NO. 16, VISHWAKARMA 302013
JAIPUR

We certify that the material described below fully confirms to 2062(PART 1):2025. Chemical composition and Mechanical / Physical properties of the product as tested in accordance with the scheme of testing and inspection contained in BIS Certification Marks License No: CM/L-0484856 are as indicated against each Coil / Cast No or Order No. The Material supplied conforms to the standard rolling / dimensional and weight tolerances.

(Please refer to 2062(PART 1):2025 for details of specification requirements)

Chemical Analysis, Mechanical Properties, Specifications & Other Information																
ITEM NO.	CAST NO.	BATCH NO.	SALES ORDER & SIZE (MM)	TON	C% (0.22 MAX)	Mn% (1.50 MAX)	P% (0.045 MAX)	S % (0.045 MAX)	Si% (0.03-0.40)	Al% (0.01-0.10)	CE% (0.41 MAX)	YS MPa (250 MIN)	UTS MPa (410 MIN)	EL % (23 MIN)	BEND (2T)	GRADE
1	2652432	1354639	1201070442 16.000X1.500	28.450	0.16	1.22	0.037	0.005	0.204	0.035	0.371	365.0	472.0	27.0	OK	IS 2062 E250BR
TOTAL TONNAGE :				28.45												
SIALK																

Remarks: MTC is issued according to EN 10204 TYPE 3.1. Second set of mechanical properties pertains to the same heat

This is to certify that the above mentioned product do not contain any radioactive element higher than the natural level. The product or packing material does not contain any hazardous substance as per RoHS norms.

LEGEND (where applicable):			THIRD PARTY / DDQA		AUTHORISED SIGNATORY	
One Mpa=1 Nsq.mm=0.102 kg/sq.mm	MAE = Micro Alloying Elements	Hard = Hardness				
EL = Elongation	GC = Galvanised Corrugated	IMP = Impact Value (full size)				
YS = Yield Stress	GPD = Galvanised Plain Deep Drawing	ST-RL=Stretched & Roller Levelled				
UTS = Ultimate Tensile Strength	TXWX L = ThicknessXWidthXLength	COR-OD=Corrugated Ordinary				
CE = Carbon Equivalent	D.DRW = Deep Drawing					
CUP = Cupping Value		Process Route : BOF-LF-CCS-HSM		FOR SENIOR MANAGER (MTL)		
						RESEARCH & CONTROL LABORATORY