



संज्ञा SAIL

STEEL AUTHORITY OF INDIA LIMITED
BOKARO STEEL PLANT
BOKARO STEEL CITY - 827001, JHARKHAND, INDIA

Test Certificate

HOT ROLLED STEEL SHEET, PLATE AND STRIP FOR FORMING AND FLANGING PURPOSES

IS 5986



MATERIAL DESCRIPTION : HR COIL IS5986 ISH330S SIALK

TEST CERTIFICATE NO. : 1124796

SHIPPING ADVICE NO. : 81437380

WAGON NO. : SWR54565

MILL : HSM

DATE : 12.03.2026

DATE : 11.03.2026

TO

BM BSO JAIPUR

RAJASTHAN ISPAT UDYOG (DISTRIBUTOR)

E-341, ROAD NO. 16, VISHWAKARMA 302013

JAIPUR

We certify that the material described below fully conforms to 5986 : 2017. Chemical composition and Mechanical / Physical properties of the product as tested in accordance with the scheme of testing and inspection contained in BIS Certification Marks License No: CM/L # 0563246 are as indicated against each Coil / Cast No or Order No. The Material supplied conforms to the standard rolling / dimensional and weight tolerances.

(Please refer to 5986 : 2017 for details of specification requirements)

Chemical Analysis, Mechanical Properties, Specifications & Other Information															
ITEM NO.	CAST NO.	BATCH NO.	SALES ORDER & SIZE (MM) T X W X L	TON	C% (0.15 MAX)	Mn% (0.80 MAX)	P% (0.040 MAX)	S % (0.040 MAX)	Si% (0.500 MAX)	Al% (0.010 MIN)	YS MPa (205 MIN)	UTS MPa (330-440)	EL % (20/28 MIN)	BEND (T/2T)	GRADE
1	2652406	1354193	1201070445 4.000X1,500	28.150	0.09	0.35	0.016	0.005	0.175	0.022	312.0	418.0	36.0	OK	IS5986 ISH330S
TOTAL TONNAGE :				28.15											
											SIALK				

Remarks: MTC is issued according to EN 10204 TYPE 3.1

This is to certify that the above mentioned product do not contain any radioactive element higher than the natural level. The product or packing material does not contain any hazardous substance as per RoHS norms.

LEGEND (where applicable):			
One Mpa=1 Nsq.mm=0.102 kg/sq.mm	MAE = Micro Alloying Elements	Hard = Hardness	THIRD PARTY / DDOA
EL = Elongation	GC = Galvanised Corrugated	IMP = Impact Value (full size)	AUTHORISED SIGNATORY
YS = Yield Stress	GPD = Galvanised Plain Deep Drawing ST-RL-Stretched & Roller Levelled	COR-OD=Corrugated Ordinary	
UTS = Ultimate Tensile Strength	TXWX L = ThicknessXWidthXLength		
CE = Carbon Equivalent	D.DRW = Deep Drawing		
	CUP = Cupping Value	Process Route : BOF-LF-CCS-HSM	FOR SENIOR MANAGER (MTL)
			RESEARCH & CONTROL LABORATORY