

MIVI

Will Bennett

12/13/2023

Effects of Latitude and Elevation on the Phenology of an Invasive Grass

Japanese Stiltgrass (*Microstegium vimineum*)

Data source: iNaturalist ([link](#))

Total observations (North America): 13,782

Observations needing phenology annotation: 5,940 ([link for reviewing](#))

Setup

```
# set lwd
setwd("~/Documents/MIVI/")

library(dplyr)
library(ggplot2)
library(elevatr)
library(corrtable)
library(table1)
library(knitr)
```

Loading data

Export iNaturalist Data

1. Export all *Microstegium vimineum* observations from iNat with columns (id, observed_on, latitude, longitude, place_state_name, place_country_name): [Link](#)
2. Export all *M. vimineum* observations with phenology 'No Evidence of Flowering' with column id: [Link](#)
3. Export all *M. vimineum* observations with phenology 'Flowering' with column id: [Link](#)
4. Export all *M. vimineum* observations with phenology 'Fruiting' with column id: [Link](#)

```

# 1
mivi_all <- read.csv("./MIVI-ALL.csv") %>%
  mutate(date=as.Date(observed_on, format="%Y-%m-%d")) %>% select(-observed_on)

# 2
mivi_young <- read.csv("MIVI-YOUNG.csv") %>%
  mutate(stage="Vegetation")

# 3
mivi_flowering <- read.csv("./MIVI-FLOWERING.csv") %>%
  mutate(stage="Flowering")
mivi_flowering <- mivi_flowering %>% left_join(mivi_all, by="id")

# 4
mivi_fruiting <- read.csv("./MIVI-FRUITING.csv") %>%
  mutate(stage="Fruiting")

# join each based on id
mivi_all <- mivi_all %>% left_join(mivi_young, by="id")
mivi_all <- mivi_all %>% left_join(mivi_fruiting, by="id") %>%
  mutate(stage = coalesce(stage.x, stage.y)) %>% select(-stage.x, -stage.y)
mivi_all <- rbind(mivi_all, mivi_flowering)

# memory cleanup
rm(mivi_young, mivi_flowering, mivi_fruiting)

```

Or load from processed file

```

mivi_all <- read.csv("./MIVI-PROCESSED.csv") %>% select(-X) %>%
  mutate(date=as.Date(date, format="%Y-%m-%d"))

```

Data processing

```

# remove known incorrect records
mivi_all <- subset(mivi_all, id != "130398055")

# Get Julian day
mivi_all <- mivi_all %>% mutate(julian = as.integer(strftime(date, format="%j")))

# make phenology a factor type (not necessary)
mivi_all$stage <- factor(mivi_all$stage, ordered=TRUE,
  levels=c("Vegetation", "Flowering", "Fruiting"))

# Select only observations with phenology data
mivi_annotated <- mivi_all %>% filter(!is.na(stage))


# Group into quartiles by latitude
mivi_annotated$group <- ntile(mivi_annotated$latitude, 4)

```

Basic Descriptive Plots


```
# Density of all observations by lat/lon  
ggplot(mivi_all, aes(x=longitude,y=latitude)) + geom_point(alpha=0.25) +  
  labs(title="Density of observations by location")
```

Density of observations by location




```
# Histogram of all observations by lat  
ggplot(mivi_all, aes(x=latitude)) + geom_histogram(binwidth=0.2) +  
  labs(title="Histogram of observations by latitude")
```

Histogram of observations by latitude




```
# Histogram with city labels
ggplot(mivi_all, aes(x=latitude)) + geom_histogram(binwidth=0.2) +
  geom_vline(xintercept=33.75) + annotate("text", x=33.5, y=900, label="Atlanta", angle=90) +
  geom_vline(xintercept=35.84) + annotate("text", x=35.59, y=900, label="Raleigh", angle=90) +
  geom_vline(xintercept=37.54) + annotate("text", x=37.29, y=900, label="Richmond", angle=90) +
  geom_vline(xintercept=38.9) + annotate("text", x=38.65, y=900, label="Washington", angle=90) +
  geom_vline(xintercept=40.75) + annotate("text", x=41, y=900, label="New York", angle=90) +
  ylab("count") + labs(title="Histogram of observations by latitude")
```

Histogram of observations by latitude



```
# Boxplots of phenology by quartile (notches break hinges for Flowering)
# Slight earlier trend in Fruiting visible
ggplot(mivi_annotated, aes(julian, stage)) + geom_boxplot() + facet_grid(~group) +
  coord_flip() + xlab("Julian day") + labs(title="Phenology stage, quartiles by latitude")
```


Phenology stage, quartiles by latitude



Time Series Plots

```
# Latitude against Julian day
ggplot(mivi_annotated, aes(julian, latitude)) + geom_point(aes(color=stage), alpha=0.5) +
  scale_color_hue() + xlab("Julian day") +
  labs(title="Annotated Observations by Latitude and Julian Day")
```


Annotated Observations by Latitude and Julian Day



```
# Latitude against Julian day
# ggplot(mivi_all, aes(julian, latitude)) + geom_point(aes(color=stage), alpha=0.5) +
#   scale_color_hue() + xlab("Julian day") +
#   labs(title="Observations by Latitude and Julian Day")

# Time series by latitude, color by stage
ggplot(mivi_all, aes(date, latitude)) + geom_point(aes(color=stage), alpha=0.5) +
  scale_x_date(date_breaks = "1 year", date_labels = "%Y") + scale_color_hue() +
  labs(title="Observations by latitude over time")
```


Observations by latitude over time



```
# Zoom in on recent data
timeclip <- c(as.Date("2019-02-01"), as.Date("2023-11-30"))
ggplot(mivi_all, aes(date, latitude)) + geom_point(aes(color=stage), alpha=0.5) +
  scale_x_date(limits=timeclip, date_breaks = "1 year", date_labels = "%Y") + scale_color_hue() +
  labs(title="Observations by latitude over time (2019-2023)")
```

```
## Warning: Removed 1758 rows containing missing values ('geom_point()').
```


Observations by latitude over time (2019–2023)



Retrieve Elevation Information

```
coords <- data.frame(x=mivi_annotated$longitude,
                     y=mivi_annotated$latitude, ele_id=mivi_annotated$id)
# pipe to 'slice(1:100)' to get a subset for reducing retrieval time

# retrieve elevation from USGS (takes a while)
elevations <- get_elev_point(coords, prj=4326, src="epqs")

mivi_all <- mivi_all %>% left_join(elevations, by=join_by("id" == "ele_id")) %>%
  select(-elev_units, -geometry)

rm(coords, elevations)

mivi_annotated <- mivi_all %>% filter(!is.na(stage))
write.csv(mivi_all, file="./MIVI-PROCESSED.csv", na='')
```

Analysis!

```

# Note: returns Inf if there are none in the selection
first_fruit <- function(df) {
  df <- df %>% filter(stage == "Fruiting")
  if(nrow(df)==0) {return (Inf)}
  return (min(df$julian))
}

```

Latitude

```

get_lat_quants <- function(df, n) {
  # create groups
  df$group <- ntile(df$latitude, n)

  # calculate latitude variables for each group
  a <- df %>% group_by(group) %>% summarize(avglat=mean(latitude),
                                           minlat=min(latitude),
                                           maxlat=max(latitude))

  # first fruiting date in each group
  b <- df %>% group_by(group) %>% group_map(~first_fruit(.x))

  a <- bind_cols(a, do.call(rbind.data.frame, b)[,1], .name_repair = "unique_quiet") %>%
    mutate(firstfruit = ...5) %>% select(-...5)
  a <- remove_missing(a, finite=TRUE, na.rm=TRUE) # remove any Inf's


  return (a)
}

# Loop to determine best quantile amount for correlation
quants = data.frame()

for(i in 10:300) {
  # print(i)
  a <- get_lat_quants(mivi_annotated, i)
  quants <- rbind(quants, data.frame(i, cor(a$firstfruit, a$avglat)))
}
rm(i, a)

colnames(quants) <- c("n quantiles", "correlation")
plot(quants)

```



```
y <- which.min(quants$corr)
n <- quants[y,1] # select n with strongest correlation
paste0("n quantiles for best correlation is: ", n)
```

```
## [1] "n quantiles for best correlation is: 225"
```


```
rm(quants, y)

# Latitude linear model
data <- get_lat_quants(mivi_annotated, n)
model_lat <- lm(firstfruit~avglat, data=data)

# Plot linear model
print(
  ggplot(data, aes(avglat, firstfruit)) + geom_point() + geom_smooth(method='lm') +
    ylab("Julian day") + xlab("mean latitude") + labs(title="First Fruiting Day by Latitude")
)
```


```
## 'geom_smooth()' using formula = 'y ~ x'
```

First Fruiting Day by Latitude



```
# Q-Q residual plot  
res <- resid(model_lat)  
qqnorm(res)  
qqline(res)
```

Normal Q-Q Plot



```
paste0("Average absolute residual: ", format(mad(res), digits=6))
```

```
## [1] "Average absolute residual: 11.5295"
```

```
# Pearson's correlation test
```

```
cor.test(data$firstfruit, data$avglat, alternative="less")
```

```
##
## Pearson's product-moment correlation
##
## data: data$firstfruit and data$avglat
## t = -10.748, df = 221, p-value < 2.2e-16
## alternative hypothesis: true correlation is less than 0
## 95 percent confidence interval:
## -1.000000 -0.508346
## sample estimates:
## cor
## -0.5858954
```

```
correlation_matrix(data, use="lower")
```

```
##          group      avglat      minlat      maxlat      firstfruit
## group    " 1.000  " ""      ""        ""          ""
## avglat    " 0.980***" " 1.000  " ""      ""          ""
```

```
## minlat      " 0.979***" " 1.000***" " 1.000    " ""      ""
## maxlat      " 0.981***" " 1.000***" " 0.999***" " 1.000    " ""
## firstfruit  "-0.584***" "-0.586***" "-0.585***" "-0.585***" " 1.000    "

# kable(correlation_matrix(data, use="lower"), booktabs=TRUE, format="latex")
# kable(correlation_matrix(data, use="lower"), booktabs=TRUE)

rm(data, model_lat, res)
```

Elevation

```
get_ele_quants <- function(df, n) {
  # Create groups
  df$group <- ntile(mivi_annotated$elevation, n)

  # mean lat for each group
  a <- df %>% group_by(group) %>% summarize(avgele=mean(elevation))

  # first fruiting date in each group
  b <- df %>% group_by(group) %>% group_map(~first_fruit(.x))


  a <- bind_cols(a, do.call(rbind.data.frame, b)[,1], .name_repair = "unique_quiet") %>%
    mutate(firstfruit = ...3) %>% select(-...3)
  a <- remove_missing(a, finite=TRUE, na.rm=TRUE) # remove any Inf's

  return (a)
}

# Loop to determine best quantile amount for correlation
quants = data.frame()

for(i in 10:300) {
  # print(i)
  a <- get_ele_quants(mivi_annotated, i)
  quants <- rbind(quants, data.frame(i, cor(a$firstfruit, a$avgele)))
}
rm(i, a)

colnames(quants) <- c("n quantiles", "correlation")
plot(quants)
```



```
y <- which.min(quants$corr)
n <- quants[y,1] # select n with strongest correlation
paste0("n quantiles for best correlation is: ", n)
```

```
## [1] "n quantiles for best correlation is: 272"
```

```
rm(quants, y)
```

```
# Elevation linear model
```

```
data = get_ele_quants(mivi_annotated, n)
```


```
model_ele <- lm(firstfruit~avgele, data=data)
```

```
# Plot linear model
```

```
ggplot(data, aes(avgele, firstfruit)) + geom_point() + geom_smooth(method='lm') +
  ylab("Julian day") + xlab("mean elevation") + labs(title="First Fruiting Day by Elevation")
```


```
## 'geom_smooth()' using formula = 'y ~ x'
```

First Fruiting Day by Elevation



```
# Q-Q residual plot  
res <- resid(model_ele)  
qqnorm(res)  
qqline(res)
```


Normal Q-Q Plot



```
paste0("Average absolute residual: ", format(mad(res), digits=6))
```

```
## [1] "Average absolute residual: 9.02279"
```

```
# Pearson's correlation test
```

```
cor.test(data$firstfruit, data$avgele, alternative="less")
```

```
##
```

```
## Pearson's product-moment correlation
```

```
##
```

```
## data: data$firstfruit and data$avgele
```

```
## t = -4.2576, df = 269, p-value = 1.429e-05
```

```
## alternative hypothesis: true correlation is less than 0
```

```
## 95 percent confidence interval:
```

```
## -1.0000000 -0.1550266
```

```
## sample estimates:
```

```
## cor
```

```
## -0.2512646
```

```
rm(data, model_ele, res)
```

Tables

```
# All observations by country
table1(~ place_country_name, data=mivi_all)
```

	Overall
	(N=14039)
place_country_name	
Canada	26 (0.2%)
United States	14013 (99.8%)

```
# All observations by state (includes Ontario)
table1(~ place_state_name, data=mivi_all)
```

	Overall
	(N=14039)
place_state_name	
Alabama	213 (1.5%)
Arkansas	160 (1.1%)
Connecticut	229 (1.6%)
Delaware	227 (1.6%)
District of Columbia	125 (0.9%)
Georgia	599 (4.3%)
Illinois	123 (0.9%)
Indiana	132 (0.9%)
Iowa	3 (0.0%)
Kentucky	350 (2.5%)
Louisiana	2 (0.0%)
Maine	4 (0.0%)
Maryland	1725 (12.3%)
Massachusetts	92 (0.7%)
Michigan	7 (0.0%)
Mississippi	131 (0.9%)
Missouri	56 (0.4%)
Nebraska	2 (0.0%)
New Jersey	1294 (9.2%)
New York	778 (5.5%)
North Carolina	2028 (14.4%)
Ohio	541 (3.9%)
Oklahoma	9 (0.1%)
Ontario	26 (0.2%)
Pennsylvania	1946 (13.9%)
Rhode Island	17 (0.1%)
South Carolina	246 (1.8%)
Tennessee	653 (4.7%)
Texas	1 (0.0%)
Vermont	15 (0.1%)
Virginia	1972 (14.0%)
West Virginia	333 (2.4%)

```
table1(~ latitude + longitude + elevation + julian + place_country_name | stage, data=mivi_all %>% muta
```

	Vegetation	Flowering	Fruiting	NA	Overall
	(N=4999)	(N=186)	(N=1580)	(N=7274)	(N=14039)
latitude					
Mean (SD)	38.0 (2.43)	39.2 (1.94)	38.9 (2.30)	38.5 (2.20)	38.4 (2.31)
Median [Min, Max]	38.8 [31.8, 44.0]	39.6 [32.6, 41.5]	39.3 [31.7, 43.5]	39.1 [32.2, 43.0]	39.0 [31.7, 44.0]
longitude					
Mean (SD)	-79.3 (4.33)	-77.6 (3.85)	-78.6 (4.40)	-79.0 (4.27)	-79.1 (4.31)
Median [Min, Max]	-78.4 [-97.7, -69.7]	-76.9 [-90.9, -72.9]	-77.5 [-95.8, -70.6]	-77.7 [-95.2, -70.8]	-77.9 [-97.7, -69.7]
elevation					
Mean (SD)	193 (197)	175 (197)	203 (211)	NA (NA)	195 (200)
Median [Min, Max]	132 [-0.850, 1720]	108 [0.400, 1010]	137 [0.400, 1600]	NA [NA, NA]	133 [-0.850, 1720]
Missing	144 (2.9%)	8 (4.3%)	41 (2.6%)	7274 (100%)	7467 (53.2%)
julian					
Mean (SD)	178 (47.9)	258 (11.6)	270 (17.5)	225 (45.5)	214 (53.2)
Median [Min, Max]	171 [60.0, 328]	257 [224, 285]	269 [207, 330]	229 [1.00, 365]	221 [1.00, 365]
place_country_name					
Canada	20 (0.4%)	0 (0%)	6 (0.4%)	0 (0%)	26 (0.2%)
United States	4979 (99.6%)	186 (100%)	1574 (99.6%)	7274 (100%)	14013 (99.8%)