

My SubTitle



date and time

Contents

A.1 Start	1
[1t] Run examples	1
[2t] Codespace	2
[3t] rvt-portable	3
[4t] System and uv	4
rvt-uv	4
A.2 Motivations	5
[1t] Background	5
[2t] Use Cases	6
A.3 FAQ	7
[1t] Contact	7
[2t] Licenses	7
[3t] <i>rvt</i> design and development	7
B.1 Overview	8
[1t] Summary	8
[2t] rvt docs	8
[2t] rvt API	9
[3t] Files/Folders	10
[5t] Framework	10
B.1 Framework	11
[1t] Install <i>rvt-framework</i>	11
C.1 Docs	11
[1t] Doc Files	11
[2t] Reports	12
D.2 Files	12
[1t] File Types	12
[2t] Reports	15
D.3 Folders	17
[1t] rvt Folders	17
D.4 Configuration Files	19
[1] Config Files	19
D.4 Example	19
[1] rvt file	19
D.1 Markup	21
[1t] API functions	21

[2t] rvt string	22
[3t] Tags and Commands	24
[4t] Folders	24
C.2 Line Tags	25
[1t] Line Tag Summary	25
[2t] Center text	26
[3t] Right justify text	26
[4t] Text math	26
[5t] LaTeX math	27
[6t] Endnote number	27
[7t] Glossary link	27
[8t] Section link	28
[9t] Doc link	28
[10t] URL link	29
[11t] Variable value	29
[12t] Equation number	29
[13t] Table number	30
[14t] Figure number	30
[15t] New Page	31
C.3 Block Tags	31
[1t] Block Tag Summary	31
[2t] Shell script	32
[3t] Indent text	32
[4t] Indent italic	33
[5t] Endnotes	33
[6t] Text	34
[7t] Topic	34
[8t] Box	35
[9t] Python	35
[10t] Markup block	36
[11t] Metadata	36
[12t] Layout block	37
[13t] End block	37
C.4 Commands	38
[1t] Command Summary	38
[2t] Shell file	39
[3t] Text file	39

[4t] Table file	40
[5t] Image file	41
[6t] Adjacent images	41
[7t] Valtable file	41
[8t] Define value	42
[9t] Assign value	43
[9t] Function value	43
[10t] Compare values	43
[11t] Python file	44
[12t] Markup file	44
[13t] Attach PDF	45
[14t] Publish doc	45
C.5 Run - rv.R	46
[1i] rv.R Markup	46
[2i] Block Tags	46
[3i] Commands	46
C.6 Insert - rv.I	46
[1i] rv.I Markup	46
[2i] Line Tags	46
[3i] Block Tags	47
[4i] Commands	47
C.7 Values - rv.V	47
[1i] rv.V Markup	47
[2i] Line Tags	48
[3i] Block Tags	48
[2i] Commands	48
C.8 Tool - rv.T	49
[1i] rv.T Markup	49
[2i] Block Tags	49
[3i] Commands	49
C.9 Doc - rv.D	49
[1i] rv.D Markup	49
[2i] Block Tags	49
[3i] Commands	49
E.1 Collaboration	50
[1t] Overview	50
[2t] Open Models	50

[3t] Git and GitHub	51
[4t] VSCode	51
E.2 Public files	51
[1t] Overview	51
[2t] Public Folder	52
[3t] Example	53
E.3 Git	53
[1t] Git	53
E.4 GitHub Search	53
[1t] GitHub Global Search	53
[2t] GitHub Organization Search	53
F.1 Quick Ref	53
[1t] API	53
[2t] Line Tags	54
[3t] Block Tags	55
[4t] Commands	56
[5t] Folders	58
[6t] Python Requirements	59
[7t] VSCode Settings	60
A.2 Terms	65
[1t] rivt Terms	65
[2t] Python Terms	67
[3t] GitHub and VSCode Terms	67
Index	69



rivt is a highly extensible, open source program for writing and formatting engineering documents as text, HTML or PDF files (referred to as *rivt docs*). A *rivt doc* is generated from a *rivt* file (.py) that includes *rivt* markup and imports the [rivtlib](#) Python package. Multiple *rivt docs* may be organized and linked as a *rivt* report. This site is an example of an HTML *rivt report*.

An interface for finding public *rivt files* on *GitHub* is [here](#) and a repository of open source models and calculations, including *rivt*, is [here](#).

A.1 Start

[1t] Run examples

This section explains how to get started in editing and running *rivt file* examples. Examples can be run in the cloud or on a local computer. In both cases editing is typically carried out in an IDE.

For a general overview of *rivt* start [here](#).


The three methods for installing and running *rivt* are:

1. *rivt-Codespace* in the cloud is described [here](#)
2. *rivt-portable* installation on Windows is described [here](#)
3. System installation with or without *uv* is described [here](#)

rivt-portable is recommended for Windows users unfamiliar with Python. *rivt-Codespace* is recommended when local installation is not practical or work is shared with teams. System installations are recommended for the most general and flexible implementation.

A typical **IDE** layout can be viewed at [Codesandbox](#).

[2t] Codespace



This explorable browser example gives a feel for a rvt file (left panel) and text doc (right panel). Docs (output files) may be downloaded from the file explorer (far left panel) including the text, pdf and html reports.

[2t] Codespace

VSCoDe can be run locally or in the cloud. For local installation see [5t] Framework.


The cloud version is a [Codespace](#). A rvt Codespace is a VSCoDe cloud environment with *rvt* extensions for editing and running *rvt* files. It can be forked (copied) into a personal Github account. Github setup is described [here](#).

A rvt Codespace can be forked from [this repository](#) by following the steps below. Example rvt files are included.

Fork a rvt Codespace

1. Click the Fork button in the upper right corner.
This creates a copy of the repository in your GitHub account.
2. Switch to your GitHub account and open the forked repository
3. Click the green Code button
4. Select the Codespaces tab
5. Click the rvt-codespace-examples option.
6. This creates a Codespace environment in your GitHub account and opens the repository in the online VSCoDe IDE. The environment includes the rvt packages and extensions needed to run and publish rvt docs and files.

[3t] rvt-portable



Local installation methods

1. Windows portable zip folder ([3t] rvt-portable) *rvt-portable* is recommended for Windows users unfamiliar with Python.
2. System Python ([4t] System and uv) with or without uv manager (rvt-uv)

[3t] rvt-portable

A *rvt-portable* installation is recommended for Windows users unfamiliar with Python. *rvt-portable* is a zip file :

```
win64-rvt-portable-n.n.n[an].zip
```

where n is a number representing the major, minor and patch release number. An *an* appended to the version is an *alpha* release where users should expect that features are missing and *rvt markup* syntax may change in the future. Zip file contents must be unzipped into a directory with read-write access - typically the users home folder or a flash drive.

The zipped and unzipped file sizes include the following contents and are approximately 1GB and 2GB respectively:

```
release: rvt-portable-1.0.0a4.zip
```

1. Python 3.14 with rvt packages
2. VSCode 1.109 with rvt extensions

[4t] System and uv

3. `rivt-1.1.0a4`
4. Example `rivt` files

Releases may be download from the [GitHub repository](#).

The primary advantages of *rivt-portable* are

1. simplified installation
2. package integration
3. isolation from system files.

After unzipping, VSCode and examples are started with a single shortcut.

The primary disadvantages of *rivt-portable* are that *rivt* packages and extensions must be updated by updating the zip file as a whole, and it is more difficult to integrate with other Python programs.

[4t] System and uv

rivt may be installed at the system level.

1. Install Python using [Python installers](#) The minimum version required by *rivt* is Python 3.14.
2. Install *rivtlib* and dependencies using `pip`

```
pip install rivtlib
```

A list of the dependencies is here.

rivt-uv

Rather than installing *rivtlib* at the system level, it can be installed in an isolated environment using the [uv package manager](#). The primary advantage of *rivt-uv* is the simplicity of updating packages while keeping them isolated from the system Python.

rivt-uv installation is recommended for users with some familiarity with Python and programming.

Step 1. Install uv

Different methods for installing *uv* are described [here](#).

The recommended method for installing *uv* is from the command line:

Windows:

```
winget install --id=astral-sh.uv -e  
  
or  
  
powershell -ExecutionPolicy Bypass -c "irm https://astral.sh/uv/install.ps1 | iex
```

macOS and Linux:

```
curl -Lsf https://astral.sh/uv/install.sh | sh
```

Step 2. Create the rivt environment

After installing *uv*, download and run the following rivt install script. It installs an isolated *rivt environment* and example files in a folder named *rivt-examples* in the users *Home* directory.

Windows: `rivtuv.cmd`

OSX and Linux: `rivtuv.sh`

Step 3. Run the example program from Pyzo.

The *rivt environment* is activated by:

Windows:

```
./venv/Scripts/activate
```

macOS and Linux:

```
source venv/bin/activate
```

rivt includes the [Pyzo](#) IDE for editing and running examples. Typing the command *pyzo-example* from the environment root will load the example file *rv00-simple-doc.py* where it can be edited and run.

The example file can also be run from the command line with the command:

```
python -m rivt rv001-single-doc.py
```

The *uv* environment can be completely removed with the following commands.

```
uv deactivate
rmdir /s /q rivt-examples
uv cache clean
```

A.2 Motivations

[1t] Background

rivt is an open source software project that simplifies sharing and reuse of engineering documents. This has always been a challenge because the inclusion of text, images, tables, calculations, models and computer code required in engineering reports has led to development of incompatible, mutually exclusive software. Sharing and reuse has been restricted by design and terms of use of existing software. This includes:

- incompatible documents from different programs
- frequent software updates needed to maintain document access
- high update costs
- software limited to specific platforms
- limited document version control
- limited report generation features
- limited collaboration features

rivt is designed to address these limitations and function as a complement or replacement to existing software. The table below summarizes and compares limitations between different software programs.

Software Comparison

Program	Rep ¹	Ver ²	Txt ³	Comp ⁴	CP ⁵	Collab ⁶
Matlab	no	no	no	no	no	no
Mathcad	no	no	no	no	no	no
Mathematica	no	no	no	no	no	no
Cloud SaaS	limited	no	no	no	yes	limited
Excel	limited	no	no	yes	no	yes
Jupyter	no	no	no	yes	yes	yes
rivt	yes	yes	yes	yes	yes	yes

- 1 Report generation
- 2 Native version control
- 3 Plain text, readable input files
- 4 Forward and backward compatibility
- 5 Cross-platform
- 6 Collaboration support

[2t] Use Cases

The primary use case for *rivt* is producing engineering documents that lie between back of envelope calculations and sketches, and formal journal publications. In other words, it produces clear, formatted, organized documents that are easy to write and edit.

The second use case is when flexibility is needed to produce documents in a variety of formats including text, PDF or HTML.

A third use case is when documents need to interact with other software programs.

rivt files can function as a front and back end for:

1. software control
2. visualization
3. instrumentation

rivt docs can be used for:

1. internal communication
2. research documentation
3. government permits

4. technical reports
5. funding applications

Because *rivt* is compatible with collaborative tools it may be used for:

1. teaching
2. presentations
3. real time collaboration

A.3 FAQ

[1t] Contact

support@rivt.info

[2t] Licenses

What is the open source license for *rivtlib*?

rivtlib is distributed under the [MIT open source license](#).

Which open source licenses applies to *rivt*?

The Python packages that are part of the *rivt project* are distributed primarily under the BSD, Appache and MIT open source licenses. Python itself is distributed under the Python Software Foundation License (PSFL).

Which open source licenses apply to *rivt files*?

The open source license for a public *rivt* file is specified in the `__[[Metadata]]` block tag. The default license is the MIT license.

Which open source licenses apply to the *rivt framework*?

VSCode - Visual Studio Code uses a proprietary Microsoft license for the compiled product, allowing free use for development, testing and commercial applications. The source code ("Code - OSS") is under the MIT license. You can use VS Code freely for any purpose, including commercial projects, but some bundled extensions or specialized components (connections to the Microsoft servers and marketplace) may have different terms. Most extentions in the Marketplace use the MIT license.

VSCodium is a fully open source alternative that removes Microsoft's proprietary components and built-in telemetry. However its extension marketplace is less complete.

LaTeX - LaTeX is released under the LaTeX Project Public License (LPPL) for LaTeX components and MIT and BSD variants for many core utilities and packages.

QCAD - The QCAD source code is distributed under the open source license GPLv3 with exceptions to allow proprietary extensions.

Git - The Git software is released under the GNU General Public License Version 2.0 (GPLv2).

[3t] *rivt* design and development

What is the *rivt* release schedule?

1.0.x bug releases are issued as needed.

1.x.0 minor releases are planned monthly following the release of version 1.0.0

B.1 Overview

X.0.0. major releases will have backward compatibility. See [past releases](#) and [changelog](#) .

What are the programs and libraries used to build *rivt*?

The *rivt project* uses dozens of Python libraries (see [6t] Python Requirements):

- numpy, sympy and related scientific computing libraries
- docutils and related text processing libraries
- Reportlab, rst2pdf and related PDF generation libraries
- Sphinx, Pydata and related HTML libraries

The *rivt framework* uses the following open source and free programs:

- [VSCode](#) for editing
- [LaTeX](#) for PDF generation
- [QCAD](#) for diagramming
- [Git](#) for document sharing and version control

B.1 Overview


[1t] Summary

rivt is an open source Python project that imports the [rivtlib Python package](#) and dependencies ([6t] Python Requirements). A *rivt file* publishes a formatted *rivt doc* as a text, PDF or HTML file. A *rivt file* is a Python file (.py) that imports the rivtlib Python package and includes *rivt markup*. A collection of *rivt docs* may be assembled into a *rivt report*.

rivt files are generally edited and run in an IDE. The lightweight [Pyzo](#) IDE is installed with rivtlib. The [VSCode IDE](#) is a full featured IDE that is part of the *rivt framework* and included with [3t] *rivt-portable*.

rivt file examples are provided [here](#). An interface for searching *public rivt files* on [GitHub](#) is [here](#). A *public rivt file* is the parts of a *rivt file* the author chooses to share under an [Open Source license](#). *rivt* itself is distributed under the [MIT open source license](#). (see [2t] Licenses).

[2t] rivt docs



rivt Doc Processing

Each rvt file outputs a corresponding doc in the format specified in *rv.D()* API. A rvt file number has the form:

```
rvAnn-filename.py
```

where rv is a required prefix, A is an alphanumeric character and nn are two digit non-negative integers. The prefix is used to organize reports into divisions and subdivisions.

Corresponding rvt docs are output as:

```
rvAnn-filename.txt  
rvAnn-filename.pdf  
rvAnn-filename.html
```

A *rvt report* is organized using the *rvt file numbers*. If the rvt file names are:

```
rvA01-filename.py  
rv105-filename.py  
rv212-filename.py
```

the corresponding *doc numbers* in the would be:

- A.1 (division A, subdivision 1)
- 1.5 (division 1, subdivision 5)
- 2.12 (division 2, subdivision 12)

Docs are sorted alpha-numerically into divisions and subdivisions. A *doc number* corresponds to a report subdivision. Note that leading zeroes are dropped in the formatted output.

[2t] rvt API

The *rvt API* includes API functions, [3t] Tags and Commands and files. The API is designed to be:

- **lightweight**
rivt markup is made up of about 3 dozen tags and commands, and wraps reStructuredText.
- **flexible**
A *rvt file* produces a text, HTML or PDF *doc*. Multiple *docs* can be organized into a report.
- **extensible**
rivtlib is written in Python with direct access to thousands of Python packages.

An API function starts in the first column and takes a triple quoted rvt string (rS) containing rvt markup as the argument. The first line of a *rvt string* is a header substring, followed by a content substring indented 4 spaces for improved readability and section folding.

The *header substring* specifies the section title and other processing parameters. The content substring includes rvt markup and other arbitrary text. For further details see [here](#).

```
rv._("""Section Label | parameters  
    Content text that is
```

```
    indented four spaces.  
  
    ...  
  
    """)
```

[3t] Files/Folders

A rvt file is a Python plain text file (*.py*) that includes *rvt markup* and imports the rivtlib package and API into the *rv* namespace:

```
import rivtlib.rvapi as rv
```

rvt files are stored in a root folder designated with the prefix *rvt-*. Each *rvt file* and corresponding *rvt doc* has a prefix that is used to organize the report. The prefix has the form

```
rvANN-filename.py
```

where A is an alpha-numeric character used for organizing report divisions, and NN is a two digit number used to organize sub-divisions. The file name is used as the *doc* title unless overridden in *rv.D*. Use hyphens rather than spaces to separate words in a file name. They are replaced with spaces when a *doc* title is extracted.

The top level folder structure is shown below. A more detailed description of the folder structure is here.

[rvt-]Report-Label/	Report Folder
├── conf.py	configuration file
├── rv101-filename1.py	rvt file
├── rv102-filename2.py	rvt file
├── rv201-filename3.py	rvt file
├── rv202-filename4.py	rvt file
├── ...	
├── .vscode/	optional VSCode settings
├── _publish/	published docs and reports
├── _rstdocs/	restructured text files
├── _shared/	public rvt files
├── _stored/	stored files
├── Src/	author source files
└── README.txt	searchable text report

[5t] Framework

The *rvt framework* includes separate programs that provide additional editing , formatting, version control, and diagramming tools.

Purpose	Link
Editing	VSCode
Editing Extensions	[7t] VSCode Settings

Purpose	Link
Added Formatting	LaTeX
Version Control	Git
2D Diagramming	QCAD
3D Diagramming	FreeCad

B.1 Framework

[1t] Install *rivt-framework*

The *rivt framework* includes separate programs that provide additional editing , formatting, version control, and diagramming tools.

Purpose	Link
Editing	VSCode
Editing Extensions	[7t] VSCode Settings
Added Formatting	LaTeX
Version Control	Git
2D Diagramming	QCAD
3D Diagramming	FreeCad

The *rivt framework* includes installation of the following programs:

1. [VSCode](#) and [VSCode extensions](#). *rivt* extensions and snippets are here.
2. [Git](#) and set up a [GitHub](#)
3. [LaTeX](#)
4. [FreeCad](#)

C.1 Docs

[1t] Doc Files

A *rivt doc* is the output of a *rivt file* processed by *rivtlib*. Each *rivt file* outputs a corresponding formatted doc with a *doc number* derived from the *rivt file* name. A *rivt report* is organized using the *rivt doc numbers*. The *rivt file* name has the form:

```
rvAnn - filename.py
```

where *rv* is a required prefix, *A* is an alphanumeric character and *nn* are non-negative integers.

```
import rivtlib.rvapi as rv

# rv public=True
```

If the *rv* file names are:

```
rvA01-filename.py
rv105-filename.py
rv212-filename.py
```

the corresponding *doc* references would be:

```
doc file names
rvA01-filename.type
rv105-filename.type
rv212-filename.type

doc references
A.1 (division A, subdivision 1)
1.5 (division 1, subdivision 5)
2.12 (division 2, subdivision 12)
```

Note that leading zeroes are dropped. *Docs* are sorted alpha-numerically into divisions and subdivisions in the *report*.

[2t] Reports

Each *rv* file outputs a corresponding *doc* written to the *publish* folder in the specified format. A *rv* report is assembled from a set of *docs* using the *rvt-report.py* script. The *report folder structure* is described in [1t] *rv* Folders.

Docs may be output as text, HTML or PDF. PDF and HTML *docs* are produced using the *rst2pdf* and *Sphinx* Python libraries.

Reports are assembled from *docs* using the *rvt-report.py* script in the *Src/Tools* folder. A single *doc* that is not part of a report does not require running the *rvt-report.py* script.

D.2 Files

[1t] File Types

rv file

rv files are written by the author. Each *rv* file has a prefix that specifies the division label and subdivision number of the published *doc*. *rv* reports are assembled using *doc numbers* that organize the report into divisions and subdivisions. The *d*subdivision** name is taken from the name that follows the *doc number*. It may be overridden in the *API Meta* function. *Division* names are specified in the report script.

The *doc number* prefix includes a single digit capital alphanumeric division label *D*, followed by a two digit subdivision number *ss*. For example:

```
[rvDss-]file-name.py  
rvD02-Beam-Loads.py
```

where the default doc name is “Beam Loads” in subdivision 2 of division C. Hyphens are stripped from file name.

Note:

The following files are read and written by *rivtlib* when processing a *rivt file*. Files are labeled by origin and folder.

origin: author input

folder: *rivt-report-folder-name*

Refer to markup for *command* details.

Run file

A *run file* is a shell or command script executed using the | RUN | command.

origin: author input

folder: *src/* - or a user created subfolder of */src*

API function: *rv.R*

Insert file

An *insert file* is an image, table or text file executed using the | IMAGE | , | TABLE | , or | TEXT | command.

origin: author input

folder: *src/* - or a user created subfolder of */src*

API function: *rv.I*

Value file

A *value file* is a *csv* file that defines variable values. It is imported using the | VALUE | command. Values defined by equations and a `[[VALUES]]` block are written to a file with the name composed of the *doc* and *section* number. The file may be read by other *rivt files*.

Read

origin: author input

folder: *src/Values* - or a user created subfolder of */src*

API function: *rv.V*

Write

origin: program output

folder: *src/Values*

API function: *rv.V*

Tool file

Tool files can be executed by | PYTHON | , | HTML | , | RST | or | LATEX | commands. They may be used for analysis and generation of text, tables, images and other formatted content. Executing a tool file may:

- define functions and classes for use in the *rivt file*
- generate images, tables and text for inclusion in the *doc*
- insert markup text into the *doc*

Read

origin: author input

folder: *src/Tools* or a user created subfolder of */src*

API function: *rv.T*

Write

origin: program output

folder: *src/Tools*

API function: *rv.T*

Doc file

Each *rivt file* outputs a *doc file* with the same *doc name and number* and the selected *doc type* suffix. *Doc* files are written to the *publish folder* as text, PDF or HTML files using | PUBLISH | command.

PDF files may be prepended or appended to the *doc* using the | APPEND | command.

origin: program output

folder: *src/* - or a user created subfolder of */src*

API function: *rv.D*

Report file

A *report file* is generated by the Python *report script* and is written to the designated *publish subfolder*. The *report file name* is taken from the *report folder name* unless specified in the *rivt-report.py* script.

origin: program output

folder: */publish/* subfolder

Report script

The *report script* is a Python file that assembles the *report*. It specifies the *docs* that should be included, whether the *rivt files* should be re-executed and other format settings.

origin: author input

folder: */publish*

Public rvt file

origin: program output

folder: */public*

A public rvt file is a copy of the *rvt file* that includes all of the sections marked as *public* in the *header*. It has the same name as the *rvt file* with an added hyphen between “rv” and the docnumber e.g. *rv-Dss-filename.py*

Log file

Log files are written to the *log folder*. They include:

- a backup of the rvt file
- a file listing the execution steps when processing the *rvt file*
- a file listing each API function call with the header.

origin: program output

folder: */logs*

[2t] Reports

A report is assembled from multiple *docs* organized by division and subdivision numbers. Each *doc* is a subdivision of a *report*. A typical workflow for writing *reports* is to start with a similar *report* and edit the *rvt files* and *report script* that produces the *report*.

The Python *report script* includes settings that specify assembly parameters and override defaults. These include:

- *Docs* to be included in the report
- Division names
- recompiling *docs*
- report cover page and title

provides the option to either regenerate all *docs* or to assemble the report from previously generated *docs*. Most aspects of the *report* appearance are determined at when generating *docs*.

An example script is shown below.

```
#!/ python

from rivtlib.rvreport import * # noqa: F403

""" generate a rvt report

Sample report generating and config file.

Run this Python file to generate a rvt report. The report generating file
```

must located in /publish/subfolder where subfolder is the doc type. The report output file name is the report title. It is written to the same folder as the report script. Duplicate report file names are incremented.

A flag determines whether the report is assembled from existing doc files or whether docs are regenerated prior to assembly. If a rivt or doc file is specified for inclusion and not found a warning is given but the report is still assembled.

A rivt report is a compilation of rivt docs organized into divisions and subdivisions. rivt doc numbers define the organization. Default titles for subdivisions are generated by stripping the doc number from the file name and replacing hyphens with spaces. The default titles may be overridden in rv.M for each rivt file.

See src/styles/rivt.ini for additional settings

```

"""
# =====
# report type
# =====
rptype = "pdf" # report type [html; pdf; pdftex; text]
rvrun = False # regenerate docs [True; False]

# =====
# report cover settings
# =====
# cover pages are located in /src
rptitle = "Solar Canopy Calculations"
rpstitle = "Larkspur, Ca"
rpauthor = "rhh"
rpdate = "<datetime>"
rptoc = True # add table of contents, "" to omit
rpscover = "/publish/cover1.pdf" # cover page, "" to omit

# =====
# include docs
# =====
# include these divisions in report
divlist = [[dv01, "Codes and Loads"],
            [dv02, "Frame"],
            [dv03, "Foundation"]]
# include these docs in report
# doc label is for reference only, may be empty string
doclist = [[rv101, "Codes"],
            [rv102, "Loads"],
            [rv201, "Frame"],
            [rv202, "Solar"],
            [rv301, "Foundation"],
            [rv302, "Walls"]]

genreport() # noqa: F405

```

D.3 Folders

[1t] rvt Folders

A *rvt* report is assembled from a set of *docs*. Reports are organized using *doc numbers*. If the *rvt* file names are:

```
rvA01-filename.py
rv105-filename.py
```

The *report numbers* used in the published report would be:

```
A.1
1.5
2.12
```

where leading zeroes are dropped and *docs* are sorted alpha-numerically into divisions and subdivisions in the *report*.

Reports are organized under a single root report folder with the prefix *rvt-*. *rvt* files are stored in the root folder and *rvt markup* file paths are relative to the root. Resource files are stored in five subfolders:

_public

Includes *rvt* files written by *rvtlib* intended for upload to a public repository. The prefix *rvAnn-* is changed to *rvAnn_* to avoid confusion with private files.

_publish

Includes formatted *docs* and *reports* written by *rvtlib*.

_stored

Includes output files written by *rvtlib* including *logs*, *values*, *hidden sections*, *metadata* and *reports*

_rstdocs

Includes restructured *docs* written by *rvtlib*.

Src Includes author provided content and formatting for *docs*, *reports*.

An example report folder structure is shown in the following section.

Folder Names

Top Level Folders

[rvt-]Report-Label/	Report Folder
├── [conf.py]	configuration file
├── [rv101-]filename1.py	rvt file
├── [rv102-]filename2.py	rvt file
├── [rv201-]filename3.py	rvt file
├── [rv202-]filename4.py	rvt file
├── ...	
├── .vscode/	optional VSCode settings
├── [_publish]/	published docs and reports
├── [_rstdocs]/	restructured text files
├── [_shared]/	public rvt files
├── [_stored]/	stored files

<pre>└─ [Src]/ └─ README.txt</pre>	<pre>source files searchable text report</pre>
------------------------------------	--

Expanded Folders

	Report Folder Name
[rivt-]Report-Label/	
└─ .vscode/	optional VSCode settings
└─ [conf.py]	configuration file
└─ [rv101-]filename1.py	rivt file
└─ [rv102-]filename2.py	rivt file
└─ [rv201-]filename3.py	rivt file
└─ [rv202-]filename4.py	rivt file
└─ [_publish]/	published docs and reports
└─ └─ [docs]/	html docs
└─ └─ └─ _images/	
└─ └─ └─ _sources/	
└─ └─ └─ _static/	
└─ └─ └─ process folders/	
└─ └─ └─ site folders/	
└─ └─ └─ rv101-filename1.html	
└─ └─ └─ rv102-filename2.html	
└─ └─ └─ rv201-filename3.html	
└─ └─ └─ rv202-filename4.html	
└─ └─ [pdfdocs]/	pdf docs
└─ └─ └─ process folders/	
└─ └─ └─ rv101-filename1.pdf	
└─ └─ └─ rv102-filename1.pdf	
└─ └─ └─ rv201-filename3.pdf	
└─ └─ └─ rv202-filename4.pdf	
└─ └─ [txtdocs]/	text docs
└─ └─ └─ rv101-filename1.txt	
└─ └─ └─ rv102-filename1.txt	
└─ └─ └─ rv201-filename3.txt	
└─ └─ └─ rv202-filename4.txt	
└─ [_rstdocs]/	restructured text files
└─ └─ _downloads/	
└─ └─ _static/	
└─ └─ _locale/	
└─ └─ _templates/	
└─ └─ rv101-filename1.rst	
└─ └─ rv102-filename2.rst	
└─ └─ rv201-filename3.rst	
└─ └─ rv202-filename4.rst	
└─ [_shared]/	public rivt files
└─ └─ rv-101-filename1.py	
└─ └─ rv-102-filename1.py	
└─ └─ rv-201-filename3.py	
└─ └─ rv-202-filename4.py	
└─ [_stored]/	stored files genereatd by rivt
└─ └─ [Logs]/	log files
└─ └─ └─ rv101-log.txt	

└─ rv102-log.txt	
└─ [Sect]/	sections
└─ rv202-5d.txt	
└─ rv103-4t.txt	
└─ rv301-2r.txt	
└─ [Temp]/	temp files
└─ rv101-label3.tex	
└─ [Vals]/	stored value files
└─ v101-2.csv	
└─ v102-3.csv	
└─ [Src]	source files from author
└─ data/	author created subfolder
└─ data1.csv	
└─ opensees1.txt	
└─ conc-vals.csv	
└─ image/	author created subfolder
└─ fig1.png	
└─ fig2.jpg	
└─ [Run]/	OS commands
└─ run1_win.cmd	windows command file
└─ run1_linux.sh	linux command file
└─ [Tools]/	scripts and functions
└─ rivt-report.py	report generating script
└─ new-units.py	define new units
└─ coverpage.rst	cover page template
└─ logoname.png	cover page logo
└─ plot.py	functions
└─ loads.py	functions
└─ [Vals]/	value files
└─ steel-vals.csv	
└─ plastic-vals.csv	
└─ README.txt	searchable text report

D.4 Configuration Files

[1] Config Files

D.4 Example

[1] rivt file

This is a small rivt file that publishes a single *doc*. It has 4 API functions - two of them are published. The output is written to the terminal.

```
#!/python
import rivtlib.rvapi as rv

# rv singledoc: True
```

```

# %% loads
rv.I("""Load Combinations

ASCE 7-05 Load Effects _[T]
=====
Equation No.    Load Combination
=====
16-1            1.4(D+F)
16-2            1.2(D+F+T) + 1.6(L+H) + 0.5(Lr or S or R)
16-3            1.2(D+F+T) + 1.6(Lr or S or R) + (f1L or 0.8W)
=====

| IMAGE | beam.png | Beam Geometry, .65, num

Bending Stress Formula _[E]
o1 = M1 / S1 _[M]

""")
# %% values
rv.V("""Loads and Geometry

Beam Loads _[T]
D_1 =: 3.8*psf | psf, kPA, 2 | joists DL
D_2 =: 2.1*psf | psf, kPA, 2 | plywood DL
D_3 =: 10.0*psf | psf, kPA, 2 | partitions DL
D_4 =: 2*0.5*klf | klf, kN_m, 2 | fixed machinery DL
L_1 =: 40*psf | psf, kPA, 2 | ASCE7-05 LL

| VALTABLE | beam1-v.csv | Beam Geometry, 0:0, num

Uniform Distributed Loads
dl_1 <=: 1.2 * (W_1 * (D_1 + D_2 + D_3) + D_4) | klf, kN_m, 2 | dead load : ASCE7-05 2.3.2 _[E]

ll_1 <=: 1.6 * W_1 * L_1 | klf, kN_m, 2 | live load : ASCE7-05 2.3.2 _[E]

omega_1 <=: dl_1 + ll_1 | klf, kN_m, 2 | total load : ASCE7-05 2.3.2 _[E]

""")
# %% section properties
rv.V("""Beam Section Properties

| PYTHON | sectprop.py | nodocstring

section_1 <=: rectsect(10*inch, 18*inch) | in3, cm3, 2 | function: rect sect modulus _[E]

inertia_1 <=: rectinertia(10*inch, 18*inch) | in4, cm4, 1 | function: rect moment inertia _[E]

""")
# %% force
rv.V("""Force and Stress

m_1 <=: omega_1 * S_1**2 / 8 | ftkips, mkN, 2 | mid-span UDL moment _[E]

fb_1 <=: m_1 / section_1 | psi, MPA, 1 | bending stress _[E]

fb_1 < 10*ksi | ok, not ok, blue, red, right _[E]

""")
# %% tool

```

```

rv.T("""Metadata

_ [[PYTHON]]
rv_metaD = {
  "authors": "rholland",
  "version": "0.7.2",
  "email": "rod.h.holland@gmail.com",
  "repo": "https://github.com/rivt-info/rivt-single-doc",
  "license": "https://opensource.org/licenses/mit/",
  "fork1": ["author", "version", "email", "repo"],
  "fork2": [],
}
_ [[END]]

""")
# %% doc
rv.D("""Publish Doc

_ [[LAYOUT]]
  logopathP: logo.png
  pdfheaderL: [docnameS, pageS, totalpageS]
  footerL: [logo0, date0, time0, filenameS, versionS]
_ [[END]]

| PUBLISH | rivt | rst2pdf

""")

```

D.1 Markup

[1t] API functions

rivt has seven API functions. The name *rivt* is an acronym taken from the four functions that process content. The remaining three functions are used for document generation and debugging.

API Function	Name	Purpose
rv.R (rS)	Run	Run shell commands
rv.I (rS)	Insert	Insert static sources
rv.V (rS)	Values	Calculate values
rv.T (rS)	Tools	Python and markup scripts
rv.D (rS)	Doc	Publish docs
rv.S (rS)	Skip	Skip section (comments and debugging)
rv.X (rS)	Exit	Exit rivt (debugging)

[2t] rvt string

API functions define doc sections. If interactive IDEs like *VSCode* or *Spyder* are used to edit and run *rvt files*, functions can be processed individually as cells by using the standard notebook hash notation:

```
# %% optional label
rv.API("""rvt string""")
```

[2t] rvt string

Each API function takes a triple quoted rvt string argument composed of a line header substring line followed by a multiple-line content substring.

The *header substring* defines section processing parameters. The *content substring* includes rvt markup and is indented four spaces for improved readability and navigation (e.g. section folding).

Header substring

The header substring starts with a *section label*, used as the section title, followed by a vertical bar and three comma separated *section parameters* that override default behavior.

```
rv._("""Section Label | doc;stored, private;public, section;merge
    Content substring indented 4 spaces
    ...
    """)
```

The parameters include the following, in any order:

private/public

Determines whether the API section text is copied to the the *Public* folder *rvt file* for sharing.

doc/stored

Determines whether the *rvt string* is formatted and printed in the doc, or just annotated in the doc and written to a file in the *Stored* folder for optional inclusion as an appendix.

section/merge

Determines whether the API starts a new *doc* section or is merged into the previous section.

Default settings in the *header substring* do not need to be specified. The default setting for each API is listed first (in bold) in the table below. The default privacy settings for all sections in a rvt file may be reversed by including the *public comment setting* immediately following the *rivlib import statement*. Individual sections may still be set as private in the header substring.

```
import rivtlib.rvapi as rv
# rv public=True
```

API	private; public	doc; stored	section; merge
rv.R	private ; public	stored ; doc	merge ; section
rv.l	private ; public	doc ; stored	section ; merge

API	private; public	doc; stored	section; merge
rv.V	private ; public	doc ; stored	section ; merge
rv.T	private ; public	stored ; doc	merge ; section
rv.S	private ; public	stored	merge
rv.D	public	stored	merge
rv.X	•	•	•

Examples of *header substring* settings are shown below.

- An example with explicit defaults (they do not have to be declared).

```
# This
rv.I("""A New Section | private, doc, section
    Content text
    ...
    """)
# is equivalent to:
rv.I("""A New Section
    Content text
    ...
    """)
```

- An example that merges a section into the previous section.

```
rv.I("""A Merged Section | merge
    Content text
    ...
    """)
```

Content substring

The content substring is indented four spaces for legibility and code folding. It includes line tags, block tags and commands along with text.

[3t] Tags and Commands

```
rv._( ""Section Label
    Content text indented 4 spaces.
    ...
    "" )
```

Content is converted line by line into formatted text and [RestructuredText](#), and then further processed into HTML or PDF. If a line does not contain a *command* or *tag* it is passed through as is, which allows for the *Insert* function (rv.I) including some *restructured text* directly i.e. surrounding words with * or ** will format a word as italic or bold respectively.

In addition block tags in the *Tools function* (rv.T) directly supports processing HTML, LaTeX and reStructuredText scripts.

[3t] Tags and Commands

Line Tags

A line tag formats a line of text and is denoted with a single **_[[LETTER]]**, placed at or near the end of the line, depending on the tag.

Block Tags

A block tag formats a block of text and begins with **_[[TAGNAME]]** and terminates with **_[[END]]**.

Commands

rv.t commands read and write external files. They typically start in the first column with a vertical bar (|) followed by the command name, file path, and parameters.

The exceptions are the definition (**==:**), assignment (**<=:**), function (**:=:**) and compare (**<>**) commands that are used to define, assign and compare values.

```
| COMMAND | relative path | parameters
```

File paths are specified relative to the *rv.t root folder*. The *rv.t report* folder structure is described here.

If the path is omitted the default path for each command is applied. If the *singledoc* parameter is set, the *resource files* and *docs* are stored in the *rv.t root folder*.

Tag and Command syntax for each API type is defined and described using the following format:

[4t] Folders

The top level folder structure is shown below. A more detailed description of the folder structure is here.

Top Level Folders

```

[rvt-]Report-Label/
├── [conf.py]           Report Folder
│                       configuration file
├── [rv101-]filename1.py rvt file
├── [rv102-]filename2.py rvt file
├── [rv201-]filename3.py rvt file
├── [rv202-]filename4.py rvt file
├── ...
├── .vscode/           optional VSCode settings
├── [_publish]/        published docs and reports
├── [_rstdocs]/        restructured text files
├── [_shared]/         public rvt files
├── [_stored]/         stored files
├── [Src]/             source files
└── README.txt         searchable text report

```

C.2 Line Tags

[1t] Line Tag Summary

Format a line of text

API Scope	Line Tag	Description
rv.l	text _[C]	[2t] Center text
rv.l	text _[R]	[3t] Right justify text
rv.l	text math _[M]	[4t] Text math
rv.l	LaTeX math _[L]	[5t] LaTeX math
rv.l	text _[#] text	[6t] Endnote number
rv.l	text _[G] glossary term text	[7t] Glossary link
rv.l	text _[S] label, section text	[8t] Section link
rv.l	text _[D] label, file name text	[9t] Doc link
rv.l	text _[U] label, url text	[10t] URL link
rv.V, l	text _[V] var_name text	[11t] Variable value
rv.V, l	text _[E]	[12t] Equation number
rv.V, l	title _[T]	[13t] Table number
rv.V, l	caption _[F]	[14t] Figure number
rv.V, l	_[P]	[15t] New Page
rv.V, l	## text	nonprinting comment

[2t] Center text

Center line of text within the page margins.

`_[C]`

Syntax:

`text _[C]`

Example:

`This text will be centered. _[C]`

API Scope	Insert
Doc Types	text, PDF, HTML

[3t] Right justify text

Right justify line of text within the page margins.

`_[R]`

Syntax:

`text _[R]`

Example:

`This text will be right justified _[R]`

API Scope	Insert
Doc Types	text, PDF, HTML

[4t] Text math

Format math expression into text.

`_[M]`

Syntax:

`text math expression _[M]`

Example:

`f(x,y) = sin(x)**2 + y/5 _[M]`

[3t] Tags and Commands

API Scope	Insert
Doc Types	text, PDF, HTML

[5t] LaTeX math

Format LaTeX math expression.

`_[L]`

Syntax:
LaTeX math expression `_[L]`

Example:
`\frac{1}{\sqrt{x}}` `_[L]`

API Scope	Insert
Doc Types	PDF, HTML

[6t] Endnote number

Assign endnote number to the text in order of processing. Endnotes are defined with the block tag `_[[ENDNOTE]]` and are listed at the end of the *doc*.

`_[#]`

Syntax:
text `_[#]` more text

Example:
This is a sentence with an endnote `_[#]` tag.

API Scope	Insert
Doc Types	text, PDF, HTML

[7t] Glossary link

Link a term to the glossary.

`_[G]`

Syntax:

text `_[G]` glossary term

Example:

A definition of `_[G]` namespace
is provided in the glossary.

API Scope	Insert
Doc Types	PDF, HTML

[8t] Section link

Create a link to the section label defined in the API header with optional link text. If the text is omitted the section label is used for the link.

`_[S]`

Syntax:

text `_[S]` link text, section title

Example:

This creates a link to `_[S]` Section Title, actual section label which provides more detail.

API Scope	Insert
Doc Types	PDF, HTML

[9t] Doc link

Link to a *doc* in a *report* with an optional link text. If the link text is omitted the *doc* title will be inserted as the link term.

`_[D]`

Syntax:

text `_[D]` text, rivt_file

Example:

This is a link to `_[D]` rv101-filename1
for reference.

API Scope	Insert
Doc Types	PDF, HTML

[10t] URL link

Link to a an external site with optional link text. If the link text is omitted the url will be inserted as the link term.

`_[U]`

Syntax:

```
text _[U] link label ,external url
```

Example:

```
text _[U] github, https://www.github.com
```

API Scope	Insert
Doc Types	PDF, HTML

[11t] Variable value

Insert the value of var_name `_[V]` in the sentence.

`_[V]`

Syntax:

```
text var_name _[V] more text
```

Example:

```
The value of my_var is my_var _[V].
```

API Scope	Insert, Values
Doc Types	text, PDF, HTML

[12t] Equation number

Assign equation number to a line of text.

`_[E]`

Syntax:

`math text or label _[E]`

`assignment command _[E]`

Example:

`3x * 4/(1+n) _[E]`

`x <= 3*IN + 4.1*FT | inch, cm, 2 | example 1 _[E]`

API Scope	Insert, Values
Doc Types	text, PDF, HTML

[13t] Table number

`_[T]`

Syntax:

`Table Title _[T]`

Example:

`A New Table _[T]`

API Scope	Insert, Values
Doc Types	text, PDF, HTML

[14t] Figure number

`_[F]`

Syntax:

`Figure caption _[F]`

Example:

`Stress Distribution _[F]`

API Scope	Insert, Values
Doc Types	text, PDF, HTML

[15t] New Page`_[P]`

Syntax:

`text _[P]`

Example:

Preceded by text or stand alone. `_[P]``_[P]`

API Scope	Insert, Values
Doc Types	text, PDF, HTML

C.3 Block Tags**[1t]** Block Tag Summary**Format blocks of text**

API Scope	Block Tag	Description
rv.R	<code>_[[SHELL]]</code> process parameters	[2t] Shell script
rv.l	<code>_[[INDENT]]</code> spaces (4 default)	[3t] Indent text
rv.l	<code>_[[ITALIC]]</code> spaces (4 default)	[4t] Indent italic
rv.l	<code>_[[ENDNOTES]]</code> optional label	[5t] Endnotes
rv.l	<code>_[[TEXT]]</code> optional language	[6t] Text
rv.l	<code>_[[TOPIC]]</code> topic	[7t] Topic
rv.l	<code>_[[BOX]]</code> label	[8t] Box
rv.V,T	<code>_[[PYTHON]]</code> namespace	[9t] Python
rv.T	<code>_[[MARKUP]]</code> type	[10t] Markup block
rv.D	<code>_[[METADATA]]</code> label	[11t] Metadata
rv.D	<code>_[[LAYOUT]]</code> label	[12t] Layout block
all	<code>_[[END]]</code>	[13t] End block

[2t] Shell script

Runs shell scripts that run external programs. The shell parameters include specifying the operating system, process control and terminal window control. The os parameter specifies the terminal type. The wait parameter specifies whether rvt file processing waits for the script to complete before continuing. The open parameter specifies whether to keep the shell window open after execution.

`_[[SHELL]]`

Syntax:

```
_[[SHELL]] win;mac;linux,wait; nowait,open; close
shell command
...
_[[END]]
```

Example:

```
_[[SHELL]] win,nowait,open
dir
path
_[[END]]
```

API Scope	Insert
Doc Types	text, PDF, HTML

[3t] Indent text

Indents text block the specified number of spaces.

`_[[INDENT]]`

Syntax:

```
_[[INDENT]] number of spaces
text
text
...
_[[END]]
```

Example:

```
_[[INDENT]] 8
This is a sentence that will be
indented 8 spaces.
_[[END]]
```

API Scope	Insert
Doc Types	text, PDF, HTML

[4t] Indent italic

`_[[ITALIC]]`

Italicizes and indents the text block the specified number of spaces.

```
Syntax:
  _[[ITALIC]] number of spaces
  text
  ...
  _[[END]]

Example:
  _[[ITALIC]] 4
  This is a sentence that will be
  italicized and indented 4 spaces.
  _[[END]]
```

API Scope	Insert
Doc Types	text, PDF, HTML

[5t] Endnotes

`_[[ENDNOTES]]`

Assigns numbers and formats endnotes in order of processing. Each endnote is separated by a blank line and is numbered in order of occurrence.

```
Syntax:
  _[[ENDNOTES]] label
  Endnote 1.

  Endnote 2.
  ...
  _[[END]]

Example:
  _[[ENDNOTES]] ACI citations
  This endnote is assigned to the first endnote tag (_[#]) in order of
  of processing.

  This second endnote is separated by a blank line and assigned
  to the second

  This is a third endnote.
  _[[END]]
```

API Scope	Insert
Doc Types	text, PDF, HTML

[6t] Text

`_[[TEXT]]`

Reads and formats text and code. The language parameter specifies formatting and syntax coloring. Languages include:

- *literal*
- *python*
- *text*
- *sh*
- *cmd*

Syntax:

```
_[[TEXT]] language
text and code
...
_[[END]]
```

Example:

```
_[[TEXT]] python
# some code
print(1)
a = 1 + 3
_[[END]]
```

API Scope	Insert
Doc Types	text, PDF, HTML

[7t] Topic

`_[[TOPIC]]`

Formats a topic block.

Syntax:

```
_[[TOPIC]] topic title
text
...
_[[END]]
```

Example:


```
_[[TOPIC]] topic title
Text related to the topic.
_[[END]]
```

API Scope	Insert
Doc Types	text, PDF, HTML

[8t] Box

_**[[BOX]]**

Draws a box around the block of text.

```
Syntax:
_[[BOX]] optional label
text
...
_[[END]]

Example:
_[[BOX]]
This is a sentence.
A second sentence.
A box is drawn around the sentences.
_[[END]]
```

API Scope	Insert
Doc Types	text, PDF, HTML

[9t] Python

_**[[PYTHON]]**

Executes Python script in the *rivt namespace* or a user specified namespace. File paths in the script are relative to the *rivt file* folder.

```
Syntax:
_[[Python]] topic title
code
...
_[[END]]

Example:
_[[PYTHON]] *rvspace*; user namespace
```

```
b = 1*inch + 2.2*ft
print(b)
_[]END[]
```

API Scope	Value, Tool
Doc Types	text, PDF, HTML

[10t] Markup block

Inserts HTML into an HTML *doc*, LaTeX into a PDF *doc*, and reStructuredText into either PDF or HTML.

_[]MARKUP[]

Syntax:

```
_[]MARKUP[] *html;latex;rst*
markup
...
_[]END[]
```

Example:

```
_[]MARKUP[] rst
This is bold and
this is italic in
reStructuredtext
...
_[]END[]
```

API Scope	Tool
Doc Types	text, PDF, HTML

[11t] Metadata

_[]METADATA[]

Metadata is written to the *rvAnn-apilog.py* file and is converted internally to a Python dictionary *rvmetaD* with key name taken from the label e.g. *docnameS* or *authorsD*.

Syntax - defaults:

```
_[]METADATA[] optional label
docname = ""
authors = ""
version = 0.0.0
email = ""
repo = ""
```

```
license = https://opensource.org/license/mit
fork1 = author, version, email, repo
fork2 = author, version, email, repo
_{{END}}
```

Example:

```
_{{METADATA}}
docname = Bearing Pressures
authors = rholland, rward
version = 0.1.1
email = rholland@email.com
repo = https://github.com/rivt-info/rivt-simple-doc
license = https://opensource.org/license/mit
_{{END}}
```

API Scope	Docs
Doc Types	text, PDF, HTML

[12t] Layout block

Overrides default layout settings.

_{{LAYOUT}}

```
Syntax - defaults:
_{{LAYOUT}} optional label
variables
...
_{{END}}
```

Example:

```
_{{LAYOUT}}
docname = ""
footer = date, docname, page
_{{END}}
```

API Scope	Doc
Doc Types	text, PDF, HTML

[13t] End block

_{{END}}

Terminates a block tag.

Syntax:
 _[[NEWPAGE]] optional label

Example:
 _[[END]]

API Scope	All
Doc Types	text, PDF, HTML

C.4 Commands

[1t] Command Summary

format files and equations

API Scope	Command	Description
rv.R	SHELL rel path os, wait	[2t] Shell file
rv.l	TEXT rel path language	[3t] Text file
rv.V, l	TABLE rel path title, width, rows, align, head	[4t] Table file
rv.V, l	IMAGE rel path caption, scale, number	[5t] Image file
rv.V, l	IMAGE2 rel pth1, rel pth2 cap1,cap2,sca1,sca2,num	[6t] Adjacent images
rv.V	VALTABLE rel path title, rows, number	[7t] Valtable file
rv.V	a ==: 1*IN unit1, unit2, decimal label	[8t] Define value
rv.V	c <=: expression unit1, unit2, decimal label	[9t] Assign value
rv.V	c :=: expression unit1, unit2, decimal label	[9t] Function value
rv.V	a < c decimal text1, text2, color1, color2	[10t] Compare values
rv.T, V	PYTHON rel path namespace	[11t] Python file
rv.T	MARKUP rel path type	[12t] Markup file
rv.D	ATTACHPDF rel path place, title	[13t] Attach PDF
rv.D	PUBLISH doc title type	[14t] Publish doc

Default command paths

See here for the folder structure. If files are in the default path only the file name needs to be provided.

Command	Default Path
SHELL	/Files/Scripts/
TEXT	/Files/Data/
TABLE	/Files/Data/
IMAGE	/Files/Image/
IMAGE2	/Files/Image/
VALTABLE	/Files/Data/ [1]
PYTHON	/Files/Scripts/
MARKUP	/Files/Scripts/
ATTACHPDF	/Files/Attach/
PUBLISH	depends on file type

[1] use /stored/data/filename to read values defined in the rvt file

[2t] Shell file

The SHELL command runs shell scripts including .cmd, .bat and .sh files. The *os* parameter specifies the operating system: *win*, *mac* or *linux*. The *wait*; *nowait* specifies whether rvt file processing waits for the script to complete before continuing.

If the *doc* is part of a report and no path is specified, the file is assumed to be in the default folder */src/run/*. Otherwise the path is specified relative to the report root (rvt file folder). If the *doc* is a single doc the file is read from the rvt file folder.

Syntax:

```
| SHELL | relative file path | win;mac;linux,wait;nowait
```

Example:

```
| SHELL | file1.cmd | win, nowait
```

API Scope	rv.R
File Types	.cmd, .bat, .sh, .bsh
Doc Types	text, PDF, HTML

[3t] Text file

The TEXT command reads and formats text and code files. The *language* parameter specifies formatting and syntax coloring. Language types include:

- *literal*

- *python*
- *text*
- *sh*
- *cmd*
- *reStructuredText*

The *literal* type inserts text into the *doc* without formatting.

If a *doc* is part of a report and no path is specified, the file is assumed to be in the default folder */src/data/* . Otherwise the path needs to be specified relative to the report root (rivt file folder). If the doc is a single doc the file is read from the rivt file folder.

Syntax:
| TEXT | relative file path | language - see list above

Example:
| TEXT | file1.txt | literal

API Scope	rv.l
File Types	txt, .py, .cmd, .bat, .sh, .rst
Doc Types	text, PDF, HTML

[4t] Table file

The TABLE command reads csv, xls, and rst files and outputs formatted tables. The title may be omitted by inserting a hyphen "-". The width parameter specifies the maximum character width of a column. The align parameter specifies the cell justification - left, center, right. The number parameter specifies whether the table is numbered. For csv files, the head parameter specifies whether the first row is a column header.

If a *doc* is part of a report and no path is specified, the file is assumed to be in the default folder */src/data/* . Otherwise the path needs to be specified relative to the report root (rivt file folder). If the doc is a single doc the file is read from the rivt file folder.

| TABLE |

Syntax:
| TABLE | rel path | title, max width, rows, l;c;r, head;nohead, num;nonum

Example:
| TABLE | file1.csv | Forces, 30, 0:0, c, nohead, num

API Scope	rv.l, rv.V
File Types	csv, xls, rst
Doc Types	text, PDF, HTML

[5t] Image file

The IMAGE command reads a PNG or JPEG file and centers it in the *doc*. The scale parameter is a decimal fraction of the page width. The caption may be omitted by using a single hyphen. The *num;nonum* parameter specifies whether to assign a figure number. The image path is inserted in the text *doc* instead of the image.

If a *doc* is part of a report and no path is specified, the file is assumed to be in the default folder */src/img/*. Otherwise the path needs to be specified relative to the report root (rivt file folder). If the doc is a single doc the file is read from the rivt file folder.

Syntax:

```
| IMAGE | relative path | caption, scale, num;nonum
```

Example:

```
| IMAGE | file1.png | Map, 0.5, num
```

API Scope	rv.V, rv.I
File Types	PNG, JPG
Doc Types	PDF, HTML

[6t] Adjacent images

The IMAGE2 command reads two PNG or JPEG file and places them side by side in the *doc*. The scale parameters are a decimal fraction of the page width. The captions may be omitted by using a single hyphen for either or both images. The *fig;nofig* parameters specify whether to assign a figure number to either or both images. The image path is inserted in the text *doc* instead of the image.

If a *doc* is part of a report and no path is specified, the file is assumed to be in the default folder */src/img/*. Otherwise the path needs to be specified relative to the report root (rivt file folder). If the doc is a single doc the file is read from the rivt file folder.

Syntax:

```
| IMAGE2 | relative path | cap1, cap2, scale1, scale2, num;nonum, num;nonum
```

Example:

```
| IMAGE2 | file1.png, file2.png | Map, Photo, .5,.5, num, num
```

API Scope	rv.I, rv.V
File Types	PNG, JPG jenn
Doc Types	PDF, HTML

[7t] Valtable file

The VALTABLE command imports and defines values from a *csv* or *x/s* file. The file format is:

```
var = value, unit1, unit2, decimal, label
```

The path variable is either from *src* or *stored* depending on if the values were generated by rivtlib or provided by the author. The title parameter is the table title. A hyphen omits the title. The *rows* parameter specifies the rows to import. The *num; nonum* parameter specifies whether to assign a table number to the values table.

If a *doc* is part of a report and no path is specified, the file is assumed to be in the default folder */src/vals/*. Otherwise the path needs to be specified relative to the report root (rivt file folder). If the values are read from prior calculated values, they will be found in the */stored/vals* folder. If the doc is a single doc the file is read from the rivt file folder.

Syntax:

```
| VALTABLE | relative path | title, rows, *num;nonum*
```

Example:

If read from the default folder:

```
| VALTABLE | newvals.csv | Beam Properties, 1:10, num
```

If read from the stored folder:

```
| VALTABLE | /stored/vals/vA01-2.csv | Beam Properties, 1-10, num
```

API Scope	rv.V
File Types	.csv, .xls,
Doc Types	text, PDF, HTML

[8t] Define value

Defines a value and writes it to the file *vdocnum-s.csv* where *num* is the *docnumber* and *s* is the section number. The file is written to the folder *stored/vals* unless *singledocB* is set to *True* in the comment variable.

The stored values can read and defined in other rivt files using the VALUES command.

Syntax:

```
c =: 5*unit | unit1, unit2, decimals | label, *num,nonum*
```

Example:

```
D_1 =: 10*IN | IN, M, 3 | beam depth, num
```

API Scope	rv.V
File Types	.csv
Doc Types	text, PDF, HTML

[9t] Assign value

Assigns a value to an equation and writes the values to a file *vdocnum-s.csv* where *num* is the *doc number* and *s* is the section number. The file is written to the folder *stored/vals* unless *rv single doc* is set to *True* in which case values are stored in the rivt file folder (root).

The label is a reference printed with the equation. The units specify the result expressed in two different units. The integer specifies the number of places after the decimals.

Syntax:

```
b <=: a * 10*FT | unit1, unit2, decimals | label, num;nonum
```

Example:

```
b_1 <=: E_1 * 12.1*IN^2 | KIP, KN, 2 | Std. 123, num
```

API Scope	rv.V
File Types	.csv
Doc Types	text, PDF, HTML

[9t] Function value

Assigns a value to an equation and writes the values to a file *vdocnum-s.csv* where *num* is the *doc number* and *s* is the section number. The file is written to the folder *stored/vals* unless *rv single doc* is set to *True* in which case values are stored in the rivt file folder (root).

The label is a reference printed with the equation. The units specify the result expressed in two different units. The integer specifies the number of places after the decimals.

Syntax:

```
c :=: function name() | unit1, unit2, decimals | label, num;nonum
```

Example:

```
c_1 :=: func1(a,b) | KIP, KN, 2 | ACI 318-19 Table 22.5.5.1, num
```

API Scope	rv.V
File Types	.csv
Doc Types	text, PDF, HTML

[10t] Compare values

Inserts a text with alignment and color on the following line if the expression evaluates to true. text1 and text2 are printed if true or false respectively. Colors are assigned accordingly as *red;blue;yellow;green;black;gray* defined in the *style files*. The text is right aligned.

Comparison operators:

```

==    Equal x == y
!=    Not equal    x != y
>     Greater than x > y
<     Less than    x < y
>=    Greater than or equal to x >= y
<=    Less than or equal to x <= y

```

<>

Syntax:
a < b | text1, text2, color1, color2

Example:
a < b |OK, NOT OK, blue, red

API Scope	rv.V
Doc Types	text, PDF, HTML

[11t] Python file

Executes Python code in the *rv namespace* or user specified namespace. File paths used in the script are relative to the root *rv* folder.

Syntax:
| PYTHON | relative path | *rvspace*; user space

Example:
| PYTHON | script1.py | rv-space

API Scope	rv.V, rv.T
File Types	.csv
Doc Types	text, PDF, HTML

[12t] Markup file

Inserts HTML into an HTML *doc*, LaTeX into a PDF *doc*, and reStructuredText into either PDF or HTML. LaTeX requires the installation of *texlive*.

| MARKUP |

Syntax:
| MARKUP | relative path | *rst, html, latex*

Example:
| MARKUP | script.rst | rst

API Scope	rv.t
File Types	html, rst, tex
Doc Types	text, PDF, HTML

[13t] Attach PDF

Appends or prepends a PDF file to the *doc*. The title parameter generates an Appendix cover page with the specified title. A "-" omits the over page. For HTML *docs* the file is inserted as a download link.

| ATTACHPDF |

Syntax:
| ATTACHPDF | relative path | *front;back*, title

Example:
| ATTACHPDF | relative path | *front;back*, title

API Scope	rv.D
File Types	tex, html, text, pdf
Doc Types	text, PDF, HTML

[14t] Publish doc

Publishes a *doc*.

Syntax:
| PUBLISH | ini relative path | rst2pdf, texpdf, tex, hmtl

Example:
| PUBLISH | ini relative path | rst2pdf

API Scope	rv.D
File Types	tex, html, text, pdf

API Scope	rv.D
Doc Types	text, PDF, HTML

C.5 Run - rv.R

[1i] rv.R Markup

The *Run* API function executes shell commands.

[2i] Block Tags

Block Tag	Description
<code>_[[SHELL]]</code> process parameters	[2t] Shell script
<code>_[[END]]</code>	[13t] End block

[3i] Commands

Command	Description
SHELL relative path os, wait	[2t] Shell file

C.6 Insert - rv.I

[1i] rv.I Markup

The *Insert* API function inserts and formats static sources into the *doc*, including images, tables, links and formatted text.

[2i] Line Tags

Line Tag	Description
text <code>_[C]</code>	[2t] Center text
text <code>_[R]</code>	[3t] Right justify text
text math <code>_[M]</code>	[4t] Text math
LaTeX math <code>_[L]</code>	[5t] LaTeX math
text <code>_[#]</code> text	[6t] Endnote number
text <code>_[G]</code> text, section label	[8t] Section link

Line Tag	Description
text _[D] text, rivt_file	[9t] Doc link
text _[U] text, label	[10t] URL link
text _[V] var_name text	[11t] Variable value
assign var or label _[E]	[12t] Equation number
title _[T]	[13t] Table number
caption _[F]	[14t] Figure number

[3i] Block Tags

Block Tag	Description
_[[INDENT]] spaces (4 default)	[3t] Indent text
_[[ITALIC]] spaces (4 default)	[4t] Indent italic
_[[ENDNOTES]] optional label	[5t] Endnotes
_[[TEXT]] optional language	[6t] Text
_[[TOPIC]] topic	[7t] Topic
_[[END]]	[13t] End block

[4i] Commands

Command	Description
IMAGE relative path scale, caption, figure	[5t] Image file
IMAGE2 rel path1, rel path2 s1, s2, c1, c2, fig1, fig2	[6t] Adjacent images
TEXT relative path language	[3t] Text file
TABLE rel path title, width, rows, align, head	[4t] Table file

C.7 Values - rv.V**[1i] rv.V Markup**

The *Values* API function defines values and evaluates equations and functions.

[2i] Line Tags**Format a line of text**

Line Tag	Description
text _ [V] var_name text	[11t] Variable value
label _ [E]	[12t] Equation number
title _ [T]	[13t] Table number
caption _ [F]	[14t] Figure number

[3i] Block Tags**Format or execute a block of text**

Block Tag	Description
_ [[PYTHON]] namespace	[9t] Python
_ [[END]]	[13t] End block

[2i] Commands**Format files and calculations**

Command	Description
TABLE rel path title,width,rows,align,head,num	[4t] Table file
IMAGE relative path scale, caption, figure	[5t] Image file
IMAGE2 rel path1, rel path2 c1, c2, s1, s2, f1, f2	[6t] Adjacent images
VALTABLE rel path title, width, rows	[7t] Valtable file
PYTHON relative path namespace	[11t] Python file
a ==: 1*IN unit1, unit2, decimal, num label	[8t] Define value
c <=: expression unit1, unit2, decimal, num label	[9t] Assign value
c :=: expression unit1, unit2, decimal label, number	[9t] Function value

Command	Description
a < c decimal text1,text2,align, num	[10t] Compare values

C.8 Tool - rv.T

[1i] rv.T Markup

The *Tools* API function executes markup and scripts.

[2i] Block Tags

Block Tag	Description
_[[PYTHON]] namespace	[9t] Python
_[[MARKUP]] type	[10t] Markup block
_[[END]]	[13t] End block

[3i] Commands

Command	Description
PYTHON relative path namespace	[11t] Python file
MARKUP relative path type	[12t] Markup file

C.9 Doc - rv.D

[1i] rv.D Markup

The *Doc API* publishes formatted *docs* from the rivt API strings.

[2i] Block Tags

Block Tag	Description
_[[LAYOUT]] label	[12t] Layout block
_[[METADATA]] label	[11t] Metadata

[3i] Commands

Command	Description
PDFATTACH relative path place, cover	[13t] Attach PDF
PUBLISH ini rel. path type	[14t] Publish doc

E.1 Collaboration

[1t] Overview

There are several ways to collaborate on *rivt files* by using tools available in the Python, GitHub and VSCode ecosystem.

1. Public rivt files may be shared by uploading them to repositories e.g. *GitHub*. Public *rivt files* can be found and downloaded using the search interface. *Public rivt files* are identified with the naming convention

```
rv-DocNumber-filename.py
```

where the doc name and number are the doc number of the corresponding *doc* e.g. with an added hyphen prefix. The file is writtnen to the *_shared* folder. This is in contrast with the form:

```
rvDocNumber-filename.py
```

for active, private files stored in the report root directory. After downloading shared rivt files, use a *batch rename* extension or utility to delete the hyphen and convert it to an active rivt file form. *Public rivt files* may be collaboratively improved by:

- forking to create different versions.
 - providing pull requests.
 - submitting issues and bugs.
2. Contributions to rivtlib at [rivtlib-dev](#) and documentation at [rivt-info](#) in the form of;
 - report issues and bugs
 - issue pull requests to propose changes
 - improved documentation
 3. Contributioons to extensions and scripts that improve the interaction of *rivt* with other components in the *rivt framework*.
 4. Collaborative editing in VSCode using [Visual Studio Live Share](#).

[2t] Open Models

The web site [OpenModels.info](#) is a *Google Drive* repository of open source engineernig model files, including *rivt files* and *reports*.

[3t] Git and GitHub

[Git](#) and [GitHub](#) are part of the *rivt framework*. *Git* is a free, open-source, distributed version control system designed to manage and track changes in files. It allows multiple people to work on the same project simultaneously without overwriting each other's work. *GitHub* is a web-based platform for hosting, managing, and collaborating on code built around Git. It allows teams to work together efficiently on software projects and provides features like pull requests, issue tracking, and project management.

Each *rivt project* is typically stored in its own repository. Every user of GitHub has a personal account with essentially unlimited repositories. Free accounts provide for:

- Unlimited Repositories: You can create as many public and private repositories as you need.
- Unlimited Collaborators: There is no limit to the number of people you can work with on your repositories.
- Community Support: You have access to the GitHub Community Discussions for help.
- Core Services with Usage Limits: The free plan includes a certain amount of monthly usage for services:
 - **GitHub Actions: 2,000 minutes per month for private repositories** (unlimited for public repositories).
 - GitHub Codespaces: 120 core hours and 15 GB of storage per month.

GitHub Codespaces is a VSCode cloud-based development environment connected to GitHub files. It can be set up with *rivt extensions* that provide a complete *rivt* editing and collaboration environment in the cloud.

[4t] VSCode

[VSCode](#) is an open source IDE with a large set of extensions, including collaboration support. Collaboration is facilitated by the [Visual Studio Live Share](#). You can start a *Live Share* session either within *CodeSpaces* in your browser, or within the *VS Code* desktop application. *CodeSpaces* is a cloud based GitHub implementation of VSCode that shares many of the same features.

The *Live Share* extension enables:

- Real-time Co-editing: Multiple participants can work on the same file simultaneously, seeing each other's cursors, selections, and edits instantly, much like in Google Docs..
- Shared Terminals and Servers: The host can share their terminal and localhost servers with guests, eliminating the need for guests to set up their own environments or dependencies.
- Navigation and Following: Participants can independently navigate the project or choose to "follow" another collaborator, keeping their editor synchronized with the leader's actions.
- File Access Control: Hosts can use a `.vsls.json` file to control which files and folders are visible or editable by guests, ensuring security and focus

E.2 Public files

[1t] Overview

A feature of *rivt* is fine-grained control over public sharing of all or parts of a *rivt* file. *Public rivt files* are generated by *rivtlib* on a section by section basis defined by the API header substring. Each API function defines a section and has a public/private setting in the header. Sections are private by default (see `:doc: <rvF01-quickref>`).

```
rv._("""Section Label | doc;stored, private;public, section;merge
    Content substring indented 4 spaces
    ...
    """)
```

Sections are written to a rvt file in the */public* folder with a file name composed as:

```
rv file name
    rvAnn-filename.py
modified with an additional hyphen
    rv-Ann-filename.py
```

The public folder may be uploaded to a GitHub repo for public sharing. When downloaded the extra hyphens may be removed with a batch remove command (e.g. in VSCode).

[2t] Public Folder

For each rvt file that is published a corresponding *public rvt file* is written to the *public* folder. The default contents of the file are the API rvt string headers. If the header parameter *public* is included in the header, the rvt string content is also written to the *public rvt file*.

[rvt]-Report-Label/	Report Folder Name
[rv101-]filename1.py	rvt file
[rv102-]filename2.py	rvt file
[rv201-]filename3.py	rvt file
[rv202-]filename4.py	rvt file
...	
[public]/	public rvt files
rv-101-filename1.py	
rv-102-filename1.py	
rv-201-filename3.py	
rv-202-filename4.py	

The *public folder* can be uploaded to a public repository and updated with Git as the project develops.

F.1 Quick Ref

[3t] Example

E.3 Git

[1t] Git

GitHub is a popular and widely used cloud and version control system based on the Git program that may be downloaded [here](#).

E.4 GitHub Search

[1t] GitHub Global Search

This page is a search interface for **rivt** files on GitHub. The search covers the full text of the **rivt** README.txt file in the *repo* directory. The README file contains the *rivt report*. For advanced searching use the [GitHub interface](#).

[S] Search GitHub <Ctrl+Enter>

[C] Clear input <Ctrl+R>

Example: solar+steel+frame is passed to GitHub as rivt+solar+steel+frame

[2t] GitHub Organization Search

Restrict search to the following comma separated GitHub organizations:

F.1 Quick Ref

[1t] API

API functions

Function	Name	Purpose
rv.R (rS)	Run	Run shell commands
rv.I (rS)	Insert	Insert static sources
rv.V (rS)	Values	Calculate values
rv.T (rS)	Tools	Python and markup scripts
rv.D (rS)	Doc	Publish docs
rv.S (rS)	Skip	Skip section (comments and debugging)
rv.X (rS)	Exit	Exit rivt (debugging)

where **rS** is a *rivt string*. The first line of a *rivt string* (rS) is the header substring.

Header substrings

```
rv.I("""A New Section | private, doc, section
    Content text
    ...
    """)
```

Default settings in the *header substring* do not need to be specified. The default setting for each API is listed first (in bold) in the table below. The default privacy settings for all sections in a rivt file may be reversed by including the *public setting* and setting it to True, immediately following the *rivlib import statement*. Individual sections may still be set as private in the header substring.

```
import rivtlib.rvapi as rv
# rv public=True
```

Header substring defaults

API	private;public	doc;stored	section;merge
rv.R	private ;public	stored ;doc	merge ;section
rv.I	private ;public	doc ;stored	section ;merge
rv.V	private ;public	doc ;stored	section ;merge
rv.T	private ;public	stored ;doc	merge ;section
rv.S	private ;public	stored	merge
rv.D	public	stored	merge
rv.X	•	•	•

[2t] Line Tags

Format a line of text

API Scope	Line Tag	Description
rv.I	text [C]	[2t] Center text
rv.I	text [R]	[3t] Right justify text
rv.I	text math [M]	[4t] Text math
rv.I	LaTeX math [L]	[5t] LaTeX math

[3t] Block Tags

API Scope	Line Tag	Description
rv.l	text _[#] text	[6t] Endnote number
rv.l	text _[G] glossary term text	[7t] Glossary link
rv.l	text _[S] label, section text	[8t] Section link
rv.l	text _[D] label, file name text	[9t] Doc link
rv.l	text _[U] label, url text	[10t] URL link
rv.V, l	text _[V] var_name text	[11t] Variable value
rv.V, l	text _[E]	[12t] Equation number
rv.V, l	title _[T]	[13t] Table number
rv.V, l	caption _[F]	[14t] Figure number
rv.V, l	_[P]	[15t] New Page
rv.V, l	## text	nonprinting comment

[3t] Block Tags

Format a block of text

API Scope	Block Tag	Description
rv.R	_[[SHELL]] process parameters	[2t] Shell script
rv.l	_[[INDENT]] spaces (4 default)	[3t] Indent text
rv.l	_[[ITALIC]] spaces (4 default)	[4t] Indent italic
rv.l	_[[ENDNOTES]] optional label	[5t] Endnotes
rv.l	_[[TEXT]] optional language	[6t] Text
rv.l	_[[TOPIC]] topic	[7t] Topic
rv.l	_[[BOX]] label	[8t] Box
rv.V, T	_[[PYTHON]] namespace	[9t] Python
rv.D	_[[METADATA]] label	[11t] Metadata
rv.D	_[[LAYOUT]] label	[12t] Layout block
all	_[[END]]	[13t] End block

[4t] Commands**format files and calculations**

API Scope	Command	Description
rv.R	SHELL rel path os, wait	[2t] Shell file
rv.l	TEXT rel path language	[3t] Text file
rv.V, l	TABLE rel path title,width,rows,align,head,num	[4t] Table file
rv.V, l	IMAGE rel path caption, scale, number	[5t] Image file
rv.V, l	IMAGE2 rel pth1, rel pth2 cap1,cap2,sca1,sca2,num	[6t] Adjacent images
rv.V	VALTABLE rel path title, rows, number	[7t] Valtable file
rv.V	a ==: 1*IN unit1, unit2, decimal label	[8t] Define value
rv.V	c <=: expression unit1, unit2, decimal label, number	[9t] Assign value
rv.V	c :=: expression unit1, unit2, decimal label, number	[9t] Function value
rv.V	a < c decimal text1, text2, color1, color2	[10t] Compare values
rv.V, T	PYTHON rel path namespace	[11t] Python file
rv.T	MARKUP rel path type	[12t] Markup file
rv.D	ATTACHPDF rel path place, title	[13t] Attach PDF
rv.D	PUBLISH doc title type	[14t] Publish doc

default paths for single docs

See here for the folder structure. If files are in the default path only the file name needs to be provided.

Command	Default Path
SHELL	folder root
TEXT	folder root
TABLE	folder root
IMAGE	folder root
IMAGE2	folder root
VALTABLE	folder root
PYTHON	folder root
MARKUP	folder root
ATTACHPDF	folder root
PUBLISH	folder root

Default command paths for report

See here for the folder structure. If files are in the default path only the file name needs to be provided.

Command	Default Path
SHELL	/Files/Scripts/
TEXT	/Files/Data/
TABLE	/Files/Data/
IMAGE	/Files/Image/
IMAGE2	/Files/Image/
VALTABLE	/Files/Data/ [1]
PYTHON	/Files/Scripts/
MARKUP	/Files/Scripts/
ATTACHPDF	/Files/Attach/
PUBLISH	depends on file type

[1] use /stored/data/filename to read values defined in the rivt file

[5t] Folders

[rivt-]Report-Label/	Report Folder Name
├── .vscode/	optional VSCode settings
├── [conf.py]	configuration file
├── [rv101-]filename1.py	rivt file
├── [rv102-]filename2.py	rivt file
├── [rv201-]filename3.py	rivt file
├── [rv202-]filename4.py	rivt file
├── [_publish]/	published docs and reports
│ ├── [docs]/	html docs
│ │ ├── _images/	
│ │ ├── _sources/	
│ │ ├── _static/	
│ │ ├── process folders/	
│ │ ├── site folders/	
│ │ ├── rv101-filename1.html	
│ │ ├── rv102-filename2.html	
│ │ ├── rv201-filename3.html	
│ │ └── rv202-filename4.html	
│ ├── [pdfdocs]/	pdf docs
│ │ ├── process folders/	
│ │ ├── rv101-filename1.pdf	
│ │ ├── rv102-filename1.pdf	
│ │ ├── rv201-filename3.pdf	
│ │ └── rv202-filename4.pdf	
│ └── [txtdocs]/	text docs
│ ├── rv101-filename1.txt	
│ ├── rv102-filename1.txt	
│ ├── rv201-filename3.txt	
│ └── rv202-filename4.txt	
├── [_rstdocs]/	restructured text files
│ ├── _downloads/	
│ ├── _static/	
│ ├── _locale/	
│ ├── _templates/	
│ ├── rv101-filename1.rst	
│ ├── rv102-filename2.rst	
│ ├── rv201-filename3.rst	
│ └── rv202-filename4.rst	
├── [_shared]/	public rivt files
│ ├── rv-101-filename1.py	
│ ├── rv-102-filename1.py	
│ ├── rv-201-filename3.py	
│ └── rv-202-filename4.py	
├── [_stored]/	stored files genereatd by rivt
│ ├── [Logs]/	log files
│ │ ├── rv101-log.txt	
│ │ └── rv102-log.txt	
│ ├── [Sect]/	sections
│ ├── rv202-5d.txt	
│ └── rv103-4t.txt	

[6t] Python Requirements



[6t] Python Requirements

The minimum Python version is 3.14. *rivt* project packages include the following categories:

- formatting
- numerical analysis
- symbolic processing
- visualization
- IDE

Dependency	description
"pyzo>=4.20.0"	lightweight IDE
"pyside6>=6.10.1"	QT bindings
"fastcore>=1.8.16"	code simplification
"tabulate>=0.9.0"	format tables
"pillow>=11.2.1"	image processing
"matplotlib>=3.10.1"	data visualization

Dependency	description
"sympy>=1.13.3"	symbolic analysis
"numpy>=2.2.5"	numerical analysis
"scipy>=1.16.3"	numerical analysis
"pandas>=2.2.3"	data analysis
"docutils>=0.21.2"	reStructuredText processing
"ipython>=8.16.2"	interactive Python shell
"ipykernel>=6.28.1"	Jupyter kernel for Python
"reportlab>=4.4.0"	PDF generation without LaTeX
"rst2pdf>=0.103.1"	PDF generation without LaTeX
"pypdf>=1.0.3"	PDF manipulation
"Sphinx>=8.2.3"	HTML generation
"pydata-sphinx-theme>=0.16.1"	HTML generation
"sphinx-copybutton>=0.5.2"	HTML generation
"sphinx_design>=0.6.1"	HTML generation
"sphinx-favicon>=1.0.1"	HTML generation
"sphinx-togglebutton>=0.3.2"	HTML generation
"sphinxcontrib-applehelp>=2.0.0"	HTML generation
"sphinxcontrib-devhelp>=2.0.0"	HTML generation
"sphinxcontrib-email>=0.3.6"	HTML generation
"sphinxcontrib-htmlhelp>=2.1.0"	HTML generation
"sphinxcontrib-jquery>=4.1"	HTML generation
"sphinxcontrib-jsmath>=1.0.1"	HTML generation
"sphinxcontrib-qthelp>=2.0.0"	HTML generation
"sphinxcontrib-serializinghtml>=2.0.0"	HTML generation

[7t] VSCode Settings

Workspace extension and other settings are stored in the `.vscode` folder and can be included and moved as part of a *rivt report*. Settings that affect the *rivt* environment include:

- `rivt.code-snippets`

- settings.json (extension settings)
- tasks.json
- launch.json

Global settings can be exported and imported using VSCode Profiles. VSCode *rixt* extensions and settings may be installed from this link.

Extension	description
BUTTONS	—
tombonnike.vscode-status-bar-format-toggle	format button
gsppvo.vscode-commandbar	command buttons
AdamAnand.adamstool	command buttons
nanlei.save-all	save all button
Ho-Wan.setting-toggle	toggle settings
yasukotelin.toggle-panel	toggle panel
fabiospampinato.vscode-commands	user command buttons
jerrygoyal.shortcut-menu-bar	menu bar
EDITING	—
henryclayton.context-menu-toggle-comments	toggle comments
TroelsDamgaard.reflow-paragraph	wrap paragraph
streetsidesoftware.code-spell-checker	spell check
jmviz.quote-list	quote elements in a list
njpwerner.autodocstring	insert doc string
oijaz.unicode-latex	unicode symbols from latex
jsynowiec.vscode-insertdatestring	insert date string
janisdd.vscode-edit-csv	csv editor
VIEWS	—
GrapeCity.gc-excelviewer	excel viewer
SimonSiefke.svg-preview	svg viewer
tomoki1207.pdf	pdf viewer
RandomFractalsInc.vscode-data-preview	data viewing tools
Fr43nk.seito-openfile	open file from path

Extension	description
vikyd.vscode-fold-level	line folding tool
file-icons.file-icons	icon library
tintinweb.vscode-inline-bookmarks	inline bookmarks
MANAGEMENT	—
alefragnani.project-manager	folder, project management
Anjali.clipboard-history	clipboard history
dionmunk.vscode-notes	notepad
hbenl.vscode-test-explorer	test explorer
mightyco.co.fsdeploy	save file to second location
lyzerk.linecounter	count lines in files
sandcastle.vscode-open	open files in default app
zjffun.snippetsmanager	snippet manager
spmeesseman.vscode-taskexplorer	task explorer
GITHUB	—
GitHub.codespaces	run files in codespaces
GitHub.remotehub	run remote files
ettoreciprian.vscode-websearch	search github within VSCode
donjayamane.git-history	git history
MichaelCurrin.auto-commit-msg	git auto commit message
github.vscode-github-actions	github actions
GitHub.vscode-pull-request-github	github pull request
k9982874.github-gist-explorer	gist explorer
vsls-contrib.gistfs	gist tools
PYTHON	—
ms-python.autopep8	python pep8 formatting
ms-python.isort	python sort imports
donjayamane.python-environment-manager	python library list
ms-python.python	python tools

Extension	description
ms-python.vscode-pylance	python language server
ms-toolsai.jupyter	jupyter tools
ms-toolsai.jupyter-keymap	jupyter tools
ms-toolsai.jupyter-renderers	jupyter tools
ms-toolsai.vscode-jupyter-cell-tags	jupyter tools
ms-toolsai.vscode-jupyter-slideshow	jupyter tools
LANGUAGES	—
qwtel.sqlite-viewer	sqlite tools
RDebugger.r-debugger	R tools
REditorSupport.r	R tools
ms-vscode-remote.remote-wsl	windows linux tools
James-Yu.latex-workshop	latex tools
lextudio.restructuredtext	restructured text tools
trond-snekvik.simple-rst	restructured syntax
yzane.markdown-pdf	markdown to pdf
yzhang.markdown-all-in-one	markdown tools

Snippets and extensions

Keystrokes	Description
rvr	API Run
rvi	API Insert
rvv	API Values
rvt	API Tools
rvd	API Docs
alt+ctrl+c	insert cell marker with label above API function
alt+q	rewrap paragraph with hard line feeds (80 default)
alt+p	open file under cursor
alt+.	select correct spelling under cursor

Keystrokes	Description
alt+8	insert date
alt+9	insert time
ctl+1	focus on first editor
ctl+2	focus on next editor
ctl+3	focus on previous editor
ctl+8	focus on explorer pane
ctl+9	focus on github pane
ctl+alt+x	reload window
ctl+alt+[	reload window
ctl+alt+]	unfold all code
ctl+alt+u	unfold all code
ctl+alt+f	fold code level 2 (rivt sections visible)
ctl+alt+a	fold code - all levels
ctl+alt+t	toggle local fold
ctl+alt+e	toggle explorer sort order
ctl+alt+s	toggle spell check
ctl+alt+g	next editor group
ctl+shift+u	open URL under cursor in browser
ctl+shift+s	open GitHub README search for rivt
ctl+shift+a	commit all
ctl+shift+z	commit the current editor
ctl+shift+x	post to remote

Modified Keyboard Shortcuts

Keystroke	Description
alt+q	rewrap paragraph with hard line feeds (80 default)
alt+p	open file under cursor
alt+.	select correct spelling under cursor

Keystroke	Description
alt+8	insert date
alt+9	insert time
ctl+1	focus on first editor
ctl+2	focus on next editor
ctl+3	focus on previous editor
ctl+8	focus on explorer pane
ctl+9	focus on github pane
ctl+alt+x	reload window
ctl+alt+u	unfold all code
ctl+alt+f	fold code level 2 (rivt sections visible)
ctl+alt+a	fold code - all levels
ctl+alt+t	toggle local fold
ctl+alt+e	toggle explorer sort order
ctl+alt+s	toggle spell check
ctl+alt+g	next editor group
ctl+shift+u	open URL under cursor in browser
ctl+shift+s	open GitHub rivt README search
ctl+shift+a	commit all
ctl+shift+z	commit current editor
ctl+shift+x	post to remote

A.2 Terms

[1t] rivt Terms

block tag : block tags

A block tag formats a block of text that begins with `_[[TAG]]` and terminates with `_[[Q]]`.

command : commands

rivt commands read and write external files and assign values to variables. They start in the initial columns with a vertical bar (|) followed by the file path, name and parameters. The path is relative to the rivt report root folder. If the metadata variable `rv_localB` is set to true resources will be read from and written to the local *rivt file* folder.

COMMAND relative path parameters

content : content text : content substring

The text in a *rivt string* that follows the *header substring*. The text is utf-8 (Unicode Transformation Format - 8-bit), a character encoding standard that is a superset of ASCII, handles text from any language, and is constant across all platforms.

division

A group of related rivt files organized in a report and labeled in the rivt file name. Optionally organized in a division folder.

doc : docs

A formatted document file output using the rivtlib package. A doc is a text, PDF or HTML file with the default name of the *rivt file* and file type suffix.

doc number

Prefix of a rivt and doc file name and used to organize a report. It has the form *rvDss-filename.py* where D is a capital alphanumeric division number and ss is the subdivision number.

header : headers : header text : header substring

The first line of a *rivt string* that includes a section title, followed by comma separated parameters.

line tag : line tags

A line tag has the form *_[TAG]* and formats a line of text.

report : reports : rivt report : rivt reports

A group of compiled *docs* organized by rivt file number.

report folder : report folders

The folder structure for producing a report is described here.

report script

A Python script that assembles *docs* into a *report*.

rivt

An open source Python project that includes rivtlib and approximately two dozen Python packages. When *rivt* is installed docs and reports may be edited and published using a text editor.

rivt doc : rivt docs

A formatted document file output from a *rivt file* using the rivtlib package. A doc is a text, PDF or HTML file with the default name of the *rivt file* and file type suffix.

rivt file : rivt files

A Python file that imports *rivtlib* and includes *rivt markup*.

rivt file number

Prefix of rivt file name used to organize a report (rvDss-). It has the form *rvDss-filename.py* where D is a capital alphanumeric division number and ss is the subdivision number.

rivt folder

A folder containing a rivt file and all of its resources in the same folder. Generally used

rivt framework : framework

The recommended *rivt-framework* includes the following separately installed programs:

1. VSCode <<https://code.visualstudio.com/>> and VSCode extensions <<https://marketplace.visualstudio.com/vscode>>. rivt extensions and snippets are here.
2. Git <<https://git-scm.com>> and set up a GitHub <<https://github.com>>

3. *LaTeX* <<https://www.tug.org/texlive/>>
4. *QCAD* <<https://qcad.io/en/>>

rvt log file

rvt file execution log written to the *log folder* as *rvDss-log.txt*.

rvt markup

A light weight markup that wraps restructuredText and outputs reports in text, PDF and HTML. Markup is included in string arguments to rvt API functions.

rvt report folder

A folder containing multiple rvt files to be organized in a report and resources organized in subfolders

rvt string

Triple quoted string argument to an API function.

rvtlib

Open source [Python package](#) that generates docs and reports from a rvt file

rvspace

rvt alias name for the global rvt file namespace. Other user namespaces may be specified

section parameter : section parameters

Comma separated parameters in a *header* that specify the section processing.

single doc : single docs

A single doc is a rvt file that publishes a doc that is not part of a report and is used for quick docs that only require limited formatting.

It is specified in a comment variable directly after the *rvtlib* import statement.

```
# rv singledoc = True
```

The default setting is False. The rvt file folder is used for source and output files. A folder structure is not used.

[2t] Python Terms

docutils

A Python package that processes [restructured text](#) files into HTML, LaTeX, and other formats.

namespace

Provides [scope](#) for functions and variables.

Python : python

A [programming language](#) that lets you work quickly and integrate systems more effectively

restructuredtext : restructuredtext markup

A lightweight markup language designed to be processed by document software including [docutils](#), Sphinx and rvt.

[3t] GitHub and VSCode Terms

fork : forked

A fork is a copy of a repository. Forking a repository allows you to freely experiment with changes without affecting the original project. Most commonly, forks are used to either propose changes to someone else's project or to use someone else's project as a starting point for your own idea.

Git : git

A [version control system](#) that lets you manage and keep track of your source code history.

IDE : ide

Integrated Development Environment. A software application that provides comprehensive facilities to computer programmers for software development. An IDE typically includes a code editor, build automation tools, and a debugger. *rivt extensions* have been developed for VSCode. Other IDEs include PyCharm, Spyder, and JupyterLab.

profile

Allows VSCode users to customize their environment for different workflows, projects, or tasks. This feature provides a way to manage distinct configurations of settings, extensions, keyboard shortcuts, snippets, and tasks.

repo : repository

a storage location for software packages

rivt Codespace : rivt codespace

A Codespace set up with extensions, snippets and keyboard shortcuts for editing and publishing *rivt docs*.

Index

B

[block tag](#)
[block tags](#)

C

[command](#)
[commands](#)
[content](#)
[content substring](#)
[content text](#)

D

[division](#)
[doc](#)
[doc number](#)
[docs](#)
[docutils](#)

F

[fork](#)
[forked](#)
[framework](#)

G

[Git](#)
[git](#)

H

[header](#)
[header substring](#)
[header text](#)
[headers](#)

I

[IDE](#)
[ide](#)

L

[line tag](#)
[line tags](#)

N

[namespace](#)

P

[profile](#)
[Python](#)
[python](#)

R

[repo](#)
[report](#)
[report folder](#)
[report folders](#)
[report script](#)
[reports](#)
[repository](#)
[restructuredtext](#)
[restructuredtext markup](#)
[rivt](#)
[rivt Codespace](#)
[rivt codespace](#)
[rivt doc](#)
[rivt docs](#)
[rivt file](#)
[rivt file number](#)
[rivt files](#)
[rivt folder](#)
[rivt framework](#)
[rivt log file](#)
[rivt markup](#)
[rivt report](#)
[rivt report folder](#)
[rivt reports](#)
[rivt string](#)

[rivtlib](#)
[rvspace](#)

S
[section parameter](#)
[section parameters](#)
[single doc](#)
[single docs](#)