

## Practical -18

**Aim:-** Write a Program for a basic hash function in a programming language of your choice. Demonstrate its usage to store and retrieve key-value pairs.

### Algorithm :-

#### 1. Initialization:

- Create a **HashMap<String, Integer>** to store key-value pairs (country names and populations).

#### 2. Add Key-Value Pair (put):

- To add a new key-value pair:
  - Use **map.put(key, value)** to insert the key and its corresponding value into the map.

#### 3. Update Value:

- To update the value associated with an existing key:
  - Use **map.put(key, newValue)** to overwrite the existing value.

#### 4. Remove Key-Value Pair (remove):

- To remove a key-value pair:
  - Use **map.remove(key)** to delete the entry associated with the specified key.

#### 5. Check for Key Existence (containsKey):

- To check if a key exists in the map:
  - Use **map.containsKey(key)** which returns **true** if the key is present, otherwise **false**.

#### 6. Retrieve Value (get):

- To retrieve the value associated with a key:

- Use **map.get(key)** which returns the value if the key exists, or **null** if it does not.

#### 7. Display All Key-Value Pairs:

- To display all entries in the map:
  - Iterate through **map.keySet()** and print each key along with its corresponding value.

#### 8. Array Operations (Optional):

- Create an array and demonstrate accessing its elements using both a traditional for loop and an enhanced for loop.

#### Program:-

```
import java.util.HashMap;
```

```
public class Hashh {  
    public static void main(String[] args) {  
        // Create a HashMap to store country populations  
        HashMap<String, Integer> map = new HashMap<>();  
  
        // Adding key-value pairs  
        map.put("India", 120);  
        map.put("USA", 30);  
        map.put("China", 150);  
        System.out.println("Initial Population Map: " + map);  
  
        // Updating a value
```

```
map.put("USA", 35);

System.out.println("Updated Population of USA: " + map.get("USA")); //
Output: 35
```

```
// Removing a key-value pair

map.remove("China");

System.out.println("Population of China after removal: " +
map.get("China")); // Output: null
```

```
// Searching for a key

if (map.containsKey("China")) {

    System.out.println("Key 'China' is present in the map.");

} else {

    System.out.println("Key 'China' is not present in the map.");

}
```

```
// Getting values of keys

System.out.println("Population of India: " + map.get("India")); // Key exists

System.out.println("Population of Indonesia: " + map.get("Indonesia")); //
Key doesn't exist
```

```
// Displaying all key-value pairs

System.out.println("All populations in the map:");

for (String country : map.keySet()) {

    System.out.println(country + ": " + map.get(country));

}
```

```

// Example of an array
int arr[] = {12, 15, 18};

System.out.println("Array elements:");
for (int i = 0; i < arr.length; i++) {
    System.out.print(arr[i] + " ");
}

System.out.println();

// Enhanced for loop for array
System.out.println("Array elements using enhanced for loop:");
for (int val : arr) {
    System.out.print(val + " ");
}

System.out.println();
}
}

```

```

Initial Population Map: {USA=30, China=150, India=120}
Updated Population of USA: 35
Population of China after removal: null
Key 'China' is not present in the map.
Population of India: 120
Population of Indonesia: null
All populations in the map:
USA: 35
India: 120
Array elements:
12 15 18
Array elements using enhanced for loop:
12 15 18
PS C:\Users\HP\OneDrive\Desktop\CC Program>

```