CS & IT ENGINEERING

Data Structure & Programming

Tree

Lec - 01

By- Pankaj Sharma sir

Tree-1

Tree

1. Directory structure
2. Organization
3. HTML/XML
4. Parse tree
5. Binary Search tree
6. Binary Heap
7. B-Tree, B+-Trees → DBMS



① Node : Each element is rep. by a node.

② child : 20 and 30 are child for node 10

7 is the child of 20
10 is the child of 20

③ Parent :



① Node : Each element is rep. by a node.

② child : 20 and 30 are child for node 100

7 is the child of 20
10 is the child of 20

③ Parent : 20 is the parent of 7.
20 is the parent of 10.
30 is the parent of 8, 3, 80



4) Root Node : Distinguishable node

Only node without any Parent.

100 is the root node.



5) Leaf Node : A node without any childs.

7, 10, 8, 5, 50, 80
all are leaf nodes.

6) Internal Node : Node with atleast 1 child.
(1 or more childs)

100, 20, 30, 3 are Internal nodes



7) Degree of a node : In tree,

degree of a node represents the no. of childs of a node.

degree of node with key 100 ⇒ 2

" " " 30 ⇒ 3

8.] Height of a node : Height of a node X is the length of path from node X to the farthest leaf node.



Height of a leaf node = 0





$$h(N) = 1 + \max(h_1, h_2, h_3)$$





Height of tree

= height of root node



tree with height = 3

9.) Level/Depth of a Node :

Level of a node X is the length of path from root node to node X.

Level of root node = 0






Root
100
20
30
7
10
8
3
80
5
50

10) Ancestor of a node :

If there is a path from node p to node q, then all the nodes in the path other than q are called as ancestor of q.

3, 30 and 100 are ancestor of 50.



10) Ancestor of a node :

If there is a path from node p to node q, then all the nodes in the path other than q are called as ancestor of q.

3, 30 and 100 are ancestor of 50.

OR

(i) Parent of a node is an ancestor.

and

(ii) Parent of some ancestor is also an ancestor



5 ⇒ direct Parent 3

30 is the parent of 3

⇒ 30 is also ancestor of 5

⇒ Parent of 30 is also an ancestor.

10) Ancestor of a node :



100 — None

20 — 100

30 — 100

7 — 20, 100

10 — 20, 100

8 — 30, 100

3 — 30, 100

80 — 30, 100

5 — 3, 30, 100

50 — 3, 30, 100

10) descendent of a node :

Ancestor

7 → 20, 100

7 is a descendent for 20

7 " " " 100



11) Sibling : Nodes with same parent

7, 10 are sibling

8, 3, 80 are siblings.

20, 30 are siblings.

5, 50 sibling

10, 8 → ~~sibling~~

Root Node Can not Have a sibling



12. Generation : All Nodes at a particular level belongs to same generation.



13. **Size of a node** : The no. of descendent of a node (including the node itself) is called as size of the node.

Size of node 30 ⇒ 6



13. **Size of a node**: The no. of descendent of a node (including the node itself) is called as size of the node.

Size of node 30 ⇒ 6

Size of leaf node ⇒ 1



Binary tree

Every node can have almost 2-child.

Node can have ⇒ 0 - child (leaf node)

1 - child

2 - child

[Internal node]


T1
1
T2
2
1
T3
3
2
1
T4
10
20
5
T5
1
2
3
4
T6
5
6
7
9
8
T7
1
2
3
10
20
5
3-childs

No. of nodes





$\Rightarrow$ FBT (Full Binary Tree)

What is the max. no. of nodes possible in a binary tree of height h ?

$h = 2$



Level	# of node
0	2^0
1	2^1
2	2^2
	7



Level	# nodes
0	2^0
1	2^1
2	2^2
3	2^3

$\#\text{nodes} = 2^0 + 2^1 + 2^2 + 2^3$ (G.P)

$= \frac{2^4 - 1}{2 - 1} = 2^4 - 1$

$= 15$



Level	Nodes
0	2^0
1	2^1
2	2^2
⋮	⋮
h-1	2^{h-1}
h	2^h

$$\text{Total} = 2^0 + 2^1 + 2^2 + \cdots + 2^h$$
$$= 1 + 2^1 + 2^2 + \cdots + 2^h$$
$$= \frac{2^{h+1} - 1}{2 - 1} = 2^{h+1} - 1$$

$$n_{max} = 2^{h+1} - 1$$

No. of nodes



What is the min. no. of nodes in a binary tree of height h ?

$h = 2$



$$n_{min} = h+1$$

{gmp <P.S Gate}

P x Q → more than 80

logic → → with time

Doubt ?

CP

↳ Prog lang

C++ Java

STL Collections

C, DS, Algo — Min 18

18-22 marks

1st year / 2nd year] standard Text books }

↓

10 subjects

Sem

C, Maths

6-7

College

→ bus/✓

→ Young

24 Hrs

5 AM → 1 hr

WhatsappX

↳ 1 hr

Job

Sat, Sun ⇒ 10 hrs × 2 = 20 hrs

weekdays ⇒ 2 hrs

30 hrs

```
int a;
cin>>a;
```

```
scanf("%d", &a);
```


THANK YOU GW
SOLDIERS !