Leakage_Aware_Flood_Forecasting_IEEE_REVISED_6page_...

Dhaka International University

Document Details

Submission ID
trn:oid:::3618:155812090

Submission Date
Oct 25, 2026, 3:54 PM GMT+6

Download Date
Oct 25, 2026, 3:57 PM GMT+6

File Name
Leakage_Aware_Flood_Forecasting_IEEE_REVISED_6page_UPDATED.docx

File Size
229.9 KB

6 Pages

5,449 Words

31,262 Characters

27% detected as AI

The percentage indicates the combined amount of likely AI-generated text as well as likely AI-generated text that was also likely revised by AI.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.

22 AI-generated 27%
Likely generated or likely generated and revised by AI.

Disclaimer
Our AI writing assessment is designed to help educators identify text that might be prepared by a generative AI tool. Our AI writing assessment may not always be accurate (it may misidentify writing that is likely human generated as AI generated and likely AI generated as human generated) so it should not be used as the sole basis for adverse actions against a student. It takes further scrutiny and human judgment in conjunction with an organization's application of its specific academic policies to determine whether any academic misconduct has occurred.

Leakage-Aware Probabilistic Flood Forecasting for Bangladesh: A Spatiotemporal Evaluation of Machine Learning and Deep Learning Models

Author Names and Affiliations Omitted for Double-Blind Review

Abstract—Flood models can appear overly skillful when temporal dependence, station overlap, or forward-looking features leak information. We present a leakage-aware framework for probabilistic danger-level forecasting at 133 Bangladesh Flood Forecasting and Warning Centre (FFWC) stations over 24, 48, and 72 h. The 200,665 station-day dataset combines 3-hourly water levels with meteorological, geospatial, upstream-discharge, soil-wetness, and neighbouring-station information. Predictors obey an issue-time boundary, and evaluation uses chronological validation, rolling-origin refits, station-disjoint folds, and a frozen post-2022 test. Twenty-four baseline, classical-ML, and deep-learning configurations are compared through one scoring pathway. The selected per-horizon model (D16) achieves mean PR-AUC 0.9574 on 2022 validation and 0.7708 on the frozen test, versus 0.6675 for persistence, outperforming persistence on all 21 test cell–horizon points. The best deep configuration reaches 0.9356 on validation; a matched fusion rematch remains 0.0206 below XGBoost. The ECE is 0.003–0.009, and TreeSHAP assigns 64% of 24 h attribution to local hydrology. A protocol audit also determined and corrected an intermediary in-sample scoring defect without changing the chosen model or frozen-test result. The findings show that reliable flood AI evidence depends as much on leakage-aware evaluation and robust baselines as on model complexity.

***Index Terms*—Flood forecasting, Bangladesh, probabilistic prediction, data leakage, spatiotemporal validation, gradient boosting, deep learning, calibration, SHAP.**

I. Introduction

Bangladesh is one of the most flood-exposed countries in the world, with riverine and coastal districts that depend on periodic warnings rather than on a single forecast of water level [1]. The Flood Forecasting and Warning Centre (FFWC) of the Bangladesh Water Development Board publishes station-specific warnings relative to a danger level: a fixed threshold above which a station is advised to be in flood [2]. Therefore, the concern is not the exact future stage in metres, but whether a station will cross that threshold in the next 24, 48, or 72 h. A probabilistic answer is more appropriate in this case because it allows warning authorities to trade missed events against false alarms.

Machine learning (ML) and deep learning (DL) are extensively used for short-term flood forecasting [3]–[5]. Studies in Bangladesh have explored rainfall–runoff behaviour, water-level regression, and climate scenarios [6]–[11], while broader work spans gradient boosting, recurrent networks, temporal convolutions, attention, and graph models [3], [4], [12]. However, most works anticipate the continuous stage, use a single split, or segregate models under different inputs. Thus, the results do not establish the skill for danger-level warning.

Three issues are central to warning-oriented evaluation. Hydro-meteorological autocorrelation makes random splits optimistic [13]; feature engineering and preprocessing can cause leakage [14], [15]; and accuracy or ROC-AUC can be misleading for drifting exceedance rates [16]. We therefore incorporate an issue-time information boundary, temporal and spatial refitting, consistent benchmarking, calibration, and event-oriented metrics.

We make three contributions. First, we formulate 24/48/72 h station-specific danger-level exceedance with leakage-controlled rolling-origin and station-disjoint evaluation, including a documented protocol correction. Second, we compare 24 configurations that include seven baselines, five classical models, and twelve DL configurations under common partitions, labels, seeds, metric code, and tuning budget. Third, we assess the selected model against persistence on trained, new-network, and unseen stations using calibration, cost-sensitive thresholds, event detection, and TreeSHAP. The objective is a decision-oriented benchmark rather than a claim that one architecture is universally superior.

II. Related Work and Research Gap

Data-driven flood forecasting now employs tree ensembles, recurrent and convolutional sequence models, transformers, and graph networks [12], [17]–[26]. LSTM-based rainfall–runoff modelling has demonstrated strong sequence-learning capability [21], [38], while XGBoost and LightGBM remain competitive for engineered tabular predictors [17], [18]. Reviews progressively emphasise interpretability and reliable out-of-sample testing alongside predictive accuracy [39], [40].

Recent work in Bangladesh has shown effective signal for water-level and discharge prediction and has begun to examine spatial transferability [6]–[11]. However, the operational FFWC task is different from generic regression: the goal is a rare threshold crossing for specific stations, miss and false-alarm costs differ, and useful evidence must differentiate future-time from unseen-station generalisation.

Therefore, the research gap is methodological: leakage-aware, multi-horizon, station-level evidence that uses a persistence reference, segregates temporal and spatial generalisation, reports calibration and event detection, and explains predictions hydrologically remains limited [13], [16], [29]–[32]. This gap is addressed by treating evaluation design as a first-class contribution and by reporting an internal protocol correction transparently.

III. Dataset and Forecast Formulation

A. Data Sources and Coverage

Primary data include the FFWC station master and 1,052,044 three-hourly water-level observations between January 2017 and October 2026. From a list of 153 stations, 133 have usable danger levels and at least one valid label; 2018 is excluded as missing. Predictor data include NASA POWER/MERRA-2 meteorological data [37], SRTM topographic data [36], OpenStreetMap and geoBoundaries attributes [41], [42], GloFAS discharge data [35], and POWER soil moisture. ERA5-Land [34] was tested but not used because it did not improve validation skill.

Three-hourly observations were summarised into daily maxima, mean, minima, last observed, and reading count using a full calendar of station-days. After quality control, the dataset contains 200,665 station-days across 133 stations. The number of stations in the network progresses from 85 in 2017 to 133 by the end of the record. This increase is reflected in the validation setup (Table I).

TABLE I
Data Partitions and Danger-Level Base Rates

Partition	Rows	Stations	24 h	48 h	72 h
Training	77,571	105	9.60	10.72	11.73
Validation	21,920	105	5.08	5.96	6.64
Frozen test	101,174	133	1.41	1.77	2.12

Base rates are percentages of labelled station-days. The test period is 2023-01-27 to 2026-10-05; 2018 is absent from the FFWC archive.

Table note: The training and validation numbers in the table include station-holdout data, which are not used during model fitting under P1. The actual numbers are 61,991 training and 17,538 validation rows, and the frozen test is unchanged (101,174 rows, 133 stations).




Fig. 1. Temporal coverage and label prevalence. (a) Training, validation, and frozen-test spans; the 2018 archive gap is preserved as missing. (b) Annual 72 h positive rate, showing the 14-fold decline from 2017 to 2023 and the higher prevalence of the development years. Cell-level, not pooled, evaluation follows from this drift.

B. Forecast Formulation and Labels

Let s index a station, t an issue day, and $h \in \{24,48,72\}$ the lead time in hours. The model estimates the probability that station s reaches its danger level D_s within the next h hours, using only information available at the end of day t:

$$P_{s,t,h} = \Pr(Y_{s,t,h} = 1 \mid I_{s,t}) \quad (1)$$

where $I_{s,t}$ is the issue-time information set. The label is an indicator of any observed 3-hourly reading in the forward window reaching the station danger level:

$$Y_{s,t,h} = 1\{\max_u \in (t,t+h]\ W_{s,u} \geq D_s\} \quad (2)$$

A negative label is assigned only when the full forecast window is sufficiently observed and no reading reaches danger level; otherwise the label is missing. Positives are retained when any observed exceedance occurs. Valid labels number 200,559, 197,748, and 195,174 at 24, 48, and 72 h, with positive rates of 4.98%, 5.68%, and 6.32%. Strong temporal drift—the 72 h rate falls from 16.81% in 2017 to 1.19% in 2023—and a 5.4× monsoon/non-monsoon contrast motivate cell- and season-specific reporting.

C. Spatiotemporal Partitions

Random partitioning is avoided. The chronological split uses 2017–2021 for training (77,571 rows), 2022 for validation (21,920), and 2023–2026 for the frozen test (101,174). Natural dry-season gaps of 88–131 days separate the periods; a seven-day embargo is retained as a safety rule.

Spatial generalisation uses five station-disjoint folds. Fold 0 is the frozen unseen holdout (26 stations); folds 1–4 support development. Test stations are also classified as trained, new-network, or unseen. Five protocols are used: P1 primary 2022 validation; P2 rolling-origin 2020–2022 refits; P3 four-fold station-disjoint refits; P4 frozen unseen-station testing; and P5 monsoon/non-monsoon stratification. The seven development cells are val_2020, val_2021, val_2022, and spatial folds 1–4.

IV. Methodology

A. Features and Leakage Control

FULL contains 62 predictors spanning weather, rainfall history, geography, local hydrology, and the station network. With the addition of soil moisture, GloFAS flow, water-level persistence, and antecedent precipitation features, the controlled dataset FULL_V2 holds 110 features. Hydrological features include relative water levels, distance to danger, recent maxima, rise rates, exceedance counts, and antecedent rainfall.

All features used on issue day t capture only information available at the end of day t. Any IDs, dates, labels, origin information, and future observations are excluded; lagged and rolling features are always backward-looking; preprocessing is fitted within each training fold; and sequence-based features cannot overlap across station or split boundaries. Neighbour features are created on the operational station network prior to assigning folds. As a result, rows of the target variable are disjoint between stations, but the covariates are not completely disjoint. This is noted as a shortcoming.

B. Models and Tuning

We compare 24 model configurations: seven baseline models (including D7 hydrological persistence), five classical models—random forest [19], gradient boosting [20], XGBoost [17], LightGBM [18], and XGBoost with feature selection—and twelve deep learning configurations (LSTM [21], GRU [22], TCN [23], fusion models, GCN [25], GAT [26], GNN–

LSTM, and Transformer [24]). Models were trained separately for each horizon. Classical models were trained using tabular features, while sequential models use a 12-variable raw sequence and fusion models combine both.

Hyperparameters are fixed with common splits, labels, seeds, and metric code. D16 shows the highest horizon-mean PR-AUC on val_2022 while achieving higher accuracy than D7 in each development cell with ECE ≤ 0.02; it was selected using LightGBM (24/48 h) and XGBoost (72 h) on FULL_V2. A supplementary matched fusion rematch had the same engineered vector, five anchors, three seeds, and station bootstrap; because only the fusion family completed this rig, it is confirmatory rather than a full DL rerun.

C. Metrics and Decision Rules

The area under the precision–recall curve (PR-AUC, average precision) was treated as the primary metric for each horizon, cell, and season [16]. A secondary metric, ROC-AUC, is also reported. Average precision is

$$\mathrm{AP} = \Sigma_n (R_n - R_{n-1}) P_n \quad (3)$$

where P_n and R_n stand for precision and recall at the n-th threshold. Operational metrics include recall, precision, missed flood rows, and false-alarm rate at a cost-sensitive threshold. Calibration is assessed using the Brier score [31] and expected calibration error (ECE) with ten equal-width bins:

$$\mathrm{ECE} = \Sigma_{b=1}^{B} (n_b/N) \, |\bar{y}_b - \bar{p}_b| \quad (4)$$

The operating threshold is chosen to minimize the row cost

$$C(\tau) = C_{FN} \, \mathrm{FN}(\tau) + C_{FP} \, \mathrm{FP}(\tau) \quad (5)$$

with C_{FN}:C_{FP} = 10:1 for the main experiment and 5:1 and 20:1 for assessing sensitivities. These thresholds were derived using development data and were kept frozen before the test read. Four research risk levels (low, moderate, high, and very high) were set based on the cost-optimal threshold; these are not official FFWC warning levels. Events were labelled by grouping together consecutive positive days at each station, bridging one-day gaps. During the test read with the frozen threshold, events were detected when there was any anomaly in the time period [start − h, end]. During development, a stricter event definition was used: events must be preceded by a warning, unverifiable events were excluded, and false-alarm episodes were counted outside the event and lead window.

Explanations use exact TreeSHAP on each frozen booster [27], [28]. SHAP values are aggregated to the nine feature groups, and cross-model agreement is measured by Spearman rank correlation against the Phase-33 XGBoost incumbent. Permutation importance is computed as a second opinion, but it is known to be unstable under collinearity; disagreements are reported rather than hidden.

D. Reproducibility and Test Discipline

All runs use seed 20261008; uncertainty uses station bootstrap, and scripts/configurations are preserved with a SHA-256 manifest. The programme-level frozen test was opened six times (five predictive reads, one invalid and retracted, plus one label-statistics read). D16's reported MI-6 read was pre-registered and reproduced bit-for-bit by MI-9. Thus the test is frozen for D16 but not pristine for the programme, and this history is disclosed explicitly.

V. Results

A. Classical ML versus Deep Learning

Table II reports validation PR-AUC on P1 val_2022 for representative models; the full 24-configuration table is preserved in the reproducibility package. The best classical model is XGBoost, with a horizon mean of 0.9546 (0.9681, 0.9549, and 0.9408 at 24, 48, and 72 h). LightGBM is statistically indistinguishable at 0.9534, and the top four classical models lie within 0.0023 of one another. The fusion model stands highest among all deep learning models at 0.9356 (0.9444, 0.9385, and 0.9238), which is 0.0190 below XGBoost. All classical models outperform all deep learning models at all horizons. However, not all deep learning models are equal: the transformer and GCN models fall around the middle of the deep learning models (higher than TCN but lower than the other models).

TABLE II
P1 Validation PR-AUC on val_2022 (all season)

Model	24 h	48 h	72 h	Mean
D7 persistence	0.9203	0.8954	0.8683	0.8947
Climatology	0.0509	0.0594	0.0658	0.0587
Logistic regression	0.9401	0.9241	0.9053	0.9232
Gradient boosting	0.9618	0.9457	0.9338	0.9471
Random forest	0.9665	0.9516	0.9389	0.9523
XGBoost-selected	0.9663	0.9533	0.9422	0.9539
LightGBM	0.9682	0.9538	0.9384	0.9534
XGBoost	0.9681	0.9549	0.9408	0.9546
LSTM-3	0.9421	0.9253	0.9129	0.9268
GRU	0.9359	0.9263	0.9086	0.9236
TCN	0.9405	0.9224	0.9008	0.9212
Fusion	0.9444	0.9385	0.9238	0.9356
GCN	0.9421	0.9353	0.9141	0.9305
GAT	0.9408	0.9315	0.9136	0.9286
GNN–LSTM	0.9424	0.9264	0.9153	0.9280
Transformer	0.9437	0.9330	0.9183	0.9317

Representative subset of the 24 configurations. D16 is the selected per-horizon ensemble (0.9708/0.9565/0.9450; mean 0.9574), not a single row in this table.




Fig. 2. Validation PR-AUC by horizon for representative models. Gradient-boosted trees occupy the top of every horizon; the fusion model is the strongest DL configuration but remains below the classical leaders. Values are from the P1 val_2022 cell.

Cell-level intervals overlap because only 84 validation stations contribute to one year, but paired bootstrap comparisons favour XGBoost over the matched fusion model at all horizons: −0.0228, −0.0190, and −0.0165 (fusion minus XGBoost), with all 95% intervals excluding zero. The mean gap is −0.0194; fusion is well calibrated but ranks worse and yields more false alarms.

Model complexity does not improve this task: the fusion model has 58,817 weights and is slower than XGBoost-selected, while its spatial-fold performance degrades more sharply. Engineered lag features therefore capture local persistence more efficiently than the tested DL representations.

B. Selected Model and Frozen Test

D16 achieves 0.9708, 0.9565, and 0.9450 on val_2022 (mean 0.9574), marginally above the best single classical model because it selects the best per-horizon learner rather than forcing one family. On the frozen test (Table III), D16 achieves 0.8362, 0.7690, and 0.7071 (mean 0.7708), against D7 persistence at 0.7340, 0.6625, and 0.6062 (mean 0.6676). The performance of D16 is higher than persistence for each cell–horizon pair. The smallest improvement is recorded at unseen stations (72 h, +0.0424).

TABLE III
Frozen-Test PR-AUC: D16 versus D7 Persistence

Test cell	24 h	48 h	72 h	Mean Δ
2023	0.796 / 0.628	0.681 / 0.552	0.626 / 0.511	+0.137
2024	0.918 / 0.802	0.857 / 0.730	0.804 / 0.673	+0.125
2025	0.805 / 0.733	0.760 / 0.667	0.702 / 0.604	+0.088
2026	0.794 / 0.723	0.747 / 0.649	0.702 / 0.593	+0.092
Trained	0.869 / 0.747	0.806 / 0.702	0.764 / 0.593	+0.133
New network	0.843 / 0.736	0.787 / 0.693	0.713 / 0.646	+0.090
Unseen	0.830 / 0.770	0.742 / 0.669	0.641 / 0.599	+0.058
Mean	0.836 / 0.734	0.769 / 0.663	0.707 / 0.606	+0.103

Each cell shows D16 / D7. Mean Δ is the mean of the three per-horizon differences, not a difference of means. All 21 cell–horizon comparisons favour D16.




Fig. 3. Frozen-test PR-AUC by cell and horizon. Circles are D16 and squares are D7 persistence. D16 is above persistence in every cell–horizon pair; the smallest margin is unseen stations at 72 h (+0.0424).

Test scores are lower than validation because prevalence changes sharply: the 24 h base rate falls from 5.08% to 1.41%. D16 still exceeds persistence for all test cell–horizon pairs, but performs least well at 72 h and 2023. This variation highlights the importance of temporally separated evaluation.

D16 outperforms XGBoost in 6 of 7 test cells; XGBoost is better only in 2025, with a slightly higher 72 h mean (0.7092 vs. 0.7071). Gains over persistence are therefore consistent, although D16 does not beat every classical alternative.

The model is well calibrated, with a mean ECE of 0.0028, 0.0042, and 0.0085 at 24/48/72 h and all 21 cell–horizon pairs below 0.02. At the frozen 10:1 thresholds, recall is 0.918, 0.903, and 0.856 and precision is 0.549, 0.388, and 0.351. The best operating point will be selected by the warning service.

During validation, approximately 5–6% of rows fell in the very high risk category, with an actual flood rate near 90%; these are only research categories, not FFWC warning levels. Under the lenient frozen-test event criteria, the model detected 93.0%, 96.5%, and 96.9% of events at 24, 48, and 72 h, versus 86.4%, 92.7%, and 91.2% for D7.

C. Temporal and Spatial Generalisation

After the preregistered correction, D16 has a higher score than D7 on all 21 development cell–horizons (minimum +0.0156). The corrected average score is 0.9665 across the seven cells; however, this should be interpreted descriptively due to near saturation of four spatial folds and a much lower test base rate.

The three classical models exceed D7 in all 63 cell–horizon comparisons for all seasons. However, in extreme rainfall and stricter one-day issue-shift scenarios there are losses. It can therefore be stated that D16 performs well across all seasons but is not overall superior.

The ablation study shows that adding local hydrology to weather and geography raises mean PR-AUC by +0.4702 (95% CI +0.389 to +0.539), whereas the station-network features contribute only +0.0009 and dropping four upstream columns changes the mean by −0.0001. Therefore, the model is mainly driven by local hydrological features and rainfall history. This is supported by the SHAP analysis and by the small increases from the GNN.

D. Protocol Audit and the P2/P3 Correction

The protocol audit demonstrated that the intermediate MI-8 probe scored six of the seven development cells using a model already fitted on those rows. The average scores for the FULL, FULL_V2, and FULL_V3 models improve by refitting each cell. These improve from 0.9834, 0.9868, and 0.9882 to 0.9641, 0.9659, and 0.9678, respectively (Table IV). The feature audit still passed, and val_2022 and the frozen test were untouched.

TABLE IV
P2/P3 Re-Scoring Correction

Quantity	Archived	Corrected	Change
FULL, 7-cell mean	0.9834	0.9641	−0.0194
FULL_V2, 7-cell mean	0.9868	0.9659	−0.0209
FULL_V3, 7-cell mean	0.9882	0.9678	−0.0204
FULL_V3 − FULL_V2	+0.00136	+0.00187	+0.00051
V3 wins, cell–horizon points	21/21	20/21	−1
D16 − D7 floor	+0.0225	+0.0156	−0.0069

The archived values scored six cells with a model fitted on those cells. Corrected values refit each cell. The champion and the frozen-test read are unchanged because val_2022 was always out of sample.

The corrected scores show that FULL_V3 exceeds the other model by +0.00187 and wins 20/21 cell–horizon points; the minimum gap between D16 and D7 is now +0.0156. This episode is important because leakage-aware evaluation must audit scoring masks as well as predictor construction.

E. Strict Event-Level Evaluation

Performance is considered in terms of strict development analysis, which ensures that a warning is issued only before the event occurs. D16 has better recall at all horizons compared to D7, with 50.9%, 72.4%, and 88.1% at 24, 48, and 72 h, respectively. D7 had recall values of 45.2%, 64.9%, and 76.7%.

TABLE V
Strict Event-Level Performance on Development Cells

Horizon	D16 recall	D7 recall	D16 FA	D7 FA
24 h	50.9%	45.2%	0.58	1.56
48 h	72.4%	64.9%	0.98	1.97
72 h	88.1%	76.7%	2.30	2.44

Mean across all seven development cells. Recall requires a warning before event onset; FA is false alarms per station-year. The frozen test was not reopened.

The relaxed event definition results in higher recall by including any alert within the lead/event period. However, the stricter definition counts false-alarm episodes outside the event periods. Considering both metrics separately avoids any claim that one definition benefited from the other.

F. Hydrologically Interpretable Explanations

The local hydrology group accounts for 64.0% of mean absolute 24 h attribution using TreeSHAP in the frozen D16 boosters. Geography, network, weather, GloFAS, and interactions contribute 8.4%, 6.1%, 4.7%, 4.6%, and 4.1%, respectively, whilst soil moisture, flow memory, and rainfall history contribute 4.1%, 2.4%, and 1.5%. The top individual features are current water level as a fraction of danger level, distance to danger, seven-day maximum water level, upstream water level, and 72 h rainfall. This is intuitive to a hydrologist: local stage dominates the analysis, followed by upstream and rainfall information providing context.




Fig. 4. Share of mean absolute TreeSHAP attribution by feature group at 24 h on val_2022. Hydrology dominates; network and rainfall-history groups are small once local stage is known.

Feature-group explanations are stable across models (Spearman ρ = 0.755–0.878 between D16 and the earlier XGBoost incumbent). Permutation importance, however, varies at 24 h due to collinearity; therefore only feature-group TreeSHAP was used for interpretation, and individual feature ranks were not over-interpreted.

VI. Discussion and Limitations

A. Why Gradient Boosting Wins Here

This is a task-specific result. Exceeding danger levels can be seen as a rare-event problem using tabular, autocorrelated data with engineered lags. Gradient-boosted trees use the threshold nature and persistence effectively. Although the fusion rematch lessens the variation in the representation, it still underperforms compared to XGBoost by 0.0206. This does not mean that DL is not suitable for flood forecasting; it simply shows that there are not enough inputs to justify the additional complexity.

The ablation highlights this: the majority of the skill comes from the local hydrology group, while the network features do not contribute much once local stage is known. This indicates that data quality, label definitions, and hydrological features are more important than having a larger architecture for this situation.

B. What the Protocol Audit Changes

The P2/P3 defect is a validation leak, not a feature leak. Refitting the model per cell can reduce the development means by approximately 0.02, as they were close to saturation; however, this did not affect the champion or frozen test results, as val_2022 was always out of sample. Automated leakage checks must therefore test evaluation masks as well as features.

The test ledger showed that the programme entered the frozen period before D16 was finalised. Although the preregistered read of D16 was carried out exactly as specified, the test was not immaculate. Therefore, benchmark studies should report each test opening, the model version, and whether the result impacted selection.

C. Operational Interpretation

The findings indicate that D16 is better suited to support operational flood forecasting than to replace existing models. At 24 h it exceeds persistence, although precision at the 10:1 threshold remains 0.55; at 72 h it is less competitive, with the earlier XGBoost model slightly higher. Because it uses no forecast rainfall or numerical weather prediction (NWP) data, its predictions rely on observed water level, upstream propagation, and recent rainfall. Forecast rainfall is therefore the clearest route to longer-lead skill.

Cost-sensitive thresholds provide an explicit way to audit the trade-off between flood events and false alarms, but the 5:1–20:1 ratios and four risk bands represent research assumptions. These thresholds should be recalibrated using cost estimates and input from relevant stakeholders.

D. Limitations

Several limitations should be considered. These include the non-immaculate programme-level test history, the absence of future rainfall and NWP inputs, the missing 2018 archive, and the incomplete 2026 record. Variations in station coverage and administrative danger levels may also affect data consistency, and neighbour/upstream variables are not fully isolated across spatial folds, limiting spatial independence.

The deep-learning comparison also has limitations: a matched rematch was conducted only for the fusion configuration, and val_2022 was blocked during model selection. The strict development event definition also differs from the permissive test definition, which may affect comparability. Finally, SHAP explanations indicate associations, not causal relationships.

Acknowledging these limitations, D16 is best regarded as a strong benchmark and a promising candidate for prospective evaluation. Further testing under operational conditions is necessary before it can be considered suitable for deployment as a flood-warning system.

VII. Conclusion

We present a leakage-aware probabilistic framework for 24/48/72 h FFWC danger-level risk prediction in Bangladesh. D16 stands at the top when evaluated on the 2022 validation set (mean PR-AUC: 0.9574) and achieves 0.7708 on the frozen test. It exceeds persistence results (PR-AUC: 0.6675) across all 21 test cell–horizon points. The top-performing DL model achieved a PR-AUC of 0.9356 on the validation set, and a

matched fusion rematch remained 0.0206 below XGBoost. The model is well calibrated, strict event recall improved over persistence at 48–72 h, and TreeSHAP attributes 64% of 24 h importance to local hydrology. An intermediate in-sample scoring defect was corrected during a protocol audit but did not affect the scores of the top performers. Overall, it has been shown that reliable flood AI requires methods that are leakage-aware, with good hydrological baselines and transparent test discipline. Future work should include forecast rainfall and potential operational evaluation.

REFERENCES

[1] J. Rentschler, M. Salhab, and B. A. Jafino, "Flood exposure and poverty in 188 countries," Nature Communications, vol. 13, no. 1, Art. no. 3527, 2022, doi: 10.1038/s41467-022-30727-4.

[2] Flood Forecasting and Warning Centre, Bangladesh Water Development Board, "Annual flood report 2023," Dhaka, Bangladesh, 2023. [Online]. Available: http://www.ffwc.gov.bd/

[3] M. Asif, M. M. Kuglitsch, I. Pelivan, and R. Albano, "Review and intercomparison of machine learning applications for short-term flood forecasting," Water Resources Management, vol. 39, pp. 1971–1991, 2025, doi: 10.1007/s11269-025-04093-x.

[4] B. Kuhaneswaran, G. Sorwar, A. R. Alaei, and F. Tong, "Evolution of data-driven flood forecasting: Trends, technologies, and gaps—A systematic mapping study," Water, vol. 17, no. 15, Art. no. 2281, 2025, doi: 10.3390/w17152281.

[5] A. H. Akinsoji, B. Adelodun, Q. Adeyi, R. A. Salau, G. Odey, and K. S. Choi, "Integrating machine learning models with comprehensive data strategies and optimization techniques to enhance flood prediction accuracy: A review," Water Resources Management, vol. 38, no. 12, pp. 4735–4761, 2024, doi: 10.1007/s11269-024-03885-x.

[6] F. Noor, S. Haq, M. Rakib, T. Ahmed, Z. Jamal, Z. S. Siam, R. T. Hasan, M. S. G. Adnan, A. Dewan, and R. M. Rahman, "Water level forecasting using spatiotemporal attention-based long short-term memory network," Water, vol. 14, no. 4, Art. no. 612, 2022, doi: 10.3390/w14040612.

[7] M. T. Islam, S. C. Roy, N. Jahan, A. A. Ferdaus, K. Fujisawa, and A. K. M. Adham, "Comparative evaluation of machine learning models for extreme river water level forecasting in Bangladesh: Implications for flood and drought resilience," Progress in Disaster Science, vol. 27, Art. no. 100449, 2025, doi: 10.1016/j.pdisas.2025.100449.

[8] M. T. Islam, M. A. Al-Sufi Ridoy, N. Jahan, S. C. Roy, and A. K. M. Adham, "From short to long-term horizons: Comparative assessment of machine learning and deep learning for river stage prediction with spatial transferability analysis," Results in Engineering, vol. 28, Art. no. 108194, 2025, doi: 10.1016/j.rineng.2025.108194.

[9] M. T. Islam, S. C. Roy, N. Jahan, N. Islam, and A. K. M. Adham, "From climate signals to smart predictions: Advanced machine learning and deep learning for hydrological modeling in data-scarce Bangladesh," H2Open Journal, vol. 9, no. 2, pp. 81–109, 2026, doi: 10.2166/h2oj.2026.036.

[10] M. T. Islam, S. C. Roy, N. Jahan, M. S. I. Yousuf, and A. K. M. Adham, "Extending river discharge forecast lead times with machine and deep learning for proactive hydrological hazard management in Bangladesh," H2Open Journal, vol. 9, no. 3, Art. no. 100013, 2026, doi: 10.2166/h2oj.2026.100013.

[11] K. N.-e.-A. Siddiquee, M. T. Sarker, M. Al Qwaid, N. Barua, K. S. Akter, S. Chowdhury, and M. S. Hossen, "Advanced machine learning techniques for daily streamflow forecasting: A case study of the Brahmaputra River," Scientific Reports, 2026, doi: 10.1038/s41598-026-69747-1.

[12] A. Mosavi, P. Ozturk, and K.-W. Chau, "Flood prediction using machine learning models: Literature review," Water, vol. 10, no. 11, Art. no. 1536, 2018, doi: 10.3390/w10111536.

[13] D. R. Roberts et al., "Cross-validation strategies for data with temporal, spatial, hierarchical, or phylogenetic structure," Ecography, vol. 40, no. 8, pp. 913–929, 2017, doi: 10.1111/ecog.02881.

[14] S. Kaufman, S. Rosset, C. Perlich, and O. Stitelman, "Leakage in data mining: Formulation, detection, and avoidance," ACM Transactions on Knowledge Discovery from Data, vol. 6, no. 4, Art. no. 15, pp. 1–21, 2012, doi: 10.1145/2382577.2382579.

[15] S. Kapoor and A. Narayanan, "Leakage and the reproducibility crisis in machine-learning-based science," Patterns, vol. 4, no. 9, Art. no. 100804, 2023, doi: 10.1016/j.patter.2023.100804.

[16] T. Saito and M. Rehmsmeier, "The precision-recall plot is more informative than the ROC plot when evaluating binary classifiers on imbalanced datasets," PLoS ONE, vol. 10, no. 3, Art. no. e0118432, 2015, doi: 10.1371/journal.pone.0118432.

[17] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in Proc. 22nd ACM SIGKDD Int. Conf. Knowledge Discovery and Data Mining, 2016, pp. 785–794, doi: 10.1145/2939672.2939785.

[18] G. Ke et al., "LightGBM: A highly efficient gradient boosting decision tree," in Advances in Neural Information Processing Systems, vol. 30, 2017, pp. 3146–3154.

[19] L. Breiman, "Random forests," Machine Learning, vol. 45, no. 1, pp. 5–32, 2001, doi: 10.1023/A:1010933404324.

[20] J. H. Friedman, "Greedy function approximation: A gradient boosting machine," The Annals of Statistics, vol. 29, no. 5, pp. 1189–1232, 2001, doi: 10.1214/aos/1013203451.

[21] S. Hochreiter and J. Schmidhuber, "Long short-term memory," Neural Computation, vol. 9, no. 8, pp. 1735–1780, 1997, doi: 10.1162/neco.1997.9.8.1735.

[22] K. Cho et al., "Learning phrase representations using RNN encoder–decoder for statistical machine translation," in Proc. Conf. Empirical Methods in Natural Language Processing, 2014, pp. 1724–1734, doi: 10.3115/v1/D14-1179.

[23] S. Bai, J. Z. Kolter, and V. Koltun, "An empirical evaluation of generic convolutional and recurrent networks for sequence modeling," arXiv:1803.01271, 2018.

[24] A. Vaswani et al., "Attention is all you need," in Advances in Neural Information Processing Systems, vol. 30, 2017, pp. 5998–6008.

[25] T. N. Kipf and M. Welling, "Semi-supervised classification with graph convolutional networks," in Proc. Int. Conf. Learning Representations, 2017.

[26] P. Veličković et al., "Graph attention networks," in Proc. Int. Conf. Learning Representations, 2018.

[27] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in Advances in Neural Information Processing Systems, vol. 30, 2017, pp. 4765–4774.

[28] S. M. Lundberg et al., "From local explanations to global understanding with explainable AI for trees," Nature Machine Intelligence, vol. 2, no. 1, pp. 56–67, 2020, doi: 10.1038/s42256-019-0138-9.

[29] A. Niculescu-Mizil and R. Caruana, "Predicting good probabilities with supervised learning," in Proc. 22nd Int. Conf. Machine Learning, 2005, pp. 625–632, doi: 10.1145/1102351.1102430.

[30] C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger, "On calibration of modern neural networks," in Proc. 34th Int. Conf. Machine Learning, 2017, pp. 1321–1330.

[31] G. W. Brier, "Verification of forecasts expressed in terms of probability," Monthly Weather Review, vol. 78, no. 1, pp. 1–3, 1950, doi: 10.1175/1520-0493(1950)078<0001:VOFEIT>2.0.CO;2.

[32] C. A. T. Ferro and D. B. Stephenson, "Extremal dependence indices: Improved verification measures for deterministic forecasts of rare binary events," Weather and Forecasting, vol. 26, no. 5, pp. 699–713, 2011, doi: 10.1175/WAF-D-10-05030.1.

[33] B. Efron and R. J. Tibshirani, An Introduction to the Bootstrap. New York, NY, USA: Chapman & Hall, 1993.

[34] J. Muñoz-Sabater et al., "ERA5-Land: A state-of-the-art global reanalysis dataset for land applications," Earth System Science Data, vol. 13, no. 9, pp. 4349–4383, 2021, doi: 10.5194/essd-13-4349-2021.

[35] L. Alfieri et al., "GloFAS – global ensemble streamflow forecasting and flood early warning," Hydrology and Earth System Sciences, vol. 17, no. 3, pp. 1161–1175, 2013, doi: 10.5194/hess-17-1161-2013.

[36] T. G. Farr et al., "The Shuttle Radar Topography Mission," Reviews of Geophysics, vol. 45, no. 2, Art. no. RG2004, 2007, doi: 10.1029/2005RG000183.

[37] NASA Langley Research Center, "POWER project data sets," 2024. [Online]. Available: https://power.larc.nasa.gov/

[38] F. Kratzert, D. Klotz, C. Brenner, K. Schulz, and M. Herrnegger, "Rainfall–runoff modelling using long short-term memory (LSTM) networks," Hydrology and Earth System Sciences, vol. 22, no. 11, pp. 6005–6022, 2018, doi: 10.5194/hess-22-6005-2018.

[39] M. Reichstein et al., "Deep learning and process understanding for data-driven Earth system science," Nature, vol. 566, pp. 195–204, 2019, doi: 10.1038/s41586-019-0912-1.

[40] M. Sit et al., "A comprehensive review of deep learning applications in hydrology and water resources," Water Science and Technology, vol. 82, no. 12, pp. 2635–2670, 2020, doi: 10.2166/wst.2020.369.

[41] OpenStreetMap contributors, "Planet dump," 2024. [Online]. Available: https://planet.openstreetmap.org/

[42] D. Runfola et al., "geoBoundaries: A global database of political administrative boundaries," PLoS ONE, vol. 15, no. 4, Art. no. e0231866, 2020, doi: 10.1371/journal.pone.0231866.