PROGRAMMING WITH PYTHON
SUBJECT CODE : 202044504

DEPARTMENT OF INFORMATION TECHNOLOGY
SEMESTER 5

NAME : Rana Riyancee
ENROLLMENT NO. : 12402080601119
BATCH :IT_B (2B8)
ACADEMIC YEAR : 2026-27

Github Link :
https://github.com/12502080603005adit/12502080603005_Python_Assignment/tree/main/Assignment2

ASSIGNMENT-2

PROBLEM STATEMENT 1: Given a large text file containing noisy text, extract all valid email addresses whose top-level domain is com, edu or org. Username may contain letters, digits, plus, dot, underscore or hyphen. For each domain, print the number of unique users and the lexicographically smallest email. Invalid emails must be ignored.

CODE :

```
import re from collections import
defaultdict

def main():
    filename = input("Enter text file path: ").strip()
    pattern = re.compile(r'(?<![\w.+-])[\w.+-]+@[\w.-]+\.(?:com|edu|org)\b')
    emails = defaultdict(set)

    try: with open(filename, encoding="utf-8") as
        f:
            for line in f:
                for email in pattern.findall(line):
                    domain = email.split("@", 1)[1]
                    emails[domain].add(email)

        for domain in sorted(emails):
            values = sorted(emails[domain]) print(domain,
            len(values), values[0])

    except FileNotFoundError:
        print("File not found.")

if name ____== " main ": main()
```

OUTPUT :

```
Enter text file path: emails.txt
adit.edu 1 a.b+1@adit.edu
x.org 1 test-user@x.org
```

PROBLEM STATEMENT 2: You are given multiple saved HTML pages of product listings. Extract product name, price and rating from each page using regular expressions or an HTML

parser. Normalize prices, remove duplicate products by name, and print the top K products with highest rating; ties are broken by lower price and then lexicographic product name.

CODE :

```
import re import
os

def read_products(filename):
    with open(filename, encoding="utf-8") as f: html
        = f.read()

    pattern = re.compile( r'<h2[^>]*>(.*?)</h2>.*?'
        r'class=["\'][^"\']*price[^"\']*["\'][^>]*>(.*?)</[^>]+>.*
        ?'
        r'class=["\'][^"\']*rating[^"\']*["\'][^>]*>(.*?)</[^>]+>',
        re.I | re.S
    )

    products = [] for name, price, rating in
    pattern.findall(html): name =
    re.sub(r"<[^>]+>", "", name).strip() price =
    float(re.sub(r"[^\d.]", "", price)) rating =
    float(re.sub(r"[^\d.]", "", rating))
    products.append((name, price, rating))
    return products
def main(): try:
        p, k = map(int, input().split())
        products = {}

        for _ in range(p):
            filename = input().strip() if
            not os.path.isfile(filename):
                print("File not found:", filename) return

            for name, price, rating in read_products(filename):
                if name not in products or (rating, -price) > (
                products[name][1], -products[name][0]
                ):
                    products[name] = (price, rating)
```

```
    result = sorted(
        products.items(), key=lambda x: (-
        x[1][1], x[1][0], x[0])
    )[:k]

    for name, (price, rating) in result: price =
        int(price) if price.is_integer() else price
        print(name, price, rating)

except ValueError:
    print("Invalid input.")

if name ____== " main ": main()
```

OUTPUT :

```
2 2
page1.html
page2.html
Python Book 499 4.8
C++ Book 599 4.8
```

PROBLEM STATEMENT 3: Create a Python program that connects to a MySQL database, creates Student and Course Registration tables if they do not exist, inserts records from CSV files, and displays students registered for a given course with SPI greater than a threshold. Use parameterized queries and handle database exceptions.

CODE :

```
import csv
import mysql.connector

def connect(): return
  mysql.connector.connect(
  host="localhost",
    user="root",
    password="YOUR_PASSWORD",
    database="college"
  )

def
  create_tables(conn):
```

```
    cur = conn.cursor()
    cur.execute("""
       CREATE TABLE IF NOT EXISTS Student(
          student_id INT PRIMARY KEY, name
          VARCHAR(100) NOT NULL,
          spi DECIMAL(3,2) NOT NULL
       ) """)
    cur.execute(""
    "
       CREATE TABLE IF NOT EXISTS CourseRegistration(
          student_id INT, course_id VARCHAR(20),
          FOREIGN KEY(student_id) REFERENCES Student(student_id)
       ) """)
    conn.commit(
    )
    cur.close()

 def insert_students(conn, filename):
    cur = conn.cursor() with open(filename, newline="",
    encoding="utf-8") as f:
       for row in csv.DictReader(f):
          cur.execute(
             "INSERT IGNORE INTO Student VALUES (%s,%s,%s)",
             (row["student_id"], row["name"], row["spi"])
          )
    conn.commit()
    cur.close()

 def insert_registrations(conn, filename): cur =
    conn.cursor() with open(filename, newline="",
    encoding="utf-8") as f:
       for row in csv.DictReader(f): cur.execute(
             "INSERT INTO CourseRegistration VALUES (%s,%s)",
             (row["student_id"], row["course_id"])
          )
    conn.commit()
    cur.close()

 def show_students(conn, course_id, threshold):
    cur = conn.cursor() cur.execute("""
       SELECT s.student_id, s.name, s.spi, r.course_id
```

```
        FROM Student s
        JOIN CourseRegistration r ON s.student_id = r.student_id
        WHERE r.course_id = %s AND s.spi > %s
        ORDER BY s.spi DESC, s.student_id ASC
    """, (course_id, threshold))

    for row in cur:
        print(*row)
    cur.close()
def main():
    student_file = input("Student CSV: ").strip()
    registration_file = input("Registration CSV: ").strip()
    course_id = input("Course ID: ").strip()

    try:
        threshold = float(input("SPI threshold: "))
        if not 0 <= threshold <= 10: raise
        ValueError


        conn = connect()
        create_tables(conn)
        insert_students(conn,
        student_file)
        insert_registrations(conn,
        registration_file)
        show_students(conn,
        course_id, threshold)
        conn.close()

    except (ValueError, mysql.connector.Error, FileNotFoundError) as e:
        print("Error:", e)

if name ____== " main ": main()
```

OUTPUT :

```
Student CSV: student.csv
Registration CSV: registration.csv
Course ID: PY101
SPI threshold: 8.0
2201 Asha 9.1 PY101
2207 Dev 8.4 PY101
```

PROBLEM STATEMENT 4: Build a command-line query builder that receives filter conditions and generates safe parameterized SQL for joining Student, Course and CourseRegistration tables. It must support WHERE, ORDER BY, LIMIT and selected projection fields. Reject invalid columns and unsafe input before executing.

CODE :

```
import mysql.connector
ALLOWED_COLUMNS = {
   "student.id": "s.student_id",
   "student.name": "s.name", "student.spi":
   "s.spi",
   "course.id": "c.course_id",
   "course.name": "c.course_name"
}

def build_query(columns, filters, order_column, direction, limit):
   if not columns or any(c not in ALLOWED_COLUMNS for c in columns):
      raise ValueError("Invalid column")

   if order_column not in ALLOWED_COLUMNS: raise
      ValueError("Invalid order column")

   if direction.upper() not in ("ASC", "DESC"):
      raise ValueError("Invalid sort direction")

   if not 1 <= limit <= 1000:
      raise ValueError("Invalid limit")

   selected = ", ".join(ALLOWED_COLUMNS[c] for c in columns) query
   = f"""
      SELECT
      {selected} FROM
      Student s
      JOIN CourseRegistration r ON s.student_id = r.student_id
      JOIN Course c ON r.course_id = c.course_id """

   params = [] if filters: conditions = [] for
   column, operator, value in filters:
         if column not in ALLOWED_COLUMNS: raise
            ValueError("Invalid filter column")
```

```
        if operator not in ("=", ">", "<", ">=", "<=", "LIKE"): raise
            ValueError("Invalid operator")
        conditions.append(f"{ALLOWED_COLUMNS[column]} {operator} %s")
    params.append(value) query += " WHERE " + " AND ".join(conditions)

query += f" ORDER BY {ALLOWED_COLUMNS[order_column]} {direction.upper()}"
query += " LIMIT %s" params.append(limit) return query, params

def
  main():
  try:
    columns = input("Columns: ").split(",") columns
    = [c.strip() for c in columns]

    filters = [] text = input("Filter (column,operator,value) or
    blank: ").strip()

    if text:
      column, operator, value = map(str.strip, text.split(",", 2))
      filters.append((column, operator, value))

    order_column = input("Order column: ").strip()
    direction = input("Direction: ").strip() limit
    = int(input("Limit: "))

    query, params = build_query( columns, filters,
      order_column, direction, limit
    )

    print("SQL_OK")
    print(query)
    print("Parameters:", params)

    conn =
      mysql.connector.connect(
      host="localhost", user="root",
      password="YOUR_PASSWO
      RD",database="college"
    )
    cur = conn.cursor() cur.execute(query,
    params)
```

```
    for row in cur:
        print(*row)

    cur.close() conn.close()

except (ValueError, mysql.connector.Error) as e:
    print("Error:", e)

if name ____== " main ": main()
```

OUTPUT :

```
Columns: student.name,course.name
Filter (column,operator,value) or blank: course.id,=,PY101
Order column: student.spi
Direction: DESC
Limit: 2
SQL_OK

        SELECT s.name, c.course_name
        FROM Student s
        JOIN CourseRegistration r ON s.student_id = r.student_id
        JOIN Course c ON r.course_id = c.course_id
    WHERE c.course_id = %s ORDER BY s.spi DESC LIMIT %s
Parameters: ['PY101', 2]
```

PROBLEM STATEMENT 5: Develop a Tkinter contact manager that stores contacts in MySQL. It must support create, update, delete, search by name/email/phone, and sorted display. Use Entry, Text, Radio Button or Check Button, Listbox/Menu and Combobox widgets. Validate email using regex before insert/update.

CODE :

```
import tkinter as tk
from tkinter import ttk, messagebox
import sqlite3 import re

def connect():
    return sqlite3.connect("contacts.db")

def setup():
    conn = connect()
    conn.execute("""
```

```
        CREATE TABLE IF NOT EXISTS Contact( id
          INTEGER PRIMARY KEY AUTOINCREMENT,
          name TEXT NOT NULL, email TEXT UNIQUE
          NOT NULL,
          phone TEXT, category
          TEXT,
          notes TEXT
        ) """)
    conn.commit(
    )
    return conn

class App:
    def init (self, root): self.root =
        root     self.root.title("Contact
        Manager") self.conn = setup()

        labels = ["Name", "Email", "Phone", "Category", "Notes"]
        self.entries = {}

        for i, label in enumerate(labels):
            tk.Label(root, text=label).grid(row=i, column=0, padx=5, pady=5)
           if label == "Category":
               entry = ttk.Combobox( root,
                   values=["Faculty", "Student", "Friend", "Other"],
                   width=32
               ) else: entry = tk.Entry(root,
            width=35)

            entry.grid(row=i,       column=1,       padx=5,       pady=5)
            self.entries[label] = entry

        tk.Button(root,     text="Add",     command=self.add).grid(row=5,     column=0,     padx=5)
        tk.Button(root,  text="Update",  command=self.update).grid(row=5,  column=1,  padx=5)
        tk.Button(root,  text="Delete",  command=self.delete).grid(row=5,  column=2,  padx=5)
        tk.Button(root,  text="Search",  command=self.search).grid(row=5,  column=3,  padx=5)
        tk.Button(root, text="Show All", command=self.show_all).grid(row=5, column=4, padx=5)

        self.listbox = tk.Listbox(root, width=100, height=15)
        self.listbox.grid(row=6, column=0, columnspan=5, padx=5, pady=10) self.show_all()
    def      get_values(self):      return      (
        self.entries["Name"].get().strip(),
```

```
        self.entries["Email"].get().strip(),
        self.entries["Phone"].get().strip(),
        self.entries["Category"].get().strip(),
            self.entries["Notes"].get().strip()
        )

    def valid_email(self, email):
        return          re.fullmatch(r"[\w.+-]+@[\w.-]+\.[A-Za-z]{2,}",
        email)

    def add(self):
        name, email, phone, category, notes = self.get_values()

        if not name or not email:
            messagebox.showerror("Error", "Name and Email are required") return
if not self.valid_email(email):
            messagebox.showerror("Error", "Invalid email") return

        try:
            self.conn.execute(
                "INSERT    INTO    Contact(name,email,phone,category,notes)    VALUES(?,?,?,?,?)",
                (name, email, phone, category, notes)
            )
            self.conn.commit()
            self.clear()
            self.show_all()
            messagebox.showinfo("Success", "Contact added")
        except sqlite3.IntegrityError: messagebox.showerror("Error",
            "Email already exists")

    def update(self):
        selected = self.listbox.curselection()

        if not selected:
            messagebox.showerror("Error", "Select a contact") return
        name, email, phone, category, notes = self.get_values()
        if                not                self.valid_email(email):
        messagebox.showerror("Error",      "Invalid      email")
        return
```

```
        contact_id = self.listbox.get(selected[0]).split("|")[0].strip()
        try:
            self.conn.execute(
                """UPDATE Contact
                   SET name=?, email=?, phone=?, category=?, notes=?
                   WHERE id=?""",
                (name, email, phone, category, notes, contact_id)
            )
            self.conn.commit()
            self.clear()
            self.show_all()
            messagebox.showinfo("Success", "Contact updated")
        except sqlite3.IntegrityError: messagebox.showerror("Error",
            "Email already exists")
    def delete(self):
        selected = self.listbox.curselection()

        if not selected:
            messagebox.showerror("Error", "Select a contact") return
        contact_id = self.listbox.get(selected[0]).split("|")[0].strip()
        self.conn.execute(
            "DELETE FROM Contact WHERE id=?",
            (contact_id,)
        )
        self.conn.commit()

        self.clear()
        self.show_all()
        messagebox.showinfo("Success", "Contact deleted")

    def search(self):
        term = self.entries["Name"].get().strip()

        rows = self.conn.execute(
            """SELECT id,name,email,phone,category
               FROM Contact
               WHERE name LIKE ? OR email LIKE ? OR phone LIKE ? ORDER
               BY name""",
            (f"%{term}%", f"%{term}%", f"%{term}%")
```

```
        ).fetchall()

        self.display(rows)

    def show_all(self):
        rows = self.conn.execute(
            """SELECT id,name,email,phone,category
              FROM Contact
              ORDER BY name"""

        ).fetchall()


        self.display(rows)


    def display(self, rows): self.listbox.delete(0, tk.END)
        for row in rows: self.listbox.insert(tk.END, " |
        ".join(map(str, row)))

    def clear(self):
        for entry in self.entries.values():
            entry.delete(0, tk.END)


root = tk.Tk()
App(root)
root.mainloop()
```

OUTPUT :



PROBLEM STATEMENT 6: Given timestamped application logs, detect every user who has at least X failed login attempts within any T-minute window followed by a successful login from a different IP address. Use regex to parse log lines and an optimized sliding window per user. **CODE :**

```
import re from collections import
defaultdict, deque

def to_minutes(t): h, m =
   map(int, t.split(":")) return
   h * 60 + m

def
   main():
   try:
      X, T = map(int, input().split()) n
      = int(input())

      failures = defaultdict(deque) suspicious
      = {}

      pattern = re.compile(
         r"^(\d{2}:\d{2})\s+(\S+)\s+(\S+)\s+(FAIL|SUCCESS)$"
      )
```

```
    for _ in range(n): line =
      input().strip() match =
      pattern.match(line)

      if not match:
        continue

      timestamp, user, ip, status = match.groups()
      current = to_minutes(timestamp)

      if status == "FAIL":
        q = failures[user]

        while q and current - q[0][0] > T:
          q.popleft()

        q.append((current, ip))
      else:q = failures[user]

        while q and current - q[0][0] > T:
          q.popleft()
        if len(q) >= X and any(old_ip != ip for _, old_ip in q):
          suspicious.setdefault(user, timestamp)

    for user in sorted(suspicious):
      print(user, suspicious[user])

  except ValueError: print("Invalid
    input.")

if name ____== " main ": main()
```

OUTPUT :

```
3 10
5
00:00 u1 1.1.1.1 FAIL
00:03 u1 1.1.1.1 FAIL
00:05 u1 1.1.1.1 FAIL
00:07 u1 2.2.2.2 SUCCESS
00:08 u2 3.3.3.3 SUCCESS
u1 00:07
```

PROBLEM STATEMENT 7: Create an ETL pipeline using generator functions that reads a large JSON-lines file of sensor records, filters corrupted records, transforms units, groups readings by device and produces summary statistics. The program must not load the full file into memory.

CODE :

```
import json from collections
import defaultdict

def read_records(filename):
    with open(filename, encoding="utf-8") as f:
        for line in f: try:
                yield json.loads(line)
            except json.JSONDecodeError:
                yield None

def main():
    filename = input("Enter JSONL file path: ").strip() data
    = defaultdict(lambda: {
        "count": 0,
        "min": float("inf"),
        "max": float("-inf"),
        "sum": 0.0,
        "corrupted": 0
    })

    try:
        for record in
            read_records(filename): if not
            isinstance(record, dict):
            continue

            device = record.get("device_id")
            temperature = record.get("temperature_c")

            if not device or not isinstance(temperature, (int, float)):
                if device:
                    data[device]["corrupted"] += 1
                continue

            d = data[device]

            d["count"] += 1
            d["min"] = min(d["min"], temperature)
            d["max"] = max(d["max"], temperature) d["sum"] += temperature
```

```
    for device in sorted(data):
        d = data[device] if
        d["count"]:
            avg = d["sum"] / d["count"]
            print(
                f"{device} count={d['count']} " f"min={d['min']}
                max={d['max']} "
                f"avg={avg:.2f} corrupted={d['corrupted']}"
            ) else: print(f"{device} count=0
        corrupted={d['corrupted']}")

except FileNotFoundError:
    print("File not found.")

if name ____== " main ": main()
```

OUTPUT :

```
Enter JSONL file path: sensors.jsonl
D1 count=2 min=30 max=32 avg=31.00 corrupted=1
```

PROBLEM STATEMENT 8: Given an n x m matrix of integers, find the maximum score path from top-left to bottom-right. You may move right, down or diagonally down-right. Some cells are blocked. Also print the number of distinct maximum-score paths modulo 1000000007.

CODE :

```
MOD = 1000000007 NEG
= -10**30
def
    main():
    try:
        n, m = map(int, input().split()) matrix
        = []

        for _ in range(n): row
            = input().split()

            if    len(row)    !=    m:
                print("Invalid
                matrix.") return
```

```
    matrix.append([
        None if x == "X" else int(x) for
        x in row
    ])

if matrix[0][0] is None or matrix[n - 1][m - 1] is None:
    print("IMPOSSIBLE")
    return


score = [NEG] * m
ways = [0] * m

for i in range(n):
    new_score = [NEG] * m new_ways
    = [0] * m

    for j in range(m):
        if matrix[i][j] is None: continue
        if i == 0 and j == 0:

            new_score[j] = matrix[i][j] new_ways[j]
            = 1
            continue
        best = NEG
        count = 0

        for pi, pj in ((i - 1, j), (i, j - 1), (i - 1, j - 1)):
            if pi < 0 or pj < 0: continue
            s = score[pj] if pi == i - 1 else new_score[pj] w
            = ways[pj] if pi == i - 1 else new_ways[pj]

            if s > best:
                best = s
                count =
                w
            elif s == best:
                count = (count + w) % MOD

        if best != NEG:
            new_score[j] = best + matrix[i][j] new_ways[j]
            = count
```

```
        score, ways = new_score, new_ways
    if score[m - 1] == NEG:
        print("IMPOSSIBLE")
    else:
        print(score[m - 1], ways[m - 1] % MOD)
except ValueError:
    print("Invalid input.")

if name ____== " main ": main()
```

OUTPUT :

```
3 3
1 2 3
4 X 6
7 8 9
29 1
```

PROBLEM STATEMENT 9: Design Product and Inventory classes. Inventory must support adding products, deleting products, updating stock, comparing inventories by total value, and merging two inventories using operator overloading. Conflicting product ids must merge stock quantities but preserve the lower purchase price and higher selling price for reporting.

CODE :

```
class Product:
    def init (self, pid, name, stock, purchase, selling): self.pid
        = pid self.name = name
        self.stock      =      stock
        self.purchase = purchase
        self.selling = selling

    def value(self): return self.stock
        * self.selling

class Inventory:
    def init (self):
        self.products = {}

    def add(self, product):
        self.products[product.pid] = product
```

```
def delete(self, pid):
    self.products.pop(pid,
    None)

def update(self, pid, stock):
    if pid in self.products: self.products[pid].stock
        = stock


def total_value(self):
    return sum(p.value() for p in self.products.values())

def add (self, other): result
    = Inventory()

    for p in self.products.values(): result.add(
            Product(
                p.pid, p.name, p.stock,
                p.purchase, p.selling)
        )

    for p in other.products.values():
        if p.pid in result.products: q
            =    result.products[p.pid]
            q.stock += p.stock
            q.purchase = min(q.purchase, p.purchase)
            q.selling = max(q.selling, p.selling)
        else:
            result.add(
                Product(
                    p.pid, p.name, p.stock,
                    p.purchase, p.selling
                )
            )

    return result

def gt (self, other): return self.total_value() >
    other.total_value()

def display(self):
```

```
        for p in sorted(self.products.values(), key=lambda x: x.pid):
            print(
                f"{p.pid}        {p.name}        stock={p.stock}        "
                f"purchase={p.purchase} selling={p.selling}"
            )

def main():
    a = Inventory() b = Inventory() n =
    int(input("Products in A: ")) for _ in range(n): pid,
    name, stock, purchase, selling = input().split()
    a.add(Product(
            pid,          name,          int(stock),
            float(purchase),
            float(selling)
        ))

    n = int(input("Products in B: ")) for _ in range(n): pid,
    name, stock, purchase, selling = input().split()
    b.add(Product(        pid,        name,        int(stock),
    float(purchase),
            float(selling)
        ))

    while True: command = input("Operation:
        ").strip().split()

        if not command:
            continue

        if command[0] == "ADD":
            target = a if command[1] == "A" else b
            target.add(
                Product(
                    command[2],
                    command[3],
                    int(command[4]),
                    float(command[5]),
                    float(command[6])
                ) )

        elif command[0] == "DELETE":
```

```
        target = a if command[1] == "A" else b
        target.delete(command[2])

    elif command[0] == "UPDATE":
        target = a if command[1] == "A" else b
        target.update(command[2], int(command[3]))

    elif command[0] == "MERGE":
        merged = a + b merged.display()
        print("TOTAL",
        merged.total_value())

    elif command[0] == "COMPARE": if
        a.total_value() >
    b.total_value():
            print("A")
        elif b.total_value() > a.total_value():print("B") else:
            print("EQUAL")

    elif command[0] == "EXIT":
break if name ____== " main ":
main()
```

OUTPUT :



PROBLEM STATEMENT 10: Create a Python program that reads a CSV dataset of student marks, cleans missing values, calculates subject-wise statistics and exports at least three visualizations: grade distribution, subject-wise average comparison and top performer chart. The program may use matplotlib/pandas if permitted by faculty and must save charts as image files.

CODE :

```
import os import
pandas as pd
import matplotlib.pyplot as plt

def main():
    filename = input("CSV file path: ").strip()
    output = input("Output folder: ").strip()
    try:
        os.makedirs(output, exist_ok=True)

        df = pd.read_csv(filename) subject_cols
        = list(df.columns[2:])

        for col in subject_cols: df[col] =
            pd.to_numeric(df[col], errors="coerce") df[col] =
            df[col].fillna(df[col].mean())

        df.to_csv( os.path.join(output,
            "cleaned_marks.csv"), index=False
        )

        summary = pd.DataFrame({
            "subject": subject_cols,
            "average": [df[c].mean() for c in subject_cols],
            "minimum": [df[c].min() for c in subject_cols],
            "maximum": [df[c].max() for c in subject_cols]
        })

        summary.to_csv( os.path.join(output,
            "summary.csv"), index=False
        )
        grades = pd.cut(df[subject_cols].mean(axis=1), bins=[-1, 40, 50, 60, 70, 80, 90, 100],
            labels=["F", "D", "C", "B", "A", "A+", "O"]
        )
```

```
    grades.value_counts().sort_index().plot(kind="bar"
    ) plt.xlabel("Grade") plt.ylabel("Students")
    plt.tight_layout() plt.savefig(os.path.join(output,
    "grade_distribution.png")) plt.close()

    summary.plot(
        x="subject",
        y="average",
        kind="bar",
        legend=False
    )
    plt.ylabel("Average Marks")
    plt.tight_layout()
    plt.savefig(os.path.join(output,          "subject_average.png"))
    plt.close()

    df["average"] = df[subject_cols].mean(axis=1) top
    = df.nlargest(5, "average")

    plt.bar(top["name"],
    top["average"])
    plt.xlabel("Student")
    plt.ylabel("Average")
    plt.xticks(rotation=30)
    plt.tight_layout()
    plt.savefig(os.path.join(output,          "top_performers.png"))
    plt.close()

    print("cleaned_marks.csv")
    print("summary.csv")
    print("grade_distribution.png")
    print("subject_average.png")
    print("top_performers.png")

except FileNotFoundError: print("File
    not found.") except Exception as e:
    print("Error:", e)

if name ____== " main ": main()
```

OUTPUT :

```
CSV file path: marks.csv
Output folder: output
cleaned_marks.csv
summary.csv
grade_distribution.png
subject_average.png
top_performers.png
```