

DSA Lab 4 Set 2 | SubLinkedLists

Create a linked list to store integers. The linked list supports the following operations:

- Push: Inserting a node at the head (first position)
- Pop: Deleting a node from the head (first position). If the list is empty, do nothing.
- Display the linked list
- Check Sublist: Check if the linked list is a sub-list of a given list. A list $A[1..N]$ is a sublist of $B[1..M]$ if for some i and j , $A[1..N] == B[i..j]$. Note that if $A == B$, then A **is a sublist** of B .

Input

First line contains two integers M and Q , separated by space. M indicates number of nodes in initial linked list and Q indicates the number of queries. Second line contains M space-separated integers, representing values in the initial linked list. Next Q lines contain a query in each line. The query may be one of the following:

- 1 v : Push value v in the linked list [insert at beginning].
- 2 : Pop node from the linked list [delete from beginning].
- 3 : Display values in the linked list, space separated.
- 4 $k\ a_1\ a_2\ a_3\ \dots\ a_k$: Check current list is sublist of another list of size k . This query is followed by k space separated strings in the same line to indicate the values in the other list. Refer to sample for clarity.

Constraints:

Basic Case:

- $1 \leq M \leq 10$
- $1 \leq Q \leq 50$
- $1 \leq \text{integers} \leq 10^6$
- $1 \leq k \leq 10$

Advanced Case:

- $1 \leq M \leq 500$
- $1 \leq Q \leq 500$
- $1 \leq \text{integers} \leq 10^6$
- $1 \leq k \leq 100$

Output

For every display(3) query output space separated values in the list. For every compare(4) query output 1 if the current linked-list is a sublist of the given list, 0 otherwise. The answer for each query must be printed on a separate line.

Sample Test Case

Input:

4 6

2 4 8 1

1 5

3

2

3

4 5 9 4 2 1 8

4 6 7 2 4 8 1 7

Output:

5 2 4 8 1

2 4 8 1

0

1