

Gold Price Prediction and Modelling using Deep Learning Techniques

Vidya G S

Department of Electronics and
Communication Engineering,
College of Engineering,
Chengannur, APJ Abdul Kalam
Technological University, Kerala,
India 689 121
Telephone: + 91 9446482122,
Email: vidyahari.gs@gmail.com

Hari V S

Department of Electronics and
Communication Engineering,
Chengannur, Kerala,
India, 689 121
Telephone: + 91 8547463422,
Email: harivs@ceconline.edu

Abstract— The demand for gold never ends. The gold rate trend shows that gold is one of the best investment plans. So it is wise to predict the trend of the gold rate. Different statistical models can be used for suitable modelling and prediction of data. This paper summarizes the idea of gold rate prediction using the LSTM Network. It is always visible that the price of gold follows a nonlinear nature. The prediction of prices is commanding for the proper financial and investment plans. The gold rate fluctuation can be modelled as an exponential curve. Convolutional Neural Networks is one of the best solutions for solving nonlinearities in data and among them RNNs are best suited for time series predictions and estimations. The dataset collected from the World Gold Council is used and results have shown that the proposed architecture is one of the best financial forecasting methods.

Index Terms—LSTM, Exponential, CNN, RNN, Prediction, Estimation.

I. INTRODUCTION

Finance is imperative in our life and for the development of the economy, financial prognosticating is inevitable. Recently, economists or investigators are looking into mathematical methods to analyze the financial data with the aim of making divination accurately. Financial data processing and analysing are gaining importance nowadays. It is very hard and computationally complex to study the behaviour of financial data. Many factors are affecting the pricing of different commodities. The fluctuations in the market, economic policies, epidemics, weather conditions, etc are some of the factors that greatly affect it. The financial area is highly complex and nonlinear with profuse factors influencing the estimation. So the financial data always shows a nonlinear behaviour.

The nonlinearity in the data can be extracted to analyse the behaviour and is an exquisite nowadays so that proper

financial plans can be executed. People used to go behind the gold price analysis even in the early seventies and they analysed that government policies in the US are a key factor in gold pricing [1]. Later economists used to argue that there occurred an economic dependency between gold and silver prices. But Schweikert and Karsten [2] statistically proved that there is no co-integrated relation between them in determining the price. The study of gold price volatility and market behaviour had been a fascinating topic in international finance [3, 4, 5]. Khan [6] used the ARIMA method, Box Jenkins technique to model and develop a gold prediction model. Box-Jenkins ARIMA was one of the advanced techniques of the time sequential forecasting. Eventhough the ARIMA model is good for predicting wavering variables like gold price, its limitations are that its modelling requires a long time series and forecasts could be made only for the near future [7], further substantiated by Abdullah [8]. The modelling of financial data entails different mathematical models such as ARMA models [9], Covariance Matrix estimation [10], Asymptotic Analysis [11] [12], multivariate statistical analysis [13]. Zainal et. al proposed gold price forecasting techniques using one of the optimization algorithm called Grey Wolf Optimizer (GWO) [14].

Another promising gold price prediction technique was by using Artificial Neural Network(ANN). ANN replicates the human brain mechanism to implement computing behaviour. Mombeini et. al [15] used this technique and compared with ARIMA models by analysing three performance evaluation measures viz Mean Absolute Error(MAE), Coefficient of Determination(R²), and Root Mean Square Error(RMSE). The results proved that the prediction results of the ANN model during the validation phase outperform the




Fig. 1: Methodology of work

ARIMA model. Other prediction techniques used in this area are genetic algorithm BP neural network (GA-BP) forecasting model [16], Multiple Linear Regression (MLR) method [17], Dynamic Model Averaging [18] technique, Factor-Augmented Vector Autoregressive (FA VAR) model [5] and Empirical Mode Decomposition (EMD) model [19].

The core problem in this area is the selection of optimal analysis strategy and the asset pricing theory under nonlinear conditions. Recent advances in deep learning methods have indicated exceptional outcomes in fields as diverse as technology, healthcare, finance, human resources, retail, earthquake detection, and self-driving cars. Convolutional neural networks can detect nonlinear relationships in the characteristics of data and is now revolutionizing the field of computational science. In particular, for time series data, such as signals, passenger flow, stock prices, and so on, a long short-term memory (LSTM) is the best choice for learning temporal patterns in deep neural networks (DNNs). An LSTM network does not have a vanishing gradient problem as that of in a recurrent neural network (RNN) [20, 21] and thus it is the suitable choice to learn long-term dependencies in time series data using memory cells and gates. Many endeavors have been made to forecast stock prices using this network [22] [23]. These studies confirmed that the performance of the LSTM model outshined other models. In this paper, an LSTM network is proposed to predict the gold rate from a picture of a time series of past price fluctuations.

II. METHODOLOGY

The work methodology is as shown (Fig. 1) The data for the past thirty years, obtained from the World Gold Council has been selected for the study. The collected data is tabulated into a CSV file and is processed into a format that is suitable for study. Once the preprocessing

is over, data is analysed and modelled to verify the fluctuations and nonlinearities present in it. While doing preliminary analysis on the data which contains the daily gold price rates from January 1, 1979, to July 2020 (only on trading days), it can be seen that the gold price is following an exponential curve. Deep learning techniques can very well extract the details in it. Before inputting the data onto the network, it has to be processed into a format suitable for training the network. The data is scaled to lie between a given minimum and maximum value, usually between zero and one, so that the maximum absolute value of each feature is scaled to unit size. The pre-processed data is then fed to Long Short-term Memory Networks (LSTM) to predict the sequences. The LSTM network can extricate the dependencies and can predict the variations.

III. MODEL

As we analyse the gold price rate over years, price rate on different days can be modelled as an exponentially growing curve. When the given data is validated against an exponential curve, it gave a best fit given by Fig. 2 Exponential smoothing model is a kind of important model among extrapolation methods. The robustness and accuracy of the method have led its widespread use in a variety of applications [24, 25, 26, 27, 28]. The exponential function is given by

$$X(t) = k_1(1 + e^{k_2 t}) \quad (1)$$

IV. LSTM

The traditional neural networks that are commonly used cannot carry out short-term time dependant prediction, since it is not based on the previous several time steps and dependencies between the time series. The networks that can extrapolate subsequent events using previous events is Recurrent Neural Network (RNN) [29]. The traditional Recurrent Neural Network cannot contemplate the effect of long-term memory in several practical applications. The LSTM has a knotty structure that allows it to easily retain information for an extended number of time steps [30].

The LSTM network, an artificial recurrent neural network (RNN), is first proposed by Hochreiter and Schmidhuber [31] and improved by Alex Graves [32]. The LSTM is an RNN with loops in them, allowing it to retain the information. LSTM layer consists of a series of LSTM units, called the LSTM model. Compared with other neural networks, the LSTM model has three multiplicative units, viz, input gate, output gate, and forget gate. The function of the input gate (represented as i_t) is to control the extent to which a new value flows into the cell and to memorize some information of the present. The forget gate (denoted as f_t) determines the extent to which values need to be remained or be




Fig. 2: Gold Price Modelling




Fig. 3: Predicted Output

forgotten (uses a sigmoid function that produces 0 or 1). And the output gate (denoted as o_t) determines the range to which the value in the cell is used to evaluate the output activation of the LSTM unit.

The architecture is presented by the following equations.

$$i_t = \sigma(w_i \cdot [h_{t-1}, x_t], b_i) \quad (2)$$

$$f_t = \sigma(W_f \cdot [h_{t-1}, x_t], b_f) \quad (3)$$

$$o_t = \sigma(W_o \cdot [h_{t-1}, x_t] + b_o) \quad (4)$$

Eq. (2), (3) and (4) represents the input, forget and output gate expressions respectively, which takes the weighted sum of the state of the cell at time t , the output of cell at time $t-1$, and the input at time t as the input of activation function to get the output. The activation function is generally a logistic sigmoid function represented by σ . b_x represents the biases for the respective gates(x) [33]. The equations for the cell state, candidate cell state, and the final output are as follows.

$$\tilde{c}_t = \tanh(w_c \cdot [h_{t-1}, x_t] + b_c) \quad (5)$$

$$c_t = f_t * c_{t-1} + i_t * \tilde{c}_t \quad (6)$$

$$h_t = o_t \tanh(c_t) \quad (7)$$

V. RESULTS AND CONCLUSION

To obtain an authentic dataset, the website of the World Gold Council is accessed and the data from the year 1987 to July 2020, including yearly, quarterly, monthly, and daily gold price in INR, US dollar, EURO, RMB, HK dollar, etc. per ounce. is downloaded. To be more specific, dataset specified in daily gold price (from

January 2, 1979, to July 31, 2020, total 10850 trading days) in INR per ounce is chosen to make analysis prediction.

An LSTM model is developed and data is trained using this network. The optimizer chosen is 'adam' and the performance is evaluated using root mean square error (RMSE) [34]. The output of the trained network shows that the predicted data almost follows the actual data. The RMSE value obtained is 7.385 for the test data. It is very clear from the figure that, initially the price value deflected a little bit from the original value due to the convergence time. After that prediction almost follows the actual value.

In this paper, an LSTM network is designed and developed to predict the nature of the gold rate. The results indicate that our proposed model outplays traditional methods such as ARIMA, covariance matrix estimation, deep regression, SVR, CNN. Moreover, it would be better to test different types of RNNs apart from the LSTM component for our model. For instance, using bidirectional LSTM network models might obtain better results.

REFERENCES

- [1] S. Salant and D. Henderson, "Market anticipations of government policies and the price of gold," *Journal of Political Economy*, vol. 86, no. 4, pp. 627–48, 1978. [Online]. Available: <https://EconPapers.repec.org/RePEc:ucp:jpollec:v:86:y:1978:i:4:p:627-48>
- [2] K. Schweikert, "Are gold and silver cointegrated? New evidence from quantile cointegrating regressions," *Journal of Banking & Finance*, vol. 88, no. C, pp. 44–51, 2018. [Online]. Available: <https://ideas.repec.org/a/eee/jbfin/v88y2018icp44-51.html>
- [3] S. Davidson, R. Faff, and D. Hillier, "Gold factor exposures in international asset pricing," *Journal of International Financial Markets, Institutions and Money*, vol. 13, no. 3, pp. 271–289,

2003. [Online]. Available: <https://EconPapers.repec.org/RePEc:eee:intfin:v:13:y:2003:i:3:p:271-289>
- [4] A. Malliaris and M. Malliaris, "What drives gold returns? a decision tree analysis," *Finance Research Letters*, vol. 13, no. C, pp. 45–53, 2015. [Online]. Available: <https://EconPapers.repec.org/RePEc:eee:finlet:v:13:y:2015:i:c:p:45-53>
 - [5] I. Lili and D. Chengmei, "Research of the influence of macro-economic factors on the price of gold," *Procedia Computer Science*, vol. 17, p. 7374–743, 12 2013.
 - [6] A. Ali, M. I. Ch., S. Qamar, N. Akhtar, T. Mahmood, M. Hyder, and M. T. Jamshed, "Forecasting of Daily Gold Price by Using Box-Jenkins Methodology," *International Journal of Asian Social Science*, vol. 6, no. 11, pp. 614–624, November 2016. [Online]. Available: <https://ideas.repec.org/a/asi/ijoass/2016p614-624.html>
 - [7] G. DeepikaM, G. Nambiar, M. Rajkumar, and A. Vishwavidhyapeetham, "Forecasting price and analysing factors influencing the price of gold using arima model and multiple regression analysis," 2012.
 - [8] L. Abdullah, "Arima model for gold bullion coin selling prices forecasting," *International Journal of Advances in Applied Sciences*, vol. 1, 09 2012.
 - [9] R. S. Tsay., *Analysis of Financial Time Series*. USA: Wiley Interscience, 2010.
 - [10] O. Ledoit and M. Wolf, "Improved estimation of the covariance matrix of stock returns with an application to portfolio selection," *Journal of Empirical Finance*, vol. 10, no. 5, pp. 603 – 621, 2003. [Online]. Available: <http://www.sciencedirect.com/science/article/pii/S0927539803000070>
 - [11] —, "A well-conditioned estimator for large-dimensional covariance matrices," *Journal of Multivariate Analysis*, vol. 88, no. 2, pp. 365 – 411, 2004. [Online]. Available: <http://www.sciencedirect.com/science/article/pii/S0047259X03000964>
 - [12] —, "Nonlinear shrinkage estimation of large-dimensional covariance matrices," *Ann. Statist.*, vol. 40, no. 2, pp. 1024–1060, 04 2012. [Online]. Available: <https://doi.org/10.1214/12-AOS989>
 - [13] X. Yang, "Three important applications of mathematics in financial mathematics," *American Journal of Industrial and Business Management*, vol. 07, pp. 1096–1100, 01 2017.
 - [14] N. A. Zainal and Z. Mustafa, "Developing a gold price predictive analysis using grey wolf optimizer," in *2016 IEEE Student Conference on Research and Development (SCORED)*, 2016, pp. 1–6.
 - [15] H. Mombeini and A. Yazdani Chamzini, "Modeling gold price via artificial neural network," *Journal of Economics, Business and Management*, vol. 3, pp. 699–703, 01 2015.
 - [16] C. Liu, "Price forecast for gold futures based on ga-bp neural network," 10 2009, pp. 1 – 4.
 - [17] Z. Ismail, A. Yahaya, and A. Shabri, "Forecasting gold prices using multiple linear regression method," *American Journal of Applied Sciences*, vol. 6, 08 2009.
 - [18] G. Aye, R. Gupta, S. Hammoudeh, and W. J. Kim, "Forecasting the price of gold using dynamic model averaging," *International Review of Financial Analysis*, 03 2015.
 - [19] Y. Jian-Hui and D. Wei, "Prediction of gold price based on wt-svr and emd-svr model," 11 2012, pp. 415–419.
 - [20] A. Hartl, M. Bachl, J. Fabini, and T. Zseby, "Explainability and adversarial robustness for rnns," 08 2020, pp. 148–156.
 - [21] D. Takeuchi, K. Yatabe, Y. Koizumi, Y. Oikawa, and N. Harada, "Real-time speech enhancement using equilibrated rnn," in *ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2020, pp. 851–855.
 - [22] K. Chen, Y. Zhou, and F. Dai, "A lstm-based method for stock returns prediction: A case study of china stock market," *2015 IEEE International Conference on Big Data (Big Data)*, pp. 2823–2824, 2015.
 - [23] D. Nelson, A. M. Pereira, and R. A. de Oliveira, "Stock market's price movement prediction with lstm neural networks," *2017 International Joint Conference on Neural Networks (IJCNN)*, pp. 1419–1426, 2017.
 - [24] L. Hong, L. Yu, and L. Lin, "Study on application of exponential smoothing method to water environment safety forecasting," in *2010 International Conference on E-Product E-Service and E-Entertainment*, 2010, pp. 1–3.
 - [25] C. A. G. d. A. J  nior, F. A. T. d. Carvalho, and A. L. S. Maia, "Exponential smoothing methods for forecasting bar diagram-valued time series," in *2012 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*, 2012, pp. 1361–1366.
 - [26] H. A. Rosyid, T. Widiyaningtyas, and N. F. Hadinata, "Implementation of the exponential smoothing method for forecasting food prices at provincial levels on java island," in *2019 Fourth International Conference on Informatics and Computing (ICIC)*, 2019, pp. 1–5.
 - [27] P. Ji, D. Xiong, P. Wang, and J. Chen, "A study on exponential smoothing model for load forecasting," in *2012 Asia-Pacific Power and Energy Engineering Conference*, 2012, pp. 1–4.
 - [28] A. Chusyairi, R. N. S. Pelsri, and E. Handayani, "Optimization of exponential smoothing method using genetic algorithm to predict e-report service," in *2018 3rd International Conference on Information Technology, Information System and Electrical Engineering (ICITISEE)*, 2018, pp. 292–297.
 - [29] T. Maksymyuk, L. Han, S. Larionov, B. Shubyn, A. Luntovskyy, and M. Klymash, "Intelligent spectrum management in 5g mobile networks based on recurrent neural networks," in *2019 IEEE 15th International Conference on the Experience of Designing and Application of CAD Systems (CADSM)*, Feb 2019, pp. 1–4.
 - [30] B. Yang, S. Sun, J. Li, X. Lin, and Y. Tian, "Traffic flow prediction using lstm with feature enhancement," *Neurocomputing*, vol. 332, pp. 320–327, 2019.
 - [31] S. Hochreiter and J. Schmidhuber, "Long short-term memory," *Neural Computation*, vol. 9, no. 8, pp. 1735–1780, 1997. [Online]. Available: <https://doi.org/10.1162/neco.1997.9.8.1735>
 - [32] A. Graves, A. Mohamed, and G. Hinton, "Speech recognition with deep recurrent neural networks," in *2013 IEEE International Conference on Acoustics, Speech and Signal Processing*, 2013, pp. 6645–6649.
 - [33] S. Ren, B. Yang, L. Zhang, and Z. Li, "Traffic speed prediction with convolutional neural network adapted for non-linear spatio-temporal dynamics," in *Proceedings of the 7th ACM SIGSPATIAL International Workshop on Analytics for Big Geospatial Data*, ser. BigSpatial 2018. New York, NY, USA: ACM, 2018, pp. 32–41. [Online]. Available: <http://doi.acm.org/10.1145/3282834.3282836>
 - [34] P. M. Tsang, P. Kwok, S. Choy, R. Kwan, S. Ng, J. Mak, J. Tsang, K. Koong, and T.-L. Wong, "Design and implementation of nn5 for hong kong stock price forecasting," *Engineering Applications of Artificial Intelligence*, vol. 20, no. 4, pp. 453 – 461, 2007. [Online]. Available: <http://www.sciencedirect.com/science/article/pii/S095219760600162X>