FALED88 LED Flood/Area Light



FALED88

FEATURES

- · Die Cast Aluminum Housing
- · Clear Glass Lens
- · Chroma Guard Bronze Powder Coat Finish
- CRI LED Array Aluminum Substrate Board
- · Replaces up to 400W HID
- 50,000 Hour Rated Life
- 5000K Sun Emulating LEDs
- Electronic 120-277V Driver

APPLICATIONS

- · General Area
- Parking
- Roadway
- Security

MOUNTING

 Mounts to pole with 6" Arm, U-Bkt, or Slip Fitter Mount

LED WATTAGE/LUMENS

• 88W - 10,566 Lumens

COLORS

- · Bronze Powder Coat Finish
- · Custom Colors Available Upon Request

AVAILABLE LISTINGS

- ILTL/Optional UL
- Listed for Wet Locations


Job Name:

Type:

Qty:

Approvals:

Notes:



Ordering Information: Example FALED 88W UNV

FALED

LED Flood/Area Series

Watts

88W 88W

FALED88

Options

A6 SF

Volts UNV 120-277V 6" Arm Slip Fitter

UB U-Bkt SP Surge Protection UL UL Listing



(

SF

UB

CRI \$\pi LED

MERICA LIGHT LED Series