

1	UART Pin Header Male	RX_TX	Plastik & Logam	2.54 mm	Mengirim Data ke Laptop		
1	LCD TFT ST7789	LCD TFT	Semikonduktor	1,47 inch	Display Data		
1	LM1085IT-3.3V	LM1085IT-3.3	Semikonduktor	TO-220	Regulator 3,3 V		
2	Kapasitor 470 uF	C2, C3	Keramik	12V	Pengstabil Regulator		
1	Kapasitor 22 uF	C1	Keramik	12V	Filter RC		
1	Resistor 4K7 Ω	R1	Film Karbon	± 5%	Filter RC		
1	Push Button Bawah	PB_Bawah	Plastik & Logam	7 mm	Mengurangi Setpoint		
1	Push Button Atas	PB_Atas	Plastik & Logam	7 mm	Menambah Setpoint		
1	Push Button Halaman	PB_Halaman	Plastik & Logam	7 mm	Memilih Mode Kontrol		
1	Push Button Stop	PB_Stop	Plastik & Logam	7 mm	Menghentikan Sistem		
1	Push Button OK	PB_OK	Plastik & Logam	7 mm	Konfirmasi Pengguna		
1	Push Button Reset	PB_Reset	Plastik & Logam	7 mm	Reset Sistem		
1	STM32F401RCT6	H1, H2	Silikon	23 x 53 mm	Mikrokontroler		
Jml	Nama Komponen	Posisi	Bahan	Ukuran	Keterangan		
	Perubahan	Perbandingan Kinerja Kontrol Gain Scheduling Proportional Integral Derivative dan Fuzzy Mamdani Pada Modul Pemanas Udara		Skala 1:1	DiGbr	Tim	01 - 01 - 2026
					DiPrk	S. Tebe N.	02 - 01 - 2026
				No Hal : 1		Jml Hal : 1	
 POLITEKNIK NEGERI SEMARANG				SMG RE TA DKE 26 7A 21 03			