OTAG-433 Module

The OTAG-433 module provides a means for any electronic device to implement low cost wireless connectivity. This module operates on 434 MHz custom band with proprietary protocol.

OTAG-433 module is ideal for application where longer battery life and range is required. It is built around Silicon Labs EZR32HG220 Wireless MCU family with ARM Cortex-M0+ and sub-GHz Radio with energy efficient 32 bit Microcontroller with 64kB flash. The architecture isolates the wireless software without sacrificing RF performance or security for applications.

Benefits

- Proprietary 434.212 MHz Orion network connectivity
- A rich set of hardware peripherals such as GPIO, UART, and timers
- A great choice for battery oriented applications with
  - Low Transmit and Receive Currents
  - Ultra Low Power Standby and Sleep modes
  - Fast Wake-up Time
  - AES Accelerator with 128-bit keys
- Supports deployment of a dense network with long coverage

Specifications

Performance	
Data Rate	Up to 1Mbps
TX Current Consumption	18mA@ +10dBm
RX Current Consumption	13mA
RX Sensitivity	Up to -133 dBm
Features	
Processor	ARM Cortex M0+
Clock/ Speed	Up to 25 MHz
Memory	64 kB Flash, 8 kB RAM
Modes	Run, Stop, Shutoff
Serial Interface	1 x UART
Antenna Options	Solder pad and through-hole 2mm pitch connector
Size (LxWxH in mm)	40 x 15.5 x 4
Electrical Specification	
Supply Voltage	2.5V to 5V DC
Operating Temperature	0 °C to 40 °C

For more information contact at http://www.nebulae.io/ or sales@nebulae.io

System Level Solutions
USA | India | UK
Tel.: 91-2692-232 501 / 502 / 001-408-852-0067 / 001-408-705-2339
E-mail: info@slscorp.com • Website: www.slscorp.com