

RS485 MODBUS TO 4G IOT GATEWAY NLG0192



NEBULAE[®]
DESIGN TO CONNECT



**Host/Webpage/Serial
configuration**



Industrial grade



**Simultaneous
communication with
multiple slave**



Configurable MQTT client



FOTA



Remote device management

RS485 MODBUS TO 4G IOT GATEWAY



NLG0192

Nebulae introduces the NLG0192 RS485 Modbus Gateway – a compact, industrial-grade IoT device built to seamlessly connect legacy Modbus systems to modern cloud platforms. Supporting RS485 Modbus RTU, this gateway enables simultaneous communication with multiple Modbus slave devices, while offering secure wireless connectivity, effortless FOTA upgrades, and mission-critical LTE performance. The NLG0192 empowers users with remote device management, scalable integration, and robust data handling for industrial automation, energy monitoring, and smart infrastructure. Engineered for reliability, it features a versatile RS485 interface and lightweight, power-efficient design. Plus, it allows customers to configure their own MQTT client, enabling flexible and secure cloud communication tailored to specific needs.

Gateway Application



Energy Meters



Industrial Automation



Solar Monitoring



Temperature Alerts



Generator Control



Water Level Control



Windmill & SCADA



Pump & Flow Control

General Specification	
Product Name	NLG0192 - RS485 Modbus to 4G IoT Gateway
Connectivity	
Cellular	LTE Cat 1 (10 Mbps DL / 5 Mbps UL) Bands: B1/B3/B5/B8/B34/B38/B39/B40/B41
Serial Communication	RS485 (MODBUS RTU supported) Configurable Baud Rate (1200–115200 bps) 1× Terminal Block
Antenna Interfaces	LTE: External (U.FL) Internal (optional)
SIM Card	Nano SIM (4FF)
Protocols & Cloud	
Protocols Supported	Modbus RTU (Master) MQTT over 4G
Cloud Support	MQTT (AWS, Azure IoT, ThingsBoard, Custom Brokers) REST APIs
Offline Data Storage	500 KB
Interfaces & Indicators	
I/O Interfaces	1 × RS485 (terminal block)
LED Status	Network Searching – Solid On Network Registered – Blink at every 200ms SIM Card Not Available – Solid Off
Power & Environment	
Operating Voltage	5V – 12V DC
Power Consumption	<2W average
Operating Temperature	–20°C to +70°C
Humidity Range	10% to 90% RH (non-condensing)
Physical Attributes	
Enclosure	ABS Plastic
Dimensions	Approx. L 85 mm × W 60 mm × H 35 mm
Mounting Options	DIN Rail / Wall Mount
Package Contents	1 x 4G Gateway, 1 x 4G GSM Antenna, 1 x Power Supply AC (100V to 240V) to DC (12V, 2A), 1 x 2 pin Matting Screw Connector for RS485, 2 x Wall Mount Screw
DIN Rail / Wall Mount	
Firmware Update	FOTA (Firmware Over-The-Air) via 4G
Security Features	TLS/SSL Encryption Secure Boot
Certification & Customization	
Certifications	CE, RoHS (optional on request)
Customization Options	Logo, UI, Protocol Extensions, Cloud Platform Mapping

Why Choose Us?

Nebulae is a division of **System Level Solutions (SLS)** that focuses on simplifying the implementation of IoT solutions. It is a full-stack Internet of Things integration platform that drives a digital transformation and enables IoT developers to develop their solution for delivering the business logic.

Contact Us



+91 2692-232501



Plot#32, Zone-D/4, Phase-1 GIDC Estate,
V.U.Nagar - 388121 Gujarat, india



www.nebulae.io



sales@nebulae.io