

Street Light Controller

Pole Mount | Retrofit

A sustainable solution for smart cities of tomorrow



Pole Mount & Retrofit Street Light Controller

Vialight's Pole Mount & Retrofit Street Light Controller is a vital part of smart lighting solutions. It manages street light ON/OFF schedules, monitors temperature, and offers over and under voltage protection. It also measures power, energy, current, and voltage, helping track and optimize overall energy consumption.



Features



Robust and Reliable

Offer long range, deep coverage, high availability and managed Low Power Wide Area Network (LPWAN)



Remote Controlling

Supports multiple control modes, including Manual and Configurable ON/OFF/Dimming.



Power Measurements

High performance Analog front end solutions measuring electrical parameters such as Current, Voltage, Frequency, Power Factor, kW and kWh



Grouping

Smart grouping of lights based on application needs, enabling efficient remote group-wise control.



Dimming Controls

Supports dimming via 0–10 VDC and PWM with up to 10 configurable schedules, enabling autonomous brightness control through LDR input.

*LDR applicable for pole-mount variant only.



Fault Monitoring

Reports on lamp burnouts, abnormal power consumptions, low power factor, and more via cloud.



Alerts

Notifies users via e-mail or text (SMS) messages as soon as it occurs

Technical Specification

Hardware

Processor	Cortex-M4 STM32WL 32bit, RISC 48Mhz	
Antenna Options	External LoRaWAN Antenna	
Mounting Type	Retrofit, Pole Mount	
IP Enclosure Rating	IP65 (Pole Mount), Standard Poly Carbonate	
Metering Measurement	Voltage, Current, Frequency, Power Factor	
Real Time Clock	Battery - Backup RTC	
Ambient Sensor Support	Detect amount of light in vicinity and based on that turn ON/OFF the light	
Dimension (L*W*H)	Pole Mount - 160 x 80 x 55 mm	Retrofit - 168.53 x 74.62 x 40 mm
Weight	~250 gm	~ 200 gm

Networking and Security

Protocol	LoRaWAN
Frequency Band	865 to 867 MHz, 902 to 915 MHz
Encryption	AES 128 Bit for MAC and Application (DTLS) Layers
Open Field Range	Upto *10000 meters (LOS)
Data Rate	37.5 Kbps Max
TX Power	+20 dBm
RX Sensitivity	-128 dBm

Software and Control

Notification	Lamp Over Voltage, Lamp Under Voltage, Light Fault, Meter Chip Fault, and Relay Fault
Monitoring Parameter	Voltage, Current, Power Factor, Frequency, Power (kW), Energy (kWh)
Central Management System	Web-based software that allows remote configuration, Monitoring control and reporting

Electrical Specification

Supply Type	Single Phase
Power Supply Range	90 VAC to 528 VAC, 50/60 Hz
Operating Temperature	-10°C to +60°C
Humidity Range	10% to 90% RH
Surge Protection	IEC/EN61000-4-5, 10KV
Switching Load Capacity	10A, 230 VAC
High Voltage Cutoff	290 VAC

Certificate

Surge	IEC/EN61000-4-5
IP Enclosure Rating	IP65 (Pole Mount)
LoRaWAN Module	WPC

System Level Solutions (India) Pvt. Ltd.
32, D4, Phase 1, GIDC Estate, V.U. Nagar,
Gujarat 388121, India

✉ info@slscorp.com
🌐 www.vialights.com
☎ +91 98980 42339

