

Reliable | Safe | Sustainable  
Ecosystem Solutions for  
Electric Mobility



# Kspira DC Charger

30 kW



# Kspira DC Charger

30 kW

Experience innovation on-the-go with VerdeMobility's 30kW DC Charger, tailored for businesses electrifying their commercial parking. Our cutting-edge solution ensures lightning-fast recharges, offering seamless integration and unparalleled convenience.

## Plugs Available

- North American Charging Standard (NACS)
- Combined Charging System (CCS)



## Display

- Enhanced 10" Graphics LCD

## Connectivity

- GSM
- Ethernet
- Wi-fi

## Communication

- OCPP 1.6J compliant (Upgradable to 2.0.1)

## Benefits:-

- Lightning-Fast Recharge
- Scalable Solutions
- User-Friendly Design
- Convenience Redefined
- Tailored for businesses

## Input Power

|                 |                            |
|-----------------|----------------------------|
| Input Voltage   | 415 VAC ( ± 15% )          |
| Input Frequency | 50 Hz                      |
| Wires           | Three-Phase (L1 L2 L3 N E) |

## Output Power

|                     |                      |
|---------------------|----------------------|
| Output connector    | CCS2                 |
| Number of connector | 1                    |
| Output current      | 120 A                |
| Output voltage      | 150 V DC - 1000 V DC |

## Electrical Parameter

|               |                              |
|---------------|------------------------------|
| Ripple Factor | $\leq + 5\%$                 |
| Efficiency    | $\geq 95\%$                  |
| Power Factor  | $\geq 0.99$ (above 50% load) |
| THD           | $< 5\%$ (above 50% load)     |

## Environment

|                     |                                            |
|---------------------|--------------------------------------------|
| Ambient Temperature | 0° C to 60° C (derating starts from 55° C) |
| Storage Temperature | -20 C to 70 Celsius                        |
| Altitude            | 2000 ft                                    |
| Humidity            | 5% to 95%                                  |
| Noice Level         | $\leq 60$ dB                               |

## User Interface And Control

|                     |                                                                                 |
|---------------------|---------------------------------------------------------------------------------|
| Display             | 0.4" TFT LCD Touch Screen                                                       |
| Language            | English                                                                         |
| Push Button         | Mushroom Type, Emergency Stop                                                   |
| User Authentication | Using Mobile Application or User Interface QR Codes/ RFID Cards/ Password login |
| Visual Indication   | RGB LEDs                                                                        |
| RFID Specifications | RC 522 RFID Reader ISO/ IEC 14443A/ MIFAR                                       |

## Protection

|            |                                                                                                                                                                                                                               |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protection | Overvoltage, Overcurrent, Undervoltage, Surge Protection, Overtemperature, Ground Fault, Polarity Reverse Protection, Insulation Monitoring, Leakage Protection, Charge Cable Temperature Detection, Earth Presence Detection |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Communication

|                      |                                                                            |
|----------------------|----------------------------------------------------------------------------|
| Connectivity and CMS | OCPP 1.6J over 10/100 Base-T Ethernet (Standard), GSM Modem (4G) and Wi-Fi |
| Charger and Vehicle  | DIN 70121, ISO15118(EIM and PNC), IEC61851                                 |

## Mechanical

|                           |                                   |
|---------------------------|-----------------------------------|
| IP Rating                 | IP 54                             |
| Shell Material            | CRCA Sheet                        |
| Cooling                   | Air Cooling                       |
| Product Dimension (L*W*H) | 264.09 mm × 346.87 mm × 165.31 mm |
| Product Weight            | 106 kg                            |



# About VerdeMobility

We believe that well-engineered, sustainable ecosystem solutions backed by innovative technology can promote electric mobility adoption.

Go *Verde* with our innovative, made-in-India technology solutions for electric mobility. We provide, EV charging solutions, integrating advanced IoT technology for seamless management.

Our Offerings Includes:-



## EV-Chargers

AC chargers 3.3 kw to 240 kW chargers for homes, businesses, CPOs, Dealership, fleets, Infra and DC chargers 30 kW to 240 kW for fleets and infrastructure



## IoT Solutions

Smart AC-DC charger controllers, CMS, and mobile applications for real-time monitoring and control.



## Customized Support

Tailored mobility, customization, and ecosystem support to enhance EV adoption



## Ecosystem Support

EV simulators and fleet electrification calculators to optimize efficiency and sustainability