

POWER THAT PERFORMS

30 kW DC CHARGER

High performance, protection, and safety.



**ARAI in Progress*



BUILT-IN SAFETY

- Over-Current
- Over-Voltage and Under-Voltage
- Ground Fault Detection
- Surge Protection
- Emergency Stop Machine
- Polarity Reverse Protection
- Cable Temperature Detection
- Earth Presence Detection



LOAD MANAGEMENT

- Built-in Energy Meter
- Set up for External Energy Meter Integration or Dynamic Load Management
- Ready for Integration with Advanced Smart Building Energy Systems



DESIGN

- Three-phase Input
- IEC 15118 EIM & PNC
- CCS2 (IEC 62196.3-2014)



CONNECTIVITY

- GSM, Ethernet, Bluetooth and Wi-Fi
- OCPP 1.6J (upgradable to 2.1)
- Compliant Authentication via App or RFID
- Configuration via App, Web Portal

Input Supply

Input Voltage	415 VAC ($\pm 15\%$) 3-phase, 50 Hz
Wires	Three Phase (L1, L2, L3, N, PE)

Output Power

Output Interface	CCS2
Output Power	30 kW
Output Current	100A

Electrical Parameter

Efficiency	95% at nominal output power
Power Factor	0.99 at nominal output power
Current THD	5% at nominal output power

Environment

Operating Temperature	-10°C to +55°C (Derating applies)
Storage Temperature	-10°C to +70°C (Dry environment)
Altitude	2000 m
Humidity	5% to 95%, non-condensing
Noise Level	≤ 60 dB

User Interface and Control

Display	10.4" TFT LCD Touch Screen
Emergency Stop	Mushroom Type
User Authentication	App / QR / RFID / Password / Optional Autocharge / Optional UPI
Visual Indication	RGB Neo Pixel LEDs
RFID Specifications	RC522, ISO / IEC 14443A/MIFARE

Protection

Protection Features	Over-Voltage, Over-Current, Under-Voltage, Surge, Over-Temperature, Ground Fault, Polarity Reverse, Insulation Monitoring, Leakage, Cable Temperature Detection, Earth Detection, Short Circuit, Emergency Shutdown
---------------------	---

Communication

Network Connection	GSM/3G/4G; Ethernet; Wi-Fi, Bluetooth
Protocol	OCPP 1.6J (Upgradable to 2.1)
Vehicle Standards	IEC61851, ISO15118, DIN70121

Mechanical

IP Rating	IP54
Shell Material	Metal Enclosure
Cooling	Air Cooling
Cable Length	15 ft. Standard
Product Dimension (L*W*H)	1720 mm * 540 mm * 275 mm
Product Weight	130 kg