



POWER THAT PERFORMS

7.5 kW AC COMPACT CHARGER

High performance, protection, and safety.



**IS17017 Series, ARAI Certified*



BUILT-IN SAFETY

- Over-Current
- Over-Voltage and Under-Voltage
- Surge Protection
- Emergency Shutdown
- Polarity Reverse
- Short Circuit



LOAD MANAGEMENT

- Built-in Energy Meter
- Set up for External Energy Meter Integration or Dynamic Load Management
- Ready for Integration with Advanced Smart Building Energy Systems



DESIGN

- Single Phase Input
- Type 2 Gun



CONNECTIVITY

- Wi-Fi, GSM / 3G / 4G, Ethernet, Bluetooth
- OCPP 1.6J (Upgradable to 2.1)
- Authentication via App or RFID

VARIANTS

Variants	Features	Ordering Code
 Compact Core	• RFID • Wi-Fi • LED • OCPP 1.6J upgradable to OCPP 2.1 • 5 Meter Cable • Ethernet	PINT20070493B
 Compact Smart	• RFID • Wi-Fi • LED • Ethernet • 4.3" LCD (TFT Display) • OCPP 1.6J upgradable to OCPP 2.1 • 5 Meter Cable	PINT200306B3B
 Compact Prime	• RFID • Wi-Fi • LED • Ethernet • GSM • 4.3" LCD (TFT Display) • OCPP 1.6J upgradable to OCPP 2.1 • 5 Meter Cable	PINT200706D3B-FOCH

DATASHEET



Input Supply

Input Voltage	230 VAC ($\pm 10\%$), Single Phase (L1, N, PE), 50 Hz
---------------	---

Output Supply

Output Interface	Type 2 Gun
Output Power	7.5 kW
Output Current	32A ($\pm 10\%$)

Electrical Parameters

Efficiency	99% at Nominal Output Power
Power Factor	0.99 at Nominal Output Power
Current THD	5% at Nominal Output Power

Environment

Operating Temperature	-5°C to 55°C
Storage Temperature	-10°C to 70°C
Altitude	2000 m
Humidity	5% to 95%
Noise Level	≤ 50 dB

User Interface and Control

Display	4.3" Touch LCD Screen
Emergency Stop	Mushroom Type
User Authentication	App / QR / RFID / Password
Visual Indication	RGB Neo Pixel LEDs
RFID Specifications	RC522

Protection

Protection Features	Over-Current, Over-Voltage, Over-Temperature, Under-Voltage, Surge, Short Circuit, Ground Fault, Emergency Shutdown, Polarity Reverse
---------------------	---

Communication

Network Connection	GSM / 3G / 4G, Ethernet, Wi-Fi, Bluetooth
Communication Protocol	OCPP 1.6J (Upgradable to 2.1)
Vehicle Standards	Electric 4-wheeler

Mechanical

IP Rating	IP65
Cooling	N/A
Cable Length	15 ft.
Product Dimension (L*W*H)	133.91 mm * 290.60 mm * 350.19 mm
Weight (Tentative)	10 kg