




POWER THAT PERFORMS

10 kW AC BHARAT CHARGER

High performance, protection, and safety.



VerdeMobility



*ARAI Certified



BUILT-IN SAFETY

- Over-Current
- Over-Voltage and Under-Voltage
- Surge Protection
- Emergency Shutdown
- Short Circuit



LOAD MANAGEMENT

- Built-in Energy Meter
- Set up for External Energy Meter Integration or Dynamic Load Management
- Ready for Integration with Advanced Smart Building Energy Systems



DESIGN

- Three Phase Input
- 3 x 3 Pin Socket | 3 x 3 IEC Socket



CONNECTIVITY

- Wi-Fi, GSM / 3G / 4G, Ethernet
- OCPP 1.6J
- Authentication via App or RFID

VARIANTS

Variants	Features	Ordering Code
	3 x 16A Socket Output Provision	PI1BAC2000110
	3 x 3.3 kW IEC60309	PI1BAC2000110-2
	2 x 3.3kW IEC60309 1 x 16A Socket Output Provision	PI1BAC2000110-6
	1 x 3.3 kW IEC60309 2 x 16A Socket Output Provision	PI1BAC2000110-4

DATASHEET



Input Supply

Input Voltage	415 VAC ($\pm 10\%$), Three Phase (L1, L2, L3, N, PE), 50 Hz
---------------	--

Output Supply

Output Interface	3 x 3 Pin Socket 3 x 3 IEC Socket
Output Power	3 x 3.3 kW
Output Current	16A ($\pm 10\%$) for Each 3 Connector

Electrical Parameters

Efficiency	99% at Nominal Output Power
Power Factor	0.99 at Nominal Output Power
Current THD	5% at Nominal Output Power

Environment

Operating Temperature	-5°C to 55°C
Storage Temperature	-10°C to 70°C
Altitude	2000 m
Humidity	5% to 95%
Noise Level	≤ 50 dB

User Interface and Control

Display	4.3" Touch LCD Screen
Emergency Stop	Mushroom Type
User Authentication	App / QR / RFID / Password
Visual Indication	RGB Neo Pixel LEDs
RFID Specifications	RC522

Protection

Protection Features	Over-Current, Over-Voltage, Over-Temperature, Under-Voltage, Surge, Short Circuit, Ground Fault, Emergency Shutdown
---------------------	---

Communication

Network Connection	GSM / 3G / 4G, Ethernet, Wi-Fi
Communication Protocol	OCPP 1.6J
Vehicle Standards	Electric 2-wheeler, Electric 3-wheeler

Mechanical

IP Rating	IP54
Cooling	N/A
Cable Length	N/A
Product Dimension (L*W*H)	168 mm * 450 mm * 668 mm
Weight (Tentative)	20 kg