



POWER THAT PERFORMS

14 kW AC HYBRID CHARGER

High performance, protection, and safety.



*ARAI Certified



BUILT-IN SAFETY

- Over-Current
- Over-Voltage and Under-Voltage
- Surge Protection
- Emergency Shutdown
- Short Circuit



LOAD MANAGEMENT

- Built-in Energy Meter
- Set up for External Energy Meter Integration or Dynamic Load Management
- Ready for Integration with Advanced Smart Building Energy Systems



DESIGN

- Three Phase Input
- 3 x 3 Pin Socket | 3 x 3 IEC Socket



CONNECTIVITY

- Wi-Fi, GSM / 3G / 4G, Ethernet
- OCPP 1.6J
- Authentication via App or RFID

VARIANTS

Variants	Features	Ordering Code
	1 x 7.4 kW Type 2 AC 2 x 3.3 kW IEC60309, 16A Socket Output Provision	P11HAC2300110
	1 x 7.4 kW Type 2 AC 2 x 3.3 kW IEC60309 Socket Output Provision	P11HAC2300110-2
	1 x 7.4 kW Type 2 AC 2 x 3.3 kW 16A Socket Output	P11HAC2300110-4

DATASHEET



Input Supply

Input Voltage 415 VAC ($\pm 10\%$), Three Phase (L1, L2, L3, N, PE), 50 Hz

Output Supply

Output Interface 1 x 7.4 kW & 2 x 3.3 kW

- 7.4 kW – Type 2 Gun
- 3.3 kW – IS / IEC 60309 Socket Outlet
- 3.3 kW – Universal 3 Pin Socket

Output Power 1 x 7.4 kW & 2 x 3.3 kW

Output Current 32A ($\pm 10\%$) for Gun 1 and 16A ($\pm 10\%$) for Second and Third Connector

- Type 2: 32A ($\pm 10\%$)
- Universal Socket: 16A ($\pm 10\%$)
- IEC 60309 Socket: 16A ($\pm 10\%$)

Electrical Parameters

Efficiency 99% at Nominal Output Power

Power Factor 0.99 at Nominal Output Power

Current THD 5% at Nominal Output Power

Environment

Operating Temperature -5°C to 55°C

Storage Temperature -10°C to 70°C

Altitude 2000 m

Humidity 5% to 95%

Noise Level $\leq 50\text{dB}$

User Interface and Control

Display 4.3" Touch LCD Screen

Emergency Stop Mushroom Type

User Authentication App / QR / RFID / Password

Visual Indication RGB Neo Pixel LEDs

RFID Specifications RC522

Protection

Protection Features Over-Current, Over-Voltage, Over-Temperature, Under-Voltage, Surge, Short Circuit, Ground Fault, Emergency Shutdown

Communication

Network Connection GSM / 3G / 4G, Ethernet, Wi-Fi

Communication Protocol OCPP 1.6J

Vehicle Standards Electric 2-wheeler, Electric 3-wheeler

DATASHEET



Mechanical

IP Rating	IP54
Cooling	N/A
Cable Length	15 ft.
Product Dimension (L*W*H)	168 mm * 450 mm * 668 mm
Weight (Tentative)	25 kg