

Reliable | Safe | Sustainable
Ecosystem Solutions for
Electric Mobility



Kspira DC Charger

60 kW - 240 kW



Ksipira DC Charger

60 kW - 240 kW

Built-in Safety

- Overcurrent
- Overvoltage and Undervoltage
- Ground Fault Detection
- Surge Protection
- Emergency Stop Machine
- Polarity Reverse Protection
- Charge Cable Temperature Detection
- Earth Presence Detection



Design

- Three-phase input
- 2 x CCS2 (IEC 62196.3-2014)
- IEC 15118 EIM & PNC

Load Management

- Built-in energy meter
- Set up for external energy meter integration or dynamic load management
- Ready for integration with advanced smart building energy systems

Connector Types

- CCS2 (IEC 62196.3-2014)
- GB/T

Connectivity

- GSM, Ethernet, and WiFi
- OCPP 1.6J (upgradable to 2.0.1)
- Authentication via App or RFID
- Configuration via App web portal

Capacity

Parameters

	60 kW	120 kW	240 kW
Input Power			
Input Voltage	415 VAC (+ 15%)	415 VAC(+ 15%)	415 VAC (+ 15%)
Input Frequency	50 Hz	50 Hz	50 Hz
Wires	Three-Phase (L1, L2, L3, N, PE)	Three-Phase (L1, L2, L3, N, PE)	Three-Phase (L1, L2, L3, N, PE)
Electrical Parameter			
Ripple Factor	≤ + 5%	≤ + 5%	< + 5%
Efficiency	> 95%	> 95%	> 95%
Power Factor	≥ 0.99 (above 50% load)	≥ 0.99 (above 50% load)	≥ 0.99 (above 50% load)
THD	≤ 5% (above 50% load)	< 5% (above 50% load)	< 5% (above 50% load)
Output Power			
Output Connector	CCS2 (IEC 62196.3-2014)	CCS2 (IEC 62196.3-2014)	CCS2 (IEC 62196.3-2014)
No. Of Outputs	2	2	2
Output Current	200 A (120 A per gun when both in operation)	400 A (200 A per gun when both in operation)	500 A (250 A per gun when both in operation)
Output rating	60 kW	120 kW (60 kW + 60 kW when both gun in use)	240 kW (120 kW + 120 kW when both gun in use)
Environment			
Ambient Temperature	0° C to 60° C(derating starts from 55° C)	0° C to 60° C(derating starts from 55° C)	0° C to 60° C(derating starts from 55° C)
Storage Temperature	-20° C to 70° C	-20° C to 70° C	-20° C to 70° C
Altitude	5000 Mt	5000 Mt	5000 Mt
Humidity	5% to 95%	5% to 95%	5% to 95% (Non-condensed)
Noise Level	< 60 dB	< 60 dB	< 60 dB

Capacity

	60 kW	120 kW	240 kW
Protection and Safety			
Protection	Overcurrent, Overvoltage, Overtemperature, Undervoltage, Surge Protection, Short Circuit, Ground Fault Protection, Emergency Shutdown with Alarm, Polarity Reverse Protection, Insulating Monitoring, Leakage Protection, Charge Cable Temperature Detection, Earth Presence Detection		
Communication			
Connectivity and CMS	OCPP 1.6J over 10/100 Base-T Ethernet (Standard), GSM Modem (4G) and Wi-Fi		
Charging and vehicle	DIN 70121, ISO15118(EIM & PnC), IEC-61851		
Mechanical			
IP Rating	IP 54	IP 54	IP 54
Shell Material	CRCA Sheet	CRCA Sheet	CRCA Sheet
Cooling Product	Air Cooling	Air Cooling	Air Cooling
Product Dimension (L*W*H)	800 mm × 680 mm × 2002 mm	800 mm × 680 mm × 2002 mm	800 mm × 680 mm × 2002 mm
Product Weight	305 kg	345 kg	385 kg
Certification	ARAI (IS 17017)	ARAI (IS 17017)	ARAI (IS 17017)
User interface and Control			
Display	10.1" TFT LCD Touch Screen	10.1" TFT LCD Touch Screen	10.1" TFT LCD Touch Screen
Language	English	English	English
Push Button	Mushroom Type, Emergency Stop	Mushroom Type, Emergency Stop	Mushroom Type, Emergency Stop
User Authentication	Using Mobile Application or User Interface /QR Code/ RFID Card/ Password Login/ Optional UPI payment	Using Mobile Application or User Interface /QR Code/ RFID Card/ Password Login/ Optional UPI payment	Using Mobile Application or User Interface /QR Code/ RFID Card/ Password Login/ Optional UPI payment



About VerdeMobility

We believe that well-engineered, sustainable ecosystem solutions backed by innovative technology can promote electric mobility adoption.

Go *Verde* with our innovative, made-in-India technology solutions for electric mobility. We provide, EV charging solutions, integrating advanced IoT technology for seamless management.

Our Offerings Includes:-



EV-Chargers

AC chargers 3.3 kw to 240 kW chargers for homes, businesses, CPOs, Dealership, fleets, Infra and DC chargers 30 kW to 240 kW for fleets and infrastructure



IoT Solutions

Smart AC-DC charger controllers, CMS, and mobile applications for real-time monitoring and control.



Customized Support

Tailored mobility, customization, and ecosystem support to enhance EV adoption



Ecosystem Support

EV simulators and fleet electrification calculators to optimize efficiency and sustainability