



View SQL — reporting.view_funnel_dashboard

Full SQL definition of `reporting.view_funnel_dashboard`, reproduced as it runs in production. Internal and test email exclusions have been sanitized; otherwise the logic is unchanged.

Reading this carefully before forming your own methodology is part of the exercise.

```
CREATE VIEW reporting.view_funnel_dashboard AS

WITH download_histories_emails AS (
  SELECT DISTINCT
    LOWER(dh.email) AS tracking_email
    , dh.key AS tracking_id
  FROM lakehouse.silver.pes_download_histories dh
  WHERE dh.email IS NOT NULL AND dh.key IS NOT NULL
),

hubspot_contacts AS (
  SELECT DISTINCT
    c.contact_id
    , LOWER(c.email) AS email
    , dh.tracking_id
    , l.labels
    , c.download_auth_status
    , CASE
      WHEN LOWER(l.labels) LIKE '%resellers customer%'
      OR LOWER(l.labels) LIKE '%owner%'
      THEN 1 ELSE 0
    END AS is_buyer
    , d.first_download_date
```

```

    , c.create_date AS first_contact_reference_date
    , DATE_TRUNC('week', c.create_date) AS week_start
    , DATE_TRUNC('month', c.create_date) AS month_start
    , c.apollo_job_title AS contact_apollo_job_title
    , INITCAP(c.record_source) AS contact_source_type
    , c.record_source_detail_1 AS contact_source_form
    , CASE
        WHEN c.original_traffic_source = 'AI_REFERRALS' THEN 'AI
Referrals'
        ELSE INITCAP(REPLACE(c.original_traffic_source, '_', '
'))
    END AS contact_source_traffic
FROM lakehouse.silver.hs_otl_contacts c
LEFT JOIN lakehouse.reporting.view_hubspot_downloads d
    ON c.contact_id = d.contact_id
LEFT JOIN lakehouse.silver.hs_otl_labels l
    ON c.contact_id = l.contact_id
LEFT JOIN download_histories_emails dh
    ON c.email = dh.tracking_email
),

hubspot_downloads AS (
    SELECT DISTINCT
        hs.email
        , hs.contact_id
        , hs.form_source
        , hs.first_download_date
    FROM view_hubspot_downloads hs
),

install_events AS (
    SELECT
        i.tracking_id
        , TIMESTAMP(i.start_ts) AS first_install_start
        , TIMESTAMP(i.first_success_finish_ts) AS first_install_comp
leted
    FROM view_funnel_install_events i

```

```

),

install_events_in_download_histories AS (
    SELECT DISTINCT i.tracking_id
    FROM install_events i
    INNER JOIN download_histories_emails dh ON i.tracking_id = dh.
tracking_id
    WHERE i.tracking_id IS NOT NULL
    AND dh.tracking_id IS NOT NULL
),

install_events_filtered AS (
    SELECT
        i.tracking_id
        , i.first_install_start
        , i.first_install_completed
    FROM install_events i
    INNER JOIN install_events_in_download_histories dh
        ON i.tracking_id = dh.tracking_id
),

addin_started AS (
    SELECT DISTINCT
        s.tracking_id
        , MIN(s.session_start_ts) AS first_active_session
    FROM view_appevents_addin_started s
    GROUP BY s.tracking_id
),

licenses_with_tracking AS (
    SELECT l.tracking_id, l.license_id
    FROM view_bridge_tracking_license l
    WHERE l.rn = 1
        AND l.license_id IS NOT NULL
        AND l.license_id <> '0'
        AND l.tracking_id IS NOT NULL
),

```

```

licenses_created AS (
  SELECT
    t.tracking_id
    , t.license_id
    , l.created_at AS license_created_at
  FROM licenses_with_tracking t
  INNER JOIN view_funnel_license_creation l
    ON l.license_id = t.license_id
  WHERE l.created_at IS NOT NULL
),

purchases AS (
  SELECT
    LOWER(t.email) AS transact_email
    , t.product_key_id AS license_id
    , LOWER(t.subscription_id) AS subscription_id
    , t.first_purchase_date
    , t.discriminator
  FROM view_pes_transactions t
),

subscriptions_filtered AS (
  SELECT
    LOWER(s.id) AS subscription_id
    , s.created_at AS subscription_created_at
  FROM lakehouse.silver.pes_subscriptions s
  WHERE s.created_at IS NOT NULL
),

subscriptions_created AS (
  SELECT tracking_id, subscription_id, subscription_created_at
  FROM (
    SELECT
      b.tracking_id
      , b.subscription_id
      , s.subscription_created_at

```

```

        , ROW_NUMBER() OVER (
            PARTITION BY b.tracking_id
            ORDER BY s.subscription_created_at
        ) AS rn
    FROM view_bridge_tracking_subscription b
    INNER JOIN subscriptions_filtered s
        ON s.subscription_id = b.subscription_id
    )
    WHERE rn = 1
),

master_list AS (
    SELECT DISTINCT
        c.email
        , c.contact_id
        , c.is_buyer
        , c.labels
        , c.download_auth_status
        , c.contact_apollo_job_title
        , c.contact_source_type
        , c.contact_source_form
        , c.contact_source_traffic
        , i.tracking_id
        , l.license_id
        , s.subscription_id
        , t.discriminator
        -- Funnel dates
        , c.week_start AS week_cohort
        , c.month_start AS month_cohort
        , CAST(c.first_contact_reference_date AS DATE) AS first_contact_reference_date
        , CAST(h.first_download_date AS DATE) AS first_download_date
        , CAST(i.first_install_start AS DATE) AS first_install_start
        , CAST(i.first_install_completed AS DATE) AS first_install_completed
        , CAST(a.first_active_session AS DATE) AS first_active_session

```

```

    , CAST(t.first_purchase_date AS DATE) AS first_purchase_date
    , CAST(l.license_created_at AS DATE) AS license_created_at
    , CAST(s.subscription_created_at AS DATE) AS subscription_cr
eated_at
    -- Funnel flags
    , CASE WHEN h.first_download_date IS NOT NULL THEN 1 ELSE 0
END AS has_download
    , CASE WHEN CAST(c.first_contact_reference_date AS DATE) <=
CAST(i.first_install_start AS DATE) THEN 1 ELSE 0 END AS has_sta
rt_install
    , CASE WHEN CAST(c.first_contact_reference_date AS DATE) <=
CAST(i.first_install_completed AS DATE) THEN 1 ELSE 0 END AS has
_completed_install
    , CASE WHEN CAST(c.first_contact_reference_date AS DATE) <=
CAST(a.first_active_session AS DATE) THEN 1 ELSE 0 END AS has_ac
tive_session
    , CASE WHEN CAST(c.first_contact_reference_date AS DATE) <=
CAST(t.first_purchase_date AS DATE) THEN 1 ELSE 0 END AS has_pur
chased
    , CASE WHEN CAST(c.first_contact_reference_date AS DATE) <=
CAST(l.license_created_at AS DATE) THEN 1 ELSE 0 END AS has_lice
nse_created
    , CASE WHEN CAST(c.first_contact_reference_date AS DATE) <=
CAST(s.subscription_created_at AS DATE) THEN 1 ELSE 0 END AS has
_subscription_created
    , ROW_NUMBER() OVER (
        PARTITION BY c.contact_id
        ORDER BY c.first_contact_reference_date
    ) AS rn
FROM hubspot_contacts c
LEFT JOIN hubspot_downloads h ON c.contact_id = h.cont
act_id
LEFT JOIN install_events_filtered i ON i.tracking_id = c.tra
cking_id
LEFT JOIN addin_started a ON a.tracking_id = c.tra
cking_id
LEFT JOIN purchases t ON t.transact_email = c.

```

```

email
  LEFT JOIN licenses_created l      ON l.tracking_id = c.tracking_id
  LEFT JOIN subscriptions_created s  ON s.tracking_id = c.tracking_id
),

master_list_filtered AS (
  SELECT *
  FROM master_list m
  WHERE m.rn = 1
  AND (
    m.has_download = 1
    OR m.is_buyer = 1
    OR m.has_license_created = 1
    OR m.has_subscription_created = 1
  )
  -- Internal and test email exclusions applied here
)

SELECT *
FROM master_list_filtered v
WHERE CAST(v.first_contact_reference_date AS DATE) >= DATE('2025-08-25');

```

Notes for the candidate

- The view references several upstream bridge views (`view_bridge_tracking_license`, `view_bridge_tracking_subscription`, `view_hubspot_downloads`, `view_funnel_install_events`, `view_funnel_license_creation`, `view_pes_transactions`, `view_appevents_addin_started`). Their definitions are not provided — their roles can be inferred from their names and how they're joined here.
- The view filters to contacts created on or after `2025-08-25` (the date the install tracker was deployed).

- The view does **not** apply a non-reseller filter. Whatever consumes this view (Power BI, downstream queries) may apply additional filters on top.