

[Home Page](#)[Title Page](#)[Contents](#)[Page 1 of 41](#)[Go Back](#)[Full Screen](#)[Close](#)[Quit](#)

Support Vector Machines

Sumantra Dutta Roy

Department of Electrical Engineering
Indian Institute of Technology Delhi
Hauz Khas, New Delhi - 110 016, INDIA.

<http://www.cse.iitd.ac.in/~sumantra>

sumantra@ee.iitd.ac.in

[Home Page](#)[Title Page](#)[Contents](#)[Page 2 of 41](#)[Go Back](#)[Full Screen](#)[Close](#)[Quit](#)

Introduction

- SVMs: sparse solutions: support vectors
- Convex optimisation: local optimal is also global
- Philosophy: different classifier formulations seek to optimise different criteria, make different assumptions, each fine in its own right
- Fisher: maximise 1-D projected margins
- SVM: maximise margins
- 2-class: generalisable to K classes: 1-1 or 1-rest
- 2 classes: ± 1 for notational convenience, not 0/1

[Home Page](#)[Title Page](#)[Contents](#)[Page 3 of 41](#)[Go Back](#)[Full Screen](#)[Close](#)[Quit](#)

Maximum Margin Classifiers

- 2-class restricted possible non-linearity:■
- $y(\mathbf{x}) = \mathbf{w}^T \boldsymbol{\phi}(\mathbf{x}) + b$. $y(\mathbf{x})$ is the model for target t .■
 b : bias, $\boldsymbol{\phi}(\cdot)$: feature space transformation■
- training $\{\mathbf{x}_1, \dots, \mathbf{x}_N\}$ targets $\{t_1, \dots, t_N\}$, $t_i \in \{-1, +1\}$ ■
- New data points \mathbf{x} classified acc to $y(\mathbf{x})$'s sign■
- Assume that the training data is linearly separable in the feature space i.e., \exists at least one \mathbf{w} & b :■
- $y(\mathbf{x}_i) < 0$ for $t_i = -1$ and $y(\mathbf{x}_i) > 0$ for $t_i = +1$ ■
- Combined: $t_i y(\mathbf{x}_i) > 0 \forall$ training data $\{\mathbf{x}_i, t_i\}$ ■
- Intuition: if multiple solutions, find the one which will give the smallest generalisation error■