Electronic Supplementary Information (ESI):
Master Jacobian Derivations, LOCO-CV Matrices, and Creep Kinetics for Project REGENESIS

Jacob James Rasmussen
CVTC STEM Division, Chippewa Valley Technical College
ORCID: 0009-0009-7084-6523

October 27, 2026

1 Master Jacobian Cross-Derivative Closures

The four-variable global state vector $\mathbf{x} = [T, C_i, \eta_{\text{act}}, \sigma_h]^T$ is linearized around the baseline operating point ($T_0 = 1073.15$ K, $C_0 = 12.5$ mol/m^3, $\eta_0 = 0.15$ V, $\sigma_0 = 45.0$ MPa), yielding the 4×4 Master Jacobian matrix $\mathbf{J}$:

$$\mathbf{J} = \begin{bmatrix} -0.1200 & 0.4500 & 2.1000 & 0.0100 \\ -0.0500 & -0.8500 & -0.3000 & -0.0020 \\ 0.0800 & -0.1500 & -1.2000 & 0.0400 \\ -3.5000 & 0.1000 & 0.0500 & -0.4500 \end{bmatrix} \tag{1}$$

The analytical cross-domain closures are derived as:

1. **Ohmic Heating Sensitivity:** $\frac{\partial \dot{Q}}{\partial \eta_{\text{act}}} = 2.10$ K V^{-1}s^{-1}
2. **Thermo-Mechanical Coupling:** $\frac{\partial \sigma_h}{\partial T} = -3.50$ MPa/K
3. **Mechano-Electrochemical d-Band Shift:** $\frac{\partial \eta_{\text{act}}}{\partial \sigma_h} = 0.04$ V/MPa

2 Dual-Time Strang Operator Splitting & Courant Bound

Microsecond electrochemical charge transport ($\tau_{\text{electro}} \sim 10^{-9}$ s) is integrated implicitly using CVODE, while spatial advection-diffusion is updated explicitly under the Courant-Friedrichs-Lewy (CFL) limit:

$$r = \frac{\alpha_T \Delta t}{(\Delta x)^2} \leq 0.50 \tag{2}$$

3 Leave-One-Cluster-Out Cross-Validation (LOCO-CV) Table

4 3D Anisotropic Tsai-Wu Criteria & Accelerated Aging Creep

Evaluating the 3D anisotropic tensor criterion $F_i\sigma_i + F_{ij}\sigma_i\sigma_j \leq 1.0$ at the Pareto optimal setpoint ($T_{\text{op}} = 1045.2$ K, $\eta_{\text{act}} = 0.142$ V, $Y_{\text{Sabatier}} = 1,000$ kg/hr, $\sigma_h = 45.0$ MPa) confirms FI $= 0.682 \leq 0.75$ (+31.8% safety reserve). Accelerated 10,000-hour Ni-YSZ sintering kinetics ($E_a = 112.5$ kJ/mol) and hydrostatic creep ($n = 2.40$, $d\epsilon/dt = -2.20 \times 10^{-13}$ s^{-1}) bound capacity degradation at $< 1.85\%$ per 1,000 hours ($> 81.5\%$ retention).

Table 1: LOCO-CV Spectral Stability and Generalization Performance across 5 Operational Clusters.

Fold	**Held-Out Cluster**	**Max** $\mathrm{Re}(\lambda_k)$	**RMSE (%)**	**Status**
Fold 1	C1 (Low-Temp)	-0.1454	1.19%	STABLE
Fold 2	C2 (Nominal)	-0.1372	1.36%	STABLE
Fold 3	C3 (High-Enthalpy)	-0.1325	1.82%	STABLE
Fold 4	C4 (Severe Quench)	-0.1044	3.47%	STABLE
Fold 5	C5 (1,000 kg/hr Baseline)	-0.1350	1.57%	STABLE